

WEVER & DUCRÉ
LIGHTING

“There’s no beauty without great lighting. Beauty is never loud. It hides in details, in shape, in moments, in light. Great lighting allows us to see what was always there and to transform it into something beautiful.”

ANTWERP-BASED PHOTOGRAPHER FREDERIK VERCRUYSSE

story telling

weverducre.com/coverstory26

Indoor

CEILING RECESSED 54 – 173

QITO trimless 57 | QITO 59 | MATCH POINT trimless 61 | MATCH POINT 61 | BLIEK PETIT trimless 63 | BLIEK PETIT 63 | BLIEK 67 | LINOO trimless 71

LINOO 71 | PIRRO PETIT 75 | PIRRO 77 | PLANO PETIT 83 | PLANO 85 | STRANGE PETIT trimless 87 | STRANGE trimless 89 | SNEAK trimless 91 | SNEAK 93

DEEP POINT 97 | DEEP BIJOU 99 | DEEP PETIT IQ 101 | DEEP PETIT 103 | DEEP IQ 105 | DEEP 107 | DEEPER 109 | DEEP ADJUST PETIT IQ 111 | DEEP ADJUST PETIT trimless 113

DEEP ADJUST PETIT 113 | DEEP ADJUST IQ 115 | DEEP ADJUST trimless 117 | DEEP ADJUST 119 | RONY POINT 123 | RONY PETIT 125 | RONY ADJUST PETIT 127 | RONY ADJUST 129 | CENO 131

LECA 135 | MATCH 137 | MATCH SNEAK trimless 143 | MATCH SNEAK 143 | MATCH STICK trimless 145 | MATCH STICK 145 | RUVI 147 | PLANO IP44 151 | MATCH POINT IP44 153

DEEP POINT IP44 155 | DEEP BIJOU IP65 157 | DEEP PETIT IP65 159 | DEEP IP44 | IP65 161 | DEEPER IP44 163 | TAIO IP65 165 | RINI SNEAK IP44 167 | PERLEZ IP44 169 | MIRBI 1.0 IP44 171

MIRBI 2.0 IP44 171 | CITY IP44 173

CEILING SURFACE 174 – 307

QITO 177 | BLIEK PETIT 179 | CENO 181 | LECA 189 | MATCH 193 | MICK 199

PILLO 201 | SARA 203 | SQUBE 205 | LINOO 211 | PIRRO PETIT 213 | PIRRO 215 | PIRRO OPAL 221 | PIRRO ON BASE 223 | PLANO PETIT 227

SIRRO 229 | BOX MINI 231 | BOX 235 | DOCUS MINI 239 | DOCUS 241 | HEXO MINI 243 | HEXO 245 | RAY MINI 247 | RAY 251

SOLID BIJOU 253 | SOLID PETIT 255 | SOLID 257 | TRACE 261 | FINLIN 263 | FIL SPIN 267 | TRACE SPIN 269 | PERLEZ SPIN 271 | TRACE GRID 273

PERLEZ GRID 275 | VENN 277 | DRO 279 | MIRRO 283 | CLEA 287 | J.J.W. 289 | WIRO 291 | ROOMOR 293 | PERLEZ IP44 295

MIRBI 1.0 IP44 297 | MIRBI 2.0 IP44 297 | TAIO IP65 299 | ROB IP44 301 | ROBY IP44 303 | TOWNA IP44 305 | ROSS IP54 307

STREX 48V-TRACK 312 – 359

TRACKS 313

CENO 321 | LECA 325 | DOMY 327 | MATCH 329 | TRACE MINI 331 | MICK 333 | BOX 335 | DOCUS 337 | HEXO 339

RAY 341 | DOT MODULE 343 | OPAL MODULE 343 | COZY CONE 345 | MATCH 347 | TRACE 351 | ODREY 353 | OPLIA 357 | SOLLI 359

Indoor

Indoor

1-PHASE TRACK 360 – 383

TRACKS 361 · PILLO 363 · SARA 365 · SQUBE 369 · PIRRO 371 · DRO 373 · HEXO MINI 375 · HEXO 377

RAY MINI 375 · RAY 377 · ODREY 379 · RUVI 383

3-PHASE TRACK 384 – 395

TRACKS 385 · LIKO 387 · SQUBE 389 · HEXO MINI 391 · HEXO 393 · RAY MINI 391 · RAY 393 · ROOMOR 395

SYSTEM 396 – 411

QUBBY 397 · FLYRA 401 · ELLO 405 · ILANE 409

CEILING SUSPENDED 412 – 565

MATCH LUSTA 415 · TRACE 417 · NET 421 · FINELLE 423 · FLYRA 427 · FINLIN 433 · STUDO 437 · FIL 441

DARF 445 · SHEDDA 449 · KUJO 453 · OPLIA 457 · QUBBY 459 · GIGANT 461 · CONE 463 · DRO 465 · MIRRO 467

J.J.W. 479 · WIRO 489 · ROOMOR 495 · ROOMOR 499 · COZY CONE 503 · HEXO MINI 505 | 531 · HEXO 533 · RAY MINI 507 | 535 · RAY 537

MATCH 509 · TRACE 511 | 547 · ODREY 517 | 539 · OPLIA 521 · SOLLI 523 · WETRO 549 · CLEA 557 · SHIEK 561 · DINOR 563

WALL RECESSED 566 – 581

LECA SNOOZE 569 · MATCH SNOOZE 571 · RETO 573 · LITO 1.0 575 · LITO 2.0 575 · STRIPE SLIM 577 · STRIPE 579 · ORIS 581

WALL SURFACE 582 – 711

CENO 585 · MATCH 589 · TRACE MINI 591 · TRACE 593 · TRACE SLIM 595 · ODREY 599 · BOX MINI 605 · BOX 607

DOCUS MINI 609 · HEXO MINI 611 · RAY MINI 613 · RAY 615 · CENTRAL 617 · LEENS 619 · BENTO 621 · DRO 623 · MIRRO 625

CLEA 631 · J.J.W. 633 · ROOMOR 639 · DARF 643 · CG SQUARE 647 · DOT 649 · TAPIS 651 · MILES ROUND 663 · MILES CARRÉ 667

MILES 669 · LARRA 671 · FINLIN 673 · FINLIN ROUND 679 · FIL SPIN 681 · VENN 683 · MATCH SNOOZE 685 · MICK SNOOZE 687 · SARA SNOOZE 689

MICK WALL 691 · DOMINO 693 · SCAVA 695 · HAJO IP44 697 · PERLEZ IP44 701 · MIRBA IP44 705 · MIRBI IP44 707 · RIBELLE IP65 709 · PAVIO IP65 711

Indoor

TABLE
712 – 725

DRO
715


DRO
717


CG01
719


MIRRO
721


MATCH
723


ROOMOR
725

FLOOR
726 – 735


DRO
715

FINLIN
727

MATCH
729


DRO
731


MIRRO
733


ROOMOR
735

SOFT ACOUSTICS


MIRRO SOFT
285


MIRRO SOFT
471


SPIRRA SOFT
475


WAVE SOFT
477


SOLLI COCOON
525


MIRRO SOFT
629


TAPIS SOFT
657

Outdoor

CEILING RECESSED
738 – 749


DEEP BIJOU
741


DEEP PETIT
743


DEEP
745


TAIO
747


INTRA
749

CEILING SURFACE
750 – 775


TRAM
753


TUBE
755


TAIO
757


RAY
759


TRAIN
761


TUBE CARRÉ
763


BOX
765


BLAS
767


ROB
769


ROSS
771


TRADORA
775

CEILING SUSPENDED
776 – 777


TRADORA
777

WALL RECESSED
778 – 787


RETO
781


ORIS
785

WALL SURFACE
788 – 835


CLASCO
791


KIOSK
793

TRAM
797

TUBE
799

TAIO
803

RAY
805

TRAIN
807

CENTRAL
809

TUBE CARRÉ
811

BOX
815

TAPE
817

PALOS
819

SWAM
821

TRADORA
823

RIBELLE
825

BLAS
827

X-BEAM
829

X-BEAM ROUND
829

PAVIO
831

RETO ROUND
833

RETO
835

FLOOR RECESSED
836 – 853

BLINK trimless
839

BLINK
839

CARD
843

MAP
845

MAP ASYM
849

CHART
851

CHART ASYM
853

FLOOR SURFACE
854 – 891

KIOSK
857

SWAM
859

STIPO
863

X-BEAM
865

RIBELLE
867

GATE ROUND
869

GATE CARRÉ
871

PALOS ROUND
873

PALOS CARRÉ
877

LINUS
881

GEO
885

REED
887

POLA
889

WELCOME TO OUR WORLD

We kennen het allemaal: die blik naar het plafond en de gedachte: “Iedereen heeft deze armatuur.” Daarom creëren we verlichtingsoplossingen die echt uniek zijn – geïnspireerd door mensen zoals jij, die waarde hechten aan design en kwaliteit. Want life is too short for boring lighting.

Nous le connaissons tous : ce regard vers le plafond en pensant « Tout le monde a cette lampe » . C’est pourquoi nous créons des solutions d’éclairage uniques – inspirées par des personnes comme vous, qui apprécient le design et la qualité. La vie est trop courte pour des lampes ennuyeuses.

weverducre.com/about

our world





availability

READY FOR AN ONLINE DATE

Zo gaat het met onze armaturen: zodra je verliefd bent, wil je ze meteen hebben. Goed nieuws: we verzenden alle producten binnen 48 uur! Controleer online de beschikbaarheid van je favoriet.

C’est comme ça avec nos luminaires : une fois que vous en êtes tombé amoureux, vous les voulez tout de suite. Bonne nouvelle : nous expédions tous les produits sous 48 heures ! Vérifiez la disponibilité de votre article préféré en ligne.

weverducre.com/products

with

FROM BELGIUM WITH LOVE

In België hangt niet alleen de geur van verse wafels en chocolade in de lucht – ook de liefde voor goed design. Hier ontmoeten creatieve geesten een rijke designtraditie, waar vakmanschap en moderne esthetiek samenkomen – voor licht dat verhalen vertelt en ruimtes laat stralen.

En Belgique, ce n’est pas seulement le parfum des gaufres et du chocolat frais qui flotte dans l’air – c’est aussi l’amour du bon design. Ici, des esprits créatifs rencontrent une longue tradition du design, mêlant artisanat et esthétique moderne – pour une lumière qui fait rayonner les espaces.

weverducre.com/about



13&9 DESIGN



design



CHRISTOPHE GEVERS



JULES WABBES

that

OUR SIGNATURE PIECES

Al meer dan 40 jaar geeft Wever & Ducré vorm aan licht. Geworteld in het Belgische erfgoed werkt het merk samen met iconen als Christophe Gevers, Serge Cornelissen en Jules Wabbes, evenals internationale ontwerpers zoals 13&9 Design – voor tijdloze elegantie en inspirerende lichtkunst.

Depuis plus de 40 ans, Wever & Ducré façonne la lumière comme une expression du design. Ancrée dans l'héritage belge, la marque collabore sur des produits de Christophe Gevers, Serge Cornelissen et Jules Wabbes, ainsi qu'avec des designers internationaux tels que 13&9 Design – pour créer une élégance intemporelle et un art lumineux inspirant.

weverducre.com/iconicproducts



S + R CORNELISSEN

lasts

CHRISTOPHE GEVERS



Christophe Gevers (1928–2007) was een vooraanstaand Belgisch interieurarchitect en ontwerper, bekend onder andere voor zijn karakteristieke restaurantconcepten. Zijn combinatie van vakmanschap en esthetiek bepaalden zijn werk en maken zijn creaties uniek en veelzijdig.

Christophe Gevers (1928–2007) était un important architecte d'intérieur et designer belge, connu pour ses concepts de restaurants distinctifs. Son alliance de savoir-faire et d'esthétique a marqué son œuvre, rendant ses créations à la fois uniques et polyvalentes.

gevers

weverducre.com/gevers





13&9 DESIGN

13&9 design

13&9 Design – het creatieve duo van Anastasija en Martin Lesjak – staat sinds 2013 voor visionair Oostenrijks design. Voor Wever & Ducré ontwierpen zij iconische creaties zoals MIRRO, DRO en SHEDDA fractal. Hun stijl: fractale patronen, modulaire akoestiek – lichtsystemen en sculpturale vormen die het welzijn van mensen en sfeervolle ruimtes centraal stellen.

13&9 Design – le duo créatif formé par Anastasija et Martin Lesjak – incarne depuis 2013 un design visionnaire venu d'Autriche. Pour Wever & Ducré, ils ont créé des pièces phares comme MIRRO, DRO et SHEDDA fractal. Leur style : des motifs fractals, une acoustique modulaire – des systèmes d'éclairage et des formes sculpturales qui placent le bien-être des personnes et les espaces atmosphériques au centre.



weverducre.com/13and9design

jules wabbes



J.J.W.

Jules J. Wabbes is al jarenlang een klassieker van Wever & Ducré. De sierlijk gebogen lijnen getuigen van verfijnde esthetiek. Wij beschouwen dit als traditie in de beste zin van het woord en zetten de reeks voort met plafond- en wandarmaturen.

Jules J. Wabbes est depuis de nombreuses années un classique de Wever & Ducré. Les lignes gracieusement courbées témoignent d'une esthétique raffinée. Nous considérons cela comme une tradition dans le meilleur sens du terme et poursuivons la gamme de produits avec des plafonniers et des appliques murales.

weverducre.com/jjw



serge & robert

S+R CORNELISSEN

Serge Cornelissen had meer dan 20 jaar ervaring in het ontwerpen van verlichtingsoplossingen voor architecturale toepassingen. Vanuit zijn achtergrond combineerde hij esthetiek, technologie en functionaliteit tot bekroonde concepten – bijvoorbeeld voor Wever & Ducré met MICK, VENN, HAJO en QUBBY.

Serge Cornelissen possédait plus de 20 ans d'expérience dans la conception de solutions d'éclairage pour l'architecture. Grâce à sa formation en architecture, il associait esthétique, technologie et fonctionnalité dans des concepts primés – notamment pour Wever & Ducré avec MICK, VENN, HAJO et QUBBY.



weverducre.com/cornelissen

ALL AROUND THE WORLD

Wever & Ducré-armaturen voelen zich overal ter wereld thuis – van rooftopbars in London tot stadsappartementen in Berlijn. Hun geheim? Uitzonderlijk design en hoogwaardige materialen. En het beste: we leveren al onze producten volledig plasticvrij. Waar vind je ons? Bijna overal. Ontdek onze locaties online en boek eenvoudig je volgende showroombezoek.

Les luminaires Wever & Ducré se sentent chez eux partout dans le monde – des rooftop bars de Londres aux appartements citadins de Berlin. Leur secret ? Un design exceptionnel et des matériaux de première qualité. En het beste van al is: nous livrons tous nos produits sans plastique. Où nous trouver ? Presque partout. Découvrez nos emplacements en ligne et réservez facilement votre prochaine visite en showroom.



KORTRIJK



PARIS

world

weverducre.com/locations



FRANKFURT

lifetime



SUSTAINABILITY BY FUNCTION

Ons doel? Armaturen die jarenlang blijven stralen. Doordacht ecodesign, duurzame vervangonderdelen en LED-engines die tot 20 jaar vervangbaar blijven. Een LED-module wisselen gaat eenvoudig, dankzij gereedschapsloze modules. En daar doen we nog 5 jaar garantie* bovenop. Eerlijk, toch?

Notre objectif : des luminaires qui brillent même après des années. Grâce à la qualité conforme à la directive sur l'écoconception à des pièces de rechange durables et à des LED engines offrant 20 ans de remplaçabilité. Changer le module LED ? Rien de plus simple grâce aux unités sans outil. Et en plus, 5 ans de garantie* – équitable, non ?

*De garantievoorwaarden beschikbaar op weverducre.com zijn van toepassing.
*Les conditions de garantie indiquées sur le site weverducre.com s'appliquent.

weverducre.com/sustainability

HOW SOFT CAN IT GET?

Onze wereld is luid – des te belangrijker zijn plekken die rust uitstralen. De Wever & Ducré Soft-collectie biedt sfeervolle verlichting, gecombineerd met design. Het materiaal? Vilt van gerecyclede PET-flessen. Klinkt goed, toch?

Notre monde est bruyant – d'où l'importance de lieux qui dégagent du calme. La collection Soft de Wever & Ducré offre une lumière chaleureuse, alliée à un design plein d'atmosphère. Le matériau ? Du feutre fabriqué à partir de bouteilles PET recyclées. Ça sonne bien, non ?

weverducre.com/soft-acoustics



soft
acoustics



3D PRINTED
by IQ LUX

layer by

layer



PRINTED IN 3D

Sinds 2023 experimenteren we samen met IQ LUX met duurzame materialen om armaturen met een minimale milieu-impact te ontwikkelen. Deze visie maakt nu deel uit van onze productportfolio met de nieuwe IQ-serie van de DEEP Family. Een grondstofbesparend geproduceerd armatuur, uitgerust met zeer efficiënte LED-modules.

Depuis 2023, nous expérimentons avec IQ LUX des matériaux durables afin de développer des luminaires à impact environnemental minimal. Cette vision fait désormais partie du notre portefeuille de produits avec la nouvelle série IQ de la famille DEEP. Un boîtier fabriqué de manière économe en ressources, équipé de modules LED à très haut rendement.

weverducre.com/iqlux

THE FUTURE SHINES BRIGHT

Onze armaturen blijven hangen – niet alleen door hun design, maar ook dankzij slimme technologie. Nieuw in ons assortiment: een selectie armaturen met geïntegreerde Loxone Tree-technologie, die eenvoudig te verbinden zijn met de gebouw-automatisering van Loxone. Zo zijn zowel kleine als grote projecten eenvoudig te realiseren.

Nos luminaires marquent les esprits – non seulement par leur design, mais aussi grâce à une technologie intelligente. Nouveauté : une sélection de luminaires avec technologie Loxone Tree intégrée, facilement connectables à l'automatisation du bâtiment Loxone. Les petits comme les grands projets se réalisent ainsi en toute simplicité.

ALL LOXONE LUMINAIRES ONLINE
weverducre.com/loxone

loxone



works with Loxone

READY TO TUNE UP YOUR PROJECT?

Opvallende verlichtingssystemen onbetaalbaar? Nonsens! Met Wever & Ducré weet je wel beter. Zo laat je zien hoe eenvoudig het is om met het juiste licht de perfecte sfeer te creëren, voor een project dat je nauw aan het hart ligt.

Des systèmes d'éclairage remarquables seraient-ils inabordables ? Absurde ! Avec Wever & Ducré, vous savez que c'est tout le contraire. Il devient simple de créer l'atmosphère parfaite grâce à la bonne lumière, pour un projet qui vous tient réellement à cœur.



LEEUWARDEN | THE NETHERLANDS



HASSELT | BELGIUM

tune up



COLOGNE | GERMANY

weverducre.com/tune-up





HERO OF THE YEAR 2025

projects



weverducre.com/picture-gallery

to fall in *love*

light guide



THE KEY TO A BRIGHTER HOME

Hoe we licht waarnemen, bepaalt hoe we ons in een ruimte voelen. Daarom moet verlichting altijd passen bij de functie – om te werken, te spelen of te ontspannen. Weet je al waarvoor? Perfect! Begin dan met plannen – of ontdek de basis in onze Lightguide.

La façon dont nous percevons la lumière influence notre bien-être dans un espace. C’est pourquoi l’éclairage doit toujours s’adapter à sa fonction – que ce soit pour le travail, le jeu ou la détente. Vous savez déjà ce que vous voulez ? Parfait ! Lancez la planification ou découvrez les bases dans notre Lightguide.

weverducre.com/basic-lightguide



THREE OF US IS A PRODUCT FAMILY

Ben je zo verliefd op een design dat je het overal wil hebben? Let dan op de Mounting Icons! Zie je er minstens drie, dan behoort de armatuur tot een familie – ideaal om ruimtes in een uniforme stijl te creëren. En ja, dat kan ook buiten, met onze outdoor-varianten.

Vous aimez tellement un design que vous le voudriez partout ? Alors, regardez les Mounting Icons ! S'il y en a au moins trois, le luminaire fait partie d'une famille – parfait pour créer une harmonie dans vos espaces. Et bonne nouvelle : nos versions outdoor le permettent aussi.


CEILING RECESSED


CEILING SURFACE


TRACKS


CEILING SUSPENDED


WALL RECESSED


WALL SURFACE


TABLE | FLOOR


CEILING RECESSED


CEILING SURFACE


CEILING SUSPENDED


WALL RECESSED


WALL SURFACE


FLOOR RECESSED


FLOOR SURFACE

Highlight families

CENO


SEMI-RECESSED 131


SURFACE 181


ON STREX 321


WALL 585

MATCH


RECESSED 61


SEMI-RECESSED 137


SURFACE 193


ON STREX 329

ON STREX \| SUSPENDED 347 \| 509


LUSTA 415


SNOOZE WALL RECESSED 571

WALL 589


SNOOZE WALL SURFACE 685


TABLE 723


FLOOR 729

TRACE

SURFACE 261


SPIN 269


GRID 273


MINI ON STREX 331

ON STREX \| SUSPENDED 351 \| 511


CHANDELIER 417

WALL 591

SLIM WALL 595

FINLIN

SURFACE 263

SUSPENDED 433


WALL 673


WALL ROUND 679

FLOOR 727

ODREY


ON STREX 353

ON 1-PHASE TRACK 379


SUSPENDED 517


WALL 599

LECA


RECESSED 135


SURFACE 189


ON STREX 325


SNOOZE 569

PERLEZ

SEMI-RECESSED 169


SPIN 271


GRID 275


SURFACE 295

WALL 701

MIRROR CLIP 703

ROOMOR

OFFICE SURFACE 293

OFFICE ON TRACK 395

SUSPENDED 495

OFFICE SUSPENDED 499

WALL 639

TABLE 725

FLOOR 735

DRO

SURFACE 279

ON TRACK 373

SUSPENDED 465

WALL 623

TABLE / FLOOR 715

TABLE 717

FLOOR 731

MIRRO

SURFACE 283

CEILING SOFT 285

SUSPENDED 467

SUSPENDED SOFT 471

WALL 625

WALL SOFT 629

TABLE 721

FLOOR 733

J.J.W.

SURFACE 289

SUSPENDED 479

SUSPENDED 481

WALL 633

WALL 635

CLEA

SURFACE 287

SUSPENDED 557

WALL 631

TRADORA

SURFACE 775

SUSPENDED 777

WALL 823



I MADE YOU LOOK

Orienteerbare spots zoals LECA zorgen niet alleen in hotels, maar ook thuis voor stijlvolle accenten. Voor grotere ruimtes is LECA beschikbaar met meerdere spots, voor een gelijkmatige verlichting. De ronde spot is verkrijgbaar als inbouw-, opbouw-, snooze- of STREX-inset-armatuur in drie kleuren.

Des spots orientables comme LECA créent des accents élégants, non seulement dans les hôtels mais aussi à la maison. Pour les espaces plus grands, LECA est disponible avec plusieurs spots – pour un éclairage uniforme. Le spot rond est proposé en version encastrée, en saillie, snooze ou en applique STREX, disponible en trois couleurs.

weverducre.com/leca

leca





finlin

FOLLOW THE LINE

Op het eerste gezicht lijkt FINLIN een moderne sculptuur. Achter het verfijnde design schuilen slanke aluminium buizen die zorgen voor een elegante uitstraling. Als plafond-, hang-, staande of wandarmatuur overtuigt FINLIN in zwart, goud of chic champagne.

À première vue, FINLIN ressemble à une sculpture moderne. Mais derrière son design délicat se cachent de fins tubes en aluminium pour un rendu élégant. Qu'elle soit plafonnier, suspension, lampadaire ou applique, FINLIN séduit en noir, or ou champagne raffiné.

weverducre.com/finlin



LIGHT A MATCH

Sta je al in vuur en vlam? Geen wonder. De armaturen van de MATCH familie doen niet voor niets denken aan lucifers en kunnen heel precies op specifieke objecten worden gericht. Perfect om foto's en legplanken te accentueren, een boek te lezen of extra sfeer te creëren rond de bar. En dit alles in een duidelijk en gestandaardiseerd ontwerp.

Alors, vous avez flashé ? Pas étonnant. Les luminaires de la famille MATCH sont élancés comme des allumettes et peuvent être dirigés précisément vers les objets. Parfaits pour mettre en valeur des tableaux et des étagères, améliorer la visibilité de votre roman préféré ou sublimer votre bar. Et tout cela avec un design clair et uniforme.



weverducre.com/match

match





odrey

LITTLE BLACK LAMP

Ze straalt de charme van de jaren 50 uit — en nee, we hebben het niet over Audrey Hepburn, maar over onze ODREY-armatuur. Een echte must-have voor elke cocktailparty: zo veelzijdig als een filmster en schitterend in glanzend goud, elegant zwart, brons, wit of aluminium.

Elle dégage un charme des années 1950 – et nous ne parlons pas d'Audrey Hepburn, mais de notre luminaire ODREY. Un véritable indispensable pour toute soirée cocktail : aussi polyvalente qu'une star de cinéma et aussi éblouissante en or scintillant, qu'en noir élégant, en bronze, blanc, ou en aluminium.



weverducre.com/odrey

indoor

Ceiling recessed

54 – 173

SPOT LIGHTS



QITO TRIMLESS
57



QITO
59

MATCH POINT TRIMLESS
61

MATCH POINT
61



BLIEK PETIT TRIMLESS
63



BLIEK PETIT
63



BLIEK
67

LINOO TRIMLESS
71



LINOO
71



PIRRO PETIT
75



PIRRO
77



PLANO PETIT
83



PLANO
85



STRANGE PETIT TRIMLESS
87



STRANGE TRIMLESS
89



SNEAK TRIMLESS
91



SNEAK
93



DEEP POINT
97



DEEP BIJOU
99



DEEP PETIT IQ
101



DEEP PETIT
103



DEEP IQ
105



DEEP
107



DEEPER
109



DEEP ADJUST PETIT IQ
111



DEEP ADJUST PETIT TRIMLESS
113



DEEP ADJUST PETIT
113



DEEP ADJUST IQ
115



DEEP ADJUST TRIMLESS
117



DEEP ADJUST
119



RONY POINT
123



RONY PETIT
125



RONY ADJUST PETIT
127



RONY ADJUST
129

SEMI RECESSED



CENO
131



LECA
135



MATCH TRIMLESS
137



MATCH
137



MATCH SNEAK TRIMLESS
143



MATCH SNEAK
143

MATCH STICK TRIMLESS
145

MATCH STICK
145

RUVI
147

IP-RATED

PLANO IP44
151

MATCH POINT IP44
153

DEEP POINT IP44
155

DEEP BIJOU IP65
157

DEEP PETIT IP65
159

DEEP IP65 | IP44
161

DEEPER IP44
163

TAIO IP65
165

RINI SNEAK IP44
167

PERLEZ IP44
169

MIRBI IP44 1.0
171

MIRBI IP44 2.0
171

CITY IP44
173

back



QITO

Ceiling recessed











35

ø73

1.0 TRIMLESS

LED COB 5W | 250mA | 18V
aluminium

IP20 0°-35°|360° M-31° L80|50K

	EUR	CODE
	128,00	198261W_
	144,00	198261L_
	144,00	198261M_
	144,00	198261Q_
	144,00	198261GM_
	128,00	198261B_

LIGHT COLOUR	LUMEN | CRI	CODE
2700K	420 | >90	3
3000K	440 | >90	5

ALWAYS USE

alu plasterkit 78-80 80 12.5, 15, 20, 25

	EUR	CODE
	22,00	90017210

quick connect driver | 250mA

	EUR	CODE
5W dim	33,00	90226201
10W DALI*	64,50	90246403

*revision opening required
more options and specs on page 895















OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

back

QITO

Ceiling recessed

177







1.0

LED COB 5W | 250mA | 18V
aluminium

IP20 0°-35°|360° M-31° L80|50K

blade springs 68-70 60 2-25

	EUR	CODE
	118,00	198161W_
	134,00	198161L_
	134,00	198161M_
	134,00	198161Q_
	134,00	198161GM_
	118,00	198161B_

LIGHT COLOUR	LUMEN|CRI	CODE
2700K	420|>90	3
3000K	440|>90	5





OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

ALWAYS USE

quick connect driver | 250mA

	EUR	CODE
5W dim	33,00	90226201
10W DALI*	64,50	90246403

*revision opening required
more options and specs on page 895

back



PRIVATE RESIDENCE GREECE

MATCH point

Ceiling recessed









1.0 TRIMLESS

LED COB 5W | 250mA | 17V
aluminium

IP20 M-32° L80|50K

45-47 60 4-26

	EUR	CODE
	82,50	191861B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	315	>90	3
3000K	335	>90	5

1.0

LED COB 5W | 250mA | 17V
aluminium

IP20 M-32° L80|50K

wire springs 28-31 50 4-25

	EUR	CODE
	52,00	191361W_
	52,00	191361B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	315	>90	3
3000K	335	>90	5

1.0 IP44

LED COB 5W | 250mA | 17V
aluminium

IP44 M-32° L80|50K

wire springs 40-41 68 4-25

	EUR	CODE
	65,00	191261W_
	65,00	191261B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	295	>90	3
3000K	325	>90	5



ALWAYS USE

quick connect driver | 250mA

	EUR	CODE
5W dim	33,00	90226201
10W DALI	64,50	90246403

revision opening required
more options and specs on page 895

ALWAYS USE

quick connect driver | 250mA

	EUR	CODE
5W dim	33,00	90226201
10W DALI	64,50	90246403

revision opening required
more options and specs on page 895

ALWAYS USE

quick connect driver | 250mA

	EUR	CODE
5W dim | IP20	33,00	90226201
10W DALI | IP20*	64,50	90246403

*revision opening required
more options and specs on page 895

LOXONE VERSIONS ONLINE
weverducre.com/more-match-point

193
329 | 347
415 | 509
571
589 | 685
723 | 729

back



RESTAURANT AUX PETITS OIGNONS | COVARTE JODOIGNE | BELGIUM

BLIEK petit

Ceiling recessed

















OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

LOXONE VERSIONS ONLINE
weverducre.com/more-bliek-petit

1.0 TRIMLESS

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-60°|355° M-31° L70|55K

	EUR	CODE
	149,00	164561W_
	149,00	164561CH_
	149,00	164561B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	495	>90	3
3000K	530	>90	5
2000-3000K | 16V	340	>90	9

ALWAYS USE

alu plasterkit 78-80 85 12.5, 15, 20, 25

	EUR	CODE
	22,00	90017210

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
10W dim	35,50	90223406
14W DALI	64,50	90243502

*revision opening required and
more options and specs on page 898

1.0

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-60°|355° M-31° L70|55K

wire springs 86-89 60 4-23

	EUR	CODE
	139,00	164461W_
	139,00	164461CH_
	139,00	164461B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	495	>90	3
3000K	530	>90	5
2000-3000K | 16V	340	>90	9

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
10W dim	35,50	90223406
14W DALI*	64,50	90243502

*revision opening required and
more options and specs on page 898

2.0

2x LED COB 6W | 700mA | 17V
aluminium

IP20 0°-60°|355° M-31° L70|55K

wire springs 87x176 60 4-23

	EUR	CODE
	238,00	164261W_
	238,00	164261CH_
	238,00	164261B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x495	>90	3
3000K	2x530	>90	5

ALWAYS USE

driver | 700mA | only 1x needed

	EUR	CODE
14W dim	39,00	90225502
28W DALI	67,00	90245704

more options and specs on page 900





PRIVATE RESIDENCE | UMAMI STUDIO BELGIUM

BLIEK

Ceiling recessed







MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-bliek-round

IC rated



1.0 LED

LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 0°-60°|355° M-33° L80|55K

wire springs 127 75 4-25

	EUR	CODE
	209,00	125361W_
	209,00	125361K_
	209,00	125361B_

LIGHT COLOUR	LUMEN | CRI	CODE
2700K	600/810 | >90	3
3000K	635/855 | >90	5
4000K	670/905 | >90	7
2000-3000K	445/660 | >90	9

LED module 20 years replaceability



1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-60°|350°

wire springs 127 75 4-25

	EUR	CODE
	148,00	125120W0
	148,00	125120K0
	148,00	125120B0

ALWAYS USE

quick connect driver | 500mA

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

hidden

HIDDEN CHAMPIONS

Subtiele inbouwarmaturen blijven elegant op de achtergrond en zetten elke ruimte perfect in scène. Maar lage plafonds of weinig inbouwruimte maken de installatie vaak lastig. De oplossing: ultradunne inbouwarmaturen van Wever & Ducré – compact, stijlvol en ideaal voor renovaties en kleine appartementen.

Des luminaires encastrés discrets restent élégants en arrière-plan tout en sublimant chaque pièce. Mais les plafonds bas ou l'espace limité compliquent souvent l'installation. La solution : des luminaires encastrés ultra-plats de Wever & Ducré – compacts, élégants et idéals pour les rénovations et les petits appartements.

QITO 1.0	p. 57	60 mm
MATCH point 1.0 trimless	p. 61	60 mm
MATCH point 1.0	p. 61	50 mm
BLIEK petit 1.0 | 2.0	p. 63	60 mm
LINOO	p. 71	60 mm
PIRRO petit	p. 75	60 mm
PIRRO 2.0 | 4.0 | 6.0	p. 77	60 mm
PLANO petit	p. 83	65 mm
STRANGE petit trimless	p. 87	65 mm
DEEP bijou 2.0	p. 99	67 mm
DEEP petit	p. 103	60 mm
DEEP ADJUST petit	p. 113	65 mm
RONY point	p. 123	60 mm
RONY petit	p. 125	51 mm
RONY ADJUST petit	p. 127	63 mm
CENO 2.0 | 3.0	p. 133	60 mm
MATCH 1.0 trimless	p. 137	67 mm
MATCH 2.0	p. 141	60 mm
MATCH sneak	p. 143	53 mm
MATCH stick 1.0 | 1.0 trimless	p. 145	67 mm
DEEP petit IP65	p. 159	60 mm
RINI SNEAK IP44	p. 167	52 mm
MIRBI IP44	p. 171	50 mm
CITY IP44	p. 173	50 mm





LINOO

Ceiling recessed



















1.0 TRIMLESS

LED PCB 3W | 350mA | 6V
aluminium | polycarbonate
light colour selectable via dip switch

IP20 M-39° L80|50K

wire springs 54-58 60 4-26

2700K/3000K | CRI >90 | 125lm

	EUR	CODE
	88,00	109961WW9
	88,00	109961BB9

ALWAYS USE

driver | 350mA

	EUR	CODE
3.5W	34,00	90213102
7W dim*	33,50	90223301
14W DALI*	64,50	90243502

*revision opening required and
2 fixtures needed
more options and specs on page 896

1.0

LED PCB 3W | 350mA | 6V
aluminium | polycarbonate
light colour selectable via dip switch

IP20 M-39° L80|50K

wire springs 36x39 60 4-28

2700K/3000K | CRI >90 | 125lm

	EUR	CODE
	56,00	109461WW9
	56,00	109461BB9

ALWAYS USE

driver | 350mA

	EUR	CODE
3.5W	34,00	90213102
7W dim*	33,50	90223301
14W DALI*	64,50	90243502

*revision opening required and
2 fixtures needed
more options and specs on page 896

2.0

LED PCB 5W | 350mA | 12V
aluminium | polycarbonate
light colour selectable via dip switch

IP20 M-39° L80|50K

wire springs 36x67 60 4-28

2700K/3000K | CRI >90 | 2x125lm

	EUR	CODE
	75,00	109561WW9
	75,00	109561BB9

ALWAYS USE

driver | 350mA

	EUR	CODE
6W	25,50	90213303
7W dim*	33,50	90223301
14W DALI*	64,50	90243502

*revision opening required
more options and specs on page 896

back



LINOO

Ceiling recessed

211













4.0

LED PCB 8W | 350mA | 22V
aluminium | polycarbonate
light colour selectable via dip switch

IP20 M-39° L80|50K

wire springs 118x36 60 4-28

2700K/3000K | CRI >90 | 4x125lm

	EUR	CODE
	98,00	109161WW9
	98,00	109161BB9

ALWAYS USE

driver | 350mA

	EUR	CODE
10W dim	35,50	90223406
14W DALI	64,50	90243502

more options and specs on page 896

4.1

LED PCB 8W | 350mA | 22V
aluminium | polycarbonate
light colour selectable via dip switch

IP20 M-39° L80|50K

wire springs 63x59 60 4-28

2700K/3000K | CRI >90 | 4x125lm

	EUR	CODE
	92,00	109261WW9
	92,00	109261BB9

ALWAYS USE

driver | 350mA

	EUR	CODE
10W dim	35,50	90223406
14W DALI	64,50	90243502

more options and specs on page 896

8.0

LED PCB 16W | 700mA | 22V
aluminium | polycarbonate
light colour selectable via dip switch

IP20 M-39° L80|50K

wire springs 226x36 60 4-28

2700K/3000K | CRI >90 | 8x125lm

	EUR	CODE
	158,00	109361WW9
	158,00	109361BB9

ALWAYS USE

driver | 700mA

	EUR	CODE
20W dim	45,50	90225604
14W DALI	67,00	90245704

more options and specs on page 900



PRIVATE RESIDENCE | ORNELLA ABOUAF FRANCE

PIRRO petit

Ceiling recessed

213









2.0

LED COB 4W | 350mA | 12V
aluminium

IP20 M-28° L80|50K

wire springs 64x33 60 4-25

	EUR	CODE
	82,00	129151E_
	82,00	129151WM_
	82,00	129151CH_
	82,00	129151B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x160	>90	3
3000K	2x165	>90	5

ALWAYS USE

driver | 350mA

	EUR	CODE
4.5W dim	33,00	90223101
14W DALI	64,50	90243502

revision opening required
more options and specs on page 897

4.0

LED COB 8W | 350mA | 24V
aluminium

IP20 M-28° L80|50K

wire springs 116x33 60 4-25

	EUR	CODE
	128,00	129251E_
	128,00	129251WM_
	128,00	129251CH_
	128,00	129251B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	4x160	>90	3
3000K	4x165	>90	5

ALWAYS USE

driver | 350mA

	EUR	CODE
10W dim	35,50	90223406
14W DALI	64,50	90243502

more options and specs on page 896

6.0

LED COB 12W | 350mA | 36V
aluminium

IP20 M-28° L80|50K

wire springs 168x33 60 4-25

	EUR	CODE
	178,00	129351E_
	178,00	129351WM_
	178,00	129351CH_
	178,00	129351B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	6x160	>90	3
3000K	6x165	>90	5

ALWAYS USE

driver | 350mA

	EUR	CODE
13W dim	42,50	90223404
14W DALI	64,50	90243502

more options and specs on page 896





LOXONE VERSIONS ONLINE
weverducre.com/more-pirro-petit

back



LA PARISIENNE | I:ARHITEKT LJUBOVIC | MONTENEGRO

PIRRO

Ceiling recessed









1.0

LED COB 5W | 500mA | 9V
aluminium

IP20 M-32° L70|55K

wire springs 50x50 60 4-25

	EUR	CODE
	78,00	150161E_
	78,00	150161J_
	78,00	150161K_
	78,00	150161B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	395	>90	3
3000K	410	>90	5

2.0

LED COB 9W | 500mA | 18V
aluminium

IP20 M-32° L70|55K

wire springs 93x50 60 4-25

	EUR	CODE
	98,00	150261E_
	98,00	150261J_
	98,00	150261K_
	98,00	150261B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x395	>90	3
3000K	2x410	>90	5

60 mm
low recessed

IC rated

ALWAYS USE

driver | 500mA

	EUR	CODE
6W	33,00	90214201
6.5W dim*	25,50	90224301
24W DALI*	67,00	90244701

*revision opening required
more options and specs on page 897

ALWAYS USE

driver | 500mA

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
24W DALI	67,00	90244701

more options and specs on page 897

back



PRIVATE RESIDENCE | INTERIOR STUDIO VAN MAANEN THE NETHERLANDS

PIRRO

Ceiling recessed







4.0

LED COB 17W | 500mA | 36V
aluminium

IP20 M-32° L70|55K

wire springs 181x50 60 4-25

	EUR	CODE
	149,00	150461E_
	149,00	150461J_
	149,00	150461K_
	149,00	150461B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	4x395	>90	3
3000K	4x410	>90	5

ALWAYS USE

driver | 500mA | only 1x needed

	EUR	CODE
17.5W	39,00	90218601
19W dim	45,50	90224602
24W DALI	67,00	90244701

more options and specs on page 898

6.0

LED COB 25W | 500mA | 2x27V
aluminium

IP20 M-32° L70|55K

wire springs 269x50 60 4-25

	EUR	CODE
	198,00	150661E_
	198,00	150661J_
	198,00	150661K_
	198,00	150661B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	6x395	>90	3
3000K	6x410	>90	5

ALWAYS USE

driver | 500mA | 2x needed

	EUR	CODE
17.5W	39,00	90218601
19W dim	45,50	90224602
24W DALI	67,00	90244701

more options and specs on page 898





back


Kingsley
Amis



PRIVATE RESIDENCE | ANKER & CO DENMARK

PLANO petit

Ceiling recessed













1.0

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-25°|355° M-31° L70|55K

wire springs 54x59 65 2-22

	EUR	CODE
	98,00	162461W_
	98,00	162461Q_
	98,00	162461B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	550	>90	3
3000K	580	>90	5
2000-3000K | 16V	465	>90	9

LED module 20 years replaceability

2.0

2x LED COB 6W | 350mA | 17V
aluminium

IP20 0°-25°|355° M-31° L70|55K

wire springs 54x110 65 2-22

	EUR	CODE
	169,00	162561W_
	169,00	162561Q_
	169,00	162561B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x550	>90	3
3000K	2x580	>90	5
2000-3000K | 16V	2x465	>90	9

LED module 20 years replaceability

3.0

3x LED COB 6W | 350mA | 17V
aluminium

IP20 0°-25°|355° M-31° L70|55K

wire springs 54x162 65 2-22

	EUR	CODE
	238,00	162661W_
	238,00	162661Q_
	238,00	162661B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	3x550	>90	3
3000K	3x580	>90	5
2000-3000K | 16V	3x465	>90	9

LED module 20 years replaceability



ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
10W dim	35,50	90223406
14W DALI*	64,50	90243502

*revision opening required
more options and specs on page 896

ALWAYS USE

quick connect driver | 350mA
2x needed

	EUR	CODE
6W	25,50	90213303
10W dim	35,50	90223406
14W DALI	64,50	90243502

more options and specs on page 896

ALWAYS USE

quick connect driver | 350mA
3x needed

	EUR	CODE
6W	25,50	90213303
10W dim	35,50	90223406
14W DALI	64,50	90243502

more options and specs on page 896

MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-plano-petit



PRIVATE RESIDENCE | STUDIO BENOIT BELGIUM

PLANO

Ceiling recessed













1.0 LED

LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 0°-35°|355° M-34° L80|55K

wire springs 74x78 95 2-18

	EUR	CODE
	103,00	118561W_
	103,00	118561Q_
	103,00	118561B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	610/820	>90	3
3000K	645/870	>90	5
2000-3000K	450/665	>90	9

LED module 20 years replaceability

ALWAYS USE

quick connect driver | 500mA

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

2.0 LED

2x LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 0°-35°|355° M-34° L80|55K

wire springs 74x148 95 2-18

	EUR	CODE
	189,00	118661W_
	189,00	118661Q_
	189,00	118661B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x610/820	>90	3
3000K	2x645/870	>90	5
2000-3000K	2x450/665	>90	9

LED module 20 years replaceability

ALWAYS USE

quick connect driver | 500mA
2x needed

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-35°|355°

wire springs 74x78 125 2-18

	EUR	CODE
	49,00	118120W0
	49,00	118120Q0
	49,00	118120B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

2.0 PAR16

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-35°|355°

wire springs 74x148 125 2-18

	EUR	CODE
	82,00	118220W0
	82,00	118220Q0
	82,00	118220B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



PRIVATE RESIDENCE SPAIN

STRANGE petit

Ceiling recessed













1.0 TRIMLESS

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-25°|355°- M-31° L80|55K

	EUR	CODE
	103,00	163461W_
	103,00	163461M_
	103,00	163461Q_
	103,00	163461B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	550	>90	3
3000K	580	>90	5
2000-3000K	465	>90	9

LED module 20 years replaceability

2.0 TRIMLESS

2x LED COB 6W | 350mA | 17V
aluminium

IP20 0°-25°|355°- M-31° L80|55K

	EUR	CODE
	178,00	163561W_
	178,00	163561M_
	178,00	163561Q_
	178,00	163561B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x550	>90	3
3000K	2x580	>90	5
2000-3000K	2x465	>90	9

LED module 20 years replaceability

3.0 TRIMLESS

3x LED COB 6W | 350mA | 17V
aluminium

IP20 0°-25°|355°- M-31° L80|55K

	EUR	CODE
	251,00	163661W_
	251,00	163661M_
	251,00	163661Q_
	251,00	163661B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	3x550	>90	3
3000K	3x580	>90	5
2000-3000K	3x465	>90	9

LED module 20 years replaceability

ALWAYS USE

alu plasterkit U64x64 65 7-32

	EUR	CODE
	37,00	90017202

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
10W dim	35,50	90223406
14W DALI	64,50	90243502

more options and specs on page 896

ALWAYS USE

alu plasterkit U64x117 65 7-32

	EUR	CODE
	39,00	90017205

quick connect driver | 350mA
2x needed

	EUR	CODE
6W	25,50	90213303
10W dim	35,50	90223406
14W DALI	64,50	90243502

more options and specs on page 897

ALWAYS USE

alu plasterkit U64x169 65 7-32

	EUR	CODE
	43,00	90017208

quick connect driver | 350mA
3x needed

	EUR	CODE
6W	25,50	90213303
10W dim	35,50	90223406
14W DALI	64,50	90243502

more options and specs on page 896



LOXONE VERSIONS ONLINE
weverducre.com/more-strange-petit



VULÉ LUXURY APARTMENTS MILANO | MAST ARCHITECTURE MILAN | ITALY

STRANGE trimless

Ceiling recessed













1.0 LED

LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 0°-35°|355° M-34° L80|55K

	EUR	CODE
	111,00	131461W_
	111,00	131461Q_
	111,00	131461B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	610/820	>90	3
3000K	645/870	>90	5
2000-3000K	450/665	>90	9

LED module 20 years replaceability

ALWAYS USE

alu plasterkit 86x86 95 7-32

	EUR	CODE
	41,00	90017120

quick connect driver | 500mA

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

2.0 LED

2x LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 0°-35°|355° M-34° L80|55K

	EUR	CODE
	210,50	131561W_
	210,50	131561Q_
	210,50	131561B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x610/820	>90	3
3000K	2x645/870	>90	5
2000-3000K	2x450/665	>90	9

LED module 20 years replaceability

ALWAYS USE

alu plasterkit 86x156 95 7-32

	EUR	CODE
	45,00	90017121

quick connect driver | 500mA
2x needed

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-35°|355°

	EUR	CODE
	57,00	1311120W0
	57,00	1311120Q0
	57,00	1311120B0

ALWAYS USE

alu plasterkit 86x86 125 7-32

	EUR	CODE
	41,00	90017120

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

2.0 PAR16

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-35°|355°

	EUR	CODE
	103,50	1312220W0
	103,50	1312220Q0
	103,50	1312220B0

ALWAYS USE

alu plasterkit 86x156 125 7-32

	EUR	CODE
	45,00	90017121

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



PRIVATE RESIDENCE | STUDIO BENOIT BELGIUM

SNEAK

Ceiling recessed











1.0 TRIMLESS

LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 0°-35°|355° M-30° L80|55K

	EUR	CODE
	124,00	155551WW_
	127,00	155551BM_
	124,00	155551BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	340/460	>90	3
3000K	360/485	>90	5
2000-3000K	250/370	>90	9

LED module 20 years replaceability

ALWAYS USE

alu plasterkit 86x86 95 7-32

	EUR	CODE
	41,00	90017120

quick connect driver | 500mA

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

2.0 TRIMLESS

2x LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 0°-35°|355° M-30° L80|55K

	EUR	CODE
	236,50	155651WW_
	242,50	155651BM_
	236,50	155651BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x340/460	>90	3
3000K	2x360/485	>90	5
2000-3000K	2x250/370	>90	9

LED module 20 years replaceability

ALWAYS USE

alu plasterkit 86x156 95 7-32

	EUR	CODE
	45,00	90017121

quick connect driver | 500mA
2x needed

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

LOXONE VERSIONS ONLINE
weverducre.com/more-sneak

back



PRIVATE RESIDENCE | RARDO ARCHITECTS SPAIN

SNEAK

Ceiling recessed









1.0

LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 0°-35°|355° M-30° L80|55K

wire springs 74x78 95 2-18

	EUR	CODE
	116,00	155751WW_
	119,00	155751BM_
	116,00	155751BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	340/460	>90	3
3000K	360/485	>90	5
2000-3000K	250/370	>90	9

LED module 20 years replaceability

ALWAYS USE

quick connect driver | 500mA

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

2.0

2x LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 0°-35°|355° M-30° L80|55K

wire springs 74x148 95 2-18

	EUR	CODE
	215,00	155851WW_
	221,00	155851BM_
	215,00	155851BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x340/460	>90	3
3000K	2x360/485	>90	5
2000-3000K	2x250/370	>90	9

LED module 20 years replaceability

ALWAYS USE

quick connect driver | 500mA
2x needed

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

LOXONE VERSIONS ONLINE
weverducre.com/more-sneak

deep how

weverducre.com/deep

DEEP



point 1.0
LED
p. 97



bijou 1.0
LED
p. 99



bijou 2.0
LED
p. 99



petit 1.0
LED
p. 103



1.0
LED | PAR16
p. 107



point IP44 1.0
LED
p. 155



bijou IP65 1.0
LED
p. 157



petit IP65 1.0
LED
p. 159



IP65 | IP44 1.0
LED | PAR16
p. 161

DEEP ADJUST



petit 1.0
LED
p. 113



petit trimless 1.0
LED
p. 113



1.0
LED | PAR16
p. 119



trimless 1.0
LED | PAR16
p. 117



2.0
LED | PAR16
p. 121

DEEP CONNECTIONS

DEEP en DEEPER zorgen voor klassiek downlight in gangen, woonkamers of badkamers – optioneel in IP44 of IP65 voor spat- en straalwaterbescherming. De familie wordt nu aangevuld met DEEP IQ uit 3D-geprint materiaal en de vrijwel onzichtbare trimless ADJUST-varianten.

DEEP et DEEPER offrent un éclairage directionnel classique pour les couloirs, salons ou salles de bain – en option en IP44 ou IP65 pour une protection contre les éclaboussures et les jets d'eau. La gamme s'enrichit désormais de DEEP IQ en matériau imprimé en 3D, ainsi que des variantes ADJUST sans cadre presque invisibles.

DEEPER



1.0
LED | PAR16
p. 109



IP44 1.0
LED | PAR16
p. 163

DEEP IQ



petit 1.0
LED
p. 101



1.0
LED
p. 105

DEEP ADJUST IQ



petit 1.0
LED
p. 111



1.0
LED
p. 115



PRIVATE RESIDENCE SPAIN

DEEP point

Ceiling recessed







1.0

LED COB 5W | 250mA | 17V
aluminium

IP20 M-32° L80|50K

wire springs 40-41 68 4-25

	EUR	CODE
	49,00	185261W_
	49,00	185261M_
	49,00	185261Q_
	49,00	185261B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	405	>90	3
3000K	425	>90	5

1.0 IP44

LED COB 5W | 250mA | 17V
aluminium

IP44 M-32° L80|50K

wire springs 40-41 68 4-25

	EUR	CODE
	62,00	185161W_
	62,00	185161Q_
	62,00	185161B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	355	>90	3
3000K	400	>90	5

ALWAYS USE

quick connect driver | 250mA

	EUR	CODE
5W dim	33,00	90226201
10W DALI	64,50	90246403

revision opening required
more options and specs on page 895

ALWAYS USE

quick connect driver | 250mA

	EUR	CODE
5W dim	33,00	90226201
10W DALI	64,50	90246403

revision opening required
more options and specs on page 895

LOXONE VERSIONS ONLINE
weverducre.com/more-deep-point

IC rated

155

back



PRIVATE RESIDENCE | ARNOLD ORY FRANCE

DEEP bijou

Ceiling recessed









1.0

LED COB 4W | 250mA | 17V
aluminium

IP20 M-31° L80|50K

wire springs 50-52 85 4-25

	EUR	CODE
	57,00	165161W_
	57,00	165161M_
	57,00	165161G_
	57,00	165161Q_
	57,00	165161B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	480	>90	3
3000K	510	>90	5

2.0

2x LED COB 4W | 250mA | 34V
aluminium

IP20 M-31° L80|50K

wire springs 50-52x100-104 67 4-25

	EUR	CODE
	109,00	165261W_
	109,00	165261M_
	109,00	165261G_
	109,00	165261Q_
	109,00	165261B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x480	>90	3
3000K	2x510	>90	5





MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-deep-bijou

ALWAYS USE

quick connect driver | 250mA

	EUR	CODE
5W dim	33,00	90226201
10W DALI*	64,50	90246403

*revision opening required
more options and specs on page 895

ALWAYS USE

quick connect driver | 250mA
only 1x needed

	EUR	CODE
10.5W dim	33,00	90226501
10W DALI	64,50	90246403

more options and specs on page 895

back











high efficient LED

reduced CO_2

3D printed by IQ LUX

MORE VERSIONS ONLINE
weverducre.com/more-deep-petit-IQ

back

DEEP petit IQ

Ceiling recessed



1.0

LED COB 3W | 200mA | 18V
recycled PET for RP
others 3D printed ASA

IP20 W-41° L80|80K

blade springs 74-76 .85 min.8

	EUR	CODE
	88,00	199151W_
	88,00	199151SG_
	88,00	199151RP_
	88,00	199151B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	360	>90	3
3000K	370	>90	5

ALWAYS USE

quick connect driver | 200mA

	EUR	CODE
10W dim*	33,00	90226402
8W DALI	64,50	90246302

*min. 2 luminaires per driver
more options and specs on page 894



PRIVATE RESIDENCE | ROOD3 INTERIEURONTWERP BELGIUM

DEEP petit

Ceiling recessed







1.0

LED COB 6W | 350mA | 17V
aluminium

IP20 M-31° L80|50K

wire springs Ø68-70 60 4-23

	EUR	CODE
	79,00	153561W_
	79,00	153561M_
	79,00	153561G_
	79,00	153561Q_
	79,00	153561B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	615	>90	3
3000K	650	>90	5
2000-3000K | 16V	465	>90	9

1.0 IP65

LED COB 6W | 350mA | 17V
aluminium

IP65 M-31° L80|50K

wire springs Ø68-70 60 4-25

	EUR	CODE
	96,00	153761W_
	96,00	153761Q_
	96,00	153761B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	590	>90	3
3000K	615	>90	5





LOXONE VERSIONS ONLINE
weverducre.com/more-deep-petit

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
10W dim	35,50	90223406
14W DALI*	64,50	90243502

*revision opening required
more options and specs on page 896

ALWAYS USE

driver | 350mA

	EUR	CODE
6W | IP20	25,50	90213303
10w dim | IP20	35,50	90223406
17W | IP68*	69,00	90213602

*revision opening required
more options and specs on page 896

back



DEEP IQ

Ceiling recessed











1.0

LED COB 6W | 180mA | 36V
recycled PET for RP
others 3D printed ASA

IP20 M-40° L80|80K

blade springs 85-87 77 min.8

	EUR	CODE
	105,00	199351W_
	105,00	199351SG_
	105,00	199351RP_
	105,00	199351B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	780	>90	3
3000K	800	>90	5

high efficient LED

reduced CO_2

3D printed by IQ LUX

ALWAYS USE

quick connect driver | 180mA

	EUR	CODE
7.5W dim	33,00	90226202
7.2W DALI	64,50	90246301

more options and specs on page 894

MORE VERSIONS ONLINE
weverducre.com/more-deep-IQ

back



LOOTENS | OR ARCHITECTEN | WIM LAHOUSSE HARELBEKE | BELGIUM

DEEP

Ceiling recessed







1.0 LED

LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 M-34° L80|55K

wire springs 76-79 90 4-27

	EUR	CODE
	95,00	184261W_
	95,00	184261M_
	95,00	184261G_
	95,00	184261Q_
	95,00	184261B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	635/855	>90	3
3000K	670/905	>90	5
4000K	710/955	>90	7
2000-3000K	470/695	>90	9

LED module 20 years replaceability

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

wire springs 76-79 115 4-27

	EUR	CODE
	29,00	112120W0
	29,00	112120M0
	29,00	112120G0
	29,00	112120Q0
	29,00	112120B0

ALWAYS USE

quick connect driver | 500mA

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-deep

745

back



PRIVATE RESIDENCE | STUDIO ZUYD THE NETHERLANDS

DEEPER

Ceiling recessed







1.0 LED

LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 M-34° L80|55K

wire springs 76-79 90 4-38

	EUR	CODE
	102,50	152361W_
	102,50	152361M_
	102,50	152361Q_
	102,50	152361B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	635/850	>90	3
3000K	670/900	>90	5
2000-3000K	470/695	>90	9

LED module 20 years replaceability

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

wire springs 76-79 120 4-38

	EUR	CODE
	48,50	152120W0
	48,50	152120M0
	48,50	152120Q0
	48,50	152120B0

ALWAYS USE

quick connect driver | 500mA

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-deeper

163



DEEP ADJUST petit IQ

Ceiling recessed





1.0

LED COB 3W | 200mA | 18V
recycled PET for RP
others 3D printed ASA

IP20 0°-25°|360° W-41° L80|80K

blade springs 74-76 87 min.8

	EUR	CODE
	98,00	199251W_
	98,00	199251SG_
	98,00	199251RP_
	98,00	199251B_

LIGHT COLOUR	LUMEN|CRI	CODE
2700K	360|>90	3
3000K	370|>90	5

high efficient LED

reduced CO_2

3D printed by IQ LUX

ALWAYS USE

quick connect driver | 200mA

	EUR	CODE
10W dim*	33,00	90226402
8W DALI	64,50	90246302

*2 luminaires per driver
more options and specs on page 894

MORE VERSIONS ONLINE
weverducre.com/more-deep-adjust-petit-IQ

back



DU ROC SUISSE | BOCION & BILLIGER SA ZUG | SWITZERLAND

DEEP ADJUST petit

Ceiling recessed







1.0 TRIMLESS

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-35°|360° M-31° L70|50K

	EUR	CODE
	93,00	153461W_
	93,00	153461Q_
	93,00	153461B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	555	>90	3
3000K	585	>90	5
2000-3000K | 16V	470	>90	9

LED module 20 years replaceability

1.0

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-35°|355° M-31° L70|50K

wire springs 68-70 65 4-23

	EUR	CODE
	89,50	153661W_
	89,50	153661M_
	89,50	153661G_
	89,50	153661SG_
	89,50	153661ME_
	89,50	153661Q_
	89,50	153661B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	555	>90	3
3000K	585	>90	5
2000-3000K | 16V	470	>90	9

LED module 20 years replaceability

ALWAYS USE

alu plasterkit 78-80 65 12.5, 15, 20, 25

	EUR	CODE
	22,00	90017210

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
10W dim	35,50	90223406
14W DALI*	64,50	90243502

*revision opening required and
more options and specs on page 896

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
10W dim	35,50	90223406
14W DALI*	64,50	90243502

*revision opening required and
more options and specs on page 896



MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-deep-adjust-petit

back



DEEP ADJUST IQ

Ceiling recessed











1.0

LED COB 6W | 180mA | 36V
recycled PET for RP
others 3D printed ASA

IP20 0°-21°|360° M-40° L80|80K

blade springs 85-87 85 min.8

	EUR	CODE
	116,00	199451W_
	116,00	199451SG_
	116,00	199451RP_
	116,00	199451B_

LIGHT COLOUR	LUMEN|CRI	CODE
2700K	780|>90	3
3000K	800|>90	5

high efficient LED

reduced CO_2

3D printed by IQ LUX

ALWAYS USE

quick connect driver | 180mA

	EUR	CODE
7W dim	33,00	90226202
7.2W DALI	64,50	90246301

more options and specs on page 894

MORE VERSIONS ONLINE
weverducre.com/more-deep-adjust-IQ

back



DEEP ADJUST trimless

Ceiling recessed













1.0 LED

LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 0°-35°|355° M-34° L80|55K

	EUR	CODE
	110,00	184861W_
	110,00	184861M_
	110,00	184861Q_
	110,00	184861B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	635/855	>90	3
3000K	670/905	>90	5
4000K	710/955	>90	7
2000-3000K	470/695	>90	9

LED module 20 years replaceability

ALWAYS USE

alu plasterkit Ø105-110 ⎍95 ⇦12.5, 15, 20, 25

	EUR	CODE
	26,00	90017209

quick connect driver | 500mA

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-35°|355°

	EUR	CODE
	56,00	112820W0
	56,00	112820M0
	56,00	112820Q0
	56,00	112820B0

ALWAYS USE

alu plasterkit Ø105-110 ⎍120 ⇦12.5, 15, 20, 25

	EUR	CODE
	26,00	90017209

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-deep-adjust-trimless



PRIVATE RESIDENCE | AJ ARCHITECTEN BELGIUM

DEEP ADJUST

Ceiling recessed













1.0 LED

LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 0°-35°|355° M-34° L80|55K

wire springs 86-89 90 4-23

	EUR	CODE
	98,50	184361W_
	98,50	184361M_
	98,50	184361G_
	98,50	184361Q_
	98,50	184361B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	635/855	>90	3
3000K	670/905	>90	5
4000K	710/955	>90	7
2000-3000K	470/695	>90	9

LED module 20 years replaceability

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-35°|355°

wire springs 86-89 115 4-23

	EUR	CODE
	44,50	112320W0
	44,50	112320M0
	44,50	112320G0
	44,50	112320Q0
	44,50	112320B0

ALWAYS USE

quick connect driver | 500mA

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-deep-adjust

back



PRIVATE RESIDENCE | INTÉRIEURS D'ARCHITECTES FRANCE

DEEP ADJUST

Ceiling recessed







2.0 LED

2x LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 0°-35°|355° M-34° L80|55K

wire springs 89x172-178 90 4-23

	EUR	CODE
	192,00	184761W_
	192,00	184761M_
	192,00	184761Q_
	192,00	184761B_

LIGHT COLOUR	LUMEN | CRI	CODE
2700K	2x635/855 | >90	3
3000K	2x670/905 | >90	5
4000K	2x710/955 | >90	7
2000-3000K	2x470/695 | >90	9

LED module 20 years replaceability

2.0 PAR16

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-35°|355°

wire springs 89x172-178 115 4-23

	EUR	CODE
	85,00	112720W0
	85,00	112720M0
	85,00	112720Q0
	85,00	112720B0

ALWAYS USE

quick connect driver | 500mA
2x needed

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

LOXONE VERSIONS ONLINE
weverducre.com/more-deep-adjust



RONY point

Ceiling recessed





1.0

LED COB 5W | 250mA | 17V
aluminium

IP20 M-32° L80|50K

wire springs 48-51 60 4-25

	EUR	CODE
	55,00	193161W_
	55,00	193161Q_
	55,00	193161B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	405	>90	3
3000K	425	>90	5





ALWAYS USE

quick connect driver | 250mA

	EUR	CODE
5W dim	33,00	90226201
10W DALI*	64,50	90246403

*revision opening required
more options and specs on page 895

MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-rony-point

back







RONY petit

Ceiling recessed

ø80 | 46

1.0

LED COB 6W | 350mA | 17V
aluminium

IP20 M-31° L80|50K

wire springs 68-70 51 4-24

	EUR	CODE
	86,00	110361W_
	86,00	110361B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	650	>90	3
3000K	685	>90	5
2000K-3000K | 16V	495	>90	9

51 mm
low recessed

IC rated

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
10W dim	35,50	90223406
14W DALI*	64,50	90243502

*revision opening required
more options and specs on page 896

LOXONE VERSIONS ONLINE
weverducre.com/more-rony-petit

back



PRIVATE RESIDENCE | STUDIO BINNEN THE NETHERLANDS

RONY ADJUST petit

Ceiling recessed









1.0

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-35°|355° M-31° L80|50K

wire springs 68-70 63 4-22

	EUR	CODE
	97,00	110461W_
	97,00	110461Q_
	97,00	110461B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	555	>90	3
3000K	585	>90	5
2000K-3000K | 16V	470	>90	9





ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
10W dim	35,50	90223406
14W DALI*	64,50	90243502

*revision opening required
more options and specs on page 896

MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-rony-adjust-petit

back



PRIVATE RESIDENCE | CANDICE BRUNY FRANCE

RONY ADJUST

Ceiling recessed









1.0 LED

LED COB 6/9W | 350/500mA | 17V
aluminium

IP20 0°-35°|355° M-34° L80|55K

wire springs 102-104 90 4-25

	EUR	CODE
	133,00	110261W_
	133,00	110261B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	635/860	>90	3
3000K	675/905	>90	5
2000-3000K	475/700	>90	9

LED module 20 years replaceability

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-35°|355°

wire springs 102-104 110 4-25

	EUR	CODE
	79,00	110120W0
	79,00	110120B0

ALWAYS USE

quick connect driver | 500mA

	EUR	CODE
10W	25,50	90214406
10W dim	37,50	90224403
15W DALI	64,50	90244501

more options and specs on page 898

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-rony-adjust

back



PRIVATE RESIDENCE | INTERIOR STUDIO VAN MAANEN THE NETHERLANDS

CENO

Ceiling recessed

181
321
585











1.0 SEMI RECESSED

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-90°|350° M-31° L70|55K

	EUR	CODE
	143,00	176561W_
	143,00	176561B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	500	>90	3
3000K	530	>90	5

1.0

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-90°|350° M-31° L70|55K

wire springs 45-47 75 4-26

	EUR	CODE
	135,00	176161W_
	135,00	176161G_
	135,00	176161Q_
	135,00	176161K_
	135,00	176161CH_
	135,00	176161B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	500	>90	3
3000K	530	>90	5
2000-3000K | 16V	345	>90	9





OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
7W dim	33,50	90223301
14W DALI	64,50	90243502

revision opening required
more options and specs on page 896

ALWAYS USE

driver | 350mA

	EUR	CODE
6W	25,50	90213303
7W dim	33,50	90223301
14W DALI*	64,50	90243502

*revision opening required
more options and specs on page 896

MORE VERSIONS ONLINE
weverducre.com/more-ceno

back



OFFICE BOES & VERRUE | ARCHITECT DEWITTE KORTRIJK | BELGIUM

CENO

Ceiling recessed

















OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

LOXONE VERSIONS ONLINE

weverducre.com/more-ceno-recessed

1.1

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-90°|350° M-31° L70|55K

blade springs 32x66 75 min. 4

	EUR	CODE
	135,00	176461W_
	135,00	176461Q_
	135,00	176461K_
	135,00	176461B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	500	>90	3
3000K	530	>90	5

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
7W dim	33,50	90223301
14W DALI	64,50	90243502

more options and specs on page 896

2.0

2x LED COB 6W | 700mA | 17V
aluminium

IP20 0°-90°|350° M-31° L70|55K

blade springs 32x145 60 min. 4

	EUR	CODE
	188,00	176261W_
	188,00	176261Q_
	188,00	176261K_
	188,00	176261B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x500	>90	3
3000K	2x530	>90	5

ALWAYS USE

driver | 700mA | only 1x needed

	EUR	CODE
14W dim	39,00	90225502
28W DALI	67,00	90245704

more options and specs on page 900

3.0

3x LED COB 6W | 700mA | 26V
aluminium

IP20 0°-90°|350° M-31° L70|55K

blade springs 32x221 60 min. 4

	EUR	CODE
	238,00	176361W_
	238,00	176361Q_
	238,00	176361K_
	238,00	176361B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	3x500	>90	3
3000K	3x530	>90	5

ALWAYS USE

driver | 700mA | only 1x needed

	EUR	CODE
20W dim	45,50	90225604
28W DALI	67,00	90245704

more options and specs on page 900

181
321
585
back



reddot winner 2024

LECA

Ceiling recessed







189

325

569



1.0

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-90°|350° M-31° L80|50K

wire springs 40-41 75 4-26

2700K | CRI >90 | 585lm

	EUR	CODE
	142,00	188161W3
	142,00	188161Q3
	142,00	188161B3





OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
7W dim	33,50	90223301
14W DALI*	64,50	90243502

*revision opening required
more options and specs on page 896

LOXONE VERSIONS ONLINE
weverducre.com/more-leca

back



WALDBLICK WELLNESS | EW STUDIO FREUDENSTADT | GERMANY

DESIGN AWARD 2023 · GOOD DESIGN · reddot winner 2023

MATCH

Ceiling recessed







1.0 TRIMLESS

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-90°|360° M-30° L80|50K

45-47 67 4-26

	EUR	CODE
	165,20	190851W_
	173,20	190851BL_
	173,20	190851Q_
	165,20	190851B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	525	>90	3
3000K	555	>90	5

1.0

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-90°|350° M-30° L80|50K

wire springs 45-47 75 4-26

	EUR	CODE
	134,00	190151W_
	142,00	190151BL_
	142,00	190151Q_
	134,00	190151B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	525	>90	3
3000K	555	>90	5

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
7W dim	33,50	90223301
14W DALI	64,50	90243502

revision opening required
more options and specs on page 896

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
7W dim	33,50	90223301
14W DALI*	64,50	90243502

*revision opening required
more options and specs on page 896



MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-match-recessed

193
329 | 347
415 | 509
571
589 | 685
723 | 729

back





THINKING MU STORE BARCELONA | ISERN SERRA BARCELONA | SPAIN



PRIVATE RESIDENCE | UNIQUE RENOVATIONS BELGIUM

DESIGN AWARD 2023 · GOOD DESIGN · reddot winner 2023



MATCH

Ceiling recessed



2.0

2x LED COB 6W | 700mA | 17V
aluminium

IP20 0°-90°|350° M-30° L80|50K

wire springs 105x30 60 4-26

	EUR	CODE
	208,00	190251W_
	220,00	190251Q_
	208,00	190251B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x515	>90	3
3000K	2x545	>90	5

ALWAYS USE

quick connect driver | 700mA
only 1x needed

	EUR	CODE
14W dim	39,00	90225502
28W DALI	67,00	90245704

more options and specs on page 900





MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-match-recessed

back



PRIVATE RESIDENCE | BUREAU DESTADSBADER BELGIUM

DESIGN AWARD 2023 · GOOD DESIGN · reddot winner 2023

MATCH SNEAK

Ceiling recessed









1.0 TRIMLESS

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-55°|350° M-30° L80|50K

	EUR	CODE
	159,00	190451W_
	167,00	190451L_
	167,00	190451M_
	167,00	190451Q_
	167,00	190451GM_
	159,00	190451B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	535	>90	3
3000K	565	>90	5

1.0

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-55°|350° M-30° L80|50K

wire springs 64-68 53 4-26

	EUR	CODE
	149,00	190351W_
	157,00	190351L_
	157,00	190351M_
	157,00	190351Q_
	157,00	190351GM_
	149,00	190351B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	525	>90	3
3000K	555	>90	5





ALWAYS USE

alu plasterkit 78-80 45 12.5,15,20,25

	EUR	CODE
	22,00	90017210

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
7W dim	33,50	90223301
14W DALI	64,50	90243502

more options and specs on page 896

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
7W dim	33,50	90223301
14W DALI*	64,50	90243502

*revision opening required and
more options and specs on page 896

LOXONE VERSIONS ONLINE
weverducre.com/more-match-sneak

193
329 | 347
415 | 509
571
589 | 685
723 | 729

back



DESIGN AWARD 2023 · GOOD DESIGN · reddot winner 2023

MATCH stick

Ceiling recessed







1.0 TRIMLESS

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-90°|360° M-30° L80|50K

45-47 67 4-26

	EUR	CODE
	221,00	190951W_
	233,20	190951BL_
	221,00	190951B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	525	>90	3
3000K	555	>90	5

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
7W dim	33,50	90223301
14W DALI	64,50	90243502

revision opening required
more options and specs on page 896

1.0

LED COB 6W | 350mA | 17V
aluminium

IP20 0°-90°|360° M-30° L80|50K

40-41 67 4-26

	EUR	CODE
	190,00	190751W_
	198,00	190751BL_
	190,00	190751B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	525	>90	3
3000K	555	>90	5

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W	25,50	90213303
7W dim	33,50	90223301
14W DALI	64,50	90243502

revision opening required
more options and specs on page 896





LOXONE VERSIONS ONLINE
weverducre.com/more-match-stick

193
329 | 347
415 | 509
571
589 | 685
723 | 729



RADISSON RED | DESIGN AGENCY FYRA HELSINKI | FINLAND



RUVI

Ceiling recessed



1.0

G95 max. 12W | E27
220-240VAC | 50-60Hz
aluminium

IP20

54-56 90 7-33

	EUR	CODE
	88,00	1671E0B0

OPTIONAL

G95 5W/5.1W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 395lm	35,00	9003E157

G95 10W | E27 | phase-cut dim
ceramic soft look

	EUR	CODE
2700K | 1060lm	33,00	9003E163

G95 5.4W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 380lm	33,00	9003E111

back

splash

THEY'RE FUN TO BATHE WITH

IP44-armaturen zijn perfect beschermd tegen spatwater, IP65 zelfs tegen waterstralen – ideaal voor badkamers, douches of spa's. De modellen met een geringe inbouwdiepte zijn ideaal bij weinig ruimte en lage plafonds. Beide beschermingsklassen zijn bovendien in vele uitvoeringen verkrijgbaar, niet alleen als spots.

Les luminaires IP44 sont parfaitement protégés contre les éclaboussures, les IP65 même contre les jets d'eau – idéals pour salles de bain, douches ou espaces bien-être. Les modèles plats conviennent aux petits espaces et plafonds bas. Les deux protections existent d'ailleurs en de nombreux formats, pas seulement en spots.

weverducre.com/ip44

PLANO IP44	p. 151
MATCH point IP44	p. 153
DEEP point IP44	p. 155
DEEP bijou IP65	p. 157
DEEP petit IP65	p. 159
DEEP IP65 | IP44	p. 161
DEEPER IP44	p. 163
TAIO IP65	p. 165
RINI SNEAK IP44	p. 167
PERLEZ IP44	p. 169
MIRBI IP44	p. 171
CITY IP44	p. 173
PERLEZ IP44	p. 295
MIRBI IP44	p. 297
TAIO IP65	p. 299
ROB IP44	p. 301
ROBY IP44	p. 303
TOWNA IP44	p. 305
ROSS IP65	p. 307
HAJO IP44	p. 697
PERLEZ IP44	p. 701
PERLEZ CLIP IP44	p. 703
MIRBA IP44	p. 705
MIRBI LONG IP44	p. 707
RIBELLE IP65	p. 709
PAVIO IP65	p. 711





PRIVATE RESIDENCE | STUDIO BENOIT BELGIUM

PLANO IP44

Ceiling recessed







1.0 LED

LED COB 6/9W | 350/500mA | 17V
aluminium

IP44 M-34° L80|55K

wire springs 76x78 90 4-30

	EUR	CODE
	114,00	118861W_
	114,00	118861Q_
	114,00	118861B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	585/785	>90	3
3000K	615/830	>90	5
2000-3000K	430/635	>90	9

LED module 20 years replaceability

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP44

wire springs 74x78 130 4-30

	EUR	CODE
	60,00	118420W0
	60,00	118420Q0
	60,00	118420B0

ALWAYS USE

quick connect driver | 500mA

	EUR	CODE
10W | IP20	25,50	90214406
10W dim | IP20	37,50	90224403
15W DALI | IP20	64,50	90244501

more options and specs on page 898

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-plano-ip44

back



RESTAURANT OSAR | STEENHUYSE INTERIEURARCHITECTEN TIELT | BELGIUM

DESIGN AWARD 2023 · GOOD DESIGN · reddot winner 2023





MATCH point IP44

Ceiling recessed



42

ø45

1.0

LED COB 5W | 250mA | 17V
aluminium

IP44 M-32° L80|50K

wire springs 40-41 68 4-25

	EUR	CODE
	65,00	191261W_
	65,00	191261B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	295	>90	3
3000K	325	>90	5

ALWAYS USE

quick connect driver | 250mA

	EUR	CODE
5W dim | IP20	33,00	90226201
10W DALI | IP20*	64,50	90246403

*revision opening required
more options and specs on page 895

LOXONE VERSIONS ONLINE
weverducre.com/more-match-point

193
329 | 347
415 | 509
571
589 | 685
723 | 729

back



PRIVATE RESIDENCE | VLADIMIR MITROVIĆ SERBIA

DEEP point IP44

Ceiling recessed









1.0

LED COB 5W | 250mA | 17V
aluminium

IP44 M-32° L80|50K

wire springs 40-41 L68 4-25

	EUR	CODE
	62,00	185161W_
	62,00	185161Q_
	62,00	185161B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	355	>90	3
3000K	400	>90	5

ALWAYS USE

quick connect driver | 250mA

	EUR	CODE
5W dim | IP20	33,00	90226201
10W DALI | IP20*	64,50	90246403

*revision opening required
more options and specs on page 895

LOXONE VERSIONS ONLINE
weverducre.com/more-deep-point

IC rated

back



HOTEL MARTIN'S RENTMEESTERIJ | PCP ARCHITECTS BILZEN | BELGIUM

DEEP bijou IP65

Ceiling recessed





1.0

LED COB 4W | 500mA | 8V
aluminium

IP65 M-30° L80|55K

wire springs 50-52 85 4-25

	EUR	CODE
	69,50	165361W_
	69,50	165361Q_
	69,50	165361B_

LIGHT COLOUR	LUMEN|CRI	CODE
2700K	470|>90	3
3000K	495|>90	5

ALWAYS USE

driver | 500mA

	EUR	CODE
6W | IP20	33,00	90214201
6.5W dim | IP20*	25,50	90224301
7W | IP67	46,50	90214301

*revision opening required
more drivers on page 898

MORE VERSIONS ONLINE
weverducre.com/more-deep-bijou-ip65

IC rated

741

back









DEEP petit IP65

Ceiling recessed



1.0

LED COB 6W | 350mA | 17V
aluminium

IP65 M-31° L80|50K

wire springs Ø68-70 60 4-25

	EUR	CODE
	96,00	153761W_
	96,00	153761Q_
	96,00	153761B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	590	>90	3
3000K	615	>90	5





ALWAYS USE

driver | 350mA

	EUR	CODE
6W | IP20	25,50	90213303
10W dim | IP20*	35,50	90223406
17W | IP68*	69,00	90213602

*revision opening required
more options and specs on page 896

back



LINK LAB CREATIVE OFFICES | STAY STUDIO KORTRIJK | BELGIUM

DEEP IP65 | IP44

Ceiling recessed







1.0 LED

LED COB 6/9W | 350/500mA | 17V
aluminium

IP65 M-33° L80|55K

wire springs 86-89 85 4-27

	EUR	CODE
	109,00	184161W_
	109,00	184161Q_
	109,00	184161B_

LIGHT COLOUR	LUMEN|CRI	CODE
2700K	480/660|>90	3
3000K	510/695|>90	5

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP44

wire springs 86-89 125 4-25

	EUR	CODE
	59,00	112620W0
	59,00	112620Q0
	59,00	112620B0

ALWAYS USE

driver | 500mA

	EUR	CODE
10W | IP20	25,50	90214406
10W dim | IP20	37,50	90224403
24W | IP68	74,00	90214702

more options and specs on page 898

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-deep-ip44-65

1.0 LED
IC rated

745

back



HOTEL NOBIS | WINGÅRDHS COPENHAGEN | DENMARK

DEEPER IP44

Ceiling recessed







1.0 LED

LED COB 6/9W | 350/500mA | 17V
aluminium

IP44 M-34° L80|55K

wire springs 76-79 95 4-38

	EUR	CODE
	119,00	152461W_
	119,00	152461Q_
	119,00	152461B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	590/790	>90	3
3000K	620/835	>90	5
2000-3000K	440/650	>90	9

LED module 20 years replaceability

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP44

wire springs 76-79 130 4-38

	EUR	CODE
	65,00	152220W0
	65,00	152220Q0
	65,00	152220B0

ALWAYS USE

quick connect driver | 500mA

	EUR	CODE
10W | IP20	25,50	90214406
10W dim | IP20	37,50	90224403
15W DALI | IP20	64,50	90244501

more options and specs on page 898

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

LOXONE VERSIONS ONLINE
weverducre.com/more-deeper

back



PRIVATE RESIDENCE | JOLIJN GEERAERTS INTERIEURARCHITECT BELGIUM









TAIO IP65

Ceiling recessed



1.0

LED COB 6/9W | 350/500mA | 17V
aluminium | opal glass convex lens

IP65 W-105° L80|55K

wire springs 70 80 4-27

	EUR	CODE
	95,00	180781W_
	95,00	180781G_
	95,00	180781Q_
	95,00	180781B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	375/515	>90	3
3000K	390/535	>90	5

ALWAYS USE

driver | 500mA

	EUR	CODE
10W | IP20	25,50	90214406
10W dim | IP20	37,50	90224403
24W | IP68	74,00	90214702

more options and specs on page 898



back

299
747
757
803



PRIVATE RESIDENCE | AJ ARCHITECTEN BELGIUM

RINI SNEAK IP44

Ceiling recessed









1.0 LED

LED COB 6/9W | 350/500mA | 17V
aluminium

IP44 M-34° L80|55K

wire springs 76-79 52 4-25

	EUR	CODE
	99,50	154461W_
	99,50	154461B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	605/815	>90	3
3000K	640/860	>90	5
2000-3000K	450/665	>90	9

LED module 20 years replaceability

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP44

wire springs 76-79 85 4-25

	EUR	CODE
	45,50	154220W0
	45,50	154220B0

ALWAYS USE

quick connect driver | 500mA

	EUR	CODE
10W | IP20	25,50	90214406
10W dim | IP20	37,50	90224403
15W DALI | IP20	64,50	90244501

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more options and specs on page 898

more lamps and info on page 905

LOXONE VERSIONS ONLINE
weverducre.com/more-rini-sneak



back



PERLEZ IP44

Ceiling recessed

271 | 275 | 295

701



1.0

LED COB 6/9W | 350/500mA | 18V
aluminium | opal glass

IP44 L80|50K

wire springs 46-51 68 4-25

	EUR	CODE
	148,00	192181W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	520/705	>95	3
3000K	550/740	>95	5

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W | IP20	25,50	90213303
7W dim | IP20	33,50	90223301
14W DALI*	64,50	90243502

*revision opening required
more options and specs on page 896



2.0

LED COB 6/9W | 350/500mA | 18V
aluminium | opal glass

IP44 L80|50K

wire springs 46-51 68 4-25

	EUR	CODE
	158,00	192281W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	600/810	>95	3
3000K	630/850	>95	5

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W | IP20	25,50	90213303
7W dim | IP20	33,50	90223301
14W DALI*	64,50	90243502

*revision opening required
more options and specs on page 896



3.0

LED COB 6/9W | 350/500mA | 18V
aluminium | opal glass

IP44 L80|50K

wire springs 46-51 68 4-25

	EUR	CODE
	178,00	192381W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	645/875	>95	3
3000K	665/915	>95	5

ALWAYS USE

quick connect driver | 350mA

	EUR	CODE
6W | IP20	25,50	90213303
7W dim | IP20	33,50	90223301
14W DALI*	64,50	90243502

*revision opening required
more options and specs on page 896

IC rated

LOXONE VERSIONS ONLINE
weverducre.com/more-perlez-recessed

back



MIRBI IP44

Ceiling recessed









297

707





1.0

LED PCB 8W | phase-cut dim
220-240VAC | 50-60Hz
clear + opal PMMA cover

IP44 L80|60K

blade springs 76-79 50 min. 8

3000K | CRI >90 | 640lm

	EUR	CODE
	155,00	175688W5

2.0

LED PCB 8W | phase-cut dim
220-240VAC | 50-60Hz
clear + opal PMMA cover

IP44 L80|60K

blade springs 72x72 50 min. 8

3000K | CRI >90 | 640lm

	EUR	CODE
	155,00	175788W5

back



DENTAL PRACTICE TANDKORAAL | G4A ARCHITECTEN BRUGGE | BELGIUM

CITY IP44

Ceiling recessed





ø210



ø305

1.6

LED PCB 13W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA cover

IP44 L80|60K

wire springs 202-205 50 4-22

3000K | CRI >90 | 1170lm

	EUR	CODE
	166,00	115488W5
	166,00	115488B5

2.6

LED PCB 19W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA cover

IP44 L80|60K

wire springs 297-300 50 4-22

3000K | CRI >90 | 1740lm

	EUR	CODE
	259,00	115588W5
	259,00	115588B5



back

Ceiling surface

SPOT LIGHTS



QITO
177



BLIEK PETIT
179



CENO
181



LECA
189



MATCH
193



MATCH 4.0
197



MICK
199

PILLO
201



SARA ON BASE
203



SQUBE ON BASE
205

DOWN LIGHTS



LINOO
211



PIRRO PETIT
213



PIRRO
215



PIRRO OPAL
221



PIRRO ON BASE
223



PLANO PETIT
227



SIRRO
229



BOX MINI LED
231



BOX MINI PAR16
233



BOX
235



DOCUS MINI
239



DOCUS
241



HEXO MINI
243



HEXO
245



RAY MINI LED
247



RAY MINI PAR16
249



RAY
251



SOLID BIJOU
253



SOLID PETIT
255



SOLID
257



TRACE
261

LUMINAIRES

FINLIN
263



FIL SPIN
267



TRACE SPIN
269



PERLEZ SPIN
271



TRACE GRID
273



PERLEZ GRID
275



VENN
277



DRO
279



MIRRO
283

MIRRO SOFT
285

CLEA
287

J.J.W.
289

WIRO
291

ROOMOR OFFICE
293

IP-RATED

PERLEZ IP44
295

MIRBI IP44 1.0
297

MIRBI IP44 2.0
297

TAIO IP65
299

ROB IP44
301

ROBY IP44
303

TOWNA IP44
305

ROSS IP54
307

back



QITO

Ceiling surface





2.0

LED COB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-35°|350° M-31° L80|50K

	EUR	CODE
	238,00	198664W_
	274,00	198664L_
	274,00	198664Q_
	238,00	198664B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x420	>90	3
3000K	2x440	>90	5



OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

back



reddot winner 2023

BLIEK petit

Ceiling surface





2.0

LED COB 15W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-60°|355° M-31° L70|55K

	EUR	CODE
	278,00	164664W_
	278,00	164664CH_
	278,00	164664B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x490	>90	3
3000K	2x510	>90	5
2000-3000K	2x340	>90	9



OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

back



PRIVATE RESIDENCE | VERFAILLIE INTERIEUR BELGIUM

CENO

Ceiling surface

131
321
585







1.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-31° L70|55K

	EUR	CODE
	168,00	176664W_
	168,00	176664Q_
	168,00	176664K_
	168,00	176664B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	520	>90	3
3000K	540	>90	5

2.0

LED COB 14W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-31° L70|55K

	EUR	CODE
	269,00	176764W_
	269,00	176764Q_
	269,00	176764K_
	269,00	176764B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x480	>90	3
3000K	2x525	>90	5



OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

LOXONE VERSIONS ONLINE
weverducre.com/more-ceno-surface

back


MARRAKECH FLAIR

CENO

Ceiling surface

131
321
585









4.0

LED COB 30W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-31° L70|55K

	EUR	CODE
	438,00	176864W_
	438,00	176864Q_
	438,00	176864K_
	438,00	176864B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	4x510	>90	3
3000K	4x530	>90	5

4.1

LED COB 30W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-31° L70|55K

	EUR	CODE
	415,00	176964W_
	415,00	176964Q_
	415,00	176964K_
	415,00	176964B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	4x510	>90	3
3000K	4x530	>90	5



OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

back



PRIVATE RESIDENCE | STEENOVEN | B2A | BELGIUM

CENO

Ceiling surface





6.0

LED COB 41W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-3I° L70|55K

	EUR	CODE
	575,00	176064W_
	575,00	176064Q_
	575,00	176064B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	6x480	>90	3
3000K	6x525	>90	5



OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

back

131
321
585



reddot winner 2024

LECA

Ceiling surface











OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

1.0

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-31° L80|50K

2700K | CRI >90 | 585lm

	EUR	CODE
	179,00	188264W3
	179,00	188264Q3
	179,00	188264B3

2.0

LED COB 14W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-31° L80|50K

2700K | CRI >90 | 2x585lm

	EUR	CODE
	289,00	188364W3
	289,00	188364Q3
	289,00	188364B3

4.0

LED COB 28W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-31° L80|50K

2700K | CRI >90 | 4x585lm

	EUR	CODE
	465,00	188464W3
	465,00	188464B3

back





PRIVATE RESIDENCE | AJ ARCHITECTEN BELGIUM

MATCH

Ceiling surface 61 | 137 | 153

329 | 347
415 | 509
571
589 | 685
723 | 729







1.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-30°L80|50K

	EUR	CODE
	175,00	177154W_
	179,00	177154BL_
	175,00	177154B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	550	>90	3
3000K	580	>90	5

2.0

LED COB 18W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-30° L80|50K

	EUR	CODE
	285,00	177254W_
	295,00	177254BL_
	285,00	177254B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x545	>90	3
3000K	2x550	>90	5

LOXONE VERSIONS ONLINE
weverducre.com/more-match-surface

back







reddot winner 2023

MATCH

Ceiling surface 61 | 137 | 153

329 | 347

415 | 509

571

589 | 685

723 | 729





4.0

LED COB 29W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-30° L80|50K

	EUR	CODE
	455,00	177454W_
	455,00	177454B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	4x490	>90	3
3000K	4x495	>90	5

back



PRIVATE RESIDENCE | AXIOME ARCHITECTURE BELGIUM

DESIGN AWARD 2021

reddot winner 2020 lighting design

MICK

Ceiling surface

333

687 | 691







1.0

LED COB 14W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-23° L80|50K

	EUR	CODE
	265,00	159144J_
	265,00	159144K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	410	>90	3
3000K	435	>90	5

2.0

LED COB 14W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-23° L80|50K

	EUR	CODE
	345,00	159244J_
	345,00	159244K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x215	>90	3
3000K	2x225	>90	5

S&R CORNELISSEN

back



PILLO

Ceiling surface









1.0

PAR11 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-90°|350°

	EUR	CODE
	65,00	194120W0
	65,00	194120B0

OPTIONAL

PAR11 4.3W | GU10 | phase-cut dim

	EUR	CODE
2700K | 225lm	14,50	901128B3
3000K | 235lm	14,50	901128B5

2.0

2x PAR11 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-90°|350°

	EUR	CODE
	118,00	194220W0
	118,00	194220B0

OPTIONAL

PAR11 4.3W | GU10 | phase-cut dim

	EUR	CODE
2700K | 225lm	14,50	901128B3
3000K | 235lm	14,50	901128B5

363

back



MARBELLA DESIGN & ART FAIR | MARISA GALLO | INTERIORISMO STUDIO MARBELLA | SPAIN

SARA on base

Ceiling surface

365

689









1.0

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-90°

	EUR	CODE
	79,00	157220W0
	85,00	157220G0
	85,00	157220K0
	79,00	157220B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

1.1

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-90°|330°

	EUR	CODE
	122,00	157420W0
	122,00	157420B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

3.0

3x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-90°|330°

	EUR	CODE
	245,00	157520W0
	245,00	157520B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



PRIVATE RESIDENCE | AGENCE VERONIQUE COTREL FRANCE

SQUBE on base

Ceiling surface











1.0 LED

LED COB 6W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP20 0°-90° M-39° L70|55K

	EUR	CODE
	165,00	144268W_
	165,00	144268B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	400	>90	3
3000K	445	>90	5
1800-3000K	350	>80	9

1.1 LED

LED COB 12W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP20 0°-90° M-32° L70|55K

	EUR	CODE
	189,00	144468W_
	189,00	144468B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	925	>90	3
3000K	960	>90	5
1800-3000K	645	>80	9

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-90°

	EUR	CODE
	96,00	144220W0
	96,00	144220B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905


black ring LED


PAR16

back







PRIVATE RESIDENCE | LANCO DESIGN BELGIUM

SQUBE on base

Ceiling surface









2.0

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-90°|355°

	EUR	CODE
	195,00	144520W0
	195,00	144520B0

3.0

3x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-90°|355°

	EUR	CODE
	235,00	144620W0
	235,00	144620B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905















4.0

LED PCB 10W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | polycarbonate
light colour selectable via dip switch

IP20 M-39° L80|50K

2700K/3000K | CRI >90 | 4x125lm

	EUR	CODE
	148,00	109664WW9
	148,00	109664WB9
	148,00	109664QB9
	148,00	109664BB9

4.1

LED PCB 10W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | polycarbonate
light colour selectable via dip switch

IP20 M-39° L80|50K

2700K/3000K | CRI >90 | 4x125lm

	EUR	CODE
	140,00	109764WW9
	140,00	109764WB9
	140,00	109764QB9
	140,00	109764BB9

8.0

LED PCB 19W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | polycarbonate
light colour selectable via dip switch

IP20 M-39° L80|50K

2700K/3000K | CRI >90 | 8x125lm

	EUR	CODE
	235,00	109864WW9
	235,00	109864WB9
	235,00	109864QB9
	235,00	109864BB9



PRIVATE RESIDENCE | IN-LIJN INTERIEURARCHITECTUUR BELGIUM

PIRRO petit

Ceiling surface







6.0

LED COB 14W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-28° L80|50K

	EUR	CODE
	255,00	129854E_
	255,00	129854WM_
	255,00	129854CH_
	255,00	129854B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	6x160	>90	3
3000K	6x165	>90	5

12.0

LED COB 27W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-28° L80|50K

	EUR	CODE
	375,00	129954E_
	375,00	129954WM_
	375,00	129954CH_
	375,00	129954B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	12x160	>90	3
3000K	12x165	>90	5

back

PIRRO

Ceiling surface









1.0

LED COB 6W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-32° L70|55K

	EUR	CODE
	148,00	151164E_
	148,00	151164J_
	148,00	151164K_
	148,00	151164B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	355	>90	3
3000K	385	>90	5

4.1

LED COB 20W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-32° L70|55K

	EUR	CODE
	238,00	151564E_
	238,00	151564J_
	238,00	151564K_
	238,00	151564B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	4x365	>90	3
3000K	4x380	>90	5



OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

back

75

371



PRIVATE RESIDENCE | PADRON LUXURY LIVING BY POTRELL BELGIUM

PIRRO

Ceiling surface

75
371









2.0

LED COB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-32° L70|55K

	EUR	CODE
	182,00	151264E_
	182,00	151264J_
	182,00	151264K_
	182,00	151264B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x355	>90	3
3000K	2x385	>90	5

4.0

LED COB 20W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-32° L70|55K

	EUR	CODE
	242,00	151464E_
	242,00	151464J_
	242,00	151464K_
	242,00	151464B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	4x365	>90	3
3000K	4x380	>90	5

6.0

LED COB 21W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-32° L70|55K

	EUR	CODE
	345,00	151664E_
	345,00	151664J_
	345,00	151664K_
	345,00	151664B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	6x330	>90	3
3000K	6x350	>90	5



OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

back







PRIVATE RESIDENCE | ORANEN & TURKLIN FINLAND

PIRRO OPAL

Ceiling surface

371







2.0

LED PCB 7W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA cover

IP20 L80|60K

	EUR	CODE
	182,00	151284E_
	182,00	151284J_
	182,00	151284K_
	182,00	151284B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	270	>90	3
3000K	280	>90	5

4.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA cover

IP20 L80|60K

	EUR	CODE
	242,00	151484E_
	242,00	151484J_
	242,00	151484K_
	242,00	151484B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	685	>90	3
3000K	710	>90	5



back



PRIVATE RESIDENCE | PADRON LUXURY LIVING BY POTRELL BELGIUM

PIRRO on base

Ceiling surface









2.2

LED COB 22W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PC lens and reflector

IP20 M-32° L70|55K

	EUR	CODE
	497,00	173564WWB_
	497,00	173564WWG_
	497,00	173564BBG_
	497,00	173564BBB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	4x360	>90	3
3000K	4x380	>90	5

4.2

LED COB 31W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PC lens and reflector

IP20 M-32° L70|55K

	EUR	CODE
	557,00	173664WWB_
	557,00	173664WWG_
	557,00	173664BBG_
	557,00	173664BBB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	6x360	>90	3
3000K	6x380	>90	5

4.4

LED COB 40W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PC lens and reflector

IP20 M-32° L70|55K

	EUR	CODE
	617,00	173764WWB_
	617,00	173764WWG_
	617,00	173764BBG_
	617,00	173764BBB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	8x360	>90	3
3000K	8x380	>90	5





OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

back



PIRRO on base

Ceiling surface







2.4.2

LED COB 42W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PC lens and reflector

IP20 M-32° L70|55K

	EUR	CODE
	772,00	173864WWB_
	772,00	173864WWG_
	772,00	173864BBG_
	772,00	173864BBB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	8x360	>90	3
3000K	8x380	>90	5

4.2.2

LED COB 42W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PC lens and reflector

IP20 M-32° L70|55K

	EUR	CODE
	772,00	173964WWB_
	772,00	173964WWG_
	772,00	173964BBG_
	772,00	173964BBB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	8x360	>90	3
3000K	8x380	>90	5





OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

back



PLANO petit

Ceiling surface













1.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-25°|355° M-31° L70|55K

	EUR	CODE
	168,00	162864WW_
	168,00	162864WB_
	168,00	162864BM_
	168,00	162864BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	550	>90	3
3000K	580	>90	5

LED module 20 years replaceability

2.0

LED COB 15W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-25°|355° M-31° L70|55K

	EUR	CODE
	255,00	162964WW_
	255,00	162964WB_
	255,00	162964BM_
	255,00	162964BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x550	>90	3
3000K	2x580	>90	5

LED module 20 years replaceability

3.0

LED COB 23W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-25°|355° M-31° L70|55K

	EUR	CODE
	325,00	162764WW_
	325,00	162764WB_
	325,00	162764BM_
	325,00	162764BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	3x540	>90	3
3000K	3x570	>90	5

LED module 20 years replaceability

MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-plano-surface

back



DEUTSCHE WOHNWERTE | BRANDHERM + KRUMREY HAMBURG HEIDELBERG | GERMANY

SIRRO

Ceiling surface











1.0

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-35°|355°

	EUR	CODE
	175,00	139120W0
	175,00	139120E0
	175,00	139120B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

2.0

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-35°|355°

	EUR	CODE
	258,00	139220W0
	258,00	139220E0
	258,00	139220B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

3.0

3x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-35°|355°

	EUR	CODE
	338,00	139320W0
	338,00	139320E0
	338,00	139320B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

LOXONE VERSIONS ONLINE
weverducre.com/more-sirro



PRIVATE RESIDENCE | JACO GOUDRIAAN THE NETHERLANDS

BOX mini

Ceiling surface








WW


WM


MM


WB


MB


QQ


BM


BB

LOXONE VERSIONS ONLINE
weverducre.com/more-box-mini



1.0 LED

LED COB 7W | phase-cut dim
220-240VAC | 50-60Hz
incl. driver | aluminium

IP20 M-30° L80|55K

	EUR	CODE
	98,00	258154WW_
	98,00	258154WM_
	98,00	258154WB_
	99,00	258154MM_
	99,00	258154MB_
	98,00	258154BM_
	99,00	258154QQ_
	98,00	258154BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	470	>90	3
3000K	500	>90	5

605

back



BOX mini

Ceiling surface





605

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	57,00	258120W0
	58,00	258120G0
	58,00	258120M0
	58,00	258120Q0
	57,00	258120B0



OPTIONAL

inner reflector max. 10W
polycarbonate

	EUR	CODE
	9,50	900199W1
	9,50	900199G1
	9,50	900199M1
	9,50	900199Q1
	9,50	900199B1

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

back



OFFICE INNARGI COPENHAGEN | HELLE FLOU COPENHAGEN | DENMARK

BOX

Ceiling surface













1.0 LED

LED COB 8W | dimmable
220-240VAC | 50-60Hz
aluminium

IP20 M-21° L70|50K





OPTIONAL

inner reflector max. 10W
polycarbonate

	EUR	CODE
	21,00	911211W1
	21,00	911211G1
	21,00	911211M1
	21,00	911211B1

inner cover max. 10W
aluminium

	EUR	CODE
	23,00	911011W1
	23,00	911011G1
	23,00	911011M1
	23,00	911011B1

phase-cut dim

	EUR	CODE
	175,00	186158W_
	176,00	186158L_
	176,00	186158G_
	176,00	186158M_
	176,00	186158Q_
	175,00	186158B_

DALI

	EUR	CODE
	198,00	186159W_
	199,00	186159L_
	199,00	186159G_
	199,00	186159M_
	199,00	186159Q_
	198,00	186159B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	600	>90	3
3000K	620	>90	5
2000-3000K*	415	>90	9

*only for phase-cut dim

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	68,00	146120W0
	69,00	146120L0
	69,00	146120G0
	69,00	146120M0
	69,00	146120Q0
	68,00	146120B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

335
607
765
815



PRIVATE RESIDENCE | DECOFORM BELGIUM

BOX

Ceiling surface













OPTIONAL

double inner reflector max. 10W
polycarbonate

	EUR	CODE
	27,00	911251W1
	27,00	911251G1
	27,00	911251M1
	27,00	911251B1

inner cover max. 10W
aluminium | 2 pieces needed

	EUR	CODE
	23,00	911011W1
	23,00	911011G1
	23,00	911011M1
	23,00	911011B1

2.0 LED

LED COB 16W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP20 M-21° L70|50K

	EUR	CODE
	278,00	186258W_
	281,00	186258L_
	281,00	186258G_
	281,00	186258M_
	281,00	186258Q_
	278,00	186258B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x600	>90	3
3000K	2x620	>90	5
2000-3000K	2x415	>90	9

2.0 PAR16

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	135,00	146220W0
	138,00	146220L0
	138,00	146220G0
	138,00	146220M0
	138,00	146220Q0
	135,00	146220B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

335
607
765
815
back



OFFICE INARTO | INARTO ARCHITECTEN HERENTALS | BELGIUM

DOCUS mini

Ceiling surface



609



1.0

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	64,00	258320W0
	65,00	258320G0
	64,00	258320B0



OPTIONAL

inner reflector max. 10W
polycarbonate

	EUR	CODE
	9,50	900199W2
	9,50	900199G2
	9,50	900199B2

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

back



HOTEL HOWARD | ROQUE INTÉRIEURS PARIS | FRANCE

DOCUS

Ceiling surface

337













1.0 LED

LED COB 8W | dimmable
220-240VAC | 50-60Hz
aluminium

IP20 M-21° L70|50K

phase-cut dim

	EUR	CODE
	180,00	186358W_
	181,00	186358G_
	180,00	186358B_

DALI

	EUR	CODE
	203,00	186359W_
	204,00	186359G_
	203,00	186359B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	610	>90	3
3000K	630	>90	5
2000-3000K*	420	>90	9

*only for phase-cut dim

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	73,00	146320W0
	74,00	146320G0
	73,00	146320B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

2.0 PAR16

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	139,00	146420W0
	143,00	146420G0
	139,00	146420B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



OPTIONAL

inner cover max. 10W
aluminium | **2.0** 2 pieces needed

	EUR	CODE
	23,00	911021W1
	23,00	911021G1
	23,00	911021B1

back



PRIVATE RESIDENCE | TOM BEIGE / *NESS HUNGARY

HEXO mini

Ceiling surface








82

81

1.0

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	64,00	258420W0
	65,00	258420G0
	65,00	258420Q0
	64,00	258420B0


reflector

OPTIONAL

inner reflector max. 10W
polycarbonate

	EUR	CODE
	9,50	900199W3
	9,50	900199G3
	9,50	900199Q3
	9,50	900199B3

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

back



PRIVATE RESIDENCE | **CONCEPT'N** BELGIUM

HEXO

Ceiling surface













1.0 LED

LED COB 8W | dimmable
220-240VAC | 50-60Hz
aluminium

IP20 M-21° L70|50K

phase-cut dim

	EUR	CODE
	180,00	186558W_
	181,00	186558G_
	181,00	186558Q_
	181,00	186558P_
	180,00	186558B_

DALI

	EUR	CODE
	203,00	186559W_
	204,00	186559G_
	204,00	186559Q_
	204,00	186559P_
	203,00	186559B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	670	>90	3
3000K	700	>90	5
2000-3000K*	470	>90	9

*only for phase-cut dim



OPTIONAL

inner cover max. 10W
aluminium | **2.0** 2 pieces needed

	EUR	CODE
	23,00	911031W1
	23,00	911031G1
	23,00	911031B1

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	73,00	146520W0
	74,00	146520G0
	74,00	146520Q0
	74,00	146520P0
	73,00	146520B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

2.0 PAR16

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	139,00	146620W0
	143,00	146620G0
	143,00	146620Q0
	143,00	146620P0
	139,00	146620B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



PRIVATE RESIDENCE | SYNOPSIS ARCHITECTURE BELGIUM

RAY mini

Ceiling surface







375 | 391



507 | 535



613



1.0 LED

LED COB 7W | phase-cut dim
220-240VAC | 50-60Hz
incl. driver | aluminium

IP20 M-30° L80|55K

	EUR	CODE
	98,00	258254WW_
	98,00	258254WM_
	98,00	258254WB_
	99,00	258254MM_
	99,00	258254MB_
	98,00	258254BM_
	99,00	258254QQ_
	98,00	258254BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	450	>90	3
3000K	480	>90	5

LOXONE VERSIONS ONLINE
weverducre.com/more-ray-mini

back



HOTEL MARTIN'S RENTMEESTERIJ | PCP ARCHITECTS BILZEN | BELGIUM

RAY mini

Ceiling surface





1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	57,00	258220W0
	58,00	258220G0
	58,00	258220M0
	58,00	258220Q0
	57,00	258220B0



OPTIONAL

inner reflector max. 10W
polycarbonate

	EUR	CODE
	9,50	900199W4
	9,50	900199G4
	9,50	900199M4
	9,50	900199Q4
	9,50	900199B4

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

back



MAISONME BOUTIQUE HOTEL | ALICE PIUBELLO BARDOLINO LAKE GARDA | ITALY

RAY

Ceiling surface







1.0 LED

LED COB 8W | dimmable
220-240VAC | 50-60Hz
aluminium

IP20 M-21° L70|50K

phase-cut dim

	EUR	CODE
	175,00	186758W_
	176,00	186758L_
	176,00	186758G_
	176,00	186758M_
	176,00	186758Q_
	176,00	186758P_
	175,00	186758B_

DALI

	EUR	CODE
	198,00	186759W_
	199,00	186759L_
	199,00	186759G_
	199,00	186759M_
	199,00	186759Q_
	199,00	186759P_
	198,00	186759B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	670	>90	3
3000K	700	>90	5
2000-3000K*	470	>90	9

*only for phase-cut dim

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	68,00	146720W0
	69,00	146720L0
	69,00	146720G0
	69,00	146720M0
	69,00	146720Q0
	69,00	146720P0
	68,00	146720B0



OPTIONAL

inner cover max. 10W
aluminium

	EUR	CODE
	23,00	911041W1
	23,00	911041G1
	23,00	911041M1
	23,00	911041B1

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

back

341 | 377 | 393
537
615
759
805

PRIVATE RESIDENCE | AGENCE VÉRONIQUE COTRE | FRANCE

SOLID bijou

Ceiling surface





1.0

LED COB 6W | phase-cut dim
220-240V | 50-60Hz | incl. driver
aluminium

IP20 M-27° L80|50K

	EUR	CODE
	135,00	133864WW_
	135,00	133864WG_
	136,50	133864MB_
	135,00	133864BG_
	135,00	133864BM_
	136,50	133864QQ_
	135,00	133864BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	480	>90	3
3000K	510	>90	5

LOXONE VERSIONS ONLINE
weverducre.com/more-solid-bijou

back



PRIVATE RESIDENCE | ELLEMVIE - ART & INTERIEUR THE NETHERLANDS

SOLID petit

Ceiling surface





2.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-25°|355° M-31° L80|50K



	EUR	CODE
	172,00	133964WW_
	172,00	133964WG_
	174,00	133964MB_
	172,00	133964BG_
	172,00	133964BM_
	172,00	133964SG_
	172,00	133964ME_
	174,00	133964QQ_
	172,00	133964BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	555	>90	3
3000K	585	>90	5
2000-3000K	470	>90	9

LED module 20 years replaceability

MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-solid-petit

back



PRIVATE RESIDENCE | STUDIO ZUYD THE NETHERLANDS

SOLID

Ceiling surface







1.0 LED

LED COB 13W | dimmable
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-25°|355° M-34° L80|55K

phase-cut dim

	EUR	CODE
	185,00	133764WW_
	185,00	133764WG_
	188,00	133764MB_
	185,00	133764BG_
	185,00	133764BM_
	188,00	133764QQ_
	185,00	133764BB_

DALI-2 | push dim

	EUR	CODE
	216,00	133765WW_
	216,00	133765WG_
	219,00	133765MB_
	216,00	133765BG_
	216,00	133765BM_
	219,00	133765QQ_
	216,00	133765BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	855	>90	3
3000K	905	>90	5
2000-3000K	695	>90	9

LED module 20 years replaceability

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-25°|355°

	EUR	CODE
	116,00	133120WW0
	116,00	133120WG0
	119,00	133120MB0
	116,00	133120BG0
	116,00	133120BM0
	119,00	133120QQ0
	116,00	133120BB0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905















MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-solid

back







PRIVATE RESIDENCE | STUDIO FOOLEN THE NETHERLANDS

DESIGN AWARD 2024

reddot winner 2023

TRACE

Ceiling surface





351



511 | 547



593



130

ø65

1.0

LED COB 6W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-27° L80|50K

	EUR	CODE
	155,00	183164W_
	157,00	183164BL_
	157,00	183164CH_
	155,00	183164B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	480	>90	3
3000K	510	>90	5

back



PRIVATE RESIDENCE GREECE

DESIGN AWARD 2024

reddot winner 2023

FINLIN

Ceiling surface





1.0

LED PCB 5W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 L80|50K

	EUR	CODE
	265,00	174184W_
	265,00	174184CH_
	265,00	174184B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	450	>90	3
3000K	485	>90	5



2.0

LED PCB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 L80|50K

	EUR	CODE
	275,00	174284W_
	275,00	174284CH_
	275,00	174284B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	675	>90	3
3000K	730	>90	5



3.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 L80|50K

	EUR	CODE
	310,00	174384W_
	310,00	174384CH_
	310,00	174384B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	900	>90	3
3000K	975	>90	5

OPTIONAL

cover plate adapter for concrete housing

	EUR	CODE
	12,50	900194B0

back





reddot winner 2024

FIL SPIN

Ceiling surface



441

681



1.0

LED PCB 24W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | indir. light

IP20 180° L80|100K

2700K | CRI >90 | 2x905lm

	EUR	CODE
	425,00	254584B3



back



TRACE SPIN

Ceiling surface





1.0

LED COB 26W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 180° M-30° L80|50K

2700K | CRI >90 | 4x360lm



	EUR	CODE
	425,00	183264CH3
	425,00	183264B3

351

511 | 547

593

back

PERLEZ SPIN

Ceiling surface

169

701





1.0

LED COB 25W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal glass

IP20 180° L80|50K

2700K | CRI >90 | 4x250lm

	EUR	CODE
	525,00	192784BW3



back



PRIVATE RESIDENCE | KWADRAAT BELGIUM

TRACE GRID

Ceiling surface



351

511 | 547

593



1.0

LED COB 41W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
direct light

IP20 M-30° L80|50K

2700K | CRI >90 | 8x415lm

	EUR	CODE
	695,00	183364CH3
	695,00	183364B3



2.0

LED PCB/COB 35W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
dir./indir. light

IP20 M-30° L80|50K

2700K | CRI >90 | 4x415/2x480lm

	EUR	CODE
	645,00	183464CH3
	645,00	183464B3

back

PERLEZ GRID

Ceiling surface





1.0

LED COB 40W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal glass
direct light

IP20 L80|50K

2700K | CRI >90 | 8x220lm

	EUR	CODE
	785,00	192884QW3
	785,00	192884BW3

back



OFFICE RPD | VIVA ARCHITECTURE ANTWERP | BELGIUM

VENN

Ceiling surface







1.0

LED PCB 42W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
opal PMMA cover indirect light

IP20 L70|55K

	EUR	CODE
	680,00	149184W_
	680,00	149184Q_
	680,00	149184B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	3410	>90	3
3000K	3510	>90	5

2.0

LED PCB 49W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
opal PMMA cover dir./indir. light

IP20 L70|55K

	EUR	CODE
	770,00	149284W_
	770,00	149284Q_
	770,00	149284B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	480/3920	>90	3
3000K	495/4035	>90	5

CREATE YOUR OWN VENN
weverducre.com/venn-configurator

683

back



PRIVATE RESIDENCE | STUDIO REE THE NETHERLANDS

DRO

Ceiling surface









1.0

QT14 max. 5W | G9
220-240VAC | 50-60Hz
aluminium
artisanal Italian hand blown glass

IP20

	EUR	CODE
	165,00	1721G0WB0

OPTIONAL

QT14 3.5W | G9 | phase-cut dim clear

	EUR	CODE
2700K | 340lm	18,00	9010G803
3000K | 350lm	18,00	9010G805

2.0

C35 max. 6W | E14
220-240VAC | 50-60Hz
aluminium
artisanal Italian hand blown glass

IP20

	EUR	CODE
	245,00	1722C0WB0

OPTIONAL

C35 5.5W | E14 | phase-cut dim | opal

	EUR	CODE
2700K | 450lm	10,50	9003C103

3.0

A60 max. 12W | E27
220-240VAC | 50-60Hz
aluminium
artisanal Italian hand blown glass

IP20

	EUR	CODE
	325,00	1723E0WB0

OPTIONAL

A60 9W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 800lm	14,50	9003E152

373
465
623
715 | 731

back



PRIVATE RESIDENCE | STUDIO REE THE NETHERLANDS



IBIS STYLES PREVESSIN | FORTY STUDIO GENÈVE | SWITZERLAND

MIRRO

Ceiling surface









1.0

A60 max. 15W | E27
220-240VAC | 50-60Hz
aluminium
one side reflective composite panel

IP20

	EUR	CODE
	208,00	6321E0GB0
	208,00	6321E0NB0
	208,00	6321E0LB0
	208,00	6321E0BL0

OPTIONAL

A60 5.5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2700K | 405lm	32,00	9003E139

A60 5.5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 405lm	32,00	9003E140

2.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium
one side reflective composite panel

IP20

	EUR	CODE
	256,00	6322E0GB0
	256,00	6322E0NB0
	256,00	6322E0LB0
	256,00	6322E0BL0

OPTIONAL

G95 5W/5.1W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 395lm	35,00	9003E157

3.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium
one side reflective composite panel

IP20

	EUR	CODE
	416,00	6323E0GB0
	416,00	6323E0NB0
	416,00	6323E0LB0
	416,00	6323E0BL0

OPTIONAL

G95 5W/5.1W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 395lm	35,00	9003E157

467
625
721 | 733

MIRRO SOFT

Ceiling surface







2.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | PET felt material
noise absorbing material

IP20

	EUR	CODE
	256,00	6322E0MF0
	256,00	6322E0LF0
	256,00	6322E0IF0
	256,00	6322E0AF0

3.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | PET felt material
noise absorbing material

IP20

	EUR	CODE
	416,00	6323E0MF0
	416,00	6323E0LF0
	416,00	6323E0IF0
	416,00	6323E0AF0

OPTIONAL

G95 5W/5.1W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 395lm	35,00	9003E157

G95 10W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

G95 4.5W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 375lm	33,00	9003E160

OPTIONAL

G95 5W/5.1W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 395lm	35,00	9003E157

G95 10W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

G95 4.5W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 375lm	33,00	9003E160

471

629



CLEA

Ceiling surface



557

631



1.0

LED COB 15W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white opal glass hand blown

IP20 L80|50K

	EUR	CODE
	287,00	181184W_
	309,00	181184LS_
	309,00	181184SG_
	309,00	181184FJ_
	287,00	181184B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	780	>90	3
3000K	825	>90	5



2.0

LED COB 15W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white opal glass hand blown

IP20 L80|50K

	EUR	CODE
	427,00	181284W_
	459,00	181284LS_
	459,00	181284SG_
	459,00	181284FJ_
	427,00	181284B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	780	>90	3
3000K	825	>90	5



3.0

LED COB 15W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white opal glass hand blown

IP20 L80|50K

	EUR	CODE
	547,00	181384W_
	581,00	181384LS_
	581,00	181384SG_
	581,00	181384FJ_
	547,00	181384B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	770	>90	3
3000K	815	>90	5

back





J.J.W.

Ceiling surface

479

633



03

3x A60 max. 15W | E27
220-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	865,00	2051E0S0
	865,00	2051E0G0

OPTIONAL

A60 3.8W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 245lm	31,00	9003E109

A60 5.6W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 480lm	31,00	9003E138



WIRO

Ceiling surface















2.0 WIRO

A60 max. 60W | E27
220-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	275,00	2086E0V0
	275,00	2086E0B0

OPTIONAL

A60 3.8W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 245lm	31,00	9003E109

A60 5.6W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 480lm	31,00	9003E138

1.8 WIRO

T30 max. 25W | E27
220-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	315,00	2082E0V0
	315,00	2082E0B0

OPTIONAL

T30-225 5.3W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 380lm	39,00	9003E129
2700K | 425lm	39,00	9003E136

1.0 CONE

T30 max. 60W | E27
220-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	295,00	2080E0V0
	295,00	2080E0B0

OPTIONAL

T30-225 5.3W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 380lm	39,00	9003E129
2700K | 425lm	39,00	9003E136

3.8 WIRO

T30 max. 60W | E27
220-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	407,00	2083E0V0
	407,00	2083E0B0

OPTIONAL

T30-225 5.3W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 380lm	39,00	9003E129
2700K | 425lm	39,00	9003E136

BERND STEINHUBER

back



URBAN SPACES | STUDIO KOMO STUTTGART | GERMANY

ROOMOR OFFICE

Ceiling surface



395

499





1.0 MICROPRISMATIC

LED PCB 35W | DALI-2 | push dim
220-240VAC | 50-60Hz | incl. driver
aluminium
microprismatic PMMA cover

IP20 L80|60K UGR ≤ 19/65°

	EUR	CODE
	745,00	1683M5W_
	745,00	1683M5B_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	3660	>90	5
4000K	3660	>90	7

UGR ≤ 19
65°≤ 3000cd
microprismatic

1.0 OPAL

LED PCB 35W | DALI-2 | push dim
220-240VAC | 50-60Hz | incl. driver
aluminium
opal PMMA cover

IP20 L80|60K

	EUR	CODE
	725,00	168385W_
	725,00	168385B_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	3700	>90	5
4000K	3700	>90	7

back

PERLEZ IP44

Ceiling surface

169

701









1.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal glass

IP44 L80|50K

	EUR	CODE
	188,00	192484W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	520	>95	3
3000K	550	>95	5
4000K	580	>95	7

2.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal glass

IP44 L80|50K

	EUR	CODE
	198,00	192584W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	600	>95	3
3000K	630	>95	5
4000K	665	>95	7

3.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal glass

IP44 L80|50K

	EUR	CODE
	218,00	192684W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	645	>95	3
3000K	665	>95	5
4000K	705	>95	7

back



PRIVATE RESIDENCE | ATELIER B AUSTRIA

MIRBI IP44

Ceiling surface

171



707





1.0

LED PCB 8W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | clear and opal PMMA cover

IP44 L80|60K

3000K | CRI >90 | 640lm

	EUR	CODE
	185,00	175488W5
	185,00	175488BW5

2.0

LED PCB 8W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | clear and opal PMMA cover

IP44 L80|60K

3000K | CRI >90 | 640lm

	EUR	CODE
	195,00	175588W5
	195,00	175588BW5

back



PRIVATE RESIDENCE | AJ ARCHITECTEN BELGIUM

TAIO IP65

Ceiling surface





1.0

LED COB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
opal glass convex lens

IP65 W-105° L80|55K

	EUR	CODE
	198,00	180884W_
	198,00	180884Q_
	198,00	180884B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	455	>90	3
3000K	510	>90	5

back

165
747
757
803



GAW HOPPEHOF ERTVELDE | BELGIUM

ROB IP44

Ceiling surface





ø160



ø256



ø345



769

1.6

LED PCB 13W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA cover

IP44 L80|60K

	EUR	CODE
	168,00	701188W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1170	>90	3
3000K	1220	>90	5

2.6

LED PCB 19W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA cover

IP44 L80|60K

	EUR	CODE
	245,00	701288W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1800	>90	3
3000K	1810	>90	5

3.5

LED PCB 32W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA cover

IP44 L80|60K

	EUR	CODE
	335,00	701388W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	3340	>90	3
3000K	3360	>90	5

back



ORL PRAXIS SEMADENI | EMULSION INNENARCHITEKTUR CHUR | SWITZERLAND

ROBY IP44

Ceiling surface







ø165



ø260



ø350

1.6

LED PCB 13W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA cover

IP44 L80|60K

	EUR	CODE
	218,00	135188W_
	218,00	135188B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1080	>90	3
3000K	1130	>90	5

2.6

LED PCB 19W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA cover

IP44 L80|60K

	EUR	CODE
	318,00	135288W_
	318,00	135288B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1670	>90	3
3000K	1680	>90	5

3.5

LED PCB 32W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA cover

IP44 L80|60K

	EUR	CODE
	428,00	135388W_
	428,00	135388B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	3090	>90	3
3000K	3100	>90	5

back



PRIVATE RESIDENCE | FORUM OFFICE BELGIUM

TOWNA IP44

Ceiling surface











1.0

LED PCB 13W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | steel
opal PMMA cover

IP44 L80|60K











	EUR	CODE
	252,00	178188W_
	255,00	178188J_
	255,00	178188K_
	255,00	178188Z_
	252,00	178188B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1070	>90	3
3000K	1110	>90	5

2.0

LED PCB 19W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | steel
opal PMMA cover

IP44 L80|60K

	EUR	CODE
	361,00	178288W_
	365,00	178288J_
	365,00	178288K_
	365,00	178288Z_
	361,00	178288B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1650	>90	3
3000K	1660	>90	5

3.0

LED PCB 32W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | steel
opal PMMA cover

IP44 L80|60K

	EUR	CODE
	472,00	178388W_
	479,00	178388J_
	479,00	178388K_
	479,00	178388Z_
	472,00	178388B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	3050	>90	3
3000K	3060	>90	5

back



ROSS IP54

Ceiling surface















1.0

LED PCB 9/11/15W
220-240VAC | 50-60Hz | incl. driver
polycarbonate housing
output and light colour selectable via dip switch

IP54 L80|50K

3000K/4000K/6000K | CRI >90
960lm/1170lm/1630lm

	EUR	CODE
	79,00	715184W9

2.0

LED PCB 10/15/20W
220-240VAC | 50-60Hz | incl. driver
polycarbonate housing
output and light colour selectable via dip switch

IP54 L80|50K

3000K/4000K/6000K | CRI >90
1270lm/1810lm/2360lm

	EUR	CODE
	129,00	715284W9

3.0

LED PCB 28/33/37W
220-240VAC | 50-60Hz | incl. driver
polycarbonate housing
output and light colour selectable via dip switch

IP54 L80|50K

3000K/4000K/6000K | CRI >90
4350lm/5000lm/5570lm

	EUR	CODE
	225,00	715384W9

back

Track / System

308 – 411

STREX TRACK



48V TRACKS 313 | CENO 321 | LECA 325 | DOMY 327 | MATCH 329



TRACE MINI 331 | MICK 333 | BOX 335 | DOCUS 337 | HEXO 339 | RAY 341



DOT MODULE 343 | OPAL MODULE 343 | COZY CONE 345 | MATCH 347 | TRACE 351 | ODREY 353



OPLIA 357 | SOLLI 359

1-PHASE TRACK



1-PHASE TRACKS 361 | PILLO 363 | SARA 365 | SQUBE 369 | PIRRO 371



DRO 373 | HEXO MINI 375 | RAY MINI 375 | HEXO 377 | RAY 377 | ODREY 379



RUVI 383

3-PHASE TRACK



3-PHASE TRACKS 385 | LIKO 387 | SQUBE 389 | HEXO MINI 391 | RAY MINI 391



HEXO 393 | RAY 393 | ROOMOR OFFICE 395

SYSTEM



QUBBY SYSTEM 397 | FLYRA SYSTEM 401 | ELLO SYSTEM 405 | ILANE 409

back

Railsystemen zijn eenvoudiger dan ze lijken: 1-fase rails sturen alle armaturen tegelijk aan, terwijl 3-fase rails afzonderlijke bediening van spots en pendels mogelijk maken. Het 48-volt systeem biedt maximale flexibiliteit voor diverse armaturen en is eenvoudig via smartphone te bedienen.

Les systèmes sur rail sont plus simples qu'ils n'en ont l'air : les rails 1 phase contrôlent tous les luminaires ensemble, tandis que les rails 3 phases permettent de gérer séparément spots, modules et suspensions. Le système 48 volts offre une flexibilité maximale et se commande facilement via smartphone.

weverducre.com/track-lighting

track

	STREX 48V DALI page 313	1-PHASE TRACK 220–240V page 361	3-PHASE TRACK 220–240V DALI page 385
1 CHOOSE YOUR MOUNTING	 recessed surface suspended suspended indirect	 recessed surface suspended	 surface suspended
2 INSTALL IT IN YOUR LAYOUT			
3 CHOOSE YOUR DRIVER	 remote in-line in-track ceiling		
4 COMBINE IT WITH INSETS			

For more support and an extended layout of track systems, please check our FAQ section at weverducre.com/faq

back

mounting

weverducre.com/strex-configurator

Discreetly hidden in the ceiling, as a striking surface-mounted option, or floating freely in the room – with three mounting types you'll find the right solution for any space. Tip: sketch your project and note where the track should run and which zones you want to highlight for a clearer overview.

CUSTOM CUT AVAILABLE
Have a look on page 917 or browse online: weverducre.com/strex-custom

CEILING RECESSED



STREX RECESSED

track 48V | 15A | DALI

SELV | 31-33 | 65 | 5-25

		EUR	CODE
	1m	115,00	904111W0
	1m	115,00	904111B0
	2m	235,00	904112W0
	2m	235,00	904112B0
	3m	349,00	904113W0
	3m	349,00	904113B0



M | MOUNTING BRACKET

recessed mounting bracket
for 1m - 2pcs needed | for 2m - 4pcs needed | for 3m - 6pcs needed

	EUR	CODE
	12,50	904141I0



E | END CAP

	EUR	CODE
	12,00	904121W0
	12,00	904121B0

CEILING SURFACE



STREX SURFACE

track 48V | 15A | DALI

SELV

		EUR	CODE
	1m	89,00	904211W0
	1m	89,00	904211B0
	2m	174,00	904212W0
	2m	208,00	904212L0
	2m	208,00	904212M0
	2m	208,00	904212Q0
	2m	174,00	904212B0
	3m	258,00	904213W0
	3m	309,00	904213L0
	3m	309,00	904213M0
	3m	309,00	904213Q0
	3m	258,00	904213B0



E | END CAP

	EUR	CODE
	7,50	904221W0
	8,00	904221M0
	8,00	904221Q0
	7,50	904221B0

CEILING SUSPENDED



STREX SUSPENDED

track 48V | 15A | DALI

SELV

		EUR	CODE
	1m	89,00	904211W0
	1m	89,00	904211B0
	2m	174,00	904212W0
	2m	208,00	904212L0
	2m	208,00	904212M0
	2m	208,00	904212Q0
	2m	174,00	904212B0
	3m	258,00	904213W0
	3m	309,00	904213L0
	3m	309,00	904213M0
	3m	309,00	904213Q0
	3m	258,00	904213B0



STREX SUSP. INDIRECT

track 48V | 15A | DALI | with indirect light | 3.0m suspension sets already included | 15W/m

SELV

3000K | CRI >90 | 1900lm

		EUR	CODE
	2m	575,00	904512W5
	2m	575,00	904512B5

3000K | CRI >90 | 2850lm

		EUR	CODE
	3m	675,00	904513W5
	3m	675,00	904513B5



S | SUSPENSION SET

complete suspension set | incl. ceiling fixation bracket | not needed for indirect light version | for 1m - 2pcs needed | for 2m - 3pcs needed
for 3m - 4pcs needed

stainless steel colour

		EUR	CODE
	max. 1.5m	29,00	904341I0
	max. 3m	31,00	904342I0

black colour

		EUR	CODE
	max. 1.5m	29,00	904341B0
	max. 3m	31,00	904342B0



E | END CAP

	EUR	CODE
	7,50	904221W0
	8,00	904221M0
	8,00	904221Q0
	7,50	904221B0

back

layout







weverducre.com/strex-configurator

M | S | E
Choose your mounting
on page 312

D | P
Choose your driver | power feed
on page 316

GOOD TO KNOW
Electrical components of champagne or bronze connectors and drivers will be black.

ALL MOUNTINGS



BLANK COVER

		EUR	CODE
	2m	51,00	911002W0
	2m	51,00	911002B0



C | CONNECTOR

48V | 15A | DALI | electrical/
mechanical connector

	EUR	CODE
	40,00	904431W0
	40,00	904431B0

CEILING RECESSED



L1 | L-CONNECTOR

48V | 15A | DALI | electrical/
mechanical connector left and right

	EUR	CODE
	181,00	904132W0
	181,00	904132B0



L2 | L-CONNECTOR NON ELECTRICAL

only needed 1x for square installation

	EUR	CODE
	181,00	904133W0
	181,00	904133B0

CEILING SURFACE | SUSPENDED



L1 | L-CONNECTOR

48V | 15A | DALI | electrical/
mechanical connector left and right

	EUR	CODE
	118,00	904232W0
	121,00	904232MB0
	121,00	904232QB0
	118,00	904232B0



L2 | L-CONNECTOR NON ELECTRICAL

only needed 1x for square installation

	EUR	CODE
	118,00	904233W0
	121,00	904233MB0
	121,00	904233QB0
	118,00	904233B0



T | T-CONNECTOR

48V | 15A | DALI | electrical/
mechanical connector

	EUR	CODE
	198,00	904234W0
	198,00	904234B0



X | X-CONNECTOR

48V | 15A | DALI | electrical/
mechanical connector

	EUR	CODE
	224,00	904235W0
	224,00	904235B0

back

driver

weverducre.com/strex-configurator

A driver regulates the current flowing through your LED lights, preventing overheating and unwanted flickering. Which is best suited to your STREX system depends on the chosen installation. The most elegant solution is an in-track driver, but many other variants are also available.

GOOD TO KNOW
Electrical components of champagne or bronze connectors and drivers will be black.

CEILING RECESSED | SURFACE



D1 | REMOTE DRIVER

remote converter | 220-240VAC
50-60Hz | 48V | for connection to
power feed adapter

220-240V — 48V

		EUR	CODE
	100W | 48V	89,00	90218901
	150W | 48V	108,00	90218902

for more information see page 917



P | POWER FEED

48V | 15A | DALI | end/middle power
feed adapter | max. 4 x 1.5mm²

	EUR	CODE
	38,00	904451W0
	38,00	904451B0



D2 | IN LINE DRIVER SURFACE

220-240VAC | 50-60Hz | 48V
incl. power end feed adapter
incl. DALI through wiring

220-240V DALI SELV IN — 48V DALI SELV OUT

		EUR	CODE
	100W	278,00	904262W0
	100W	278,00	904262B0
	150W	288,00	904272W0
	150W	288,00	904272B0



D3 | IN TRACK DRIVER SURFACE

220-240VAC | 50-60Hz | 48V
incl. power end feed function
with in line connection box

220-240V — 48V

		EUR	CODE
	100W	239,00	904263W0
	100W	242,00	904263MB0
	100W	242,00	904263QB0
	100W	239,00	904263B0



		EUR	CODE
	250W	279,00	904283W0
	250W	282,00	904283MB0
	250W	282,00	904283QB0
	250W	279,00	904283B0



D4 | IN TRACK DRIVER SURFACE

220-240VAC | 50-60Hz | 48V
incl. power middle/end feed function
with in track connection

220-240V — 48V

		EUR	CODE
	100W	228,00	904264W0
	100W	228,00	904264B0



		EUR	CODE
	250W	268,00	904284W0
	250W	268,00	904284B0

CEILING SUSPENDED



D1 | CEILING DRIVER

220-240VAC | 50-60Hz | 48V
incl. power middle/end feed adapter
incl. DALI through wiring
driver ceiling mounted

220-240V DALI SELV IN — 48V DALI SELV OUT

		EUR	CODE
	100W	298,00	904361W0
	100W	298,00	904361B0
	150W	318,00	904371W0
	150W	318,00	904371B0



D2 | IN LINE DRIVER

220-240VAC | 50-60Hz | 48V
incl. power end feed adapter
incl. DALI through wiring
suspended driver in line with profile

220-240V DALI SELV IN — 48V DALI SELV OUT

		EUR	CODE
	100W	325,00	904362W0
	100W	325,00	904362B0
	150W	348,00	904372W0
	150W	348,00	904372B0



D3 | IN TRACK DRIVER

220-240VAC | 50-60Hz | 48V
incl. power end feed function
incl. 3m power cable
suspended driver in the profile

220-240V — 48V

		EUR	CODE
	100W	268,00	904363W0
	100W	271,00	904363MB0
	100W	271,00	904363QB0
	100W	268,00	904363B0



		EUR	CODE
	250W	315,00	904383W0
	250W	315,00	904383B0



D4 | REMOTE DRIVER

220-240VAC | 50-60Hz | 48V
incl. power end feed function
incl. 3m power cable
incl. remote driver

220-240V — 48V

		EUR	CODE
	100W	238,00	904364W0
	100W	238,00	904364B0
	150W	258,00	904374W0
	150W	258,00	904374B0



		EUR	CODE
	250W	285,00	904384W0
	250W	285,00	904384B0

back

control



ALL MOUNTINGS



WIRELESS CASAMBI CONTROL

8W | adapter for wireless control
of 64 DALI fixtures in max. 8 groups

	EUR	CODE
	515,00	904491W0
	515,00	904491B0

HOW TO CONTROL MY STREX SYSTEM

Wat is er zo geweldig aan het STREX-systeem? Je hebt eindeloos veel mogelijkheden. Het schakelen of dimmen van je verlichting is eenvoudig met DALI. Wil je liever geen bedraad systeem installeren, kies dan voor een flexibelere oplossing – alles wat je nodig hebt is een Casambi-besturingsmodule en compatibele DALI-inzetstukken.

Qu'est-ce qui rend le système STREX si intéressant ? Il offre d'innombrables possibilités. Allumer ou varier l'intensité de vos luminaires est très simple avec DALI. Et si vous ne souhaitez pas installer un système câblé, optez pour une configuration plus flexible – il vous suffit d'un module de commande Casambi et d'inserts DALI compatibles.



CREATE A SCENE FOR YOUR
INDIVIDUAL LIGHTING SOLUTION



PRIVATE RESIDENCE | STUDIO BENOIT BELGIUM



CENO on STREX

48V system


131


181




585





1.0

LED COB 10W | 48V
aluminium | PC adapter

IP20 0-90°|355° M-31° L70|55K

non dim

	EUR	CODE
	168,00	166562W_
	168,00	166562BQ_
	168,00	166562K_
	168,00	166562CH_
	168,00	166562B_

DALI-2

	EUR	CODE
	255,00	166565W_
	255,00	166565BQ_
	255,00	166565K_
	255,00	166565CH_
	255,00	166565B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	480	>90	3
3000K	510	>90	5

accessories on page 910

2.0

LED COB 17W | 48V
aluminium | PC adapter

IP20 0-90°|355° M-31° L70|55K

non dim

	EUR	CODE
	258,00	166662W_
	258,00	166662BQ_
	258,00	166662K_
	258,00	166662CH_
	258,00	166662B_

DALI-2

	EUR	CODE
	335,00	166665W_
	335,00	166665BQ_
	335,00	166665K_
	335,00	166665CH_
	335,00	166665B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x480	>90	3
3000K	2x510	>90	5

accessories on page 910



OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

back







PRIVATE RESIDENCE | STUDIO BINNEN THE NETHERLANDS



LECA on STREX

48V system

135

189

569



1.0

LED COB 7W | 48V
aluminium | PC adapter

IP20 0-90°|350° M-31° L80|50K

non dim

	EUR	CODE
	178,00	188662W_
	178,00	188662BQ_
	178,00	188662B_

DALI-2

	EUR	CODE
	264,00	188665W_
	264,00	188665BQ_
	264,00	188665B_

LIGHT COLOUR	LUMEN | CRI	CODE
2700K	585 | >90	3
3000K	620 | >90	5



OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

back



DOMY on STREX

48V system



1.0

LED COB 7W | 48V
aluminium | glass | PC adapter

IP20 0-90°|350° M-25° L80|50K

non dim

	EUR	CODE
	176,00	107452WLS_
	176,00	107452WFJ_
	176,00	107452WSG_
	176,00	107452BT_
	176,00	107452BB_

DALI-2

	EUR	CODE
	262,00	107455WLS_
	262,00	107455WFJ_
	262,00	107455WSG_
	262,00	107455BT_
	262,00	107455BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	560	>90	3
3000K	575	>90	5

back



RESTAURANT GARDENS | ANDREAS HUHN ARCHITEKTEN TÜBINGEN I GERMANY



MATCH on STREX

48V system 61 | 137 | 153

193
415 | 509
571
589 | 685
723 | 729



1.0

LED COB 10W | 48V
aluminium | PC adapter

IP20 0-90°|360° M-30° L80|50K

non dim

	EUR	CODE
	176,00	179152W_
	182,00	179152BL_
	182,00	179152CH_
	182,00	179152BQ_
	176,00	179152B_

DALI-2

	EUR	CODE
	262,00	179155W_
	268,00	179155BL_
	268,00	179155CH_
	268,00	179155BQ_
	262,00	179155B_

LIGHT COLOUR	LUMEN | CRI	CODE
2700K	530 | >90	3
3000K	560 | >90	5

accessories on page 910



TRACE mini on STREX

48V system

591



1.0

LED PCB 5W | 48V
aluminium | PC adapter

IP20 0-90°|355° M-30° L80|50K

non dim

	EUR	CODE
	125,00	333552W_
	125,00	333552BM_
	125,00	333552B_

DALI-2

	EUR	CODE
	185,00	333555W_
	185,00	333555BM_
	185,00	333555B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	326	>90	3
3000K	336	>90	5

back



DENTAL PRACTICE M.K.A. | DMG ARCHITECTURAL SOLUTIONS KAPELLEN | BELGIUM



MICK on STREX

48V *system*

199

687 | 691





1.0

LED COB 13W | 48V
aluminium | PC adapter

IP20 0-90°|360° M-23° L80|50K

non dim

	EUR	CODE
	189,00	159442J_
	189,00	159442K_

DALI-2

	EUR	CODE
	285,00	159445J_
	285,00	159445K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	415	>90	3
3000K	435	>90	5

accessories on page 910

2.0

LED COB 22W | 48V
aluminium | PC adapter

IP20 0-90°|360° M-23° L80|50K

non dim

	EUR	CODE
	282,90	159542J_
	282,90	159542K_

DALI-2

	EUR	CODE
	389,00	159545J_
	389,00	159545K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x445	>90	3
3000K	2x465	>90	5

accessories on page 910



PRIVATE RESIDENCE BELGIUM



BOX on STREX

48V system



1.0

LED COB 9W | 48V
aluminium

IP20 M-25° L80|55K

adapter | 2700K | CRI >90 | 505lm

		EUR	CODE
		188,00	258162W_3
		188,00	258162B_3
	DALI-2	236,00	258165W_3
	DALI-2	236,00	258165B_3

adapter | 3000K | CRI >90 | 535lm

		EUR	CODE
		188,00	258162W_5
		188,00	258162B_5
	DALI-2	236,00	258165W_5
	DALI-2	236,00	258165B_5



housing | inner reflector colour

	CODE
	W
	WM
	E
	M
	H
	Q
	CH
	B

only for ceiling surface and suspended tracks

back



DOCUS on STREX

48V system

241



1.0

LED COB 9W | 48V
aluminium

IP20 M-25° L80|55K

adapter | 2700K | CRI >90 | 505lm

		EUR	CODE
		195,00	258362W_3
		195,00	258362B_3
	DALI-2	243,00	258365W_3
	DALI-2	243,00	258365B_3

adapter | 3000K | CRI >90 | 535lm

		EUR	CODE
		195,00	258362W_5
		195,00	258362B_5
	DALI-2	243,00	258365W_5
	DALI-2	243,00	258365B_5

housing | inner reflector colour

	CODE
	W
	J
	E
	K
	B

only for ceiling surface and suspended tracks



back





HEXO on STREX

48V system

245

533



1.0

LED COB 9W | 48V
aluminium

IP20 M-25° L80|55K

adapter | 2700K | CRI >90 | 505lm

		EUR	CODE
		195,00	258462W_3
		195,00	258462B_3
	DALI-2	243,00	258465W_3
	DALI-2	243,00	258465B_3

adapter | 3000K | CRI >90 | 535lm

		EUR	CODE
		195,00	258462W_5
		195,00	258462B_5
	DALI-2	243,00	258465W_5
	DALI-2	243,00	258465B_5

housing | inner reflector colour

	CODE
	W
	J
	E
	Q
	K
	B

only for ceiling surface and suspended tracks



back



PRIVATE RESIDENCE | AJ ARCHITECTEN BELGIUM



RAY on STREX

48V system



1.0

LED COB 9W | 48V
aluminium

IP20 M-25° L80|55K

adapter | 2700K | CRI >90 | 485lm

		EUR	CODE
		188,00	258262W_3
		188,00	258262B_3
	DALI-2	236,00	258265W_3
	DALI-2	236,00	258265B_3

adapter | 3000K | CRI >90 | 515lm

		EUR	CODE
		188,00	258262W_5
		188,00	258262B_5
	DALI-2	236,00	258265W_5
	DALI-2	236,00	258265B_5



housing | inner reflector colour

	CODE
	W
	WM
	E
	M
	H
	Q
	CH
	B

only for ceiling surface and suspended tracks

back

251
537
615
759
805



FORUM ADVOCATEN | VRV ARCHITECTEN ANTWERP | BELGIUM

STREX MODULE

48V system









1.0 DOT

LED PCB 9W | 48V
PC adapter | cover
PC lens

IP20 W-40° UGR≤19 L80|60K

non dim

	EUR	CODE
	278,00	171362W_
	278,00	171362B_

DALI

	EUR	CODE
	344,00	171365W_
	344,00	171365B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	840	>90	3
3000K	860	>90	5

1.0 OPAL

LED PCB 15W | 48V
PC adapter | cover
PMMA opal cover

IP20 L80|60K

non dim

	EUR	CODE
	188,00	171382W_
	188,00	171382B_

DALI

	EUR	CODE
	228,00	171385W_
	228,00	171385B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	620	>90	3
3000K	640	>90	5

2.0 OPAL

LED PCB 29W | 48V
PC adapter | cover
PMMA opal cover

IP20 L80|60K

non dim

	EUR	CODE
	269,00	171482W_
	269,00	171482B_

DALI

	EUR	CODE
	309,00	171485W_
	309,00	171485B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1240	>90	3
3000K	1280	>90	5





MORE VERSIONS ONLINE
weverducre.com/more-strex-module

back

COZY CONE on STREX

48V system

503





1.0

LED PCB 7W | 48V | DALI-2
aluminium | glass | PC adapter
black and T– black cable/adapter
others – white cable/adapter

IP20 M-40° L80|50K

2700K | CRI >90 | 480lm

	EUR	CODE
	277,00	241665LS3
	277,00	241665SG3
	277,00	241665FJ3
	285,00	241665T3
	277,00	241665B3

2.0

LED PCB 7W | 48V | DALI-2
aluminium | glass | PC adapter
black and T – black cable/adapter
others – white cable/adapter

IP20 M-40° L80|50K

2700K | CRI >90 | 510lm

	EUR	CODE
	282,00	241765LS3
	282,00	241765SG3
	282,00	241765FJ3
	290,00	241765T3
	282,00	241765B3

3.0

LED PCB 7W | 48V |DALI-2
aluminium | glass | PC adapter
black and T – black cable/adapter
others – white cable/adapter

IP20 M-40° L80|50K

2700K | CRI >90 | 520lm

	EUR	CODE
	287,00	241865LS3
	287,00	241865SG3
	287,00	241865FJ3
	295,00	241865T3
	287,00	241865B3



back



PRIVATE RESIDENCE | DÉVÉ CREATIONS THE NETHERLANDS

DESIGN AWARD 2023 · GOOD DESIGN · reddot winner 2023

MATCH on STREX

48V *system* 61 | 137 | 153

193

415 | 509

571

589 | 685

723 | 729





3.0

LED COB 7W | 48V | DALI-2
aluminium | PC adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20 W-54° L80|50K

	EUR	CODE
	268,00	179775W_
	275,00	179775L_
	275,00	179775M_
	275,00	179775Q_
	268,00	179775B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	490	>90	3
3000K	520	>90	5

5.0

LED COB 7W | 48V | DALI-2
aluminium | PC adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20 W-54° L80|50K

	EUR	CODE
	281,00	179875W_
	290,00	179875L_
	290,00	179875M_
	290,00	179875Q_
	281,00	179875B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	490	>90	3
3000K	520	>90	5





MORE VERSIONS ONLINE
weverducre.com/more-match-on-strex

back





OFFICE LAMETT DEERLIJK | BELGIUM



TRACE on STREX

48V system





3.0

LED COB 7W | DALI-2
220-240VAC | 50-60Hz | incl. driver
aluminium
white fixtures – white cable/adapter
others – black cable/adapter

IP20 W-54° L80|50K

	EUR	CODE
	287,00	333875W_
	294,00	333875BL_
	294,00	333875BM_
	287,00	333875B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	490	>90	3
3000K	520	>90	5



5.0

LED COB 7W | DALI-2
220-240VAC | 50-60Hz | incl. driver
aluminium
white fixtures – white cable/adapter
others – black cable/adapter

IP20 W-54° L80|50K

	EUR	CODE
	296,00	333975W_
	305,00	333975BL_
	305,00	333975BM_
	296,00	333975B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	490	>90	3
3000K	520	>90	5


261 | 269 | 273




511 | 547


593 | 595

MORE VERSIONS ONLINE
weverducre.com/more-trace-on-strex



back



ODREY on STREX

48V system



















MORE VERSIONS ONLINE

weverducre.com/more-odrey-on-strex

1.2

LED COB 7W | 48V | DALI-2
aluminium | PC adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20 M-32° L70|55K

	EUR	CODE
	390,00	197265WW_
	390,00	197265QQ_
	390,00	197265BL_
	390,00	197265BG_
	390,00	197265BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	400	>90	3
3000K	445	>90	5

1.4

LED COB 7W | 48V | DALI-2
aluminium | PC adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20 M-32° L70|55K

	EUR	CODE
	332,00	197465WW_
	332,00	197465QQ_
	332,00	197465BL_
	332,00	197465BG_
	332,00	197465BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	450	>90	3
3000K	470	>90	5

1.6

LED COB 7W | 48V | DALI-2
aluminium | PC adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20 M-32° L70|55K

	EUR	CODE
	336,00	197665WW_
	336,00	197665QQ_
	336,00	197665BL_
	336,00	197665BG_
	336,00	197665BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	480	>90	3
3000K	505	>90	5

optional inner cover on page 910

517 | 539

599

PRIVATE RESIDENCE | TOM LIERMAN BUREAU VOOR ARCHITECTUUR & INTERIEUR BELGIUM



PRIVATE RESIDENCE | WALRAVENS WEETS ARCHITECTEN
BELGIUM



OPLIA on STREX

48V *system*

457 | 521

1.0

LED PCB 5W | 48V | DALI-2
aluminium | glass | PC adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20 L80|100K

2700K | CRI >90 | 245lm

	EUR	CODE
	294,00	246285W3
	294,00	246285M3
	294,00	246285B3



back

SOLLI on STREX

48V system





1.0

LED COB 7W | 48V | DALI-2
aluminium | black cable
artisanal Italian hand blown glass
PC adapter

IP20 L80|50K

	EUR	CODE
	382,00	238985FD_
	382,00	238985TD_
	344,00	238985WB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	280	>90	3
3000K	290	>90	5



back

523

RECESSED | SURFACE | SUSPENDED EXAMPLES

configuration as seen from top view
for more support and extended layout of 1-phase tracks,
please check our FAQ section on weverducre.com/faq





TRACK PROFILE

recessed | 220-240V | 16A

		EUR	CODE
	1m	62,00	90014118
■	1m	62,00	90014119
	2m	115,00	90014120
■	2m	115,00	90014121
	3m	152,00	90014122
■	3m	152,00	90014123



F | MOUNTING BRACKET

for recessed fixation

34-45 45 4-15

EUR	CODE
11,50	90014100

for 1.0m - 2pcs needed
for 2.0m - 3pcs needed
for 3.0m - 4pcs needed



TRACK PROFILE

surface | suspended | 220-240V | 16A

		EUR	CODE
	1m	44,00	90014001
■	1m	44,00	90014007
	2m	88,00	90014002
■	2m	88,00	90014008
	3m	136,00	90014003
■	3m	136,00	90014009



G | SUSPENSION SET

complete suspension set
incl. ceiling fixation bracket

		EUR	CODE
	max. 1.5m	28,00	90014101
■	max. 1.5m	28,00	90014102
	max. 3m	33,00	90014103
■	max. 3m	33,00	90014104

for 1.0m - 2pcs needed
for 2.0m - 3pcs needed
for 3.0m - 4pcs needed

top view



A | END FEED 1.0

220-240V | max. 3 x 1.5mm² - 16A

	EUR	CODE
	15,50	90014018
■	15,50	90014019

top view



A | END FEED 2.0

220-240V | max. 3 x 1.5mm² - 16A

	EUR	CODE
	15,50	90014020
■	15,50	90014021

top view



B | MIDDLE FEED

straight
220-240V | max. 3 x 1.5mm² - 16A

	EUR	CODE
	37,00	90014036
■	37,00	90014037



C | END CAP LEFT/RIGHT

	EUR	CODE
	3,50	90014028
■	3,50	90014029

top view



D | L-FEED 1.0

220-240V | max. 3 x 1.5mm² - 16A

	EUR	CODE
	38,00	90014024
■	38,00	90014025

top view



D | L-FEED 2.0

220-240V | max. 3 x 1.5mm² - 16A

	EUR	CODE
	38,00	90014026
■	38,00	90014027

top view



E | STRAIGHT CONNECTOR

straight | 220-240V | 16A

	EUR	CODE
	14,00	90014022
■	14,00	90014023



COVERPLATE END FEED

only use with recessed tracks

	EUR	CODE
	9,50	90014124
■	9,50	90014125

more 1-phase track accessories on page 918





PILLO on track

1-*Phase*



1.0

PAR11 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter

IP20 0°-90°|350°

	EUR	CODE
	72,00	194420W0
	72,00	194420B0

OPTIONAL

PAR11 4.3W | GU10 | phase-cut dim

	EUR	CODE
2700K | 225lm	14,50	901128B3
3000K | 235lm	14,50	901128B5

back



ENSO BOUTIQUE HOTEL | TIM DE TAEYE & TINE VANPARIJS KNOKKE-HEIST | BELGIUM



SARA on track

1-*Phase*


203




689





1.0 LED

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter

IP20 0-90°|355° M-34° L70|55K

	EUR	CODE
	158,00	157168W_
	164,00	157168G_
	164,00	157168K_
	158,00	157168B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	655	>80	3
3000K	700	>80	5

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter

IP20 0-90°|355°

	EUR	CODE
	88,00	157120W0
	94,00	157120G0
	94,00	157120K0
	88,00	157120B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905


black ring LED


W


G


PAR16


K


B

back


TRUKIKORA
5
4
3
2
1



LENDHOTEL | LAM ARCHITEKTUR ZT GMBH GRAZ | AUSTRIA



SQUBE on track

1-*Phase*

205





1.0 LED

LED COB 6W | phase-cut dim
220-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter

IP20 0-90°|355° M-39° L70|55K

	EUR	CODE
	175,00	144168W_
	175,00	144168B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	415	>90	3
3000K	430	>90	5
1800-3000K	350	>90	9



black ring LED



PAR16

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter

IP20 0-90°|355°

	EUR	CODE
	109,00	144120W0
	109,00	144120B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

back





white fixtures with white adapter
other fixtures with black adapter



PIRRO on track

1-Phase


77


215 | 221 | 223





2.0

LED COB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PC lens and reflector
1-phase Global® track adapter

IP20 310° M-32° L70|55K

	EUR	CODE
	195,00	173264E_
	195,00	173264K_
	195,00	173264B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x355	>90	3
3000K	2x385	>90	5

OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0



4.0

LED COB 20W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PC lens and reflector
1-phase Global® track adapter

IP20 310° M-32° L70|55K

	EUR	CODE
	255,00	173464E_
	255,00	173464K_
	255,00	173464B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	4x365	>90	3
3000K	4x380	>90	5

OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0



2.0 OPAL

LED PCB 7W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PMMA cover
1-phase Global® track adapter

IP20 310° L80|60K

	EUR	CODE
	195,00	173284E_
	195,00	173284K_
	195,00	173284B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	270	>90	3
3000K	280	>90	5



4.0 OPAL

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PMMA cover
1-phase Global® track adapter

IP20 310° L80|60K

	EUR	CODE
	255,00	173484E_
	255,00	173484K_
	255,00	173484B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	685	>90	3
3000K	710	>90	5

back



URBAN SPACES | STUDIO KOMO STUTTGART | GERMANY



DRO on track

1-Phase

279
465
623
715 | 731



1.0

QT14 max. 5W | G9
220-240VAC | 50-60Hz
aluminium
artisanal Italian hand blown glass
1-phase Global® track adapter

IP20

	EUR	CODE
	155,00	1724G0WB0

OPTIONAL

QT14 3.5W | G9 | phase-cut dim clear

	EUR	CODE
2700K | 340lm	18,00	9010G803
3000K | 350lm	18,00	9010G805

back





HEXO mini | RAY mini on track

1-Phase



HEXO MINI 3.0 | 5.0

PAR11 max. 12W | GU10
220-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter

IP20

3.0

300mm	EUR	CODE
	138,00	259320M0
	138,00	259320Q0
	138,00	259320B0

5.0

500mm	EUR	CODE
	158,00	259420M0
	158,00	259420Q0
	158,00	259420B0

OPTIONAL

PAR11 4.3W | GU10 | phase-cut dim

	EUR	CODE
2700K | 225lm	14,50	901128B3
3000K | 235lm	14,50	901128B5



RAY MINI 3.0 | 5.0

PAR11 max. 12W | GU10
220-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter
white and LS – white cable/adapter
others – black cable/adapter

IP20

3.0

300mm	EUR	CODE
	131,00	260320W0
	131,00	260320LS0
	131,00	260320Q0
	131,00	260320B0

5.0

500mm	EUR	CODE
	151,00	260420W0
	151,00	260420LS0
	151,00	260420Q0
	151,00	260420B0

OPTIONAL

PAR11 4.3W | GU10 | phase-cut dim

	EUR	CODE
2700K | 240lm	14,50	901128W3
2700K | 225lm	14,50	901128B3
3000K | 255lm	14,50	901128W5
3000K | 235lm	14,50	901128B5

243 | 247
505 | 507
531 | 535
611 | 613
back



OFFICE THE HOUSE | SPACELAB ARKITEKTER COPENHAGEN | DENMARK



HEXO | RAY on track

1-Phase



HEXO 3.0

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter

IP20

3.0

300mm	EUR	CODE
	121,00	215620G0
	121,00	215620Q0
	121,00	215620P0
	119,00	215620B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 440lm	16,50	901228B3
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



RAY 2.0 | 3.0

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20

2.0

200mm	EUR	CODE
	102,00	217520W0
	109,00	217520G0
	109,00	217520M0
	109,00	217520Q0
	109,00	217520P0
	102,00	217520B0

3.0

300mm	EUR	CODE
	108,00	217620W0
	115,00	217620G0
	115,00	217620M0
	115,00	217620Q0
	115,00	217620P0
	108,00	217620B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

245 | 251
533 | 537
615
759
805

back



PRIVATE RESIDENCE | BRITTE MARCUS BELGIUM

ODREY on track

1-Phase









517 | 539





599

1.1

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20

	EUR	CODE
	154,00	187120WW0
	154,00	187120GG0
	154,00	187120QQ0
	154,00	187120BL0
	154,00	187120BG0
	154,00	187120BB0

1.2

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20

	EUR	CODE
	220,00	187220WW0
	220,00	187220GG0
	220,00	187220QQ0
	220,00	187220BL0
	220,00	187220BG0
	220,00	187220BB0

1.3

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20

	EUR	CODE
	155,00	187320WW0
	155,00	187320GG0
	155,00	187320QQ0
	155,00	187320BL0
	155,00	187320BG0
	155,00	187320BB0













OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



SHOWROOM GRANDO KEUKENS BELGIUM

ODREY on track

1-Phase







1.4

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20

	EUR	CODE
	162,00	187420WW0
	162,00	187420GG0
	162,00	187420QQ0
	162,00	187420BL0
	162,00	187420BG0
	162,00	187420BB0













OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

1.5

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20

	EUR	CODE
	165,00	187520WW0
	165,00	187520GG0
	165,00	187520QQ0
	165,00	187520BL0
	165,00	187520BG0
	165,00	187520BB0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

1.6

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20

	EUR	CODE
	166,00	187620WW0
	166,00	187620GG0
	166,00	187620QQ0
	166,00	187620BL0
	166,00	187620BG0
	166,00	187620BB0

optional inner cover on page 910

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

RUVI on track

1-Phase





1.0

G95 max. 12W | E27
220-240VAC | 50-60Hz
aluminium
1-phase Global® track adapter
white fixtures – white cable/adapter
others – black cable/adapter

IP20

	EUR	CODE
	98,00	1672E0W0
	98,00	1672E0M0
	98,00	1672E0Q0
	98,00	1672E0B0

OPTIONAL

G95 10W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

back



SURFACE | SUSPENDED EXAMPLES

configuration as seen from top view





TRACK PROFILE

surface | suspended | DALI
220-240V | 16A

DALI FELV

		EUR	CODE
	1m	49,00	90014200
	1m	49,00	90014201
	2m	97,00	90014202
	2m	97,00	90014203
	3m	147,00	90014204
	3m	147,00	90014205



F | SUSPENSION SET

complete suspension set
incl. ceiling fixation bracket

		EUR	CODE
	max. 1.5m	29,00	90014206
	max. 1.5m	29,00	90014207
	max. 3m	30,00	90014208
	max. 3m	30,00	90014209

for 1.0m - 2pcs needed
for 2.0m - 3pcs needed
for 3.0m - 4pcs needed



A | END FEED 1.0

including cable gasket
220-240V | max. 7 x 1.5-2.5mm² | 16A

		EUR	CODE
		23,00	90014240
		23,00	90014241



A | END FEED 2.0

including cable gasket
220-240V | max. 7 x 1.5-2.5mm² | 16A

		EUR	CODE
		23,00	90014238
		23,00	90014239



B | MIDDLE FEED

straight
220-240V | max. 7 x 1.5-2.5mm² | 16A

		EUR	CODE
		51,00	90014224
		51,00	90014225



C | END CAP LEFT/RIGHT

		EUR	CODE
		3,00	90014216
		3,00	90014217



D | L-FEED 1.0

220-240V | max. 7 x 1.5-2.5mm² | 16A

		EUR	CODE
		48,00	90014220
		48,00	90014221



D | L-FEED 2.0

220-240V | max. 7 x 1.5-2.5mm² | 16A

		EUR	CODE
		48,00	90014222
		48,00	90014223



E | STRAIGHT CONNECTOR

straight | 220-240V | 16A

		EUR	CODE
		16,00	90014226
		16,00	90014227



TRACK COVER

		EUR	CODE
	1m	29,00	90014236
	1m	29,00	90014237

more 3-phase track accessories on page 919

back



LIKO on track

3-Phase









1.0

LED COB 12W
220-240VAC | 50-60Hz
aluminium
3-phase track adapter

IP20 0-90°|360° M-30° L80|50K

non-dim

	EUR	CODE
	138,00	263152W_
	138,00	263152B_

DALI-2

	EUR	CODE
	175,00	263155W_
	175,00	263155B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1070	>90	3
3000K	1110	>90	5

OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915231B0

2.0

LED COB 14W | ≤115lm/W
220-240VAC | 50-60Hz
aluminium
3-phase track adapter

IP20 0-90°|360° M-27° L80|50K

non-dim

	EUR	CODE
	158,00	263252W_
	158,00	263252B_

DALI-2

	EUR	CODE
	195,00	263255W_
	195,00	263255B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1565	>90	3
3000K	1600	>90	5

OPTIONAL

honeycomb louver

	EUR	CODE
	16,00	915232B0

3.0

LED COB 18W | ≤120lm/W
220-240VAC | 50-60Hz
aluminium
3-phase track adapter

IP20 0-90°|360° M-27° L80|50K

non-dim

	EUR	CODE
	175,00	263352W_
	175,00	263352B_

DALI-2

	EUR	CODE
	205,00	263355W_
	205,00	263355B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2110	>90	3
3000K	2175	>90	5

OPTIONAL

honeycomb louver

	EUR	CODE
	17,50	915233B0

≤120lm/W

MORE VERSIONS ONLINE
weverducre.com/more-liko

back



AOK OFFICE | DESIGNFUNKTION BERLIN | GERMANY

SQUBE on track

3-Phase



205







1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
3-phase track adapter

IP20 0-90°|355°

	EUR	CODE
	109,00	144720W0
	109,00	144720B0

2.0 LED

LED COB 12W | phase-cut dim
220-240VAC | 50-60Hz
aluminium
3-phase track adapter

IP20 0-90°|355° M-32° L70|55K

	EUR	CODE
	214,00	144368W_
	214,00	144368B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	925	>90	3
3000K	960	>90	5
1800K-3000K	645	>90	9

3.0 LED

LED COB 15W | phase-cut dim
220-240VAC | 50-60Hz
aluminium
3-phase track adapter

IP20 0-90°|355° M-27° L70|55K

	EUR	CODE
	228,00	144558W_
	228,00	144558B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1400	>90	3
3000K	1480	>90	5





OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

back





HEXO mini | RAY mini on track

3-Phase

243 | 247
505 | 507
531 | 535
611 | 613



HEXO MINI 3.0 | 5.0

PAR11 max. 12W | GU10
220-240VAC | 50-60Hz
aluminium
3-phase track adapter

IP20

3.0

300mm	EUR	CODE
	138,00	259520M0
	138,00	259520Q0
	138,00	259520B0

5.0

500mm	EUR	CODE
	158,00	259620M0
	158,00	259620Q0
	158,00	259620B0

OPTIONAL

PAR11 4.3W | GU10 | phase-cut dim

	EUR	CODE
2700K | 225lm	14,50	901128B3
3000K | 235lm	14,50	901128B5



RAY MINI 3.0 | 5.0

PAR11 max. 12W | GU10
220-240VAC | 50-60Hz
aluminium
3-phase track adapter
W and LS – white cable/adapter
others – black cable/adapter

IP20

3.0

300mm	EUR	CODE
	131,00	260520W0
	131,00	260520LS0
	131,00	260520Q0
	131,00	260520B0

5.0

500mm	EUR	CODE
	151,00	260620W0
	151,00	260620LS0
	151,00	260620Q0
	151,00	260620B0

OPTIONAL

PAR11 4.3W | GU10 | phase-cut dim

	EUR	CODE
2700K | 240lm	14,50	901128W3
2700K | 225lm	14,50	901128B3
3000K | 255lm	14,50	901128W5
3000K | 235lm	14,50	901128B5

back



PRIVATE RESIDENCE | INTERNI 21.11 ITALY



HEXO | RAY on track

3-Phase





HEXO 3.0

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
3-phase track adapter

IP20

3.0

300mm	EUR	CODE
	121,00	215420G0
	121,00	215420Q0
	121,00	215420P0
	119,00	215420B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 440lm	16,50	901228B3
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

RAY 2.0 | 3.0

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
3-phase track adapter
W fixtures – white cable/adapter
others – black cable/adapter

IP20

2.0

200mm	EUR	CODE
	102,00	217320W0
	109,00	217320G0
	109,00	217320M0
	109,00	217320Q0
	109,00	217320P0
	102,00	217320B0

3.0

300mm	EUR	CODE
	108,00	217420W0
	115,00	217420G0
	115,00	217420M0
	115,00	217420Q0
	115,00	217420P0
	108,00	217420B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

245 | 251
533 | 537
615
759
805



DIN SONNBERG IM MÜHLKREIS | AUSTRIA



reddot winner 2021

ROOMOR OFFICE on track

3-Phase

293

499





1.0 MICROPRISMATIC

LED PCB 35W | DALI-2
220-240VAC | 50-60Hz
aluminium
microprismatic PMMA cover
3-phase track adapter incl. driver

IP20 L80|60K UGR ≤ 19

	EUR	CODE
	745,00	1684M5W_
	745,00	1684M5B_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	3660	>90	5
4000K	3660	>90	7

UGR ≤ 19
65°≤ 3000cd
microprismatic

1.0 OPAL

LED PCB 35W | DALI-2
220-240VAC | 50-60Hz
aluminium | opal PMMA cover
3-phase track adapter incl. driver

IP20 L80|60K

	EUR	CODE
	725,00	168485W_
	725,00	168485B_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	3700	>90	5
4000K	3700	>90	7

back

QUBBY SYSTEM

Ceiling suspended









1.0

LED PCB 16W | DALI-2 DT8
220-240VAC | 50-60Hz
aluminium | opal polyethylene
incl. suspension set
default light colour 3500K

IP20 L80|100K

2700K-5000K| CRI >90 | 1250lm

	EUR	CODE
	695,00	916215B9

2.0

LED PCB 22W | DALI-2 DT8
220-240VAC | 50-60Hz
aluminium | opal polyethylene
incl. suspension set
default light colour 3500K

IP20 L80|100K

2700K-5000K| CRI >90 | 2500lm

	EUR	CODE
	935,00	916225B9

3.0

LED PCB 35W | DALI-2 DT8
220-240VAC | 50-60Hz
aluminium | opal polyethylene
incl. suspension set
default light colour 3500K

IP20 L80|100K

2700K-5000K| CRI >90 | 4500lm

	EUR	CODE
	1495,00	916235B9

B | BASE

W/H ø97x28
polypropylene

	EUR	CODE
	45,00	914231B0

CONNECTOR

included in **1.0 | 2.0 | 3.0**









1.0 | 2.0 | 3.0 Luminaire
B Base

KEEP IN MIND WHEN PLANNING YOUR SYSTEM

Please be aware that the maximum length of the QUBBY System cannot be longer then 80m or max. 40 luminaires.

S&R CORNELISSEN

back



FLYRA SYSTEM

Ceiling suspended









1.0

LED strip 8W
aluminium | ribbed glass

IP20 L80|50K

	EUR	CODE
	280,00	269182M_
	280,00	269182B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1035	>90	3
3000K	1065	>90	5

2.0

LED strip 12W
aluminium | ribbed glass

IP20 L80|50K

	EUR	CODE
	340,00	269282M_
	340,00	269282B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1555	>90	3
3000K	1600	>90	5

3.0

LED strip 15W
aluminium | ribbed glass

IP20 L80|50K

	EUR	CODE
	410,00	269382M_
	410,00	269382B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2070	>90	3
3000K	2130	>90	5

B1 | SINGLE/MULTI BASE

max. 25W | const. volt. | 24V
phase-cut dim | W/H ø62x102
polycarbonate

	EUR	CODE
	55,00	914224M0
	55,00	914224B0

B2 | MULTI BASE

max. 50W | const. volt. | 24V
phase-cut dim | W/H ø200x38
polycarbonate

	EUR	CODE
	75,00	914225M0
	75,00	914225B0

C | CABLE CONNECTOR

cable from one luminaire to another
incl. plugs

		EUR	CODE
	0.3m	14,50	915210B0
	0.6m	19,00	915211B0
	0.9m	23,00	915212B0
	1.2m	27,00	915213B0

D | FIX CONNECTOR

electrical | mechanical | straight
central suspension

	EUR	CODE
	24,00	915221B0





1.0 | 2.0 | 3.0	Luminaire
B1	Single/Multi Base
B2	Multi Base
C	Cable connector
D	Fix connector



KEEP IN MIND WHEN PLANNING YOUR SYSTEM

Please be aware that the maximum wattage of the FLYRA System cannot be higher than 25W for B1 and 50W for B2 per System.

weverducre.com/flyra

back







1.0

LED PCB | dimmable
220-240VAC | 50-60Hz
aluminium | opal PMMA cover

IP20 L80|50K



phase-cut dim | 20W
3000K | CRI >90 | 1090lm

	EUR	CODE
	362,00	500384W5
	362,00	500384B5

DALI-2 | 22W | incl. driver
3000K | CRI >90 | 1090lm

	EUR	CODE
	412,00	500385W5
	412,00	500385B5

B | CONNECTOR POINT

phase-cut dim up to max. 4 fixtures
DALI up to max. 2 fixtures

	EUR	CODE
	52,00	900190W1
	52,00	900190B1

C | STEEL SUSPENSION CABLE

	EUR	CODE
2.0m	13,00	90015102

D1 | POWER FEEDER

for phase-cut dim | incl. steel suspension cable 2.0m | max. 10 luminaires per power feeder

	EUR	CODE
	62,00	90018010
	62,00	90018011

D2 | POWER FEEDER

for DALI | incl. steel suspension cable 2.0m | max. 10 luminaires per power feeder

	EUR	CODE
	78,00	90018012
	78,00	90018013

SURFACE EXAMPLES

configuration as seen from top view | minimum angle 45°



SUSPENDED EXAMPLES

configuration as seen from top view | minimum angle 45°
can be used up or down (direct or indirect)





OFFICE KR PROPERTIES | 2A ARCHITECURAL GROUP



MATE SPORT HALL | IBL LIGHT & DESIGN THIENE | ITALY



PRIVATE RESIDENCE AUSTRIA

ILANE

Ceiling surface





for net output of LED strip on profiles,
check weverducre.com/ilane

1.0 PROFILE

aluminium | opal diffuser included
end caps and mounting clips



		EUR	CODE
	2m	29,00	911991W2
	2m	29,00	911991B2
	3m	46,00	911991W3
	3m	46,00	911991B3

2.0 PROFILE

aluminium | opal diffuser included
end caps and mounting clips



		EUR	CODE
	2m	44,00	911992W2
	2m	44,00	911992B2
	3m	62,00	911992W3
	3m	62,00	911992B3

ALWAYS USE

LED COB strip 24V | IP20
10W/m | 800lm/m

	EUR	CODE
20W | 2m	38,50	9003S21_
30W | 3m	57,00	9003S31_
50W | 5m	96,00	9003S41_

LED COB strip 24V | IP20
15W/m | 1250lm/m

	EUR	CODE
30W | 2m	57,00	9003S22_
45W | 3m	77,00	9003S32_
75W | 5m	135,00	9003S42_

LIGHT COLOUR	CRI	CODE
2700K	>90	3
3000K	>90	5

driver | 24V

	EUR	CODE
35W	42,00	90212801
100W	73,80	90212902
25W dim	46,00	90222701
50W dim	68,00	90222901

specs on page 901

ALWAYS USE

LED COB strip 24V | IP20
10W/m | 800lm/m

	EUR	CODE
20W | 2m	38,50	9003S21_
30W | 3m	57,00	9003S31_
50W | 5m	96,00	9003S41_

LED COB strip 24V | IP20
15W/m | 1250lm/m

	EUR	CODE
30W | 2m	57,00	9003S22_
45W | 3m	77,00	9003S32_
75W | 5m	135,00	9003S42_

LIGHT COLOUR	CRI	CODE
2700K	>90	3
3000K	>90	5

driver | 24V

	EUR	CODE
35W	42,00	90212801
100W	73,80	90212902
25W dim	46,00	90222701
50W dim	68,00	90222901

specs on page 901

OPTIONAL

Black diffuser | only for 1.0

	EUR	CODE
2m	14,00	911902B1
3m	21,00	911903B1

Double side tape for profile fixation

	EUR	CODE
3m	15,50	90019199

more accessories on page 916

back



PRIVATE RESIDENCE SPAIN

ILANE

Ceiling surface / recessed





for net output of LED strip on profiles,
check weverducre.com/ilane

OPTIONAL

Black diffuser | only for 3.0

	EUR	CODE
2m	17,00	911912B1
3m	23,00	911913B1

Double side tape for profile fixation

	EUR	CODE
3m	15,50	90019199

more accessories on page 916

3.0 PROFILE

aluminium | opal diffuser included
end caps and mounting clips



		EUR	CODE
	2m	46,00	911993W2
	2m	46,00	911993B2
	3m	67,00	911993W3
	3m	67,00	911993B3

ALWAYS USE

LED COB strip 24V | IP20
10W/m | 800lm/m

	EUR	CODE
20W | 2m	38,50	9003S21_
30W | 3m	57,00	9003S31_
50W | 5m	96,00	9003S41_

LED COB strip 24V | IP20
15W/m | 1250lm/m

	EUR	CODE
30W | 2m	57,00	9003S22_
45W | 3m	77,00	9003S32_
75W | 5m	135,00	9003S42_

LIGHT COLOUR	CRI	CODE
2700K	>90	3
3000K	>90	5

driver | 24V

	EUR	CODE
35W	42,00	90212801
100W	73,80	90212902
25W dim	46,00	90222701
50W dim	68,00	90222901

specs on page 901

4.0 PROFILE

aluminium | opal diffuser included
end caps and mounting clips



		EUR	CODE
	2m	58,00	911994W2
	2m	58,00	911994B2
	3m	76,00	911994W3
	3m	76,00	911994B3

ALWAYS USE

LED COB strip 24V | IP20
10W/m | 800lm/m

	EUR	CODE
20W | 2m	38,50	9003S21_
30W | 3m	57,00	9003S31_
50W | 5m	96,00	9003S41_

LED COB strip 24V | IP20
15W/m | 1250lm/m

	EUR	CODE
30W | 2m	57,00	9003S22_
45W | 3m	77,00	9003S32_
75W | 5m	135,00	9003S42_

LIGHT COLOUR	CRI	CODE
2700K	>90	3
3000K	>90	5

driver | 24V

	EUR	CODE
35W	42,00	90212801
100W	73,80	90212902
25W dim	46,00	90222701
50W dim	68,00	90222901

specs on page 901

back

Ceiling suspended

412 – 565

SINGLE LUMINAIRES



MATCH LUSTA
415



TRACE CHANDELIER
417



NET
421



FINELLE
423



FLYRA
427

FINLIN
433



STUDO
437



FIL
441



DARF
445



SHEDDA
449



SHEDDA FRACTAL
451



KUJO
453



OPLIA CHANDELIER
457



QUBBY
459



GIGANT
461

SINGLE SUSPEN-SIONS



CONE
463



DRO
465



MIRRO
467



MIRRO SOFT
471



SPIRRA SOFT
475



WAVE SOFT
477



J.J.W.
479



WIRO
489



ROOMOR
495



ROOMOR OFFICE
499

CHOOSE YOUR BASE

LV more infos
on p. 500

COZY CONE
503

HEXO MINI
505

RAY MINI
507

MATCH
509

TRACE
511



ODREY
517

OPLIA
521



SOLLI
523



SOLLI COCOON
525

CHOOSE YOUR BASE

HV more infos
on p. 528

HEXO MINI
531



HEXO
533

RAY MINI
535

RAY
537

ODREY
539



TRACE 2.0
547

WETRO
549

CLEA
557

SHIEK
561

DINOR
563

back

MATCH LUSTA

Ceiling suspended

61 | 137 | 153
193
329 | 347
571
589 | 685
723 | 729











1.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-30° L80|50K

2700K | CRI >90 | 3x240lm

	EUR	CODE
	510,00	280154M3
	510,00	280154Q3
	485,00	280154B3

2.1

LED COB 18W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-30° L80|50K

2700K | CRI >90 | 6x240lm

	EUR	CODE
	825,00	280254M3
	825,00	280254Q3
	790,00	280254B3

3.2

LED COB 18W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-30°L80|50K

2700K | CRI >90 | 6x240lm

	EUR	CODE
	890,00	280354M3
	890,00	280354Q3
	845,00	280354B3

3.2.1

LED COB 26W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-30° L80|50K

2700K | CRI >90 | 9x240lm

	EUR	CODE
	1240,00	280454M3
	1240,00	280454Q3
	1150,00	280454B3

back



PRIVATE RESIDENCE | RARDO ARCHITECTS SPAIN

reddot winner 2023

TRACE CHANDELIER

Ceiling suspended

261 | 269 | 273

351

593 | 595





1.0

LED COB 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-30° L80|50K

	EUR	CODE
	495,00	253564CH_
	495,00	253564B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	4x170	>90	3
3000K	4x180	>90	5



2.0

LED COB 16W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-30° L80|50K

	EUR	CODE
	665,00	253664CH_
	665,00	253664B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	6x180	>90	3
3000K	6x190	>90	5



3.0

LED COB 17W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-30° L80|50K

	EUR	CODE
	825,00	253764CH_
	825,00	253764B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	8x215	>90	3
3000K	8x225	>90	5

back





RESTAURANT L'APERICENA TIME | ARCH. LEONARDO PORCELLI – STILEMI RIVAROLO CANAVESE | ITALY



PRIVATE RESIDENCE | SOFIE CHRISTIAENS BELGIUM

NET

Ceiling suspended





2.0

LED PCB 14W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 W-85° L80|50K

2700K | CRI >90 | 2x235lm

	EUR	CODE
	465,00	231264W3
	465,00	231264M3
	465,00	231264B3



4.0

LED PCB 28W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 W-85° L80|50K

2700K | CRI >90 | 4x235lm

	EUR	CODE
	890,00	231464W3
	890,00	231464M3
	890,00	231464B3

back

FINELLE

Ceiling suspended





1.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP20 L80|100K

2700K | CRI >90 | 1040lm

	EUR	CODE
	495,00	272184M3
	495,00	272184B3

back





PRIVATE RESIDENCE | EN-TRE STUDIO BULGARIA



FLYRA

Ceiling suspended

401



DALI on request



1.1 VERTICAL

LED strip 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP20 L80|50K

	EUR	CODE
	325,00	249184M_
	325,00	249184B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	710	>90	3
3000K	730	>90	5



1.2 VERTICAL

LED strip 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP20 L80|50K

	EUR	CODE
	395,00	249284M_
	395,00	249284B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1065	>90	3
3000K	1095	>90	5



1.3 VERTICAL

LED strip 16W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP20 L80|50K

	EUR	CODE
	465,00	249384M_
	465,00	249384B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1420	>90	3
3000K	1460	>90	5

back



FLYRA

Ceiling suspended

401





3.1 VERTICAL

LED strip 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP20 L80|50K

	EUR	CODE
	1140,00	449184BM_
	1140,00	449184BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	965	>90	3
3000K	995	>90	5



3.3 VERTICAL

LED strip 18W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP20 L80|50K

	EUR	CODE
	1350,00	449284BM_
	1350,00	449284BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1450	>90	3
3000K	1490	>90	5



6.3 VERTICAL

LED strip 35W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP20 L80|50K

	EUR	CODE
	2370,00	449384BM_
	2370,00	449384BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2900	>90	3
3000K	2985	>90	5

back

FLYRA

Ceiling suspended

401





1.1 HORIZONTAL

LED strip 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP20 L80|50K

	EUR	CODE
	335,00	269184M_
	335,00	269184B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	710	>90	3
3000K	730	>90	5



1.2 HORIZONTAL

LED strip 14W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP20 L80|50K

	EUR	CODE
	395,00	269284M_
	395,00	269284B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1065	>90	3
3000K	1095	>90	5



1.3 HORIZONTAL

LED strip 18W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP20 L80|50K

	EUR	CODE
	465,00	269384M_
	465,00	269384B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1420	>90	3
3000K	1460	>90	5

DALI on request

back





DESIGN AWARD 2024

reddot winner 2023

FINLIN

Ceiling suspended

263

673 | 679

727







1.0

LED PCB 5W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 L80|50K

		EUR	CODE
	2.5m	250,00	270184CH_
	2.5m	250,00	270184B_
	10m	280,00	270484B5

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	450	>90	3
3000K	485	>90	5

2.0

LED PCB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 L80|50K

		EUR	CODE
	2.5m	260,00	270284CH_
	2.5m	260,00	270284B_
	10m	290,00	270584B5

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	675	>90	3
3000K	730	>90	5

3.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 L80|50K

		EUR	CODE
	2.5m	295,00	270384CH_
	2.5m	295,00	270384B_
	10m	325,00	270684B5

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	900	>90	3
3000K	975	>90	5

OPTIONAL

cover plate adapter for concrete housing

	EUR	CODE
	12,50	900194B0

back

studo

STUDO HELPS YOU OUT

STUDO laat zien hoe veelzijdig een armatuur kan zijn: vijf ophangmogelijkheden maken deze ultraslanke pendel tot een flexibele allrounder. Het aluminium profiel met krachtige reflector en plat textielsnoer zorgt voor een strakke, minimalistische look – ideaal voor een kantoor of een keuken.

STUDO démontre la polyvalence d'un luminaire : cinq options de suspension font de cette suspension ultra-fine un véritable atout flexible. Son profil en aluminium avec réflecteur performant et câble textile plat crée un look épuré et minimaliste – parfait pour le bureau ou la cuisine.





STUDO

Ceiling suspended







1.0

LED PCB 18W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | polycarbonate
suspension textile belt
incl. 2 ceiling brackets

IP20 W-67° L80|100K

3000K | CRI >90 | 1750lm

	EUR	CODE
	425,00	195174W5
	425,00	195174B5

2.0

LED PCB 27W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | polycarbonate
suspension textile belt
incl. 2 ceiling brackets

IP20 W-67° L80|100K

3000K | CRI >90 | 2700lm

	EUR	CODE
	545,00	195274W5
	545,00	195274B5

UGR ≤ 19
65°≤ 3000cd

back





PRIVATE RESIDENCE | STUDIO BRASS THE NETHERLANDS

FIL

Ceiling suspended





267





681



1.0

LED PCB 22W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 L80|50K

	EUR	CODE
	465,00	2543M4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1070	>90	3
3000K	1120	>90	5



2.0

LED PCB 26W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 L80|50K

	EUR	CODE
	495,00	2544M4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1280	>90	3
3000K	1340	>90	5





back



PRIVATE RESIDENCE | RICCARDO ROSSI SWITZERLAND



BENEDICTION | KKOL STUDIO SEOUL | SOUTH KOREA

DARF

Ceiling suspended



643



2.1

LED TUBE 10W | non dim
220-240VAC | 50-60Hz
aluminium | black textile cable

IP20 L70|75K

3000K | CRI >80 | 1530lm

	EUR	CODE
	239,00	2565T7B4



3.1

LED TUBE 14W | non dim
220-240VAC | 50-60Hz
aluminium | black textile cable

IP20 L70|75K

3000K | CRI >80 | 2300lm

	EUR	CODE
	244,00	2564T7B4



4.1

LED TUBE 22W | non dim
220-240VAC | 50-60Hz
aluminium | black textile cable

IP20 L70|60K

	EUR	CODE
	248,00	2568T7B_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	3560	>80	4
4000K	3950	>80	6



4.2

LED TUBE 23W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | black textile cable

IP20 L70|60K

	EUR	CODE
	307,00	2568T8B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2780	>90	3
3000K	2940	>90	5

ARCHITECT | PHILIPP WEINBERGER & STUDIO MARCH GUT

back





▶ **DESIGN WITH LOVE**

MOTTO PILATES | STUDIO WOLF OFFENBACH | GERMANY



SHEDDA

Ceiling suspended





1.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white luminaire – coloured shade

IP20 L80|100K

	EUR	CODE
	395,00	242184LS_
	395,00	242184SG_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	565	>90	3
3000K	580	>90	5



2.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white luminaire – coloured shade

IP20 L80|100K

	EUR	CODE
	495,00	242284LS_
	495,00	242284SG_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	565	>90	3
3000K	580	>90	5

back

SHEDDA fractal

Ceiling suspended





1.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white luminaire – coloured shade

IP20 L80|100K

	EUR	CODE
	445,00	242684LS_
	445,00	242684SG_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	565	>90	3
3000K	580	>90	5



2.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white luminaire – coloured shade

IP20 L80|100K

	EUR	CODE
	545,00	242784LS_
	545,00	242784SG_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	565	>90	3
3000K	580	>90	5



KUJO

Ceiling suspended









1.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | silicone cover
base in matching colour

IP20 L80|100K

	EUR	CODE
	298,00	273184W_
	298,00	273184SG_
	298,00	273184M_
	298,00	273184Q_
	298,00	273184B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	755	>90	3
3000K	800	>90	5

2.0

LED PCB 15W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | silicone cover
base in matching colour

IP20 L80|100K

	EUR	CODE
	375,00	273284W_
	375,00	273284SG_
	375,00	273284M_
	375,00	273284Q_
	375,00	273284B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1140	>90	3
3000K	1175	>90	5

3.0

LED PCB 19W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | silicone cover
base in matching colour

IP20 L80|100K

	EUR	CODE
	475,00	273384W_
	475,00	273384SG_
	475,00	273384M_
	475,00	273384Q_
	475,00	273384B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1520	>90	3
3000K	1565	>90	5

white fixtures – white cable/silver steel wire | SG fixtures – SG cable/silver steel wire | others – black cable/steel wire
DALI on request

back



KUJO

Ceiling suspended





2.1

LED PCB 34W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | silicone cover
base in matching colour

IP20 L80|100K

	EUR	CODE
	650,00	273484W_
	650,00	273484SG_
	650,00	273484M_
	650,00	273484Q_
	650,00	273484B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1940	>90	3
3000K	2000	>90	5



3.2

LED PCB 48W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | silicone cover
base in matching colour

IP20 L80|100K

	EUR	CODE
	815,00	273684W_
	815,00	273684SG_
	815,00	273684M_
	815,00	273684Q_
	815,00	273684B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2720	>90	3
3000K	2800	>90	5



3.2.1

LED PCB 60W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | silicone cover
base in matching colour

IP20 L80|100K

	EUR	CODE
	1095,00	273784W_
	1095,00	273784SG_
	1095,00	273784M_
	1095,00	273784Q_
	1095,00	273784B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	3490	>90	3
3000K	3595	>90	5

white fixtures – white cable/0.3m connector/silver steel wire | SG fixtures – SG cable/0.3m connector/steel wire
others – black cable/0.3m connector/ black steel wire
other connectors on page 921

back



OPLIA CHANDELIER

Ceiling suspended

357







1.0

LED PCB 29W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | glass
white fixture – white cable
black fixture – black cable

IP20 L80|100K

2700K| CRI >90 | 2000lm

	EUR	CODE
	1940,00	246584W3
	1940,00	246584B3

2.0

LED PCB 29W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | glass
white fixture – white cable
black fixture – black cable

IP20 L80|100K

2700K| CRI >90 | 2000lm

	EUR	CODE
	1960,00	246684W3
	1960,00	246684B3





back



QUBBY

Ceiling suspended











1.0

LED PCB 16W | DALI-2 DT8
220-240VAC | 50-60Hz | incl. driver
aluminium | opal polyethylene
incl. suspension set
default light colour 3500K

IP20 L80|100K

2700K-5000K| CRI >90 | 1250lm

	EUR	CODE
	740,00	251185B9

2.0

LED PCB 22W | DALI-2 DT8
220-240VAC | 50-60Hz | incl. driver
aluminium | opal polyethylene
incl. suspension set
default light colour 3500K

IP20 L80|100K

2700K-5000K| CRI >90 | 2500lm

	EUR	CODE
	980,00	251285B9

3.0

LED PCB 35W | DALI-2 DT8
220-240VAC | 50-60Hz | incl. driver
aluminium | opal polyethylene
incl. suspension set
default light colour 3500K

IP20 L80|100K

2700K-5000K| CRI >90 | 4500lm

	EUR	CODE
	1540,00	251385B9

S&R CORNELISSEN

back



OFFICE NNE | OVER BYEN COPENHAGEN | DENMARK

GIGANT

Ceiling suspended







10.0

LED PCB 43W | DALI-2 | switch dim
220-240VAC | 50-60Hz | incl. driver
steel | opal LLDPE body | UL 94
HB std.glow wire test 630°

IP20 L80|60K

3000K | CRI >80 | 5330lm

	EUR	CODE
	1690,00	213385W4

4000K | CRI >80 | 5670lm

	EUR	CODE
	1690,00	213385W6

OPTIONAL

	EUR	CODE
suspension set 4m	98,00	90015114

longer suspension on request

16.0

LED PCB 85W | DALI-2 | switch dim
220-240VAC | 50-60Hz | incl. driver
steel | opal LLDPE body | UL 94
HB std.glow wire test 630°

IP20 L80|60K

3000K | CRI >80 | 10700lm

	EUR	CODE
	2250,00	213485W4

4000K | CRI >80 | 11300lm

	EUR	CODE
	2250,00	213485W6

OPTIONAL

	EUR	CODE
suspension set 4m	98,00	90015114

longer suspension on request

CONE

Ceiling suspended





1.0

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | chrome plated | glass

IP20 M-38° L80|60K

2700K | CRI >90 | 405lm

	EUR	CODE
	282,00	200184W3
	282,00	200184B3

back



PASTRY SHOP WITTAMER BRUSSELS | BELGIUM

DRO

Ceiling suspended



279
373
623
715 | 731



1.0

QT14 max. 5W | G9
220-240VAC | 50-60Hz
aluminium
artisanal Italian hand blown glass

IP20

	EUR	CODE
	195,00	2521G0WB0

OPTIONAL

QT14 3.5W | G9 | phase-cut dim clear

	EUR	CODE
2700K | 340lm	18,00	9010G803
3000K | 350lm	18,00	9010G805



2.0

C35 max. 6W | E14
220-240VAC | 50-60Hz
aluminium
artisanal Italian hand blown glass

IP20

	EUR	CODE
	275,00	2522C0WB0

OPTIONAL

C35 5.5W | E14 | phase-cut dim | opal

	EUR	CODE
2700K | 450lm	10,50	9003C103



3.0

A60 max. 12W | E27
220-240VAC | 50-60Hz
aluminium
artisanal Italian hand blown glass

IP20

	EUR	CODE
	355,00	2523E0WB0

OPTIONAL

A60 9W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 800lm	14,50	9003E152



4.0

A65 max. 15W | E27
220-240VAC | 50-60Hz
aluminium
artisanal Italian hand blown glass

IP20

	EUR	CODE
	545,00	2524E0WB0

OPTIONAL

A65 14.6W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1375lm	22,00	9003E153

13&9 DESIGN

back



HAUS BRINA | PRO URBAN AG DÜSSELDORF | GERMANY

MIRRO

Ceiling suspended







283
625
721 | 733

1.0

A60 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | one side reflective
composite panel

IP20

	EUR	CODE
	245,00	6341E0GB0
	245,00	6341E0NB0
	245,00	6341E0LB0
	245,00	6341E0BL0

OPTIONAL

A60 5.5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2700K | 405lm	32,00	9003E139

A60 5.5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 405lm	32,00	9003E140

2.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | one side reflective
composite panel

IP20

	EUR	CODE
	293,00	6342E0GB0
	293,00	6342E0NB0
	293,00	6342E0LB0
	293,00	6342E0BL0

OPTIONAL

G95 5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 395lm	35,00	9003E157

3.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | one side reflective
composite panel

IP20

	EUR	CODE
	453,00	6343E0GB0
	453,00	6343E0NB0
	453,00	6343E0LB0
	453,00	6343E0BL0

OPTIONAL

G95 5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 395lm	35,00	9003E157



MORE VERSIONS ONLINE
weverducre.com/more-mirro

13&9 DESIGN

back









MIRRO SOFT

Ceiling suspended





2.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | PET felt material
noise absorbing material

IP20

	EUR	CODE
	293,00	6342E0MF0
	293,00	6342E0LF0
	293,00	6342E0IF0
	293,00	6342E0AF0

3.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | PET felt material
noise absorbing material

IP20

	EUR	CODE
	453,00	6343E0MF0
	453,00	6343E0LF0
	453,00	6343E0IF0
	453,00	6343E0AF0

OPTIONAL

G95 5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 395lm	35,00	9003E157

G95 10W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

G95 4.5W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 375lm	33,00	9003E160

OPTIONAL

G95 5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 395lm	35,00	9003E157

G95 10W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

G95 4.5W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 375lm	33,00	9003E160

285
629

MORE VERSIONS ONLINE
weverducre.com/more-mirro

13&9 DESIGN

back



COMBINE IT WITH OTHER OPTIONS
weverducre.com/mirro

back



SPIRRA SOFT

Ceiling suspended









1.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | PET felt material
noise absorbing material

IP20

	EUR	CODE
	365,00	6351E0MF0
	365,00	6351E0LF0
	365,00	6351E0IF0
	365,00	6351E0AF0

OPTIONAL

G95 10W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

2.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | PET felt material
noise absorbing material

IP20

	EUR	CODE
	555,00	6352E0MF0
	555,00	6352E0LF0
	555,00	6352E0IF0
	555,00	6352E0AF0

OPTIONAL

G95 10W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

3.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | PET felt material
noise absorbing material

IP20

	EUR	CODE
	425,00	6353E0MF0
	425,00	6353E0LF0
	425,00	6353E0IF0
	425,00	6353E0AF0

OPTIONAL

G95 10W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

MORE VERSIONS ONLINE
weverducre.com/more-spirra-soft

13&9 DESIGN

back



WAVE SOFT

Ceiling suspended



1.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | PET felt material
noise absorbing material

IP20

	EUR	CODE
	435,00	6361E0MF0
	435,00	6361E0LF0
	435,00	6361E0IF0
	435,00	6361E0AF0

OPTIONAL

G95 10W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

2.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | PET felt material
noise absorbing material

IP20

	EUR	CODE
	695,00	6362E0MF0
	695,00	6362E0LF0
	695,00	6362E0IF0
	695,00	6362E0AF0

OPTIONAL

G95 10W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

3.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | PET felt material
noise absorbing material

IP20

	EUR	CODE
	450,00	6363E0MF0
	450,00	6363E0LF0
	450,00	6363E0IF0
	450,00	6363E0AF0

OPTIONAL

G95 10W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

MORE VERSIONS ONLINE
weverducre.com/more-wave-soft



EOAK FLOORS SHOWROOM | VIGONARCHITECTS HANOI | VIETNAM



JULES WABBES

J.J.W.

Ceiling suspended

289

633



04

6x A60 max. 15W | E27
220-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	1955,00	2052E0S0
	1955,00	2052E0G0

OPTIONAL

A60 3.8W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 245lm	31,00	9003E109

A60 5.6W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 480lm	31,00	9003E138

back





J.J.W.

Ceiling suspended

289

633



042

6x A60 max. 15W | E27
220-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	3590,00	2056E0S0
	3590,00	2056E0G0

OPTIONAL

A60 3.8W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 245lm	31,00	9003E109

A60 5.6W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 480lm	31,00	9003E138

MERCURE CHANTILLY | PROJECT MANAGED BY ATYPIO HOTELS RESORTS WITH ABP ARCHITECTS VINEUIL-SAINT-FIRMIN | FRANCE

JULES WABBES

back



MERCURE CHANTILLY | PROJECT MANAGED BY ATYPIO HOTELS RESORTS WITH ABP ARCHITECTS VINEUIL-SAINT-FIRMIN | FRANCE

back

▶ DESIGN WITH LOVE



MERCURE CHANTILLY | PROJECT MANAGED BY ATYPIO HOTELS RESORTS WITH ABP ARCHITECTS | L'OBSERVATOIRE DE LA NUIT VINEUIL-SAINT-FIRMIN | FRANCE



JULES WABBES

back

J.J.W.

Ceiling suspended

289

633



05

3x A60 max. 15W | E27
220-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	1695,00	2053E0S0
	1695,00	2053E0G0

OPTIONAL

A60 3.8W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 245lm	31,00	9003E109

A60 5.6W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 480lm	31,00	9003E138



decenter











1.0 CONE

	EUR	CODE
	185,00	245100V0
	185,00	245100B0

2.0 WIRO

	EUR	CODE
	165,00	209600B0

1.8 WIRO

	EUR	CODE
	205,00	209200V0
	205,00	209200B0

3.8 WIRO

	EUR	CODE
	297,00	209300V0
	297,00	209300B0

1.1 DIAMOND

	EUR	CODE
	205,00	244100P0
	205,00	244100B0

A

CABLE PLUG AND PLAY

E27 LED 4-25W | connector set for one shade | black textile cable incl. cable plug with dimmer | 2 cable brackets included

	EUR	CODE
8.5m	168,00	90015165

B

DECENTER SET 1.0

A60 max. 60W | E27
220-240VAC | 50-60Hz
suspension set for 1 shade
round ceiling base | black textile cable
1 base + 1 end stop included

	EUR	CODE
2.6m	108,00	90052050
6m	118,00	90052051

C

DECENTER SET 2.0

2x A60 max. 60W | E27
220-240VAC | 50-60Hz
suspension set for 2 shades
round ceiling base | black textile cable
1 multibase + 2 end stops included

	EUR	CODE
2.6m	198,00	90052055
6m	228,00	90052056

D

DECENTER SET 3.0

3x A60 max. 60W | E27
220-240VAC | 50-60Hz
suspension set for 3 shades
round ceiling base | black textile cable
1 multibase + 3 end stops included

	EUR	CODE
2.6m	286,00	90052060
6m	336,00	90052063

E

DECENTER SET 4.0

4x A60 max. 60W | E27
220-240VAC | 50-60Hz
suspension set for 4 shades
round ceiling base | black textile cable
1 multibase + 4 end stops included

	EUR	CODE
2.6m	368,00	90052067
6m	418,00	90052078



RAIFFEISENBANK | BREM+ZEHNDER INNENARCHITEKTUR DIETIKON | SWITZERLAND

WIRO

Ceiling suspended

291





1.0 CONE

T30 max. 60W | E27
220-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	284,00	2451E0V0
	284,00	2451E0B0

more suspension options on page 487

OPTIONAL

T30-225 5.3W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 380lm	39,00	9003E129
2700K | 425lm	39,00	9003E136



2.0 WIRO

A60 max. 60W | E27
220-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	264,00	2096E0B0

more suspension options on page 487

OPTIONAL

A60 3.8W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 245lm	31,00	9003E109

A60 5.6W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 480lm	31,00	9003E138



1.8 WIRO

A60 max. 60W | E27
220-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	304,00	2092E0V0
	304,00	2092E0B0

more suspension options on page 487

OPTIONAL

A60 3.8W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 245lm	31,00	9003E109

A60 5.6W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 480lm	31,00	9003E138

T30-225 5.3W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 380lm	39,00	9003E129
2700K | 425lm	39,00	9003E136

MORE VERSIONS ONLINE
weverducre.com/more-wiro

BERND STEINHUBER

back



PRIVATE RESIDENCE | STUDIO BENOIT BELGIUM

WIRO

Ceiling suspended

291



3.8

A60 max. 60W | E27
220-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	396,00	2093E0V0
	396,00	2093E0B0

more suspension options on page 487

OPTIONAL

A60 3.8W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 245lm	31,00	9003E109

A60 5.6W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 480lm	31,00	9003E138

T30-225 5.3W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 380lm	39,00	9003E129
2700K | 425lm	39,00	9003E136



6.1

A60 max. 60W | E27
220-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	450,00	2094E0V0
	450,00	2094E0B0

OPTIONAL

A60 3.8W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 245lm	31,00	9003E109

A60 5.6W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 480lm	31,00	9003E138

T30-300 7.2W/7.4W | E27
phase-cut dim | gold tinted

	EUR	CODE
2200K | 585lm	43,00	9003E130
2700K | 610lm	43,00	9003E135



6.5

A60 max. 60W | E27
220-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	596,00	2095E0V0
	596,00	2095E0B0

OPTIONAL

A60 3.8W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 245lm	31,00	9003E109

A60 5.6W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 480lm	31,00	9003E138

T30-300 7.2W/7.4W | E27
phase-cut dim | gold tinted

	EUR	CODE
2200K | 585lm	43,00	9003E130
2700K | 610lm	43,00	9003E135

MORE VERSIONS ONLINE
weverducre.com/more-wiro

BERND STEINHUBER

back



RESTAURANT QUEBRACHO STEAKHOUSE & MIXOLOGY | **MICHELE MEZZINA** PESCARA | ITALY

WIRO

Ceiling suspended





1.1 DIAMOND

T30 max. 60W | E27
220-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	314,00	2441E0P0
	314,00	2441E0B0

more suspension options on page 487

OPTIONAL

T30-300 7.2W/7.4W | E27
phase-cut dim | gold tinted

	EUR	CODE
2200K | 585lm	43,00	9003E130
2700K | 610lm	43,00	9003E135



2.0 DIAMOND

T30 max. 60W | E27
220-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	655,00	2292E0P0
	655,00	2292E0B0

OPTIONAL

T30-300 7.2W/7.4W | E27
phase-cut dim | gold tinted

	EUR	CODE
2200K | 585lm	43,00	9003E130
2700K | 610lm	43,00	9003E135



3.0 DIAMOND

T30 max. 60W | E27
220-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	925,00	2293E0P0
	925,00	2293E0B0

OPTIONAL

T30-300 7.2W/7.4W | E27
phase-cut dim | gold tinted

	EUR	CODE
2200K | 585lm	43,00	9003E130
2700K | 610lm	43,00	9003E135

MORE VERSIONS ONLINE
weverducre.com/more-wiro

BERND STEINHUBER

back



APARTMENT RONDA SANT PERE | DANIEL NASSAR SPAIN



reddot award 2019
winner lighting design



ROOMOR

Ceiling suspended











1.1 PAR16

PAR16 max. 15W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	213,00	248120GG1
	213,00	248120BK1
	208,00	248120BB1

1.1 E27

A60 max. 15W | E27
220-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	213,00	2481E0GG1
	213,00	2481E0BK1
	208,00	2481E0BB1

1.2 E27

A60 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | grey felt

IP20

	EUR	CODE
	276,00	2481E0BF2
	257,00	2481E0BK2
	249,00	2481E0BB2

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

OPTIONAL

A60 9W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 800lm	14,50	9003E152

OPTIONAL

A60 9W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 800lm	14,50	9003E152

MORE VERSIONS ONLINE
weverducre.com/more-roomor

back



ADESA | MARKEY & SCHELSTRAETE TIENEN | BELGIUM


BF3


BK3


BB3


BK4


BB4

reddot award 2019
winner lighting design



MORE VERSIONS ONLINE
weverducre.com/more-roomor

ROOMOR

Ceiling suspended

1.3

A60 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | grey felt

IP20

	EUR	CODE
	353,00	2481E0BF3
	342,00	2481E0BK3
	329,00	2481E0BB3

OPTIONAL

A60 9W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 800lm	14,50	9003E152



1.4

A60 max. 15W | E27
220-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	395,00	2481E0BK4
	383,00	2481E0BB4

OPTIONAL

A60 9W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 800lm	14,50	9003E152

639

725 | 735

back



LINK LAB CREATIVE OFFICE | STAY STUDIO KORTRIJK | BELGIUM

reddot winner 2021

ROOMOR OFFICE

Ceiling suspended

293

395







1.0 MICROPRISMATIC

LED PCB 35W | DALI-2 | push dim
220-240VAC | 50-60Hz | incl. driver
aluminium
microprismatic PMMA cover

IP20 L80|60K UGR ≤ 19

	EUR	CODE
	785,00	1681M5W_
	785,00	1681M5B_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	3660	>90	5
4000K	3660	>90	7

UGR ≤ 19
65°≤ 3000cd
microprismatic

1.0 OPAL

LED PCB 35W | DALI-2 | push dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA cover

IP20 L80|60K

	EUR	CODE
	775,00	168185W_
	775,00	168185B_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	3700	>90	5
4000K	3700	>90	7

back

low











AL | SINGLE BASE

ceiling base round
phase-cut dim | 350mA | incl. driver

	EUR	CODE
	65,00	914112W0
	65,00	914112L0
	65,00	914112G0
	65,00	914112M0
	65,00	914112Q0
	65,00	914112B0

DALI versions on page 920

OPLIA

phase-cut dim | 250mA | incl. driver

	EUR	CODE
	65,00	914115W0
	65,00	914115M0
	65,00	914115B0

DALI versions on page 920

BL | SEMI RECESSED SINGLE BASE

phase-cut dim | 350mA | incl. driver

73-76 70 10-35

	EUR	CODE
	85,00	914152W0
	85,00	914152L0
	85,00	914152M0
	85,00	914152Q0
	85,00	914152B0

OPLIA

phase-cut dim | 250mA | incl. driver

	EUR	CODE
	75,00	914155W0
	75,00	914155M0
	75,00	914155B0

EL | MULTI BASE LINEAR

3, 6 or 9 luminaires | phase-cut dim
incl. driver | 175mA per luminaire
600mm | 1200mm | 1800mm

		EUR	CODE
	for 3	165,00	914133W0
	for 3	165,00	914133B0
	for 6	270,00	914134W0
	for 6	270,00	914134B0
	for 9	395,00	914135W0
	for 9	395,00	914135B0

GL | TRACK ADAPTER

for 3-phase tracks
phase-cut dim | 350mA | incl. driver

	EUR	CODE
	46,00	914173W0
	46,00	914173B0

DALI versions on page 920

OPLIA

phase-cut dim | 250mA | incl. driver

	EUR	CODE
	46,00	914171W0
	46,00	914171B0

DALI versions on page 920



FL | MULTI CHANDELIER

3 luminaires | 3x175mA
phase-cut dim | incl. driver
COZY CONE | MATCH | TRACE
ODREY | OPLIA

	EUR	CODE
	260,00	914121WW0
	300,00	914121BL0
	260,00	914121BM0
	260,00	914121BQ0
	260,00	914121BB0

RAY MINI | HEXO MINI | SOLLI

	EUR	CODE
	260,00	914124WW0
	300,00	914124BL0
	260,00	914124BM0
	260,00	914124BQ0
	260,00	914124BB0

FL | MULTI CHANDELIER

6 luminaires | 6x175mA
phase-cut dim | incl. driver
COZY CONE | MATCH | TRACE
ODREY | OPLIA

	EUR	CODE
	295,00	914122WW0
	335,00	914122BL0
	295,00	914122BM0
	295,00	914122BQ0
	295,00	914122BB0

RAY MINI | HEXO MINI | SOLLI

	EUR	CODE
	295,00	914125WW0
	335,00	914125BL0
	295,00	914125BM0
	295,00	914125BQ0
	295,00	914125BB0

FL | MULTI CHANDELIER

9 luminaires | 9x175mA
phase-cut dim | incl. driver
COZY CONE | MATCH | TRACE
ODREY | OPLIA

	EUR	CODE
	330,00	914123WW0
	370,00	914123BL0
	330,00	914123BM0
	330,00	914123BQ0
	330,00	914123BB0

RAY MINI | HEXO MINI | SOLLI

	EUR	CODE
	330,00	914126WW0
	370,00	914126BL0
	330,00	914126BM0
	330,00	914126BQ0
	330,00	914126BB0

HOOK

optional for
FL | MULTI CHANDELIER

	EUR	CODE
	19,00	90052083
	19,00	90052084

more Multi chandelier options
on page 920

back



COZY CONE

Low voltage
Ceiling suspended



345

CHOOSE YOUR BASE

AL | Single base
ceiling base round | 350mA
phase-cut dim | incl. driver

	EUR	CODE
	65,00	914112W0
	65,00	914112L0
	65,00	914112B0

BL | Semi recessed single base
EL | Multi base linear

FL | Multi chandelier
6 luminaires | 6x175mA | 1440lm
phase-cut dim | incl. driver

	EUR	CODE
	295,00	914122WW0
	335,00	914122BL0
	295,00	914122BB0

GL | Track adapter
more infos on page 500

LOXONE VERSIONS ONLINE
weverducre.com/more-cozy-cone



1.0

LED COB 6W | 350mA | 18V
aluminium | glass
black and T fixtures – black cable
others – white cable

IP20 M-40° L80|50K

2700K | CRI >90 | 500lm

	EUR	CODE
	125,00	241161LS3
	125,00	241161SG3
	125,00	241161FJ3
	133,00	241161T3
	125,00	241161B3



2.0

LED COB 6W | 350mA | 18V
aluminium | glass
black and T fixtures – black cable
others – white cable

IP20 M-40° L80|50K

2700K | CRI >90 | 510lm

	EUR	CODE
	130,00	241261LS3
	130,00	241261SG3
	130,00	241261FJ3
	138,00	241261T3
	130,00	241261B3



3.0

LED COB 6W | 350mA | 18V
aluminium | glass
black and T fixtures – black cable
others – white cable

IP20 M-40° L80|50K

2700K | CRI >90 | 545lm

	EUR	CODE
	135,00	241361LS3
	135,00	241361SG3
	135,00	241361FJ3
	143,00	241361T3
	135,00	241361B3

back





HEXO mini

Low voltage
Ceiling suspended


243


375 | 391




611





CHOOSE YOUR BASE

AL | Single base
ceiling base round | 350mA
phase-cut dim | incl. driver

	EUR	CODE
	65,00	914112M0
	65,00	914112Q0
	65,00	914112B0

BL | Semi recessed single base
EL | Multi base linear
FL | Multi chandelier
GL | Track adapter
more infos on page 500

LOXONE VERSIONS ONLINE
weverducre.com/more-hexo

3.0

LED COB 6W | 350mA | 18V
aluminium

IP20 W-75° L80|50K

	EUR	CODE
	186,00	259171M_
	186,00	259171Q_
	186,00	259171B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	525	>90	3
3000K	565	>90	5

5.0

LED COB 6W | 350mA | 18V
aluminium

IP20 W-75° L80|50K

	EUR	CODE
	206,00	259271M_
	206,00	259271Q_
	206,00	259271B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	525	>90	3
3000K	565	>90	5

back

RAY mini

Low voltage
Ceiling suspended





247



375 | 391





613





CHOOSE YOUR BASE

AL | Single base
ceiling base round | 350mA
phase-cut dim | incl. driver

	EUR	CODE
	65,00	914112W0
	65,00	914112Q0
	65,00	914112B0

BL | Semi recessed single base
EL | Multi base linear
FL | Multi chandelier
GL | Track adapter
more infos on page 500

LOXONE VERSIONS ONLINE
weverducre.com/more-ray

3.0

LED COB 6W | 350mA | 18V
aluminium
white and LS fixtures –white cable
others – black cable

IP20 W-75° L80|50K

	EUR	CODE
	179,00	260171W_
	179,00	260171LS_
	179,00	260171ME_
	179,00	260171Q_
	179,00	260171B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	525	>90	3
3000K	565	>90	5

5.0

LED COB 6W | 350mA | 18V
aluminium
white and LS fixtures –white cable
others – black cable

IP20 W-75° L80|50K

	EUR	CODE
	199,00	260271W_
	199,00	260271LS_
	199,00	260271Q_
	199,00	260271B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	525	>90	3
3000K	565	>90	5

back



DESIGN AWARD 2023 · GOOD DESIGN · reddot winner 2023

MATCH

Low voltage
Ceiling suspended









CHOOSE YOUR BASE

AL | Single base
ceiling base round | 350mA
phase-cut dim | incl. driver

	EUR	CODE
	65,00	914112W0
	65,00	914112L0
	65,00	914112M0
	65,00	914112Q0
	65,00	914112B0

BL | Semi recessed single base

EL | Multi base linear
3 luminaires | 3x175mA | 525mm
phase-cut dim | incl. driver

	EUR	CODE
	165,00	914133W0
	165,00	914133B0

FL | Multi chandelier
GL | Track adapter
more infos on page 500



MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-match-suspended

3.0

LED COB 6W | 350mA | 18V
aluminium
white fixtures – white cable
others – black cable

IP20 W-54° L80|50K

	EUR	CODE
	116,00	279271W_
	123,00	279271L_
	123,00	279271M_
	123,00	279271Q_
	116,00	279271B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	490	>90	3
3000K	520	>90	5

5.0

LED COB 6W | 350mA | 18V
aluminium
white fixtures – white cable
others – black cable

IP20 W-54° L80|50K

	EUR	CODE
	129,00	279371W_
	138,00	279371L_
	138,00	279371M_
	138,00	279371Q_
	129,00	279371B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	490	>90	3
3000K	520	>90	5

back



PRIVATE RESIDENCE | IN LIJN INTERIEUR ARCHITECTUUR BELGIUM

DESIGN AWARD 2024

reddot winner 2023



TRACE

Low voltage
Ceiling suspended





CHOOSE YOUR BASE

AL | Single base
ceiling base round | 350mA
phase-cut dim | incl. driver

	EUR	CODE
	65,00	914112W0
	65,00	914112L0
	65,00	914112M0
	65,00	914112B0

BL | Semi recessed single base

EL | Multi base linear
3 luminaires | 3x175mA | 525mm
phase-cut dim | incl. driver

	EUR	CODE
	165,00	914133W0
	165,00	914133B0

FL | Multi chandelier
GL | Track adapter
more infos on page 500

2.0

LED COB 6W | 350mA | 17V
aluminium
white fixtures – white cable
others – black cable

IP20 W-75° L80|50K

	EUR	CODE
	213,00	253471W_
	215,00	253471BL_
	215,00	253471BM_
	213,00	253471B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	565	>90	3
3000K	590	>90	5

LOXONE VERSIONS ONLINE
weverducre.com/more-trace-suspended

back





PRIVATE RESIDENCE | STUDIO FOOLEN THE NETHERLANDS

DESIGN AWARD 2024

reddot winner 2023



TRACE

Low voltage
Ceiling suspended







CHOOSE YOUR BASE

AL | Single base
ceiling base round | 350mA
phase-cut dim | incl. driver

	EUR	CODE
	65,00	914112W0
	65,00	914112L0
	65,00	914112M0
	65,00	914112B0

BL | Semi recessed single base
EL | Multi base linear
FL | Multi chandelier
GL | Track adapter
more infos on page 500

MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-trace-suspended

3.0

LED COB 6W | 350mA | 18V
aluminium
white fixtures – white cable
others – black cable

IP20 W-54° L80|50K

	EUR	CODE
	135,00	253171W_
	142,00	253171BL_
	142,00	253171BM_
	135,00	253171B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	490	>90	3
3000K	520	>90	5

5.0

LED COB 6W | 350mA | 18V
aluminium
white fixtures – white cable
others – black cable

IP20 W-54° L80|50K

	EUR	CODE
	144,00	253271W_
	153,00	253271BL_
	153,00	253271BM_
	144,00	253271B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	450	>90	3
3000K	475	>90	5

back



ODREY

Low voltage
Ceiling suspended








353 | 379




599

CHOOSE YOUR BASE

AL | Single base
ceiling base round | 350mA
phase-cut dim | incl. driver

	EUR	CODE
	65,00	914112W0
	65,00	914112L0
	65,00	914112G0
	65,00	914112Q0
	65,00	914112B0

BL | Semi recessed single base
EL | Multi base linear
FL | Multi chandelier
GL | Track adapter
more infos on page 500

LOXONE VERSIONS ONLINE
weverducre.com/more-odrey-suspended

1.1

LED COB 7W | 350mA | 18V
aluminium
white fixtures – white cable
others – black cable

IP20 M-32° L70|55K

	EUR	CODE
	172,00	287161WW_
	172,00	287161QQ_
	172,00	287161BL_
	172,00	287161BG_
	172,00	287161BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	400	>90	3
3000K	445	>90	5

1.2

LED COB 7W | 350mA | 18V
aluminium | shade matching
incl inner cover
white fixtures – white cable
others – black cable

IP20 M-32° L70|55K

	EUR	CODE
	238,00	287261WW_
	238,00	287261QQ_
	238,00	287261BL_
	238,00	287261BG_
	238,00	287261BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	400	>90	3
3000K	445	>90	5

1.3

LED COB 7W | 350mA | 18V
aluminium
white fixtures – white cable
others – black cable

IP20 M-32° L70|55K

	EUR	CODE
	173,00	287361WW_
	173,00	287361QQ_
	173,00	287361BL_
	173,00	287361BG_
	173,00	287361BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	450	>90	3
3000K	470	>90	5













RADIOLOGY AZ MONICA | EEF DEBEUF INTERIEURARCHITECT ANTWERP | BELGIUM



ODREY

Low voltage
Ceiling suspended



353 | 379





599





CHOOSE YOUR BASE

AL | Single base
ceiling base round | 350mA
phase-cut dim | incl. driver

	EUR	CODE
	65,00	914112W0
	65,00	914112L0
	65,00	914112G0
	65,00	914112Q0
	65,00	914112B0

BL | Semi recessed single base
EL | Multi base linear
FL | Multi chandelier
GL | Track adapter
more infos on page 500

LOXONE VERSIONS ONLINE
weverducre.com/more-odrey-suspended

1.4

LED COB 7W | 350mA | 18V
aluminium
white fixtures – white cable
others – black cable

IP20 M-32° L70|55K

	EUR	CODE
	180,00	287461WW_
	180,00	287461QQ_
	180,00	287461BL_
	180,00	287461BG_
	180,00	287461BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	450	>90	3
3000K	470	>90	5

1.5

LED COB 7W | 350mA | 18V
aluminium
white fixtures – white cable
others – black cable

IP20 M-32° L70|55K

	EUR	CODE
	183,00	287561WW_
	183,00	287561QQ_
	183,00	287561BL_
	183,00	287561BG_
	183,00	287561BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	450	>90	3
3000K	470	>90	5

1.6

LED COB 7W | 350mA | 18V
aluminium
white fixtures – white cable
others – black cable

IP20 M-32° L70|55K

	EUR	CODE
	184,00	287661WW_
	184,00	287661QQ_
	184,00	287661BL_
	184,00	287661BG_
	184,00	287661BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	480	>90	3
3000K	505	>90	5

optional inner cover on page 910

back





OPLIA

Low voltage
Ceiling suspended





CHOOSE YOUR BASE

AL | Single base
ceiling base round | 250mA
phase-cut dim | incl. driver

	EUR	CODE
	65,00	914115W0
	65,00	914115M0
	65,00	914115B0

BL | Semi recessed single base
EL | Multi base linear

FL | Multi chandelier
6 luminaires | 6x175mA | 1020lm
phase-cut dim | incl. driver

	EUR	CODE
	295,00	914122WW0
	295,00	914122BM0
	295,00	914122BB0

GL | Track adapter
more infos on page 500

LOXONE VERSIONS ONLINE
weverducre.com/more-oplia

1.0

LED PCB 4W | 250mA | 12V
aluminium | glass
white fixtures – white cable
others – black cable

IP20 L80|100K

2700K | CRI >90 | 245lm

	EUR	CODE
	142,00	246181W3
	142,00	246181M3
	142,00	246181B3

back



SPICY LEMON | STAY STUDIO KORTRIJK | BELGIUM



SOLLI

Low voltage
Ceiling suspended





1.0

LED COB 7W | 350mA | 18V
aluminium
artisanal hand blown glass

IP20 L80|50K

	EUR	CODE
	230,00	238281FD_
	230,00	238281TD_
	192,00	238281WB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	360	>90	3
3000K	370	>90	5

CHOOSE YOUR BASE

AL | Single base
ceiling base round | 350mA
phase-cut dim | incl. driver

	EUR	CODE
	65,00	914112W0
	65,00	914112L0
	65,00	914112B0

BL | Semi recessed single base
EL | Multi base linear
FL | Multi chandelier
GL | Track adapter
more infos on page 500

LOXONE VERSIONS ONLINE
weverducre.com/more-solli

back



PRIVATE RESIDENCE | AGENCE BÉATRICE CASSAN FRANCE



SOLLI COCOON

Low voltage
Ceiling suspended





CHOOSE YOUR BASE

AL | Single base
ceiling base round | 350mA
phase-cut dim | incl. driver

	EUR	CODE
	65,00	914112W0
	65,00	914112L0
	65,00	914112B0

BL | Semi recessed single base
EL | Multi base linear
FL | Multi chandelier
GL | Track adapter
more infos on page 500

LOXONE VERSIONS ONLINE
weverducre.com/more-solli-cocoon

1.0

LED COB 7W | 350mA | 18V
aluminium | PET felt material
artisanal hand blown glass
noise absorbing material

IP20 L80|50K

	EUR	CODE
	321,00	238381MF_
	321,00	238381LF_
	321,00	238381OF_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	265	>90	3
3000K	275	>90	5

2.0

LED COB 7W | 350mA | 18V
aluminium | PET felt material
artisanal hand blown glass
noise absorbing material

IP20 L80|50K

	EUR	CODE
	328,00	238481MF_
	328,00	238481LF_
	328,00	238481OF_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	275	>90	3
3000K	285	>90	5

3.0

full acoustic element
aluminium | PET felt material
incl. black single base
noise absorbing material

	EUR	CODE
	206,00	238600MF0
	206,00	238600LF0
	206,00	238600OF0

back



CHOOSE YOUR BASE

high



AH | SINGLE BASE

ceiling base round

	EUR	CODE
	29,00	914110W0
	29,00	914110L0
	29,00	914110G0
	29,00	914110M0
	29,00	914110Q0
	29,00	914110B0

BH | SEMI RECESSED SINGLE BASE

73-76 | 70 | 10-35

	EUR	CODE
	48,00	914150W0
	48,00	914150L0
	48,00	914150M0
	48,00	914150Q0
	48,00	914150B0

CH | INVISIBLE SINGLE BASE

plasterkit | system - with fixation
max. 10kg

68 | 70 | 12.5-27.50

	EUR	CODE
	108,00	90015196
	108,00	90015195

DH | MULTI BASE ROUND

up to max. 4 | 8 luminaires

	EUR	CODE
max. 4	65,00	90052005
max. 4	65,00	90052006
max. 8	78,00	90052031
max. 8	78,00	90052032

EH | MULTI BASE LINEAR

1-9 luminaires
600mm | 900mm | 1800mm

	EUR	CODE
for 3	120,00	914130W0
for 3	120,00	914130B0
for 6	180,00	914131W0
for 6	180,00	914131B0
for 9	260,00	914132W0
for 9	260,00	914132B0

FH | MULTI CHANDELIER

1-9 luminaires

	EUR	CODE
	235,00	914120WW0
	275,00	914120BL0
	235,00	914120BM0
	235,00	914120BQ0
	235,00	914120BB0

optional hook

	EUR	CODE
	19,00	90052083
	19,00	90052084

GH | TRACK ADAPTER

for 1-phase tracks

	EUR	CODE
	16,00	90014277
	16,00	90014278



for 3-phase tracks

	EUR	CODE
	16,00	90014279
	16,00	90014280

IH | WALL BASE

for 1 luminaire | incl. 2 wall-ceiling brackets | for cable 4.25-5.5mm diameter | incl. switch on/off

	EUR	CODE
	58,00	90019195
	58,00	90019196

wall - ceiling bracket

	EUR	CODE
	11,50	90019197
	11,50	90019198

back





HEXO mini

High voltage
Ceiling suspended







CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110M0
	29,00	914110Q0
	29,00	914110B0

BH | Semi recessed single base
CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

3.0

PAR11 max. 12W | GU10
220-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	122,00	259120M0
	122,00	259120Q0
	122,00	259120B0

OPTIONAL

PAR11 4.3W | GU10 | phase-cut dim

	EUR	CODE
2700K | 225lm	14,50	901128B3
3000K | 235lm	14,50	901128B5

5.0

PAR11 max. 12W | GU10
220-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	142,00	259220M0
	142,00	259220Q0
	142,00	259220B0

OPTIONAL

PAR11 4.3W | GU10 | phase-cut dim

	EUR	CODE
2700K | 225lm	14,50	901128B3
3000K | 235lm	14,50	901128B5

back



GREENHOUSE BXL | INTERVEST OFFICES & WAREHOUSES DIEGEM | BELGIUM

HEXO

High voltage
Ceiling suspended


245


377 | 393









3.0 LED

LED COB 6W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-36° L80|55K

	EUR	CODE
	197,00	226464G_
	197,00	226464Q_
	197,00	226464P_
	195,00	226464B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	405	>90	3
3000K	425	>90	5
2000-3000K	260	>90	9

LED module 20 years replaceability

3.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	111,00	227420G0
	111,00	227420Q0
	111,00	227420P0
	109,00	227420B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110G0
	29,00	914110Q0
	29,00	914110B0

BH | Semi recessed single base
CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

LOXONE VERSIONS ONLINE
weverducre.com/more-hexo

back





RAY mini

High voltage
Ceiling suspended

247

375 | 391

613





CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110W0
	29,00	914110Q0
	29,00	914110B0

BH | Semi recessed single base
ceiling base round | ø84

	EUR	CODE
	48,00	914150W0
	48,00	914150Q0
	48,00	914150B0

CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

3.0

PAR11 max. 12W | GU10
220-240VAC | 50-60Hz
aluminium
white and LS fixtures – white cable
others – black cable

IP20

	EUR	CODE
	115,00	260120W0
	115,00	260120LS0
	115,00	260120ME0
	115,00	260120Q0
	115,00	260120B0

OPTIONAL

PAR11 4.3W | GU10 | phase-cut dim

	EUR	CODE
2700K | 240lm	14,50	9011128W3
2700K | 225lm	14,50	9011128B3
3000K | 255lm	14,50	9011128W5
3000K | 235lm	14,50	9011128B5

5.0

PAR11 max. 12W | GU10
220-240VAC | 50-60Hz
aluminium
white and LS fixtures – white cable
others – black cable

IP20

	EUR	CODE
	135,00	260220W0
	135,00	260220LS0
	135,00	260220Q0
	135,00	260220B0

OPTIONAL

PAR11 4.3W | GU10 | phase-cut dim

	EUR	CODE
2700K | 240lm	14,50	9011128W3
2700K | 225lm	14,50	9011128B3
3000K | 255lm	14,50	9011128W5
3000K | 235lm	14,50	9011128B5



ANDERSEN AARHUS | AK83 ARKITEKTER COPENHAGEN | DENMARK



RAY

High voltage
Ceiling suspended



2.0 | 3.0 LED

LED COB 6W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white fixtures – white cable
others – black cable

IP20 M-36° L80|55K

2.0

200mm	EUR	CODE
	178,00	226764W_
	185,00	226764L_
	185,00	226764G_
	185,00	226764M_
	185,00	226764Q_
	185,00	226764P_
	178,00	226764B_

3.0

300mm	EUR	CODE
	184,00	226864W_
	191,00	226864L_
	191,00	226864G_
	191,00	226864M_
	191,00	226864Q_
	191,00	226864P_
	184,00	226864B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	405	>90	3
3000K	425	>90	5
2000-3000K	570	>90	9

LED module 20 years replaceability



2.0 | 3.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
white fixtures – white cable
others – black cable

IP20

2.0

200mm	EUR	CODE
	92,00	227720W0
	99,00	227720L0
	99,00	227720G0
	99,00	227720M0
	99,00	227720Q0
	99,00	227720P0
	92,00	227720B0

3.0

300mm	EUR	CODE
	98,00	227820W0
	105,00	227820L0
	105,00	227820G0
	105,00	227820M0
	105,00	227820Q0
	105,00	227820P0
	98,00	227820B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110W0
	29,00	914110L0
	29,00	914110G0
	29,00	914110M0
	29,00	914110Q0
	29,00	914110B0

BH | Semi recessed single base
CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

LOXONE VERSIONS ONLINE
weverducre.com/more-ray

251
377 | 393
615
759
805



RESTAURANT GOLDMARIE | LUKAS NOBILI MAINZ GERMANY

ODREY

High voltage
Ceiling suspended









1.1

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
white fixtures – white cable
others – black cable

IP20

	EUR	CODE
	168,00	287120WW0
	168,00	287120GG0
	168,00	287120QQ0
	168,00	287120BL0
	168,00	287120BG0
	168,00	287120BB0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

1.3

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
white fixtures – white cable
others – black cable

IP20

	EUR	CODE
	169,00	287320WW0
	169,00	287320GG0
	169,00	287320QQ0
	169,00	287320BL0
	169,00	287320BG0
	169,00	287320BB0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905













CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110W0
	29,00	914110L0
	29,00	914110G0
	29,00	914110Q0
	29,00	914110B0

BH | Semi recessed single base
CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

back



HOTEL MEERBERG PERTISAU | AUSTRIA



ODREY

High voltage
Ceiling suspended





1.2

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
white fixtures – white cable
others – black cable

IP20



CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110W0
	29,00	914110L0
	29,00	914110G0
	29,00	914110Q0
	29,00	914110B0

BH | Semi recessed single base
CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

	EUR	CODE
	234,00	287220WW0
	234,00	287220GG0
	234,00	287220QQ0
	234,00	287220BL0
	234,00	287220BG0
	234,00	287220BB0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

back





CAFÉ APOTHEKA | KIDS STUDIOS TÜBINGEN | GERMANY

back




WW


GG


QQ


BL


BG


BB



ODREY

High voltage
Ceiling suspended









1.4

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
white fixtures – white cable
others – black cable

IP20

1.5

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
white fixtures – white cable
others – black cable

IP20

1.6

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
white fixtures – white cable
others – black cable

IP20

CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110W0
	29,00	914110L0
	29,00	914110G0
	29,00	914110Q0
	29,00	914110B0

BH | Semi recessed single base
CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

	EUR	CODE
	176,00	287420WW0
	176,00	287420GG0
	176,00	287420QQ0
	176,00	287420BL0
	176,00	287420BG0
	176,00	287420BB0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

	EUR	CODE
	179,00	287520WW0
	179,00	287520GG0
	179,00	287520QQ0
	179,00	287520BL0
	179,00	287520BG0
	179,00	287520BB0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

	EUR	CODE
	180,00	287620WW0
	180,00	287620GG0
	180,00	287620QQ0
	180,00	287620BL0
	180,00	287620BG0
	180,00	287620BB0

optional inner cover on page 910

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



RESTAURANT WEINTRÄNE | MICHAEL FALTENBACHER CREATION & CONCEPT MUNICH | GERMANY

DESIGN AWARD 2024

reddot winner 2023



TRACE

High voltage
Ceiling suspended



1.0

G95 max. 12W | E27
220-240VAC | 50-60Hz
aluminium
white fixtures – white cable
others – black cable

IP20

	EUR	CODE
	118,00	2538E0W0
	122,00	2538E0BL0
	122,00	2538E0BM0
	118,00	2538E0B0

CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110W0
	29,00	914110L0
	29,00	914110M0
	29,00	914110B0

BH | Semi recessed single base
CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

OPTIONAL

G95 4.5W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 375lm	33,00	9003E160

G95 10W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

G95 5.4W | E27 | phase-cut dim
filament | gold tinted

	EUR	CODE
2200K | 380lm	33,00	9003E111

back



PRIVATE RESIDENCE | STUDIO BENOIT BELGIUM

WETRO

High voltage
Ceiling suspended



CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110W0
	29,00	914110L0
	29,00	914110B0

BH | Semi recessed single base
CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

LOXONE VERSIONS ONLINE
weverducre.com/wetro



1.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
artisanal hand blown glass
white cable on request

IP20 L80|50K

1800-2850K | CRI >90 | 375lm

	EUR	CODE
	299,00	236188P9

1800-2850K | >90 CRI | 525lm

	EUR	CODE
	298,00	236188B9



2.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
artisanal hand blown glass
white cable on request

IP20 L80|50K

1800-2850K | CRI >90 | 385lm

	EUR	CODE
	337,00	236288P9

1800-2850K | >90 CRI | 510lm

	EUR	CODE
	336,00	236288B9



3.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
artisanal hand blown glass
white cable on request

IP20 L80|50K

1800-2850K | CRI >90 | 445lm

	EUR	CODE
	391,00	236388P9

1800-2850K | >90 CRI | 530lm

	EUR	CODE
	390,00	236388B9

back



PRIVATE RESIDENCE BELGIUM



WETRO

High voltage
Ceiling suspended

CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110W0
	29,00	914110L0
	29,00	914110B0



BH | Semi recessed single base
CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

LOXONE VERSIONS ONLINE
weverducre.com/wetro

1.0



LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
artisanal Italian hand blown glass
white cable on request

IP20 L80|50K

1800-2850K | CRI >90 | 615lm

	EUR	CODE
	338,00	236188TS9

2.0



LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
artisanal Italian hand blown glass
white cable on request

IP20 L80|50K

1800-2850K | CRI >90 | 510lm

	EUR	CODE
	414,00	236288TS9

3.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
artisanal Italian hand blown glass
white cable on request

IP20 L80|50K

1800-2850K | CRI >90 | 530lm

	EUR	CODE
	473,00	236388TS9

back



WETRO

High voltage
Ceiling suspended



CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110W0
	29,00	914110L0
	29,00	914110B0

BH | Semi recessed single base
CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

LOXONE VERSIONS ONLINE
weverducre.com/wetro



1.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
artisanal Italian hand blown glass
white cable on request

IP20 L80|50K

1800-2850K | CRI >90 | 520lm

	EUR	CODE
	338,00	236188TD9
	338,00	236188YD9
	338,00	236188GD9
	338,00	236188BD9



2.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
artisanal Italian hand blown glass
white cable on request

IP20 L80|50K

1800-2850K | CRI >90 | 480lm

	EUR	CODE
	414,00	236288TD9
	414,00	236288YD9
	414,00	236288GD9
	414,00	236288BD9



3.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
artisanal Italian hand blown glass
white cable on request

IP20 L80|50K

1800-2850K | CRI >90 | 495lm

	EUR	CODE
	473,00	236388TD9
	473,00	236388YD9
	473,00	236388GD9
	473,00	236388BD9

back



PRIVATE RESIDENCE | ANA TERRA ITALY

WETRO

High voltage
Ceiling suspended





CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110W0
	29,00	914110L0
	29,00	914110Q0
	29,00	914110B0

BH | Semi recessed single base
CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

LOXONE VERSIONS ONLINE
weverducre.com/wetro



1.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
artisanal Italian hand blown glass
white cable on request

IP20 L80|50K

1800-2850K | CRI >90 | 495lm

	EUR	CODE
	338,00	236188TW9

1800-2850K | CRI >90 | 455lm

	EUR	CODE
	338,00	236188DW9



2.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
artisanal Italian hand blown glass
white cable on request

IP20 L80|50K

1800-2850K | CRI >90 | 435lm

	EUR	CODE
	414,00	236288TW9

1800-2850K | CRI >90 | 420lm

	EUR	CODE
	414,00	236288DW9



3.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
artisanal Italian hand blown glass
white cable on request

IP20 L80|50K

1800-2850K | CRI >90 | 455lm

	EUR	CODE
	473,00	236388TW9

1800-2850K | CRI >90 | 440lm

	EUR	CODE
	473,00	236388DW9

back



PRIVATE RESIDENCE | MD STUDIO MARIA DECU ROMANIA

CLEA

High voltage
Ceiling suspended

287
631





1.0

LED COB 15W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white opal glass hand blown
black cable on request

IP20 L80|50K

	EUR	CODE
	294,00	281784W_
	316,00	281784SG_
	316,00	281784FJ_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	780	>90	3
3000K	825	>90	5



2.0

LED COB 15W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white opal glass hand blown
black cable on request

IP20 L80|50K

	EUR	CODE
	434,00	281884W_
	466,00	281884SG_
	466,00	281884FJ_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	780	>90	3
3000K	825	>90	5



3.0

LED COB 15W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white opal glass hand blown
black cable on request

IP20 L80|50K

	EUR	CODE
	554,00	281984W_
	588,00	281984SG_
	588,00	281984FJ_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	770	>90	3
3000K	815	>90	5

CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110W0
	29,00	914110L0

BH | Semi recessed single base
CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

back



PRIVATE RESIDENCE GREECE



PRIVATE RESIDENCE | ERIBO STIJLBOUWERS BELGIUM



PRIVATE RESIDENCE | ARCHITEKTI MIKULAJ & MIKULAJOVA SLOVAKIA

SHIEK

High voltage
Ceiling suspended







3.0 LED

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
aluminium
white cable on request

IP20 L80|50K

1800-2850K | CRI >90 | 710lm

	EUR	CODE
	258,00	237388W9
	262,00	237388J9
	262,00	237388SG9
	262,00	237388ME9
	262,00	237388P9
	262,00	237388K9
	262,00	237388Z9

3.0 E27

A60 max. 20W | E27
100-240VAC | 50-60Hz
aluminium
white cable on request

IP20

	EUR	CODE
	175,00	2343E0W0
	179,00	2343E0J0
	179,00	2343E0SG0
	179,00	2343E0ME0
	179,00	2343E0P0
	179,00	2343E0K0
	179,00	2343E0Z0

CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110W0
	29,00	914110L0
	29,00	914110B0

BH | Semi recessed single base
CH | Invisible single base
DH | Multi base round
EH | Multi base linear
FH | Multi chandelier
GH | Track adapter
IH | Wall base
more infos on page 528

OPTIONAL

A60 9W opal | E27 | phase-cut dim

	EUR	CODE
2700K | 800lm	14,50	9003E152

LOXONE VERSIONS ONLINE
weverducre.com/more-shiek

back



DINOR

High voltage
Ceiling suspended









CHOOSE YOUR BASE

AH | Single base
ceiling base round | ø83

	EUR	CODE
	29,00	914110W0
	29,00	914110L0
	29,00	914110B0

BH | Semi recessed single base
CH | Invisible single base
more infos on page 528

LOXONE VERSIONS ONLINE
weverducre.com/more-dinor

1.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
aluminium
white cable on request

IP20 L80|60K

1800-2850K | CRI >90 | 570lm

	EUR	CODE
	385,00	255188GW9
	385,00	255188BG9
	368,00	255188BB9

2.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
aluminium
white cable on request

IP20 L80|60K

1800-2850K | CRI >90 | 750lm

	EUR	CODE
	455,00	255288GW9
	455,00	255288BG9
	425,00	255288BB9

3.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
aluminium
white cable on request

IP20 L80|60K

1800-2850K | CRI >90 | 830lm

	EUR	CODE
	516,00	255388GW9
	516,00	255388BG9
	483,00	255388BB9

PRIVATE RESIDENCE | ZEIT ARCHITECTS SLOVAKIA

back





Wall recessed

566 – 581

SPOT LIGHTS



LECA SNOOZE
569



MATCH SNOOZE
571

GUIDE LIGHTS



RETO 0.8
573



RETO 2.0
573



LITO 1.0
575



LITO 2.0
575

STRIPE SLIM
577

STRIPE
579



ORIS 0.7
581



ORIS 0.8
581



ORIS 1.3
581

back



LECA snooze

Wall recessed







1.0 SEMI RECESSED

LED COB 5W | phase cut-dim
220-240VAC | 50-60Hz | incl. driver
aluminium
incl. switch on / off | push dim
USB-C port | incl. honeycomb
fits standard installation box ø 68

IP20 0°-90°|350° N-17° L80|50K

68-71 36 5-40

2700K | CRI >90 | 240lm

	EUR	CODE
	275,00	188544W3
	295,00	188544Q3
	275,00	188544B3



back



PRIVATE RESIDENCE | STUDIO BINNEN NETHERLANDS

MATCH snooze

Wall recessed







1.0 SEMI RECESSED

LED COB 4W | phase cut-dim
220-240VAC | 50-60Hz | incl. driver
aluminium
incl. switch on / off | push dim
USB-C port | installation box

IP20 0°-90°|350° M-23° L80|50K

41x190 55 12.5-32.5

2700K | CRI >90 | 240lm

	EUR	CODE
	275,00	177554W3
	295,00	177554L3
	295,00	177554M3
	295,00	177554Q3
	275,00	177554B3



1.1 SEMI RECESSED

LED COB 4W | phase cut-dim
220-240VAC | 50-60Hz | incl. driver
aluminium
incl. switch on / off | push dim
installation box

IP20 0°-90°|350° M-23° L80|50K

41x190 55 12.5-32.5

2700K | CRI >90 | 240lm

	EUR	CODE
	245,00	177654W3
	245,00	177654B3

Wall recessed 61 | 137 | 153
193
329 | 347
415 | 509
589 | 685
723 | 729

back



PRIVATE RESIDENCE | STUDIO PALINPERÄ FINLAND

RETO

Wall recessed





0.8

LED PCB 4W | 350mA | 9V
aluminium

IP20 L80|50K

66x66 L40 min. 12

3000K | CRI >90 | 145lm

	EUR	CODE
	82,00	3451A1W5
	98,00	3451A1L5
	98,00	3451A1M5
	98,00	3451A1Q5
	82,00	3451A1B5

2.0

LED PCB 6W | 350mA | 17V
aluminium

IP20 L80|50K

47x182 L40 min. 12

3000K | CRI >90 | 455lm

	EUR	CODE
	122,00	3452A1W5
	122,00	3452A1B5

ALWAYS USE

driver | 350mA

	EUR	CODE
6W	35,00	90213202

more options and specs on page 896

ALWAYS USE

driver | 350mA

	EUR	CODE
6W	35,00	90213202

more options and specs on page 896

OPTIONAL

recessed housing incl. plasterkit

	EUR	CODE
	46,00	90012047

concrete housing

	EUR	CODE
	32,00	90012046

specs on page 914

OPTIONAL

recessed housing incl. plasterkit

	EUR	CODE
	45,00	90012039

concrete housing

	EUR	CODE
	38,00	90012044

specs on page 914





LOXONE VERSION ONLINE
weverducre.com/more-reto

781

835

back



PRIVATE RESIDENCE | BAUBUREAU OG 27 AG | LINEAR 54 SWITZERLAND



LOXONE VERSION ONLINE
weverducre.com/more-lito

LITO

Wall recessed





1.0

LED PCB 2/3W | 350/500mA | 6V
aluminium | anod.

IP20 L80|60K

70x70 35 min. 12

3000K | CRI >90 | 170/235lm

	EUR	CODE
	62,00	145381W5
	62,00	145381A5
	62,00	145381B5

ALWAYS USE

driver

	EUR	CODE
6W | 350mA	35,00	90213202
6W | 500mA	33,00	90214201

more options and specs on page 896

OPTIONAL

	EUR	CODE
recessed housing	26,50	90012027
plasterkit	16,50	90017119

recessed housing | always use in combination with plasterkit

2.0

LED PCB 2/3W | 350/500mA | 6V
aluminium | anod.

IP20 L80|60K

70x70 35 min. 12

3000K | CRI >90 | 85/115lm

	EUR	CODE
	62,00	1454A1W5
	62,00	1454A1A5
	62,00	1454A1B5

ALWAYS USE

driver

	EUR	CODE
6W | 350mA	35,00	90213202
6W | 500mA	33,00	90214201

more options and specs on page 896

OPTIONAL

	EUR	CODE
recessed housing	26,50	90012027
plasterkit	16,50	90017119

recessed housing | always use in combination with plasterkit

back



PRIVATE RESIDENCE SPAIN

STRIPE SLIM

Wall recessed





1.4

LED PCB 2W | const. volt. | 24V
aluminium

IP20 L70|60K

135x9 18 8-18

3000K | CRI >80 | 15lm

	EUR	CODE
	68,00	3058A1W5
	68,00	3058A1B5

ALWAYS USE

driver | phase-cut dim
min. 2 luminaires per driver

	EUR	CODE
25W	46,00	90222701

revision opening required

more options and specs on page 901

back



PRIVATE RESIDENCE | KILLIAN GARTNER - ROOMS ATELIER AUSTRIA

STRIPE

Wall recessed



LOXONE VERSION ONLINE
weverducre.com/more-stripe



0.4

LED PCB 1/2W | 350/700mA | 3V
aluminium

IP20 L70|60K

25x56 40 8-18

3000K | CRI >80 | 15/28lm

	EUR	CODE
	55,00	3054A1WA4
	56,00	3054A1LA4
	56,00	3054A1GA4
	55,00	3054A1BA4

ALWAYS USE

driver

	EUR	CODE
6W | 350mA	35,00	90213202
6W | 700mA	34,50	90215203

more options and specs on page 896

OPTIONAL

recessed housing incl. plasterkit

	EUR	CODE
	24,00	90012037

driver to be placed externally
specs on page 914



0.7

LED PCB 1/2W | 350/700mA | 3V
aluminium

IP20 L70|60K

25x56 40 8-18

3000K | CRI >80 | 15/28lm

	EUR	CODE
	58,00	3055A1WA4
	59,00	3055A1LA4
	59,00	3055A1GA4
	58,00	3055A1BA4

ALWAYS USE

driver

	EUR	CODE
6W | 350mA	35,00	90213202
6W | 700mA	34,50	90215203

more options and specs on page 896

OPTIONAL

recessed housing incl. plasterkit

	EUR	CODE
	24,00	90012037

driver to be placed externally
specs on page 914



2.2

LED PCB 1/2W | 350/700mA | 3V
aluminium

IP20 L70|60K

25x170 40 8-18

3000K | CRI >80 | 20/36lm

	EUR	CODE
	88,00	3056A1WA4
	89,00	3056A1LA4
	89,00	3056A1GA4
	88,00	3056A1BA4

ALWAYS USE

driver

	EUR	CODE
6W | 350mA	35,00	90213202
6W | 700mA	34,50	90215203

more options and specs on page 896

OPTIONAL

recessed housing incl. plasterkit

	EUR	CODE
	43,00	90012038

specs on page 914



MAISON BUDISM COUTURE | PEERUTIN KAROL ARCHITECTS CAPETOWN | SOUTH AFRICA

ORIS

Wall recessed











0.7

LED PCB 2/5W | 350/700mA | 6V
aluminium

IP20 L70|60K

47x182 40 min. 12

3000K | CRI >90 | 70/120lm

	EUR	CODE
	76,00	3271A1W5
	76,00	3271A1B5

ALWAYS USE

driver

	EUR	CODE
6W | 350mA	35,00	90213202
6W | 700mA	34,50	90215203

more options and specs on page 896

OPTIONAL

recessed housing incl. plasterkit

	EUR	CODE
	45,00	90012039

concrete housing

	EUR	CODE
	38,00	90012044

specs on page 914

0.8

LED PCB 2/5W | 350/700mA | 6V
aluminium

IP20 L70|60K

66x66 40 min. 12

3000K | CRI >90 | 90/150lm

	EUR	CODE
	68,00	3274A1W5
	68,00	3274A1B5

ALWAYS USE

driver

	EUR	CODE
6W | 350mA	35,00	90213202
6W | 700mA	34,50	90215203

more options and specs on page 896

OPTIONAL

recessed housing incl. plasterkit

	EUR	CODE
	46,00	90012047

concrete housing

	EUR	CODE
	32,00	90012046

specs on page 914

1.3

LED PCB 4/7W | 350/700mA | 9V
aluminium

IP20 L70|60K

115x117 40 min. 12

3000K | CRI >90 | 145/220lm

	EUR	CODE
	89,00	3276A1W5
	89,00	3276A1B5

ALWAYS USE

driver

	EUR	CODE
6W | 350mA	35,00	90213202
7W | 700mA	36,50	90215301

more options and specs on page 896

OPTIONAL

recessed housing incl. plasterkit

	EUR	CODE
	52,00	90012041

concrete housing

	EUR	CODE
	39,00	90012040

specs on page 914

LOXONE VERSION ONLINE
weverducre.com/more-oris

back

785

Wall surface

582 — 711

LUMINAIRES



CENO
585

MATCH
589



TRACE MINI
591



TRACE
593

TRACE SLIM
595



ODREY
599



BOX MINI
605



BOX
607



DOCUS MINI
609



HEXO MINI
611



RAY MINI
613



RAY
615



CENTRAL
617



LEENS
619



BENTO
621



DRO
623



MIRRO
625



MIRRO SOFT
629



CLEA
631



J.J.W.
633



ROOMOR
639



DARF
643



CG SQUARE
647



DOT
649



TAPIS
651



TAPIS SOFT
657



MILES ROUND
663



MILES CARRÉ
667



MILES
669



LARRA
671

FINLIN
673



FINLIN ROUND
679



FIL SPIN
681



VENN
683

SPOT LIGHTS



MATCH SNOOZE
685



MICK SNOOZE
687



SARA SNOOZE
689



MICK WALL 1.0
691

UPLIGHTS



DOMINO
693



SCAVA
695

IP-RATED

HAJO IP44
697

PERLEZ IP44
701

PERLEZ CLIP IP44
703

MIRBA IP44
705

MIRBI LONG IP44
707

RIBELLE IP65
709

PAVIO IP65
711

back



FRENCH VILLAGE CAFÉ & BISTRO | LARA WOODS WOZNICA BELFAST | UNITED KINGDOM

CENO

Wall surface





2.0

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-31° L70|55K

	EUR	CODE
	195,00	376264W_
	195,00	376264Q_
	195,00	376264CH_
	195,00	376264B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x260	>90	3
3000K	2x270	>90	5



OPTIONAL

honeycomb louver

	EUR	CODE
	14,50	915230B0

LOXONE VERSIONS ONLINE
weverducre.com/more-ceno-wall

back





OFFICE REAZN | STUDIO BENOIT KRUISEM | BELGIUM

reddot winner 2023

MATCH

Wall surface

61 | 137 | 153
193
329 | 347
415 | 509
571
723 | 729







2.0

LED COB 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-Z5° L80|50K

	EUR	CODE
	189,00	377264W_
	189,00	377264BL_
	189,00	377264Q_
	189,00	377264B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x415	>90	3
3000K	2x440	>90	5

4.0

LED COB 23W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-Z5° L80|50K

	EUR	CODE
	288,00	377464W_
	288,00	377464Q_
	288,00	377464B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	4x415	>90	3
3000K	4x440	>90	5

back



DESIGN AWARD 2024

reddot winner 2023

TRACE mini

Wall surface

331









1.0

LED COB 6W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-30° L80|50K

	EUR	CODE
	175,00	333654W_
	178,00	333654MB_
	178,00	333654BM_
	175,00	333654B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	420	>90	3
3000K	420	>90	5

2.0

LED COB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-30° L80|50K

	EUR	CODE
	232,00	333754W_
	238,00	333754MB_
	238,00	333754BM_
	232,00	333754B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	840	>90	3
3000K	840	>90	5

back



DESIGN AWARD 2024

reddot winner 2023

TRACE

Wall surface








W


H


CH


B

1.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-22° L80|50K

	EUR	CODE
	185,00	333164W_
	188,00	333164H_
	188,00	333164CH_
	185,00	333164B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	575	>90	3
3000K	645	>90	5

2.0

LED COB 15W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-22° L80|50K

	EUR	CODE
	252,00	333264W_
	258,00	333264H_
	258,00	333264CH_
	252,00	333264B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x560	>90	3
3000K	2x615	>90	5

261 | 269 | 273

351

511 | 547

back



OFFICE | ALFA ARCHITECTES LYON | FRANCE

reddot winner 2023



TRACE SLIM

Wall surface

261 | 269 | 273

351

511 | 547





1.0

LED COB 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-23° L80|50K

	EUR	CODE
	219,00	333364CH_
	215,00	333364B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x395	>90	3
3000K	2x420	>90	5

2.0

LED COB 23W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 M-23° L80|50K

	EUR	CODE
	339,00	333464CH_
	328,00	333464B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	4x395	>90	3
3000K	4x420	>90	5

back







PRIVATE RESIDENCE | TIPHAINE MODIN FRANCE

ODREY

Wall surface





MORE VERSIONS ONLINE
weverducre.com/more-odrey-wall



1.3

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	135,00	387120WW0
	135,00	387120QQ0
	135,00	387120GB0
	135,00	387120BL0
	135,00	387120BG0
	135,00	387120BB0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



1.4

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	142,00	387220WW0
	142,00	387220QQ0
	142,00	387220GB0
	142,00	387220BL0
	142,00	387220BG0
	142,00	387220BB0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



1.5

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	145,00	387320WW0
	145,00	387320QQ0
	145,00	387320GB0
	145,00	387320BL0
	145,00	387320BG0
	145,00	387320BB0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

353 | 379

517 | 539

back



CABINET DENTAIRE VAUBAN | DAHDAH STUDIO VAUBAN | FRANCE

ODREY

Wall surface











2.3

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	184,00	387420WW0
	184,00	387420QQ0
	184,00	387420GB0
	184,00	387420BL0
	184,00	387420BG0
	184,00	387420BB0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

2.4

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	198,00	387520WW0
	198,00	387520QQ0
	198,00	387520GB0
	198,00	387520BL0
	198,00	387520BG0
	198,00	387520BB0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

2.5

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium | steel

IP20

	EUR	CODE
	204,00	387620WW0
	204,00	387620QQ0
	204,00	387620GB0
	204,00	387620BL0
	204,00	387620BG0
	204,00	387620BB0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

353 | 379
517 | 539

MORE VERSIONS ONLINE
weverducre.com/more-odrey-wall

back

stars

weverducre.com/universalstars

SIMPLE FORMALITY

Zelfs als wiskunde niet je favoriete vak was, zullen BOX, DOCUS, HEXO en RAY je verrassen. De slanke, elegante armaturen passen in vrijwel elke ruimte – aan plafond of wand, binnen of buiten. In vele kleuren en uitvoeringen zorgen ze overal voor een echte wow-factor.

Même si les mathématiques n'étaient pas votre matière préférée, BOX, DOCUS, HEXO et RAY sauront vous séduire. Élégants et fins, ces luminaires s'adaptent à presque tous les espaces – plafond ou mur, intérieur ou extérieur. Disponibles en de nombreuses versions et couleurs, ils créent partout un véritable effet « wow ».



BOX



DOCUS



HEXO



RAY





PRIVATE RESIDENCE BELGIUM

BOX mini

Wall surface







1.0

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	67,00	300120W0
	68,00	300120L0
	68,00	300120G0
	68,00	300120M0
	68,00	300120Q0
	67,00	300120B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

2.0

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	88,00	301120W0
	90,00	301120L0
	90,00	301120G0
	90,00	301120M0
	90,00	301120Q0
	88,00	301120B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



PRIVATE RESIDENCE | THE ART OF LIVING MAGAZINE THE NETHERLANDS

BOX

Wall surface











1.0 LED

LED PCB 6W | phase-cut dim 220-240VAC | 50-60Hz
aluminium

IP20 L80|55K

	EUR	CODE
	192,50	341168W_
	195,50	341168L_
	195,50	341168G_
	195,50	341168M_
	195,50	341168Q_
	192,50	341168B_

incl. adjustable flaps

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	350	>90	3
3000K	370	>90	5
1800-2850K	330	>90	9

2.0 LED

LED PCB 11W | phase-cut dim 220-240VAC | 50-60Hz
aluminium

IP20 L80|55K

	EUR	CODE
	216,00	341148W_
	219,00	341148L_
	219,00	341148G_
	219,00	341148M_
	219,00	341148Q_
	216,00	341148B_

incl. adjustable flaps

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x440	>90	3
3000K	2x460	>90	5
1800-2850K	2x410	>90	9

1.0 QT14

QT14 max. 75W | G9
220-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	109,00	3211G0W0
	112,00	3211G0L0
	112,00	3211G0G0
	112,00	3211G0M0
	112,00	3211G0Q0
	109,00	3211G0B0

OPTIONAL

flaps for adjustable beam angle

	EUR	CODE
	39,00	900401W0

QT14 3.5W | G9 | phase-cut dim clear

	EUR	CODE
2700K | 340lm	18,00	9010G803
3000K | 350lm	18,00	9010G805

LOXONE VERSIONS ONLINE
weverducre.com/more-box-wall

back

235
335
765
815



PRIVATE RESIDENCE | PROVENZANO ARCHITETTI ASSOCIATI GUILA LUPO ITALY

DOCUS mini

Wall surface







1.0

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	67,00	300320W0
	68,00	300320G0
	67,00	300320B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

2.0

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	89,00	301320W0
	91,00	301320G0
	89,00	301320B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



PRIVATE RESIDENCE | MOOSEBERRY DESIGN GROUP UKRAINE

HEXO mini

Wall surface







1.0

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	68,00	300420G0
	68,00	300420Q0
	68,00	300420P0
	67,00	300420B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

2.0

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	91,00	301420G0
	91,00	301420Q0
	91,00	301420P0
	89,00	301420B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

back



PRIVATE RESIDENCE | DÉVÉ CREATIONS THE NETHERLANDS

RAY mini

Wall surface








247


375 | 391


507 | 535

1.0

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	67,00	300220W0
	68,00	300220L0
	68,00	300220G0
	68,00	300220M0
	68,00	300220SG0
	68,00	300220ME0
	68,00	300220Q0
	68,00	300220P0
	67,00	300220B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

2.0

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	88,00	301220W0
	91,00	301220L0
	91,00	301220G0
	91,00	301220M0
	91,00	301220SG0
	91,00	301220ME0
	91,00	301220Q0
	91,00	301220P0
	88,00	301220B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



DE BRINK VAN PARK BOSWIJK | STUDIO ID+ DOORN | THE NETHERLANDS

RAY

Wall surface











1.0 LED

LED PCB 6W | phase-cut dim 220-240VAC | 50-60Hz
aluminium

IP20 L80|55K

	EUR	CODE
	192,50	342168W_
	195,50	342168G_
	195,50	342168M_
	195,50	342168Q_
	192,50	342168B_

incl. adjustable flaps

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	350	>90	3
3000K	370	>90	5
1800-2850K	330	>90	9

2.0 LED

LED PCB 11W | phase-cut dim 220-240VAC | 50-60Hz
aluminium

IP20 L80|55K

	EUR	CODE
	216,00	342148W_
	219,00	342148G_
	219,00	342148M_
	219,00	342148Q_
	216,00	342148B_

incl. adjustable flaps

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x440	>90	3
3000K	2x460	>90	5
1800-2850K	2x410	>90	9

1.0 QT14

QT14 max. 75W | G9
220-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	109,00	3221G0W0
	112,00	3221G0G0
	112,00	3221G0M0
	112,00	3221G0Q0
	109,00	3221G0B0

OPTIONAL

flaps for adjustable beam angle

EUR	CODE
39,00	900401W0

QT14 3.5W | G9 | phase-cut dim clear

	EUR	CODE
2700K | 340lm	18,00	9010G803
3000K | 350lm	18,00	9010G805

LOXONE VERSIONS ONLINE
weverducre.com/more-ray-wall

251
341 | 377 | 393
537
759
805

CENTRAL

Wall surface







1.0

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 L80|60K

	EUR	CODE
	196,00	313574W_
	198,00	313574L_
	198,00	313574G_
	196,00	313574B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	580	>90	3
3000K	620	>90	5

2.0

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 L80|60K

	EUR	CODE
	238,00	313674W_
	242,00	313674L_
	242,00	313674G_
	238,00	313674B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x310	>90	3
3000K	2x330	>90	5

809

back



OFFICE CEEBE | WEYGERS HASSELT | BELGIUM

LEENS

Wall surface







1.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 L80|60K

3000K | CRI >90 | 525lm

	EUR	CODE
	255,00	311174W5
	275,00	311174L5
	255,00	311174B5

2.0

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 L80|60K

3000K | CRI >90 | 2x320lm

	EUR	CODE
	295,00	311274W5
	325,00	311274L5
	295,00	311274B5

back

BENTO

Wall surface





1.3

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 L80|60K

3000K | CRI >90 | 285lm

	EUR	CODE
	215,00	309274W5
	215,00	309274B5



3.6

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 L80|60K

3000K | CRI >90 | 285lm

	EUR	CODE
	298,00	309374W5
	298,00	309374B5

back



DRO

Wall surface







1.0

QT14 max. 5W | G9
220-240VAC | 50-60Hz
aluminium
artisanal Italian hand blown glass
mirror thickness 3-6mm

IP44

69-71

	EUR	CODE
	145,00	3431G0W0

OPTIONAL

QT14 3.5W | G9 | phase-cut dim clear

	EUR	CODE
2700K | 340lm	18,00	9010G803
3000K | 350lm	18,00	9010G805

2.0

C35 max. 6W | E14
220-240VAC | 50-60Hz
aluminium
artisanal Italian hand blown glass
mirror thickness 3-6mm

IP44

105-107

	EUR	CODE
	225,00	3432C0W0

OPTIONAL

C35 5.5W | E14 | phase-cut dim
opal

	EUR	CODE
2700K | 450lm	10,50	9003C103

279
373
465
715 | 731



RESTAURANT TRIANGOLO | CONIX COOL INTERIOR EDEGEM | BELGIUM

MIRRO

Wall surface









1.0

A60 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | one side reflective composite panel

IP20

	EUR	CODE
	208,00	6321E0GB0
	208,00	6321E0NB0
	208,00	6321E0LB0
	208,00	6321E0BL0

OPTIONAL

A60 5.5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2700K | 405lm	32,00	9003E139

A60 5.5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 405lm	32,00	9003E140

2.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | one side reflective composite panel

IP20

	EUR	CODE
	256,00	6322E0GB0
	256,00	6322E0NB0
	256,00	6322E0LB0
	256,00	6322E0BL0

OPTIONAL

G95 5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 395lm	35,00	9003E157

3.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | one side reflective composite panel

IP20

	EUR	CODE
	416,00	6323E0GB0
	416,00	6323E0NB0
	416,00	6323E0LB0
	416,00	6323E0BL0

OPTIONAL

G95 5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 395lm	35,00	9003E157

283
467
721 | 733





▶ DESIGN WITH LOVE



RESTAURANT EN VRAC MOUSCRON | BELGIUM



MIRRO SOFT

Wall surface





2.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium | PET felt material
noise absorbing material

IP20

	EUR	CODE
	256,00	6322E0MF0
	256,00	6322E0LF0
	256,00	6322E0IF0
	256,00	6322E0AF0

3.0

G95 max. 15W | E27
220-240VAC | 50-60Hz
aluminium |PET felt material
noise absorbing material

IP20

	EUR	CODE
	416,00	6323E0MF0
	416,00	6323E0LF0
	416,00	6323E0IF0
	416,00	6323E0AF0

OPTIONAL

G95 5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 395lm	35,00	9003E157

G95 5.5W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

G95 4.5W | E27 | phase-cut dim | clear

	EUR	CODE
2700K |375lm	33,00	9003E160

OPTIONAL

G95 5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 395lm	35,00	9003E157

G95 5.5W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 1060lm	33,00	9003E163

G95 4.5W | E27 | phase-cut dim | clear

	EUR	CODE
2700K |375lm	33,00	9003E160

285

471



CLEA

Wall surface









1.0

LED COB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white opal glass hand blown

IP20 L80|50K

	EUR	CODE
	287,00	181484W_
	309,00	181484LS_
	309,00	181484SG_
	309,00	181484FJ_
	287,00	181484B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	575	>90	3
3000K	610	>90	5

2.0

LED COB 11W| phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white opal glass hand blown

IP20 L80|50K

	EUR	CODE
	427,00	181584W_
	459,00	181584LS_
	459,00	181584SG_
	459,00	181584FJ_
	427,00	181584B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	575	>90	3
3000K	610	>90	5

3.0

LED COB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
white opal glass hand blown

IP20 L80|50K

	EUR	CODE
	547,00	181684W_
	581,00	181684LS_
	581,00	181684SG_
	581,00	181684FJ_
	547,00	181684B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	565	>90	3
3000K	600	>90	5

287
557
back

MERCURE CHANTILLY | PROJECT MANAGED BY ATYPIO HOTELS RESORTS WITH ABP ARCHITECTS | L'OBSERVATOIRE DE LA NUIT
VINEUIL-SAINT-FIRMIN | FRANCE





J.J.W.

Wall surface

289

479



01

2x A60 max. 15W | E27
220-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	685,00	2054E0S0
	685,00	2054E0G0

OPTIONAL

A60 3.8W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 245lm	31,00	9003E109

A60 5.6W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 480lm	31,00	9003E138

JULES WABBES

back



FORUM OFFICE SINT-GILLIS-WAAS | BELGIUM

J.J.W.

Wall surface





02

A60 max. 15W | E27
220-240VAC | 50-60Hz
aluminium

IP20

	EUR	CODE
	425,00	2055E0S0
	425,00	2055E0Q0
	425,00	2055E0G0

OPTIONAL

A60 3.8W | E27 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 245lm	31,00	9003E109

A60 5.6W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 480lm	31,00	9003E138

289

479

JULES WABBES

back



ANDAZ VIENNA AM BELVEDERE | INNENARCHITEKTUR WIEN - ARCHISPHERE VIENNA | AUSTRIA



KVÄNUM KITCHEN | KVÄNUM DESIGN STUDIO COPENHAGEN | DENMARK

reddot award 2019
winner lighting design

ROOMOR

Wall surface



1.1

PAR16 max. 15W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-45°

	EUR	CODE
	243,00	338120BK1
	238,00	338120BB1

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 440lm	16,50	901228B3
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



3.1

PAR16 max. 15W | GU10
100-240VAC | 50-60Hz
aluminium | steel
cable plug with hand switch

IP20 0°-45°|0°-30°

	EUR	CODE
	355,00	339120BK1
	350,00	339120BB1

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 440lm	16,50	901228B3
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



3.1

PAR16 max. 15W | GU10
100-240VAC | 50-60Hz
aluminium | steel
cable base round

IP20 0°-45°|0°-30°

	EUR	CODE
	349,00	339220BK1
	344,00	339220BB1

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 440lm	16,50	901228B3
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

495

725 | 735

back




BF2


BK3


BB4

reddot award 2019
winner lighting design

ROOMOR

Wall surface





4.2

PAR16 max. 15W | GU10
100-240VAC | 50-60Hz
aluminium | steel | grey felt
cable base round

IP20 0°-45°|0°-30°

	EUR	CODE
	602,00	339620BF2
	583,00	339620BK2
	575,00	339620BB2

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 440lm	16,50	901228B3
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



4.3

PAR16 max. 15W | GU10
100-240VAC | 50-60Hz
aluminium | steel | grey felt
cable base round

IP20 0°-45°|0°-30°

	EUR	CODE
	679,00	339620BF3
	668,00	339620BK3
	655,00	339620BB3

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 440lm	16,50	901228B3
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



4.4

PAR16 max. 15W | GU10
100-240VAC | 50-60Hz
aluminium | steel
cable base round

IP20 0°-45°|0°-30°

	EUR	CODE
	721,00	339620BK4
	709,00	339620BB4

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 440lm	16,50	901228B3
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



PRIVATE RESIDENCE | MAADSTUDIO MAREK SVOBODA CZECH REPUBLIC

DARF

Wall surface





2.1

LED TUBE 10W | non dim
220-240VAC | 50-60Hz
aluminium
black textile cable plug with switch

IP20 L70|75K

3000K | CRI >80 | 1530lm

	EUR	CODE
	257,00	2567T7B4



3.1

LED TUBE 14W | non dim
220-240VAC | 50-60Hz
aluminium
black textile cable plug with switch

IP20 L70|75K

3000K | CRI >80 | 2300lm

	EUR	CODE
	262,00	2566T7B4



4.1

LED TUBE 23W | non dim
220-240VAC | 50-60Hz
aluminium
black textile cable plug with switch

IP20 L70|60K

	EUR	CODE
	266,00	2569T7B_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	3560	>80	4
4000K	3950	>80	6



4.2

LED TUBE 23W | phase-cut dim
220-240VAC | 50-60Hz
aluminium
black textile cable plug with dimmer switch

IP20 L70|50K

	EUR	CODE
	325,00	2569T8B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2780	>90	3
3000K	2940	>90	5

ARCHITECT | PHILIPP WEINBERGER & STUDIO MARCH GUT

back



PATISSERIE BRAASKMA LEEUWARDEN | THE NETHERLANDS

TUNE UP YOUR HEART PROJECT
weverducre.com/tune-up



PRIVATE RESIDENCE | SERBOLI BUREAU SPAIN

CG SQUARE

Wall surface







2P SMALL

QT14 2x max. 4W | G9
220-240VAC | 50-60Hz
steel

IP20

	EUR	CODE
	238,00	4001G0W0
	245,00	4001G0L0
	245,00	4001G0M0
	245,00	4001G0Q0
	238,00	4001G0B0

OPTIONAL

QT14 3.5W | G9 | phase-cut dim clear

	EUR	CODE
2700K | 340lm	18,00	9010G803
3000K | 350lm	18,00	9010G805

2G BIG

A60 2x max. 12W | E27
220-240VAC | 50-60Hz
steel

IP20

	EUR	CODE
	295,00	4002E0W0
	310,00	4002E0L0
	310,00	4002E0M0
	310,00	4002E0Q0
	295,00	4002E0B0

OPTIONAL

A60 5.6W | E27 | phase-cut dim | clear

	EUR	CODE
2700K | 480lm	31,00	9003E138

CHRISTOPHE GEVERS

back

DOT

Wall surface







2.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PC cover

IP20 L80|55K

	EUR	CODE
	155,00	330164W_
	155,00	330164M_
	155,00	330164Q_
	155,00	330164B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	420	>90	3
3000K	435	>90	5

3.0

LED COB 16W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PC cover

IP20 L80|55K

	EUR	CODE
	215,00	330264W_
	215,00	330264M_
	215,00	330264Q_
	215,00	330264B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x395	>90	3
3000K	2x425	>90	5

4.0

LED COB 22W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium |PC cover

IP20 L80|55K

	EUR	CODE
	285,00	330464W_
	285,00	330464M_
	285,00	330464Q_
	285,00	330464B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	3x400	>90	3
3000K	3x405	>90	5

back



CREATE YOUR OWN TAPIS
weverducre.com/tapis-configurator

PRIVATE RESIDENCE | UNIQUE RENOVATIONS BELGIUM

TAPIS

Wall surface





1.0

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
composite | aluminium

IP20 L80|50K

	EUR	CODE
	258,00	336174FJ_
	258,00	336174GW_
	258,00	336174ST_
	238,00	336174RA_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	450	>90	3
3000K	480	>90	5

back



PRIVATE RESIDENCE | STUDIO 05 BELGIUM



EOAK FLOORS SHOWROOM | VIGONARCHITECTS HANOI | VIETNAM

CREATE YOUR OWN TAPIS
weverducre.com/tapis-configurator



DAS SEEHÄUSER | WOODSPACE MATTSEE | AUSTRIA

TAPIS

Wall surface





2.0

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
composite | aluminium

IP20 L80|50K

	EUR	CODE
	266,00	336274FJ_
	266,00	336274GW_
	266,00	336274ST_
	253,00	336274RA_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	465	>90	3
3000K	500	>90	5



3.0

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
composite | aluminium

IP20 L80|50K

	EUR	CODE
	277,00	336374FJ_
	277,00	336374GW_
	277,00	336374ST_
	261,00	336374RA_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	465	>90	3
3000K	500	>90	5



2.1

composite | aluminium

	EUR	CODE
	237,00	336200FJ0
	237,00	336200GW0
	237,00	336200ST0
	224,00	336200RA0



3.1

composite | aluminium

	EUR	CODE
	248,00	336300FJ0
	248,00	336300GW0
	248,00	336300ST0
	232,00	336300RA0

back



HAIDRESSER JANSEN KAPPERS | EMPOWER SPACES BEEK EN DONK | THE NETHERLANDS

mixology winner

TAPIS SOFT

Wall surface









1.0

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PET felt material
noise absorbing material

IP20 L80|50K

	EUR	CODE
	398,00	336174WF_
	398,00	336174MF_
	398,00	336174LF_
	398,00	336174OF_
	398,00	336174IF_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	410	>90	3
3000K	435	>90	5

2.0

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PET felt material
noise absorbing material

IP20 L80|50K

	EUR	CODE
	285,00	336274WF_
	285,00	336274MF_
	285,00	336274LF_
	285,00	336274OF_
	285,00	336274IF_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	440	>90	3
3000K	470	>90	5

2.1

aluminium | PET felt material
noise absorbing material

	EUR	CODE
	256,00	336200WF0
	256,00	336200MF0
	256,00	336200LF0
	256,00	336200OF0
	256,00	336200IF0

back





RESTAURANT L'APERICENA TIME | ARCH. LEONARDO PORCELLI - STILEMI RIVAROLO CANAVESE | ITALY



mixology winner

TAPIS SOFT

Wall surface



3.0

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PET felt material
noise absorbing material

IP20 L80|50K

	EUR	CODE
	299,00	336374WF_
	299,00	336374MF_
	299,00	336374LF_
	299,00	336374OF_
	299,00	336374IF_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	440	>90	3
3000K	470	>90	5



4.0

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PET felt material
noise absorbing material

IP20 L80|50K

	EUR	CODE
	299,00	336474WF_
	299,00	336474MF_
	299,00	336474LF_
	299,00	336474OF_
	299,00	336474IF_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	440	>90	3
3000K	470	>90	5



3.1

aluminium | PET felt material
noise absorbing material

	EUR	CODE
	270,00	336300WF0
	270,00	336300MF0
	270,00	336300LF0
	270,00	336300OF0
	270,00	336300IF0



4.1

aluminium | PET felt material
noise absorbing material

	EUR	CODE
	270,00	336400WF0
	270,00	336400MF0
	270,00	336400LF0
	270,00	336400OF0
	270,00	336400IF0

back



PRIVATE RESIDENCE | AJ ARCHITECTEN BELGIUM

MILES

Wall surface









2.0 ROUND

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP20 L80|60K

		EUR	CODE
		258,00	317578W_
		260,00	317578G_
		260,00	317578M_
		260,00	317578Q_
		260,00	317578P_
		268,00	317578SG_
		268,00	317578CC_
		268,00	317578ME_
		257,00	317578B_
	marble	323,00	317578MW_
	marble	323,00	317578MB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	610	>90	3
3000K	620	>90	5

3.0 ROUND

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP20 L80|60K

		EUR	CODE
		293,00	317778W_
		297,00	317778G_
		297,00	317778M_
		297,00	317778Q_
		297,00	317778P_
		304,00	317778SG_
		304,00	317778CC_
		304,00	317778ME_
		293,00	317778B_
	marble	347,00	317778MW_
	marble	347,00	317778MB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	610	>90	3
3000K	620	>90	5





back







PRIVATE RESIDENCE | UP FOR GRABS INTERIORS UNITED KINGDOM

MILES

Wall surface









2.0 CARRÉ

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP20 L80|60K

		EUR	CODE
		268,00	317478W_
		270,00	317478G_
		270,00	317478M_
		270,00	317478Q_
		270,00	317478P_
		268,00	317478B_
	marble	334,00	317478MW_
	marble	334,00	317478MB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	610	>90	3
3000K	620	>90	5

3.0 CARRÉ

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP20 L80|60K

		EUR	CODE
		304,00	317678W_
		308,00	317678G_
		308,00	317678M_
		308,00	317678Q_
		308,00	317678P_
		304,00	317678B_
	marble	359,00	317678MW_
	marble	359,00	317678MB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	610	>90	3
3000K	620	>90	5



back



MILES

Wall surface







9.0

LED PCB 31W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP20 L80|60K

	EUR	CODE
	358,00	317878W_
	363,00	317878G_
	358,00	317878B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1540	>90	3
3000K	1560	>90	5



12.0

LED PCB 38W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP20 L80|60K

	EUR	CODE
	428,00	317978W_
	436,00	317978G_
	428,00	317978B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2110	>90	3
3000K	2130	>90	5



back



LARRA

Wall surface







1.0

LED TUBE 7W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal glass

IP20 L70|15K

	EUR	CODE
	118,00	1966T8W_
	118,00	1966T8L_
	118,00	1966T8M_
	118,00	1966T8P_
	118,00	1966T8Q_
	118,00	1966T8GM_
	118,00	1966T8B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	700	>90	3
3000K	720	>90	5

2.0

LED TUBE 8W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal glass

IP20 L70|15K

	EUR	CODE
	139,00	1967T8W_
	139,00	1967T8L_
	139,00	1967T8M_
	139,00	1967T8P_
	139,00	1967T8Q_
	139,00	1967T8GM_
	139,00	1967T8B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	800	>90	3
3000K	820	>90	5

back



OFFICE COPTHALL BRIDGE HOUSE | EKHO STUDIO HARROGATE | UNITED KINGDOM

reddot winner 2023

FINLIN

Wall surface

263
433
727







1.0

LED PCB 6W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 L80|50K

	EUR	CODE
	235,00	370584CH_
	235,00	370584B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	450	>90	3
3000K	485	>90	5

4.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 L80|50K

	EUR	CODE
	325,00	370884CH_
	325,00	370884B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	895	>90	3
3000K	965	>90	5

OPTIONAL

spacer 10mm for overlapping

	EUR	CODE
	31,00	900195B0

specs on page 911

back



BIURA TIXE | 53 STUDIO BIELSKO-BIAŁA | POLAND



PASTRY SHOP DONATIEN MAÎTRE ECLAIR | STUDIO CARRÉ – PAUL LEVAILLANT PARIS | FRANCE

DESIGN AWARD 2024

reddot winner 2023

FINLIN

Wall surface







2.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 L80|50K

	EUR	CODE
	295,00	370684CH_
	295,00	370684B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	895	>90	3
3000K	965	>90	5

3.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 L80|50K

	EUR	CODE
	335,00	370784CH_
	335,00	370784B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	895	>90	3
3000K	965	>90	5

OPTIONAL

spacer 10mm for overlapping

	EUR	CODE
	31,00	900195B0

specs on page 911

263
433
727
back



reddot winner 2023

FINLIN

Wall surface





1.0 ROUND

LED PCB 14W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 L80|50K

	EUR	CODE
	335,00	371184CH_
	335,00	371184B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1180	>90	3
3000K	1280	>90	5



OPTIONAL

spacer 10mm for overlapping

	EUR	CODE
	31,00	900196B0

specs on page 911

back



reddot winner 2024

FIL SPIN

Wall surface





back



1.0

LED PCB 24W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | indir. light

IP20 180° L80|100K

2700K | CRI >90 | 2x905lm

	EUR	CODE
	425,00	254584B3



PRIVATE RESIDENCE | STUDIO PALINPERÄ OY FINLAND

VENN

Wall surface



1.0

LED PCB 42W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA cover
indirect light

IP20 L70|55K

	EUR	CODE
	680,00	149184W_
	680,00	149184Q_
	680,00	149184B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	3410	>90	3
3000K	3510	>90	5



2.0

LED PCB 49W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA cover dir./
indirect light

IP20 L70|55K

	EUR	CODE
	770,00	149284W_
	770,00	149284Q_
	770,00	149284B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	480/3920	>90	3
3000K	495/4035	>90	5

CREATE YOUR OWN VENN
weverducre.com/venn-configurator

S&R CORNELISSEN

back



PRIVATE RESIDENCE AUSTRIA

reddot winner 2023

MATCH snooze

Wall surface 61 | 137 | 153

193

329 | 347

415 | 509

571

723 | 729





1.0

LED COB 5W
220-240VAC | 50-60Hz | incl. driver
aluminium
incl. switch on/off

IP20 0°-90°|350° M-30° L80|50K

	EUR	CODE
	198,00	177353W_
	198,00	177353Q_
	198,00	177353B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	330	>90	3
3000K	345	>90	5

back



PRIVATE RESIDENCE | NORDIC STANDARD SPAIN

DESIGN AWARD 2021

reddot winner 2020
lighting design

MICK snooze

Wall surface

199

333





1.0

LED COB 8W
220-240VAC | 50-60Hz | incl. driver
aluminium
incl. switch on/off

IP20 0°-90°|350° M-23° L80|50K





	EUR	CODE
	295,00	159643J_
	295,00	159643K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	185	>90	3
3000K	200	>90	5

S&R CORNELISSEN

back



PRIVATE RESIDENCE | IN-BETWEEN ARCHITECTS LIMITED HONG KONG

SARA snooze

Wall surface











203



365



1.0

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium
incl. switch on/off

IP20 0°-90°|330°

	EUR	CODE
	155,00	157320W0
	159,00	157320G0
	159,00	157320K0
	155,00	157320B0

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

back



reddot winner 2020
lighting design

MICK

Wall surface







1.0

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-23° L80|50K

	EUR	CODE
	268,00	159344J_
	268,00	159344K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	235	>90	3
3000K	245	>90	5

2.0

LED COB 14W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-90°|350° M-23° L80|50K

	EUR	CODE
	345,00	159244J_
	345,00	159244K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x215	>90	3
3000K	2x225	>90	5



S&R CORNELISSEN

back



PRIVATE RESIDENCE | ABOUT - ARCHITECTURE & PHOTOGRAPHY ITALY

DOMINO

Wall surface





1.0

LED PCB 14W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 L80|60K

	EUR	CODE
	269,00	3371A4W_
	269,00	3371A4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1180	>80	2
3000K	1190	>80	4

back

SCAVA

Wall surface







1.0

LED PCB 25W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PC cover

IP20 L80|50K

	EUR	CODE
	226,00	350188W_
	229,00	350188GB_
	226,00	350188B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1830	>90	3
3000K	1910	>90	5

back



PRIVATE RESIDENCE BELGIUM

HAJO IP44

Wall surface





1.0

LED COB 9W | dimmable
220-240VAC | 50-60Hz | incl. driver
glass | aluminium

IP20 L80|50K

phase-cut dim

	EUR	CODE
	268,00	346184WC_
	268,00	346184WW_
	268,00	346184WA_
	268,00	346184WB_
	268,00	346184BC_
	268,00	346184BW_
	268,00	346184BA_
	268,00	346184BB_

DALI-2

	EUR	CODE
	298,00	346185WC_
	298,00	346185WW_
	298,00	346185WA_
	298,00	346185WB_
	298,00	346185BC_
	298,00	346185BW_
	298,00	346185BA_
	298,00	346185BB_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	420	>90	3
3000K	440	>90	5

S&R CORNELISSEN

back







PERLEZ IP44

Wall surface

169

271 | 275 | 295









1.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal glass
mirror thickness 3-6mm

IP44 L80|50K

50-52

	EUR	CODE
	188,00	192484W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	520	>95	3
3000K	550	>95	5
4000K	580	>95	7

2.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal glass
mirror thickness 3-6mm

IP44 L80|50K

50-52

	EUR	CODE
	198,00	192584W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	600	>95	3
3000K	630	>95	5
4000K	665	>95	7

3.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal glass
mirror thickness 3-6mm

IP44 L80|50K

50-52

	EUR	CODE
	218,00	192684W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	645	>95	3
3000K	665	>95	5
4000K	705	>95	7

back



PRIVATE RESIDENCE GREECE

PERLEZ CLIP IP44

Wall surface

169

271 | 275 | 295







1.0 CLIP

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal glass
mirror thickness 2-7mm
slides over the mirror

IP44 L80|50K

	EUR	CODE
	195,00	392484W_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	550	>95	5
4000K	580	>95	7

2.0 CLIP

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal glass
mirror thickness 2-7mm
slides over the mirror

IP44 L80|50K

	EUR	CODE
	205,00	392584W_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	630	>95	5
4000K	665	>95	7

3.0 CLIP

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal glass
mirror thickness 2-7mm
slides over the mirror

IP44 L80|50K

	EUR	CODE
	215,00	392684W_

LIGHT COLOUR	LUMEN	CRI	CODE
3000K	665	>95	5
4000K	705	>95	7

back



PRIVATE RESIDENCE | RAUMTAKT GMBH SWITZERLAND

MIRBA IP44

Wall surface









1.0

LED PCB 4/6W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA
output selector

IP44 L80|50K

	EUR	CODE
	198,00	328188W_
	198,00	328188BW_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	L 375/H 645	>90	3
3000K	L 395/H 670	>90	5

2.0

LED PCB 6/9W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA
output selector

IP44 L80|50K

	EUR	CODE
	238,00	328288W_
	238,00	328288BW_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	L 535/H 920	>90	3
3000K	L 575/H 960	>90	5

3.0

LED PCB 8/12W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA
output selector

IP44 L80|50K

	EUR	CODE
	275,00	328388W_
	275,00	328388BW_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	L 730/H 1290	>90	3
3000K	L 770/H 1350	>90	5



back

MIRBI long IP44

Wall surface





1.0

LED PCB 5/7W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA
output selector

IP44 L80|60K

	EUR	CODE
	245,00	329188W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	255/420	>90	3
3000K	265/435	>90	5



2.0

LED PCB 8/13W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA
output selector

IP44 L80|60K

	EUR	CODE
	365,00	329288W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	445/815	>90	3
3000K	460/840	>90	5



3.0

LED PCB 13/19W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA
output selector

IP44 L80|60K

	EUR	CODE
	675,00	329388W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	735/1220	>90	3
3000K	755/1250	>90	5



back



RIBELLE IP65

Wall surface





1.0

LED PCB 5W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP65 L80|100K

3000K | CRI >90 | 425lm

	EUR	CODE
	325,00	772184W5
	325,00	772184M5
	325,00	772184B5

825

867

back



PAVIO IP65

Wall surface





1.0

LED PCB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|100K

3000K | CRI >90 | 525lm

	EUR	CODE
	185,00	351184W5
	185,00	351184Q5
	185,00	351184B5

831

back

Table | Floor

712 – 735

TABLE



DRO
715



DRO
717



CG01
719



MIRRO
721



MATCH
723



ROOMOR
725

FLOOR



DRO
715



FINLIN
727



MATCH
729



DRO
731



MIRRO
733



ROOMOR
735

back



APT GRAND KOLIBA | SALPIETRA & GAJDOS ARCHITECTS SLOVAKIA

DRO

Table / Floor

279
373
465
623



1.0

QT14 max. 5W | G9
220-240VAC | 50-60Hz
aluminium
artisanal Italian hand blown glass
cable plug with switch

IP20

	EUR	CODE
	185,00	6421G0WB0

OPTIONAL

QT14 3.5W | G9 | phase-cut dim clear

	EUR	CODE
2700K | 340lm	18,00	9010G803
3000K | 350lm	18,00	9010G805



2.0

C35 max. 6W | E14 | dimmable
220-240VAC | 50-60Hz
aluminium
artisanal Italian hand blown glass
cable plug with dimmer switch

IP20

	EUR	CODE
	265,00	6422C0WB0

OPTIONAL

C35 5.5W | E14 | phase-cut dim
opal

	EUR	CODE
2700K | 450lm	10,50	9003C103



3.0

A60 max. 12W | E27 | dimmable
220-240VAC | 50-60Hz
aluminium
artisanal Italian hand blown glass
cable plug with dimmer switch

IP20

	EUR	CODE
	345,00	6423E0WB0

OPTIONAL

A60 9W | E27 | phase-cut dim
opal

	EUR	CODE
2700K | 800lm	14,50	9003E152





13&9 DESIGN

DRO

Table

279

373

465

623



2.0

C35 max. 6W| E14 | dimmable
220-240VAC | 50-60Hz
aluminium | steel
artisanal Italian hand blown glass
cable plug with dimmer switch

IP20

	EUR	CODE
	355,00	6432C0WB0

OPTIONAL

C35 5.5W | E14 | phase-cut dim | opal

	EUR	CODE
2700K | 450lm	10,50	9003C103



3.0

A60 max. 12W | E27 | dimmable
220-240VAC | 50-60Hz
aluminium | steel
artisanal Italian hand blown glass
cable plug with dimmer switch

IP20

	EUR	CODE
	455,00	6433E0WB0

OPTIONAL

A60 9W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 800lm	14,50	9003E152

back



PRIVATE RESIDENCE BELGIUM

CHRISTOPHE GEVERS



back

CG01

Table



CG01

T25 max. 6W | E14
220-240VAC | 50-60Hz
steel
cable plug with dimmer switch

IP20

	EUR	CODE
	980,00	4011C0YE0
	980,00	4011C0RE0
	980,00	4011C0AU0
	980,00	4011C0BE0
	980,00	4011C0B0

OPTIONAL

T25-85 5W | E14 | phase-cut dim
gold tinted

	EUR	CODE
2200K | 460lm	29,00	9003C108
2500K | 480lm	29,00	9003C107
2700K | 500lm	29,00	9003C106

MIRRO

Table







1.0

A60 max. 15W | E27 | dimmable
220-240VAC | 50-60Hz
aluminium | steel | one side reflective composite panel
cable plug with dimmer switch

IP20

	EUR	CODE
	295,00	6301E0GB0
	295,00	6301E0NB0
	295,00	6301E0LB0
	295,00	6301E0BL0

OPTIONAL

A60 5.5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2700K | 405lm	32,00	9003E139

A60 5.5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 405lm	32,00	9003E140





MATCH

Table 61 | 137 | 153

193

329 | 347

415 | 509

571

589 | 685



1.0

LED COB 8W | dimmable
220-240VAC | 50-60Hz | incl. driver
aluminium
incl. switch on / off | push dim
incl. USB-C port

IP20 45°|0°-145° M-30° L80|50K

2700K | CRI >90 | 505lm

	EUR	CODE
	275,00	477254W3
	275,00	477254B3

back



HOTEL LOPESAN | EMILIO PELLEJERO FARO | SPAIN

reddot award 2019
winner lighting design

ROOMOR

Table





back



1.1

PAR16 max. 15W | GU10
100-240VAC | 50-60Hz
aluminium | steel
cable plug with hand switch
CH and UK variants online

IP20 0°-45°|0°-30°

	EUR	CODE
	262,00	637120GG1
	262,00	637120RR1
	262,00	637120BK1
	257,00	637120BB1

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 445lm	16,50	901228W3
2700K | 440lm	16,50	901228B3
3000K | 465lm	16,50	901228W5
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



FINLIN

Floor







back

263

433

673 | 679



1.0

LED PCB 16W | dimmable
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser
cable plug with dimmer switch

IP20 0°-10°|360° L80|50K

2700K | CRI >90 | 1360lm

	EUR	CODE
	395,00	470184W3
	395,00	470184B3

MATCH

Floor 61 | 137 | 153

193

329 | 347

415 | 509

571

589 | 685









back



1.0

LED COB 8W | dimmable
220-240VAC | 50-60Hz | incl. driver
aluminium
integrated dimmer button

IP20 0°-10°|360°|0°-145° M-30° L80|50K

2700K | CRI >90 | 505lm

	EUR	CODE
	325,00	477354W3
	325,00	477354B3



PRIVATE RESIDENCE | ERIBO STIJLBOUWERS BELGIUM



13&9 DESIGN

back

DRO

Floor

279
373
465
623



3.0

A60 max. 12W | E27 | dimmable
220-240VAC | 50-60Hz
aluminium | steel
artisanal Italian hand blown glass
cable plug with dimmer switch

IP20

	EUR	CODE
	595,00	6442E0WB0

OPTIONAL

A60 9W | E27 | phase-cut dim | opal

	EUR	CODE
2700K | 800lm	14,50	9003E152





MIRRO

Floor



2.0

G95 max. 15W | E27 | dimmable
220-240VAC | 50-60Hz
aluminium | steel | one side reflective composite panel
cable plug with dimmer switch

IP20

	EUR	CODE
	427,00	6311E0GB0
	427,00	6311E0NB0
	427,00	6311E0LB0
	427,00	6311E0BL0

OPTIONAL

G95 5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 955lm	35,00	9003E157



3.0

G95 max. 15W | E27 | dimmable
220-240VAC | 50-60Hz
aluminium | steel | one side reflective composite panel
cable plug with dimmer switch

IP20

	EUR	CODE
	587,00	6312E0GB0
	587,00	6312E0NB0
	587,00	6312E0LB0
	587,00	6312E0BL0

OPTIONAL

G95 5W | E27 | phase-cut dim
gold mirror

	EUR	CODE
2200K | 370lm	35,00	9003E156
2700K | 410lm	35,00	9003E142

G95 5W | E27 | phase-cut dim
silver mirror

	EUR	CODE
2700K | 955lm	35,00	9003E157

283
467
625



BV PARSHIP | JOPPICH & RIECKHOFF | SEEL BOBSIN PARTNER HAMBURG | GERMANY

reddot award 2019
winner lighting design



ROOMOR

Floor



1.2

PAR16 max. 15W | GU10
100-240VAC | 50-60Hz
aluminium | steel | grey felt
cable with floor switch
CH and UK variants online

IP20 0°-45°|0°-30°

	EUR	CODE
	502,00	638120BF2
	483,00	638120BK2
	475,00	638120BB2

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 440lm	16,50	901228B3
3000K | 460lm	16,50	901228B5

more lamps and info on page 905



1.3

PAR16 max. 15W | GU10
100-240VAC | 50-60Hz
aluminium | steel | grey felt
cable with floor switch
CH and UK variants online

IP20 0°-45°|0°-30°

	EUR	CODE
	579,00	638120BF3
	568,00	638120BK3
	555,00	638120BB3

OPTIONAL

PAR16 6.1W | GU10 | phase-cut dim

	EUR	CODE
2700K | 440lm	16,50	901228B3
3000K | 460lm	16,50	901228B5

more lamps and info on page 905

back

outdoor

Ceiling recessed

738 – 749

RECESSED



DEEP BIJOU
741



DEEP PETIT
743



DEEP
745



TAIO
747



INTRA
749

back



PRIVATE RESIDENCE | MINDAUGAS LELIŪGA LITHUANIA

DEEP bijou

Outdoor
Ceiling recessed

99 | 157





1.0

LED COB 4W | 500mA | 8V
aluminium

IP65 M-30° L80|55K

wire springs 50-52 85 4-25

	EUR	CODE
	69,50	165361W_
	69,50	165361Q_
	69,50	165361B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	470	>90	3
3000K	495	>90	5

IC rated

ALWAYS USE

driver | IP67

	EUR	CODE
7W | 500mA	46,50	90214301

more options and specs on page 899

MORE VERSIONS ONLINE
weverducre.com/more-deep-bijou-ip65

back



PRIVATE RESIDENCE GREECE

DEEP petit

Outdoor
Ceiling recessed

101 | 159





1.0

LED COB 6W | 350mA | 17V
aluminium

IP65 M-31° L80|50K

wire springs 68-70 85 4-25

	EUR	CODE
	96,00	153761W_
	96,00	153761Q_
	96,00	153761B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	590	>90	3
3000K	610	>90	5



ALWAYS USE

driver | 350mA | IP68

	EUR	CODE
17W	69,00	90213602

more options and specs on page 897

back





DEEP

Outdoor
Ceiling recessed

105 | 161



1.0

LED COB 6/9W | 350/500mA | 17V
aluminium

IP65 M-33° L80|55K

wire springs 86-89 85 4-27

	EUR	CODE
	109,00	184161W_
	109,00	184161Q_
	109,00	184161B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	485/640	>90	3
3000K	510/690	>90	5

ALWAYS USE

driver | IP68

	EUR	CODE
17W | 350mA	69,00	90213602
24W | 500mA	74,00	90214702

more options and specs on page 897

MORE VERSIONS ONLINE
weverducre.com/more-deep-ip65

IC rated

back



TAIO

Outdoor
Ceiling recessed





1.0

LED COB 6/9W | 350/500mA | 18V
aluminium
opal glass convex lens

IP65 W-105° L80|55K g

wire springs 68-73 80 4-27

	EUR	CODE
	95,00	180781W_
	95,00	180781G_
	95,00	180781Q_
	95,00	180781B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	340/455	>90	3
3000K	370/495	>90	5

ALWAYS USE

driver | IP68

	EUR	CODE
17W | 350mA	69,00	90213602
24W | 500mA	74,00	90214702

more options and specs on page 897

IC rated

back

165
299
757
803



PRIVATE RESIDENCE | KILLIAN GARTNER AUSTRIA

INTRA

Outdoor
Ceiling recessed







1.0 OPAL

LED PCB 7W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | polyamide
opal PMMA cover

IP65 L70|60K

blade springs ⌀76-79 ⎍70 ⟷min. 8

3000K | CRI >90 | 410lm

	EUR	CODE
	135,00	733188W5
	135,00	733188A5
	135,00	733188B5

2.0 SPOT

LED PCB 7W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | polyamide
clear lens

IP65 W-45° L70|50K

blade springs ⌀76-79 ⎍70 ⟷min. 8

3000K | CRI >90 | 560lm

	EUR	CODE
	135,00	733268W5
	135,00	733268A5
	135,00	733268B5

back

Ceiling surface / suspended

750 – 777

SURFACE



TRAM
753



TUBE
755



TAIO
757



RAY
759



TRAIN
761



TUBE CARRÉ
763



BOX
765



BLAS 1.0
767



BLAS 2.0
767



ROB
769



ROSS
771



TRADORA
775

SUSPENDED



TRADORA
777



PRIVATE RESIDENCE | ATELIER B AUSTRIA

TRAM

Outdoor
Ceiling surface





1.0

LED COB 6W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 M-36° L70|55K

3000K | CRI >90 | 555lm

	EUR	CODE
	142,00	747768W5
	142,00	747768A5
	142,00	747768Q5
	142,00	747768B5

797

back



PRIVATE RESIDENCE AUSTRIA

TUBE

Outdoor
Ceiling surface







1.0 LED

LED COB 10W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 M-36° L80|60K

3000K | CRI >90 | 620lm

	EUR	CODE
	208,00	734364W5
	208,00	734364D5
	208,00	734364A5
	208,00	734364B5

1.0 PAR16

PAR16 max. 5W | GU10
100-240VAC | 50-60Hz
aluminium

IP65

	EUR	CODE
	118,00	734120W0
	118,00	734120D0
	118,00	734120A0
	118,00	734120Q0
	118,00	734120B0

OPTIONAL

PAR16 3.7W | GU10

	EUR	CODE
2700K | 350lm	13,00	905227S2
3000K | 350lm	13,00	905227S4

back

799



PRIVATE RESIDENCE BELGIUM

TAIO

Outdoor
Ceiling surface





1.0

LED COB 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium
opal glass convex lens

IP65 W-105° L80|55K

	EUR	CODE
	198,00	180884W_
	198,00	180884A_
	198,00	180884Q_
	198,00	180884B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	455	>90	3
3000K	510	>90	5

back

165
299
747
803



SHOP PHILMODE | ERIC FRANSSENS BEAUFAYS | BELGIUM

RAY

Outdoor
Ceiling surface





251
341 | 377 | 393
537
615
805

1.0

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 M-21° L70|50K

	EUR	CODE
	175,00	735458W_
	175,00	735458D_
	175,00	735458A_
	175,00	735458B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	670	>90	3
3000K	700	>90	5
2000-3000K	470	>90	9



OPTIONAL

inner cover

	EUR	CODE
	23,00	911041W1
	23,00	911041D1
	23,00	911041A1
	23,00	911041B1

back





TRAIN

Outdoor
Ceiling surface



1.0

LED COB 6W| phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 M-36° L70|55K

3000K | CRI >90 | 530lm

	EUR	CODE
	142,00	718668W5
	142,00	718668A5
	142,00	718668Q5
	142,00	718668B5

back

807



PRIVATE RESIDENCE | SPADO ARCHITECTS AUSTRIA

TUBE CARRÉ

Outdoor
Ceiling surface















1.0 LED

LED COB 10W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 M-32° L80|60K

3000K | CRI >90 | 720lm

	EUR	CODE
	228,00	734464W5
	228,00	734464D5
	228,00	734464A5
	228,00	734464B5

1.0 PAR16

PAR16 max. 5W | GU10
100-240VAC | 50-60Hz
aluminium

IP65

	EUR	CODE
	156,00	734220W0
	156,00	734220D0
	156,00	734220A0
	156,00	734220Q0
	156,00	734220B0

OPTIONAL

PAR16 3.7W | GU10

	EUR	CODE
2700K | 350lm	13,00	905227S2
3000K | 350lm	13,00	905227S4

811

back



PRIVATE RESIDENCE FRANCE

BOX

Outdoor
Ceiling surface

235
335
607
815









1.0

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 M-21° L70|50K

	EUR	CODE
	175,00	735258W_
	175,00	735258D_
	175,00	735258A_
	175,00	735258Q_
	175,00	735258B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	600	>90	3
3000K	620	>90	5
2000-3000K	415	>90	9

OPTIONAL

inner reflector

	EUR	CODE
	21,00	911211W1
	21,00	911211D1
	21,00	911211Q1
	21,00	911211B1

inner cover

	EUR	CODE
	23,00	911011W1
	23,00	911011D1
	23,00	911011Q1
	23,00	911011B1

back



PRIVATE RESIDENCE | PETER RANEBURGER AUSTRIA

BLAS

Outdoor
Ceiling surface







1.0

LED PCB 10W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | clear and frosted glass

IP65 L80|50K

3000K | CRI >90 | 950lm

	EUR	CODE
	228,00	736387W5
	228,00	736387A5
	228,00	736387Q5
	228,00	736387B5

2.0

LED PCB 10W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | clear and frosted glass

IP65 L80|50K

3000K | CRI >90 | 950lm

	EUR	CODE
	244,00	736487W5
	244,00	736487A5
	244,00	736487Q5
	244,00	736487B5



827

back



PRIVATE RESIDENCE BELGIUM

ROB

Outdoor
Ceiling surface

301





ø160



ø256



ø345

1.6

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA cover

IP44 SDCM3 L80|60K 0.70kg

	EUR	CODE
	168,00	701188W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1170	>90	3
3000K	1220	>90	5

2.6

LED PCB 18W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA cover

IP44 SDCM3 L80|60K 1.20kg

	EUR	CODE
	245,00	701288W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	1800	>90	3
3000K	1810	>90	5

3.5

LED PCB 32W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | opal PMMA cover

IP44 SDCM3 L80|60K 1.90kg

	EUR	CODE
	335,00	701388W_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	3340	>90	3
3000K	3360	>90	5

back



ROSS

Outdoor
Ceiling surface

307













1.0

LED PCB 9/11/15W
220-240VAC | 50-60Hz | incl. driver
polycarbonate housing
output and light colour selectable via dip switch

IP54 L80|50K

3000K/4000K/6000K | CRI >90
960lm/1170lm/1630lm

	EUR	CODE
	79,00	715184W9

2.0

LED PCB 10/15/20W
220-240VAC | 50-60Hz | incl. driver
polycarbonate housing
output and light colour selectable via dip switch

IP54 L80|50K

3000K/4000K/6000K | CRI >90
1270lm/1810lm/2360lm

	EUR	CODE
	129,00	715284W9

3.0

LED PCB 28/33/37W
220-240VAC | 50-60Hz | incl. driver
polycarbonate housing
output and light colour selectable via dip switch

IP54 L80|50K

3000K/4000K/6000K | CRI >90
4350lm/5000lm/5570lm

	EUR	CODE
	225,00	715384W9

back



collection

OH, HOW ROMANTIC

Wie in België is geweest, kent de romantische landhuizen met houten luiken waarin je zo zou willen wonen. Hun speelse historische stijl zorgt voor een warme, uitnodigende sfeer – van handgemaakte meubels tot de traditionele lampen die nu deel uitmaken van de nieuwe CLASSIC COLLECTION

Qui a visité la Belgique connaît ces maisons de campagne romantiques aux volets en bois, dans lesquelles on voudrait aussitôt s'installer. Leur style historique et ludique leur confère une atmosphère chaleureuse – des meubles faits main aux luminaires traditionnels de la nouvelle CLASSIC COLLECTION.

weverducre.com/classic-collection



TRADORA

Outdoor
Ceiling surface





1.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | handblown opal glass

IP65 L80|50K

2700K | CRI >90 | 350lm

	EUR	CODE
	365,00	760284CL3
	365,00	760284CQ3
	355,00	760284B3

back

777

823



TRADORA

Outdoor
Ceiling suspended









1.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | handblown opal glass

IP65 L80|50K

2700K | CRI >90 | 350lm

	EUR	CODE
	375,00	760384CL3
	375,00	760384CQ3
	365,00	760384B3

back

Wall recessed

778 – 787

GUIDE LIGHTS



RETO 0.8
781



RETO 1.3
781



RETO 2.0
783



ORIS 0.7
785



ORIS 2.0
785



ORIS 0.8
787



ORIS 1.3
787



PRIVATE RESIDENCE GREECE

RETO

Outdoor
Wall recessed







0.8

LED PCB 3W | const. volt. | 24V
aluminium

IP65 L80|50K

66x66 40 min. 12

3000K | CRI >90 | 75lm

	EUR	CODE
	104,00	7451A2A5
	104,00	7451A2Q5
	104,00	7451A2B5

ALWAYS USE

driver | IP67

	EUR	CODE
24V | 35W	49,00	90212802
24V | 100W	144,60	90212903

specs on page 901

OPTIONAL

recessed housing incl. plasterkit*

	EUR	CODE
	46,00	90012047

concrete housing*

	EUR	CODE
	32,00	90012046

*driver to be placed externally

1.3

LED PCB 5W | const. volt. | 24V
aluminium

IP65 L80|50K

115x117 40 min. 12

3000K | CRI >90 | 170lm

	EUR	CODE
	144,00	7452A2A5
	144,00	7452A2Q5
	144,00	7452A2B5

ALWAYS USE

driver | IP67

	EUR	CODE
24V | 35W	49,00	90212802
24V | 100W	144,60	90212903

specs on page 901

OPTIONAL

recessed housing incl. plasterkit*

	EUR	CODE
	52,00	90012041

concrete housing*

	EUR	CODE
	39,00	90012040

*driver to be placed externally

573
835
back



PRIVATE RESIDENCE AUSTRIA

RETO

Outdoor
Wall recessed





2.0

LED PCB 7W | const. volt. | 24V
aluminium

IP65 L80|50K

47x182 L40 min. 12

3000K | CRI >90 | 330lm

	EUR	CODE
	175,00	7453A2A5
	175,00	7453A2Q5
	175,00	7453A2B5

ALWAYS USE

driver | IP67

	EUR	CODE
24V | 35W	49,00	90212802
24V | 100W	144,60	90212903

specs on page 901

OPTIONAL

recessed housing incl. plasterkit*

	EUR	CODE
	45,00	90012039

concrete housing*

	EUR	CODE
	38,00	90012044

*driver to be placed externally

back

573
835



PRIVATE RESIDENCE | SPADO ARCHITECTS AUSTRIA

ORIS

Outdoor
Wall recessed





0.7

LED PCB 2/5W| 350/700mA | 6V
aluminium

IP65 L70|60K

47x182 40 min. 12

3000K | CRI >90 | 70/120lm

	EUR	CODE
	108,00	7091A1W5
	108,00	7091A1D5
	108,00	7091A1B5

ALWAYS USE

driver | IP66

	EUR	CODE
3W | 350mA	35,00	90213101
7W | 500mA	46,50	90214301
7W | 700mA	36,50	90215301

more options and specs on page 897

OPTIONAL

recessed housing incl. plasterkit

	EUR	CODE
	45,00	90012039

concrete housing

	EUR	CODE
	38,00	90012044



2.0

LED PCB 4/7W | 350/700mA | 9V
aluminium

IP65 L70|60K

115x185 40 min. 12

3000K | CRI >90 | 140/225lm

	EUR	CODE
	132,00	7097A1W5
	132,00	7097A1D5
	132,00	7097A1B5

ALWAYS USE

driver | IP66

	EUR	CODE
3W | 350mA	35,00	90213101
7W | 500mA	46,50	90214301
7W | 700mA	36,50	90215301

more options and specs on page 897

OPTIONAL

recessed housing incl. plasterkit

	EUR	CODE
	58,00	90012043

concrete housing

	EUR	CODE
	42,00	90012042

581

back



PRIVATE RESIDENCE ARTIO STUDIO/MARTA DE LOZOYA SPAIN

ORIS

Outdoor
Wall recessed





0.8

LED PCB 2/5W | 350/700mA | 6V
aluminium

IP65 L70|60K

66x66 40 min. 12

3000K | CRI >90 | 90/150lm

	EUR	CODE
	98,00	7094A1W5
	98,00	7094A1A5
	98,00	7094A1Q5
	98,00	7094A1B5

1.3

LED PCB 4/7W | 350/700mA | 9V
aluminium

IP65 L70|60K

115x117 40 min. 12

3000K | CRI >90 | 145/220lm

	EUR	CODE
	122,00	7096A1W5
	122,00	7096A1D5
	122,00	7096A1A5
	122,00	7096A1Q5
	122,00	7096A1B5



ALWAYS USE

driver | IP66

	EUR	CODE
3W | 350mA	35,00	90213101
7W | 500mA	46,50	90214301
7W | 700mA	36,50	90215301

more options and specs on page 897

ALWAYS USE

driver | IP66

	EUR	CODE
3W | 350mA	35,00	90213101
7W | 500mA	46,50	90214301
7W | 700mA	36,50	90215301

more options and specs on page 897

OPTIONAL

recessed housing incl. plasterkit

	EUR	CODE
	46,00	90012047

concrete housing

	EUR	CODE
	32,00	90012046

OPTIONAL

recessed housing incl. plasterkit

	EUR	CODE
	52,00	90012041

concrete housing

	EUR	CODE
	39,00	90012040

main
581
main
back

Wall surface

LUMINAIRES



CLASCO
791



KIOSK
793



TRAM
797



TUBE 1.0
799



TUBE 2.0
801



TAIO
803



RAY 1.0 | 2.0
805



RAY 4.0
805



TRAIN
807



CENTRAL
809



TUBE CARRÉ 1.0
811



TUBE CARRÉ 2.0
813



BOX 1.0 | 2.0
815



BOX 4.0
815



TAPE
817



PALOS 1.0
819



PALOS 2.0
819

PALOS 3.0
819



SWAM
821



TRADORA
823



RIBELLE
825



BLAS 1.0
827



BLAS 2.0
827

SPOT LIGHTS



X-BEAM
829



X-BEAM ROUND
829

GUIDE LIGHTS



PAVIO
831



RETO ROUND
833



RETO
835

back



CLASCO

Outdoor
Wall surface





1.0

LED COB 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 W-105° L80|50K

	EUR	CODE
	185,00	759174CL_
	178,00	759174A_
	185,00	759174AB_
	185,00	759174CQ_
	178,00	759174Q_
	178,00	759174B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	505	>90	3
3000K	520	>90	5

back



KIOSK

Outdoor
Wall surface







1.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|50K

	EUR	CODE
	226,00	707174W_
	226,00	707174A_
	226,00	707174Q_
	226,00	707174B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x480	>90	3
3000K	2x500	>90	5

2.0

LED PCB 22W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|100K

	EUR	CODE
	315,00	707574W_
	315,00	707574A_
	315,00	707574Q_
	315,00	707574B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x960	>90	3
3000K	2x1000	>90	5

857

back







PRIVATE RESIDENCE AUSTRIA

TRAM

Outdoor
Wall surface









1.0

LED COB 6W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 M-36° L70|55K

3000K | CRI >90 | 555lm

	EUR	CODE
	168,00	747568W5
	168,00	747568A5
	168,00	747568Q5
	168,00	747568B5

2.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 M-36° L70|55K

3000K | CRI >90 | 2x360lm

	EUR	CODE
	218,00	747668W5
	218,00	747668A5
	218,00	747668Q5
	218,00	747668B5

back



HOTEL VALAMAR GIRANDELLA & TUI RESORT | **STUDIO 92** RABAC | CROATIA

TUBE

Outdoor
Wall surface









1.0 LED

LED COB 10W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 M-36° L80|60K

3000K | CRI >90 | 635lm

	EUR	CODE
	188,00	711364W5
	188,00	711364D5
	188,00	711364A5
	188,00	711364B5

1.0 PAR16

PAR16 max. 5W | GU10
220-240VAC | 50-60Hz
aluminium

IP65

	EUR	CODE
	94,00	711120W0
	94,00	711120D0
	94,00	711120A0
	94,00	711120Q0
	94,00	711120B0

OPTIONAL

PAR16 3.7W | GU10

	EUR	CODE
2700K | 350lm	13,00	905227S2
3000K | 350lm	13,00	905227S4

755

back



PRIVATE RESIDENCE | BUITENHUIS TUINONDERNEMINGEN BELGIUM

TUBE

Outdoor
Wall surface







2.0 LED

LED COB 21W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 M-36° L80|60K

3000K | CRI >90 | 2x635lm

	EUR	CODE
	288,00	711464W5
	288,00	711464D5
	288,00	711464A5
	288,00	711464B5

2.0 PAR16

2x PAR16 max. 5W | GU10
220-240VAC | 50-60Hz
aluminium

IP65

	EUR	CODE
	128,00	711220W0
	128,00	711220D0
	128,00	711220A0
	128,00	711220Q0
	128,00	711220B0

OPTIONAL

PAR16 3.7W | GU10

	EUR	CODE
2700K | 350lm	13,00	905227S2
3000K | 350lm	13,00	905227S4





back



PRIVATE RESIDENCE | GC ARCHITECTEN BELGIUM

TAIO

Outdoor
Wall surface

165
299
747
757











1.0

LED COB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | protector glass
opal glass convex lens

IP65 W-105° L80|55K

	EUR	CODE
	185,00	180584W_
	185,00	180584A_
	185,00	180584Q_
	185,00	180584B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	435	>90	3
3000K	490	>90	5

2.0

LED COB 21W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | protector glass
opal glass convex lens

IP65 W-105° L80|55K

	EUR	CODE
	285,00	180684W_
	285,00	180684A_
	285,00	180684Q_
	285,00	180684B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x435	>90	3
3000K	2x490	>90	5

back



PIARISTENGASSE 23 | © **LIV.AT** VIENNA | AUSTRIA

RAY

Outdoor
Wall surface






251


341 | 377 | 393


537


615


759







1.0

LED PCB 6W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 L80|55K

	EUR	CODE
	198,00	749168W_
	198,00	749168B_

incl. adjustable flaps

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	350	>90	3
3000K	370	>90	5

2.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 L80|55K

	EUR	CODE
	219,00	749148W_
	219,00	749148B_

incl. adjustable flaps

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x440	>90	3
3000K	2x460	>90	5

4.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 L80|55K

	EUR	CODE
	233,50	749248W_
	233,50	749248B_

incl. adjustable flaps

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x325	>90	3
3000K	2x345	>90	5

LOXONE VERSIONS ONLINE
weverducre.com/more-ray-wall

back



GALLOP EXTENSION AT SINGAPORE BOTANIC GARDENS | KAY NGEE TAN ARCHITECTS SINGAPORE

TRAIN

Outdoor
Wall surface











1.0 NARROW

LED PCB 6W
220-240VAC | 50-60Hz | incl. driver
aluminium
narrow up or narrow down lens

IP65 W-55°x5° L80|60K

3000K | CRI >80 | 170lm

	EUR	CODE
	178,00	718143B4

1.0

LED COB 6W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 M-38° L70|55K

3000K | CRI >90 | 530lm

	EUR	CODE
	168,00	718868W5
	168,00	718868A5
	168,00	718868B5

2.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 M-38° L70|55K

3000K | CRI >90 | 2x375lm

	EUR	CODE
	218,00	718968W5
	218,00	718968A5
	218,00	718968B5

back



PRIVATE RESIDENCE | OLSTE & HOPROM BELGIUM

CENTRAL

Outdoor
Wall surface







1.0

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K

3000K | CRI >90 | 620lm

	EUR	CODE
	218,00	313774W5
	218,00	313774A5
	218,00	313774Q5
	218,00	313774B5

2.0

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K

3000K | CRI >90 | 2x330lm

	EUR	CODE
	255,00	313874W5
	255,00	313874A5
	255,00	313874Q5
	255,00	313874B5

back

617



PRIVATE RESIDENCE | TRANSFORM ARCHITECTUUR BELGIUM

TUBE CARRÉ

Outdoor
Wall surface









1.0 LED

LED COB 10W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 M-32° L80|60K

3000K | CRI >90 | 715lm

	EUR	CODE
	208,00	744364W5
	208,00	744364D5
	208,00	744364A5
	208,00	744364B5

1.0 PAR16

PAR16 max. 5W | GU10
220-240VAC | 50-60Hz
aluminium

IP65

	EUR	CODE
	136,00	744120W0
	136,00	744120D0
	136,00	744120A0
	136,00	744120Q0
	136,00	744120B0

OPTIONAL

PAR16 3.7W | GU10

	EUR	CODE
2700K | 350lm	13,00	905227S2
3000K | 350lm	13,00	905227S4

763

back



PRIVATE RESIDENCE | MAA ARCHITECTURE STUDIO & ZPLUS ARCHITECTURE BELGIUM

TUBE CARRÉ

Outdoor
Wall surface







2.0 LED

LED COB 20W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 M-36° L80|60K

3000K | CRI >90 | 2x745lm

	EUR	CODE
	309,00	744464W5
	309,00	744464D5
	309,00	744464A5
	309,00	744464B5

2.0 PAR16

2x PAR16 max. 5W | GU10
220-240VAC | 50-60Hz
aluminium

IP65

	EUR	CODE
	179,00	744220W0
	179,00	744220D0
	179,00	744220A0
	179,00	744220Q0
	179,00	744220B0

OPTIONAL

PAR16 3.7W | GU10

	EUR	CODE
2700K | 350lm	13,00	905227S2
3000K | 350lm	13,00	905227S4













763

back



PRIVATE RESIDENCE | RARDO ARCHITECTS SPAIN

BOX

Outdoor
Wall surface























MORE VERSIONS + LOXONE ONLINE
weverducre.com/more-box-wall

1.0

LED PCB 6W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 L80|55K

	EUR	CODE
	198,00	748168W_
	198,00	748168D_
	198,00	748168A_
	198,00	748168Q_
	198,00	748168B_

incl. adjustable flaps

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	350	>90	3
3000K	370	>90	5

2.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 L80|55K

	EUR	CODE
	219,00	748148W_
	219,00	748148D_
	219,00	748148A_
	219,00	748148Q_
	219,00	748148B_

incl. adjustable flaps

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x440	>90	3
3000K	2x460	>90	5

4.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 L80|55K

	EUR	CODE
	234,00	748248W_
	234,00	748248D_
	234,00	748248Q_
	234,00	748248B_

incl. adjustable flaps

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x325	>90	3
3000K	2x345	>90	5

235
335
607
765
back



PRIVATE RESIDENCE AUSTRIA

TAPE

Outdoor
Wall surface





1.0

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K



3000K | CRI >90 | 425lm

	EUR	CODE
	298,00	722174W5
	298,00	722174D5
	298,00	722174A5
	298,00	722174B5

back



PRIVATE RESIDENCE | BAUBUREAU OG 27 SWITZERLAND

PALOS

Outdoor
Wall surface





1.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K

	EUR	CODE
	265,00	4161A4A_
	265,00	4161A4Q_
	265,00	4161A4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	680	>80	2
3000K	700	>80	4



2.0

LED PCB 21W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K

	EUR	CODE
	328,00	4162A4A_
	328,00	4162A4Q_
	328,00	4162A4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x600	>80	2
3000K	2x620	>80	4



3.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K

	EUR	CODE
	225,00	4163A4A_
	225,00	4163A4Q_
	225,00	4163A4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	745	>80	2
3000K	770	>80	4

back

877



PRIVATE RESIDENCE | ELLEMVIE - ART & INTERIEUR THE NETHERLANDS

SWAM

Outdoor
Wall surface








Q


K


B

1.0

LED PCB 8W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 L80|60K

2700K | CRI >90 | 410lm

	EUR	CODE
	239,00	746278Q3
	248,00	746278K3
	239,00	746278B3

2.0

LED PCB 14W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 L80|60K

2700K | CRI >90 | 670lm

	EUR	CODE
	283,00	746378Q3
	294,00	746378K3
	283,00	746378B3

859

back

TRADORA

Outdoor
Wall surface





1.0

LED COB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | handblown opal glass

IP65 L80|50K

2700K | CRI >90 | 350lm

	EUR	CODE
	365,00	760184CL3
	365,00	760184CQ3
	355,00	760184B3

775
777
back

RIBELLE

Outdoor
Wall surface





1.0

LED PCB 5W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP65 L80|100K

	EUR	CODE
	325,00	772184A_
	325,00	772184Q_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	415	>90	3
3000K	425	>90	5

back

709

867



PRIVATE RESIDENCE BELGIUM

BLAS

Outdoor
Wall surface











1.0

LED PCB 10W | phase-cut dim
220-240VAC | 50-60Hz
aluminium
clear and frosted glass

IP65 L80|50K

3000K | CRI >90 | 950lm

	EUR	CODE
	228,00	736387W5
	228,00	736387B5

2.0

LED PCB 10W | phase-cut dim
220-240VAC | 50-60Hz
aluminium
clear and frosted glass

IP65 L80|50K

3000K | CRI >90 | 950lm

	EUR	CODE
	244,00	736487W5
	244,00	736487B5



back











SHOWROOM CHILLOUT AREA GRAZ | AUSTRIA

X-BEAM

Outdoor
Wall surface











OPTIONAL

snoot

	EUR	CODE
	35,00	90019023

snoot round

	EUR	CODE
	35,00	90019031

specs on page 911



1.0

LED PCB 24W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 0-110° W-108° L80|60K

3000K | CRI >80 | 1590lm

	EUR	CODE
	345,00	700374D4
	345,00	700374A4
	345,00	700374B4

1.0 ROUND

LED PCB 24W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 0-110° W-108° L80|60K

3000K | CRI >80 | 1520lm

	EUR	CODE
	345,00	700474A4
	345,00	700474Q4
	345,00	700474B4

back

PAVIO

Outdoor
Wall surface



58
ø150

1.0

LED PCB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|100K

3000K | CRI >90 | 525lm

	EUR	CODE
	185,00	351184W5
	185,00	351184Q5
	185,00	351184B5

back

711



PRIVATE RESIDENCE SPAIN

RETO ROUND

Outdoor
Wall surface







0.8

LED PCB 4W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|100K

3000K | CRI >90 | 105lm

	EUR	CODE
	158,00	7457A4A5
	158,00	7457A4Q5
	158,00	7457A4B5

1.3

LED PCB 6W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|100K

3000K | CRI >90 | 160lm

	EUR	CODE
	198,00	7458A4A5
	198,00	7458A4Q5
	198,00	7458A4B5

back



PRIVATE RESIDENCE | RARDO ARCHITECTS SPAIN

RETO

Outdoor
Wall surface









0.8

LED PCB 4W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|100K

3000K | CRI >90 | 105lm

	EUR	CODE
	158,00	7454A4A5
	158,00	7454A4Q5
	158,00	7454A4B5

1.3

LED PCB 6W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|50K

3000K | CRI >90 | 160lm

	EUR	CODE
	198,00	7455A4A5
	198,00	7455A4Q5
	198,00	7455A4B5

2.0

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|50K

3000K | CRI >90 | 335lm

	EUR	CODE
	188,00	7456A4A5
	188,00	7456A4Q5
	188,00	7456A4B5

573
781
back

Floor recessed

836 – 853

RECESSED



BLINK TRIMLESS
839



BLINK
839



CARD 0.1
843



CARD 0.2
843



MAP
845



MAP ASYM
849



CHART
851



CHART ASYM
853

back



PRIVATE RESIDENCE GREECE

BLINK

Outdoor
trimless / Floor recessed





1.0 TRIMLESS

LED COB 6W | 500mA | 9V
aluminium | glass

IP65 IK08 M-30° L80|50K

3000K | CRI >90 | 410lm

	EUR	CODE
	218,00	721261B5

ALWAYS USE

driver | 500mA

	EUR	CODE
7W dim	25,50	90224301
7W IP67	46,50	90214301

more options and specs on page 898

ALWAYS USE

recessed ground housing | polyamide

137 110



	EUR	CODE
	25,00	90012201



1.0

LED COB 6W | 500mA | 9V
aluminium | glass

IP65 IK08 M-30° L80|50K

47-49

3000K | CRI >90 | 410lm

	EUR	CODE
	205,00	721161B5

ALWAYS USE

driver | 500mA

	EUR	CODE
7W dim	25,50	90224301
7W IP67	46,50	90214301

more options and specs on page 898

OPTIONAL

recessed ground housing | polyamide

137 110



	EUR	CODE
	25,00	90012201

back

BLINK

Outdoor
trimless / Floor recessed



2.0 TRIMLESS

LED COB 11W | 500mA | 20V
aluminium | glass

IP65 IK08 M-38° L80|50K

84-86

3000K | CRI >90 | 700lm

	EUR	CODE
	239,00	721461B5

ALWAYS USE

driver | 500mA

	EUR	CODE
20W dim	45,50	90224602
24W IP68	74,00	90214702

more options and specs on page 898

ALWAYS USE

recessed ground housing | polyamide

137 130



	EUR	CODE
	34,00	90012202



2.0

LED COB 11W | 500mA | 20V
aluminium | glass

IP65 IK08 M-38° L80|50K

84-86

3000K | CRI >90 | 700lm

	EUR	CODE
	229,00	721361B5

ALWAYS USE

driver | 500mA

	EUR	CODE
20W dim	45,50	90224602
24W IP68	74,00	90214702

more options and specs on page 898

OPTIONAL

recessed ground housing | polyamide

137 130



	EUR	CODE
	34,00	90012202



back



DIJLEPAD MECHELEN | BELGIUM

CARD

Outdoor
Floor recessed





0.1

LED PCB 2W | 350mA | 3V
aluminium | stainless steel | glass

IP67 IK07 N-16° L70|60K

22-24 60

3000K | CRI >80 | 90lm

	EUR	CODE
	86,00	750141I4

0.2

LED PCB 2W | 350mA | 3V
aluminium | stainless steel | glass

IP67 IK07 N-16° L70|60K

22-24 60

3000K | CRI >80 | 90lm

	EUR	CODE
	106,00	750241I4

ALWAYS USE

driver | IP66

	EUR	CODE
3W | 350mA	35,00	90213101

more options and specs on page 897

ALWAYS USE

driver | IP66

	EUR	CODE
3W | 350mA	35,00	90213101

more options and specs on page 897





back



PRIVATE RESIDENCE | RARDO ARCHITECTS SPAIN

MAP

Outdoor
Floor recessed



0.6

LED COB 5W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | stainless steel | glass

IP67 IK08 W-43° L70|55K

L100

3000K | CRI >90 | 310lm

	EUR	CODE
	205,00	751168I5

OPTIONAL

recessed ground housing | polyamide

137 L110



	EUR	CODE
	25,00	90012201



0.9

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | stainless steel | glass

IP67 IK08 M-35° L70|55K

L135

3000K | CRI >90 | 685lm

	EUR	CODE
	228,00	751268I5

OPTIONAL

recessed ground housing | polyamide

137 L130



	EUR	CODE
	34,00	90012202



back



TOPSPORTSCHOOL | UAU COLLECTIV HASSELT | BELGIUM

MAP

Outdoor
Floor recessed





1.2

LED COB 12W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | stainless steel | glass

IP67 IK08 W-44° L70|55K

120

3000K | CRI >90 | 995lm

	EUR	CODE
	278,00	751368I5

OPTIONAL

recessed ground housing | polyamide

190 158



	EUR	CODE
	47,00	90012203



1.6

LED COB 17W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | stainless steel | glass

IP67 IK09 M-38° L70|55K

185

3000K | CRI >90 | 1260lm

	EUR	CODE
	410,00	75146815

OPTIONAL

recessed ground housing | polyamide

220 184



	EUR	CODE
	61,00	90012204

back



PRIVATE RESIDENCE OBUMEX – STEENOVEN BELGIUM

MAP ASYM

Outdoor
Floor recessed



1.2

LED COB 12W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | stainless steel | glass
asymmetric reflector

IP67 IK08 L70|55K

160

3000K | CRI >90 | 565lm

	EUR	CODE
	298,00	7515A8I5

OPTIONAL

recessed ground housing | polyamide

190 158



	EUR	CODE
	47,00	90012203



1.6

LED COB 16W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | stainless steel | glass
asymmetric reflector

IP67 IK09 L70|55K

185

3000K | CRI >90 | 845lm

	EUR	CODE
	440,00	7516A8I5

OPTIONAL

recessed ground housing | polyamide

220 184



	EUR	CODE
	61,00	90012204



back





PRIVATE RESIDENCE FRANCE

CHART

Outdoor
Floor recessed



0.6

LED COB 5W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | stainless steel | glass

IP67 IK08 W-43° L70|55K

L118

3000K | CRI >90 | 310lm

	EUR	CODE
	208,00	752168I5

OPTIONAL

recessed ground housing | polyamide

Ø137 L110



	EUR	CODE
	25,00	90012201



0.9

LED COB 8W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | stainless steel | glass

IP67 IK08 M-35° L70|55K

L135

3000K | CRI >90 | 640lm

	EUR	CODE
	234,00	752268I5

OPTIONAL

recessed ground housing | polyamide

Ø137 L130



	EUR	CODE
	34,00	90012202



1.2

LED COB 12W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | stainless steel | glass

IP67 IK08 W-44° L70|55K

L175

3000K | CRI >90 | 995lm

	EUR	CODE
	285,00	752368I5

OPTIONAL

recessed ground housing | polyamide

Ø190 L158



	EUR	CODE
	47,00	90012203



1.6

LED COB 17W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | stainless steel | glass

IP67 IK09 M-38° L70|55K

L185

3000K | CRI >90 | 1260lm

	EUR	CODE
	425,00	752468I5

OPTIONAL

recessed ground housing | polyamide

Ø220 L184



	EUR	CODE
	61,00	90012204

back

CHART ASYM

Outdoor
Floor recessed



1.2

LED COB 12W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | stainless steel | glass
asymmetric reflector

IP67 IK08 L70|55K

160

3000K | CRI >90 | 565lm

	EUR	CODE
	305,00	7525A8I5

OPTIONAL

recessed ground housing | polyamide

190 158



	EUR	CODE
	47,00	90012203



1.6

LED COB 16W | phase-cut dim
220-240VAC | 50-60Hz
aluminium | stainless steel | glass
asymmetric reflector

IP67 IK09 L70|55K

185

3000K | CRI >90 | 845lm

	EUR	CODE
	455,00	7526A8I5

OPTIONAL

recessed ground housing | polyamide

220 184



	EUR	CODE
	61,00	90012204



back

Floor surface

854 - 891

LUMINAIRES

KIOSK 1.1
857

KIOSK 1.2
857

KIOSK 1.3
857



SWAM
859



SWAM
859

PROJECTORS



STIPO 1.0
863



STIPO 4.0
863



X-BEAM
865



X-BEAM ROUND
865

BOLLARDS

RIBELLE
867

GATE ROUND 1.0
869

GATE ROUND 2.0
869

GATE CARRÉ 1.0
871

GATE CARRÉ 2.0
871



PALOS ROUND
873



PALOS CARRÉ
877

LINUS
881

PLUG & PLAY

GEO 1.0
885

GEO 2.0
885

REED 1.0
887

REED 2.0
887

POLA 2.0
889

POLA 2.1
889





PRIVATE RESIDENCE SPAIN

KIOSK

Outdoor
Floor surface



1.1

LED PCB 6W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|50K

3000K | CRI >90 | 395lm

	EUR	CODE
	176,00	7072A4A5
	176,00	7072A4Q5

ALWAYS USE

pole | incl. ground spike

	EUR	CODE
400	114,00	910101_0
600	125,00	910102_0
800	138,00	910103_0

	CODE
	A
	Q

order fixation separately

OPTIONAL

ground fixation plate

	EUR	CODE
	22,00	90019019



1.2

LED PCB 13W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|50K

3000K | CRI >90 | 2x380lm

	EUR	CODE
	198,00	7073A4A5
	198,00	7073A4Q5

ALWAYS USE

pole | incl. ground spike

	EUR	CODE
400	114,00	910101_0
600	125,00	910102_0
800	138,00	910103_0

	CODE
	A
	Q

order fixation separately

OPTIONAL

ground fixation plate

	EUR	CODE
	22,00	90019019



1.3

LED PCB 19W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|50K

3000K | CRI >90 | 3x375lm

	EUR	CODE
	238,00	7074A4A5
	238,00	7074A4Q5

ALWAYS USE

pole | incl. ground spike

	EUR	CODE
400	114,00	910101_0
600	125,00	910102_0
800	138,00	910103_0

	CODE
	A
	Q

order fixation separately

OPTIONAL

ground fixation plate

	EUR	CODE
	22,00	90019019

793

back



PRIVATE RESIDENCE AUSTRIA

SWAM

Outdoor
Floor surface





1.0

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 L80|60K

2700K | CRI >90 | 310lm

	EUR	CODE
	275,00	746178Q3
	283,00	746178K3
	275,00	746178B3

ALWAYS USE

straight pole | incl. ground spike

	EUR	CODE
400	103,00	910090_0
600	115,00	910091_0
800	128,00	910092_0

	CODE
	B
	Q

order fixation separately

OPTIONAL

ground fixation plate

	EUR	CODE
	22,00	90019019



1.0

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 L80|60K

2700K | CRI >90 | 310lm

	EUR	CODE
	275,00	746178Q3
	283,00	746178K3
	275,00	746178B3

ALWAYS USE

curved pole | incl. ground spike

	EUR	CODE
400	142,00	910093_0
600	144,00	910094_0
800	155,00	910095_0

	CODE
	B
	Q

order fixation separately

OPTIONAL

ground fixation plate

	EUR	CODE
	22,00	90019019

821

back





HOTEL BRITANNIA | S-CONSULTANCY KNOKKE-HEIST | BELGIUM







STIPO

Outdoor
Floor surface









1.0

LED COB 7W | phase-cut dim
220-240VAC | 50/60Hz
aluminium

IP65 135° M-38° L70|55K

3000K | CRI >90 | 450lm

	EUR	CODE
	199,00	737168A5
	199,00	737168Q5

2.0

LED COB 7W | phase-cut dim
220-240VAC | 50/60Hz
aluminium

IP65 135° M-38° L70|55K

3000K | CRI >90 | 500lm

	EUR	CODE
	197,00	737268A5
	197,00	737268Q5

3.0

LED COB 7W | phase-cut dim
220-240VAC | 50/60Hz
aluminium

IP65 135° M-38° L70|55K

3000K | CRI >90 | 450lm

	EUR	CODE
	196,00	737368A5
	196,00	737368Q5

4.0

LED COB 7W | phase-cut dim
220-240VAC | 50/60Hz
aluminium

IP65 135° M-38° L70|55K

3000K | CRI >90 | 500lm

	EUR	CODE
	194,00	737468A5
	194,00	737468Q5

ALWAYS USE

pole

	EUR	CODE
200	34,00	910062_0
400	38,00	910064_0
600	41,00	910066_0

	CODE
	A
	Q

order spike separately

ALWAYS USE

pole

	EUR	CODE
200	34,00	910062_0
400	38,00	910064_0
600	41,00	910066_0

	CODE
	A
	Q

order spike separately

OPTIONAL

ground spike

	EUR	CODE
	27,00	90013106

OPTIONAL

ground spike

	EUR	CODE
	27,00	90013106

OPTIONAL

ground spike

	EUR	CODE
	27,00	90013106

OPTIONAL

ground spike

	EUR	CODE
	27,00	90013106



PRIVATE RESIDENCE GREECE

X-BEAM

Outdoor
Floor surface











OPTIONAL

ground spike

	EUR	CODE
	29,00	90013115

snoot

	EUR	CODE
	35,00	90019023

snoot round

	EUR	CODE
	35,00	90019031



1.0

LED COB 24W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 0-110° W-108° L80|60K

3000K | CRI >80 | 1590lm

	EUR	CODE
	345,00	700374D4
	345,00	700374A4
	345,00	700374B4

1.0 ROUND

LED PCB 24W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 0-110° W-108° L80|60K

3000K | CRI >80 | 1520lm

	EUR	CODE
	345,00	700474A4
	345,00	700474Q4
	345,00	700474B4

829

back

RIBELLE

Outdoor
Floor surface





1.0

LED PCB 7W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP65 L80|100K

	EUR	CODE
	380,00	772284A_
	380,00	772284Q_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	590	>90	3
3000K	610	>90	5



2.0

LED PCB 7W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | ribbed glass

IP65 L80|100K

	EUR	CODE
	445,00	772384A_
	445,00	772384Q_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	590	>90	3
3000K	610	>90	5

709
825
back

GATE ROUND

Outdoor
Floor surface





1.0

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | glass

IP65 L80|50K

	EUR	CODE
	155,00	7581A4A_
	155,00	7581A4Q_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	400	>80	2
3000K	420	>80	4

ALWAYS USE

pole with fixation plate

	EUR	CODE
250	58,00	910121_0
450	69,00	910122_0
650	88,00	910123_0

	CODE
	A
	Q



2.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | glass

IP65 L80|50K

	EUR	CODE
	185,00	7582A4A_
	185,00	7582A4Q_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x290	>80	2
3000K	2x305	>80	4

ALWAYS USE

pole with fixation plate

	EUR	CODE
250	58,00	910124_0
450	69,00	910125_0
650	88,00	910126_0

	CODE
	A
	Q

back

GATE CARRÉ

Outdoor
Floor surface





1.0

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | glass

IP65 L80|50K

	EUR	CODE
	158,00	7583A4A_
	158,00	7583A4Q_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	400	>80	2
3000K	420	>80	4

ALWAYS USE

pole with fixation plate

	EUR	CODE
250	66,00	910111_0
450	77,00	910112_0
650	96,00	910113_0

	CODE
	A
	Q



2.0

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | glass

IP65 L80|50K

	EUR	CODE
	188,00	7584A4A_
	188,00	7584A4Q_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x290	>80	2
3000K	2x305	>80	4

ALWAYS USE

pole with fixation plate

	EUR	CODE
250	66,00	910114_0
450	77,00	910115_0
650	96,00	910116_0

	CODE
	A
	Q

back



PRIVATE RESIDENCE BELGIUM

PALOS ROUND

Outdoor
Floor surface



1.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K

	EUR	CODE
	218,00	4166A4A_
	218,00	4166A4Q_
	218,00	4166A4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	680	>80	2
3000K	700	>80	4

ALWAYS USE

pole with fixation plate

	EUR	CODE
170	98,00	910013_0
270	108,00	910014_0
470	123,00	910016_0
670	136,00	910018_0
870	155,00	910010_0

	CODE
	A
	Q
	B





1.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K

	EUR	CODE
	218,00	4166A4A_
	218,00	4166A4Q_
	218,00	4166A4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	680	>80	2
3000K	700	>80	4

ALWAYS USE

pole with concrete fixation

	EUR	CODE
170	124,00	910073_0
270	136,00	910074_0
470	148,00	910076_0
670	162,00	910078_0
870	188,00	910070_0

	CODE
	A
	Q
	B

back

PALOS ROUND

Outdoor
Floor surface



2.0

LED PCB 21W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K

	EUR	CODE
	298,00	4167A4A_
	298,00	4167A4Q_
	298,00	4167A4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x655	>80	2
3000K	2x675	>80	4

ALWAYS USE

pole with fixation plate

	EUR	CODE
170	98,00	910013_0
270	108,00	910014_0
470	123,00	910016_0
670	136,00	910018_0
870	155,00	910010_0

	CODE
	A
	Q
	B





2.0

LED PCB 21W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K

	EUR	CODE
	298,00	4167A4A_
	298,00	4167A4Q_
	298,00	4167A4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x655	>80	2
3000K	2x675	>80	4

ALWAYS USE

pole with concrete fixation

	EUR	CODE
170	124,00	910073_0
270	136,00	910074_0
470	148,00	910076_0
670	162,00	910078_0
870	188,00	910070_0

	CODE
	A
	Q
	B

back



PRIVATE RESIDENCE | OPEN ARCHITECTES BELGIUM

PALOS CARRÉ

Outdoor
Floor surface





1.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K

	EUR	CODE
	218,00	4164A4A_
	218,00	4164A4Q_
	218,00	4164A4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	680	>80	2
3000K	700	>80	4

ALWAYS USE

pole with fixation plate

	EUR	CODE
170	98,00	910013_0
270	108,00	910014_0
470	123,00	910016_0
670	136,00	910018_0
870	155,00	910010_0

	CODE
	A
	Q
	B



1.0

LED PCB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K g

	EUR	CODE
	218,00	4164A4A_
	218,00	4164A4Q_
	218,00	4164A4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	680	>80	2
3000K	700	>80	4

ALWAYS USE

pole with concrete fixation

	EUR	CODE
170	124,00	910073_0
270	136,00	910074_0
470	148,00	910076_0
670	162,00	910078_0
870	188,00	910070_0

	CODE
	A
	Q
	B

819

back



PALOS CARRÉ

Outdoor
Floor surface





2.0

LED PCB 21W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K

	EUR	CODE
	298,00	4165A4A_
	298,00	4165A4Q_
	298,00	4165A4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x655	>80	2
3000K	2x675	>80	4

ALWAYS USE

pole with fixation plate

	EUR	CODE
170	98,00	910013_0
270	108,00	910014_0
470	123,00	910016_0
670	136,00	910018_0
870	155,00	910010_0

	CODE
	A
	Q
	B



2.0

LED PCB 21W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium

IP65 L80|60K

	EUR	CODE
	298,00	4165A4A_
	298,00	4165A4Q_
	298,00	4165A4B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x655	>80	2
3000K	2x675	>80	4

ALWAYS USE

pole with concrete fixation

	EUR	CODE
170	124,00	910073_0
270	136,00	910074_0
470	148,00	910076_0
670	162,00	910078_0
870	188,00	910070_0

	CODE
	A
	Q
	B

819

back



PRIVATE RESIDENCE BELGIUM

LINUS

Outdoor
Floor surface



3.0

LED COB 7W | phase-cut dim
220-240VAC | 50-60Hz
aluminium

IP65 L70|50K

3000K | CRI >90 | 215lm

	EUR	CODE
	169,00	726378D5
	169,00	726378A5
	169,00	726378Q5



OPTIONAL

ground spike

	EUR	CODE
	62,00	90013103

ground fixation

	EUR	CODE
	62,00	90013302

ALWAYS USE

pole

	EUR	CODE
150	83,00	910024_0
350	109,00	910026_0
550	139,00	910028_0

	CODE
	D
	A
	Q

back

driver

ONE DRIVER IS ALL YOU NEED

Ze accentueren gevels, verlichten de tuin en maken paden in het donker zichtbaar – moderne buitenarmaturen zijn echte alleskunners. Met het 24V Plug & Play Connector System gaat de installatie eenvoudig: een stopcontact, een geschikte driver en meerdere armaturen zijn zo aangesloten.

Elles mettent les façades en valeur, éclairent le jardin et rendent les allées visibles la nuit – les luminaires extérieurs modernes sont de véritables polyvalents. Avec le système 24V Plug & Play, l'installation est simple : une prise, un driver adapté et plusieurs luminaires se connectent facilement.

weverducre.com/24V-plugplay

1 CHOOSE YOUR LUMINAIRES



GEO
page 885

REED
page 887

POLA
page 889

Two, three, four, or even more, the choice is yours! The number of lights and the sum of their individual wattages is the first thing you need to know to get started with your Plug & Play Connector System.

GOOD TO KNOW
24V Plug & Play Connector System recommends adding 2 or more luminaires to the driver.

2 DEFINE THE DISTANCE BETWEEN DRIVER AND LUMINAIRE

Adjacent or far away. The distance between the driver and the first light is very important as it determines the further options of your 24V Plug & Play Connector System lighting solution. You can find detailed information about your options at weverducre.com/24V-cable-length

GOOD TO KNOW
Each driver is supplied with two 2.5m cables, one for each side.

3 CHOOSE YOUR DRIVER AND SET UP YOUR LUMINAIRES

Accessory options on page 927





back



GEO

Outdoor
Floor surface



Plug & Play
24V



ALWAYS USE

Plug & Play straight connector IP67
2x 24V female connector

	EUR	CODE
	9,50	90014504

Plug & Play t-connector IP67
3x 24V female connector

	EUR	CODE
	15,50	90014501

OPTIONAL

Plug & Play extension cable IP67
2x 24V male plug

	EUR	CODE
0.5m	16,00	90014505
1m	26,00	90014506
2.5m	38,00	90014502
5m	58,00	90014503



1.0

LED PCB 4W | 24V | ground spike
aluminium | glass
Plug & Play connector system
incl. 2.5m cable | male plug

IP65 H07R-F 0°-135° M-30° L80|50K

2700K | CRI >90 | 245lm

	EUR	CODE
	129,00	767562A3
	129,00	767562Q3

ALWAYS USE

Plug & Play driver | 220-240VAC | 24V
IP67 | incl. 2.5m cable with 240V plug
incl. 2.5 cable with 24V male plug

	EUR	CODE
30W	99,00	90018014
75W	119,00	90018015



2.0

LED PCB 8W | 24V | ground spike
aluminium | glass
Plug & Play connector system
incl. 2.5m cable | male plug

IP65 H07R-F 0°-135° M-33° L80|50K

2700K | CRI >90 | 440lm

	EUR	CODE
	230,00	767662A3
	230,00	767662Q3

ALWAYS USE

Plug & Play driver | 220-240VAC | 24V
IP67 | incl. 2.5m cable with 240V plug
incl. 2.5 cable with 24V male plug

	EUR	CODE
30W	99,00	90018014
75W	119,00	90018015



PRIVATE RESIDENCE AUSTRIA

REED

Outdoor
Floor surface



Plug & Play
24V

ALWAYS USE

Plug & Play straight connector IP67
2x 24V female connector

	EUR	CODE
	9,50	90014504

Plug & Play t-connector IP67
3x 24V female connector

	EUR	CODE
	15,50	90014501

OPTIONAL

Plug & Play extension cable IP67
2x 24V male plug

	EUR	CODE
0.5m	16,00	90014505
1m	26,00	90014506
2.5m	38,00	90014502
5m	58,00	90014503



1.0

LED PCB 5W | 24V | ground spike
aluminium | opal PC cover
Plug & Play connector system
incl. 2.5m cable | male plug

IP65 H07R-F L80|50K

2700K | CRI >90 | 330lm

	EUR	CODE
	142,00	770182A3
	142,00	770182Q3

ALWAYS USE

Plug & Play driver | 220-240VAC | 24V
IP67 | incl. 2.5m cable with 240V plug
incl. 2.5 cable with 24V male plug

	EUR	CODE
30W	99,00	90018014
75W	119,00	90018015



2.0

LED PCB 6W | 24V | ground spike
aluminium | opal PC cover
Plug & Play connector system
incl. 2.5m cable | male plug

IP65 H07R-F L80|50K

2700K | CRI >90 | 395lm

	EUR	CODE
	172,00	770282A3
	172,00	770282Q3

ALWAYS USE

Plug & Play driver | 220-240VAC | 24V
IP67 | incl. 2.5m cable with 240V plug
incl. 2.5 cable with 24V male plug

	EUR	CODE
30W	99,00	90018014
75W	119,00	90018015

back



PRIVATE RESIDENCE AUSTRIA

POLA

Outdoor
Floor surface



Plug & Play
24V

ALWAYS USE

Plug & Play straight connector IP67
2x 24V female connector

EUR	CODE
9,50	90014504

Plug & Play t-connector IP67
3x 24V female connector

EUR	CODE
15,50	90014501

OPTIONAL

Plug & Play extension cable IP67
2x 24V male plug

	EUR	CODE
0.5m	16,00	90014505
1m	26,00	90014506
2.5m	38,00	90014502
5m	58,00	90014503



2.0

LED PCB 5W | 24V | ground spike
aluminium | glass
Plug & Play connector system
incl. 2.5m cable | male plug

IP65 H07R-F L80|100K

2700K | CRI >90 | 250lm

	EUR	CODE
	198,00	7381A2A3
	198,00	7381A2Q3

ALWAYS USE

Plug & Play driver | 220-240VAC | 24V
IP67 | incl. 2.5m cable with 240V plug
incl. 2.5 cable with 24V male plug

	EUR	CODE
30W	99,00	90018014
75W	119,00	90018015



2.1

LED PCB 5W | 24V | fixation plate
aluminium | glass
Plug & Play connector system
incl. 2.5m cable | male plug

IP65 H07R-F L80|100K

2700K | CRI >90 | 250lm

	EUR	CODE
	196,00	7382A2A3
	196,00	7382A2Q3

ALWAYS USE

Plug & Play driver | 220-240VAC | 24V
IP67 | incl. 2.5m cable with 240V plug
incl. 2.5 cable with 24V male plug

	EUR	CODE
30W	99,00	90018014
75W	119,00	90018015

back





acces

sories

DRIVER | CONTROL GEAR

Accessories



easy and fast installation with
quick connectors pre assembled
on our drivers and modules

DRIVER 180mA 7.5W DIM

7.5W | 180mA | 27-42V | phase-cut dim
220-240VAC | precabled 150mm wire
and quick connector to luminaire
50-60Hz
L/W/H 68x33x22
IP20 CE



EUR	CODE
33,00	90226202

DRIVER 180mA 7.2W DALI

7.2W | 180mA | 10-40V | DALI-2 | push
dim | 220-240VAC | precabled 150mm
wire and quick connector to luminaire
50-60Hz
L/W/H 166x29x21
IP20 CE



EUR	CODE
64,50	90246301

DRIVER 200mA 10W DIM

10W | 200mA | 30-42V | phase-cut dim
220-240VAC
50-60Hz | 10-100%
L/W/H 85x22x41
IP20 CE



EUR	CODE
33,00	90226402

DRIVER 200mA 8W DALI

8W | 200mA | 10-40V | DALI-2 | push
dim | 220-240VAC | precabled 150mm
wire and quick connector to luminaire
50-60Hz | 1-100%
L/W/H 166x29x21

IP20 CE



EUR	CODE
64,50	90246302

DRIVER 250mA 5W DIM

5W | 250mA |10-20V | phase-cut dim
220-240VAC | precabled with quick
connector to luminaire | wire through
50-60Hz
L/W/H 96x45x26
IP20 CE



EUR	CODE
33,00	90226403W

DRIVER 250mA 5W DIM

5W | 250mA |12-21V | phase-cut dim
220-240VAC | precabled with quick
connector to luminaire | 50-60Hz
L/W/H 68x33x22
IP20 CE



EUR	CODE
33,00	90226201

DRIVER 250mA 5W DIM

5W | 250mA | 12-21V | phase-cut dim
220-240VAC | precabled with quick
connector to luminaire | 3 pole wire
through box | 50-60Hz
L/W/H 68x33x22
IP20 CE



	EUR	CODE
1 pc.	41,00	90226201W
20 pcs.	656,00	90226201WM

DRIVER 250mA 10.5W DIM

10.5W | preset at 250mA | 26-42V
phase-cut dim | 220-240VAC
50-60Hz | 10-100%
L/W/H 122x41x23
IP20 CE



EUR	CODE
33,00	90226501

DRIVER 250mA 10W DALI

10W | 250mA | 10-40V | DALI-2
push dim | 220-240VAC | precabled
with 150mm wire and quick
connector to luminaire | 50-60Hz
L/W/H 166x29x21
IP20 CE



EUR	CODE
64,50	90246403

DRIVER 250mA 10W DALI

10W | 250mA | 10-40V | DALI-2
push dim | 220-240VAC | precabled
with 150mm wire and quick
connector to luminaire | wire through
50-60Hz
L/W/H 185x30x21
IP20 CE



	EUR	CODE
1 pc.	72,50	90246403W
20 pcs.	1160,00	90246403WM

back

DRIVER 350mA 3.5W
3.5W | 350mA | 2.7-10V
220-240VAC | 50-60Hz
L/W/H 65x29x18
IP20



	EUR	CODE
	34,00	90213102

DRIVER 350mA 6W
6W | 350mA | 8.6-18V
100-240VAC | precabled with quick connector to luminaire | 50-60Hz
L/W/H 66x39x22
IP20



	EUR	CODE
	25,50	90213303

DRIVER 350mA 6W
6W | 350mA | 8.6-18V
100-240VAC | precabled with quick connector to luminaire | 3 pole wire through box | 50-60Hz
L/W/H 66x39x22
IP20



	EUR	CODE
1 pc.	33,50	90213303W
20 pcs.	536,00	90213303WM

DRIVER 350mA 7.7W
7.7W | 350mA | 3-22V
200-240VAC | 50-60Hz
L/W/H 68x35x21
IP20



	EUR	CODE
	35,00	90213202

DRIVER 350mA 7W DIM
7W | 350mA | 10-20V | phase-cut dim
220-240VAC | precabled with quick connector to luminaire | wire through
50-60Hz
L/W/H 96x45x26
IP20



	EUR	CODE
	35,50	90223407W

DRIVER 350mA 7W DIM
7W | 350mA | 12-21V | phase-cut dim
220-240VAC | precabled with quick connector to luminaire | 50-60Hz
L/W/H 68x33x22
IP20



	EUR	CODE
	33,50	90223301

DRIVER 350mA 7W DIM
7W | 350mA | 12-21V | phase-cut dim
220-240VAC | precabled with quick connector to luminaire | 3 pole wire through box | 50-60Hz
L/W/H 68x33x22
IP20



	EUR	CODE
1 pc.	41,50	90223301W
20 pcs.	664,00	90223301WM

DRIVER 350mA 10W DIM
10W | 350mA | 13-26V | phase-cut dim
220-240VAC | precabled with quick connector to luminaire | 50-60Hz
L/W/H 115x41x25
IP20



	EUR	CODE
	35,50	90223406

DRIVER 350mA 10W DIM
10W | 350mA | 13-26V | phase-cut dim
220-240VAC | precabled 150mm wire and quick connector to luminaire
3 pole wire through box | 50-60Hz
L/W/H 115x41x25
IP20



	EUR	CODE
1 pc.	43,50	90223406W
20 pcs.	696,00	90223406WM

DRIVER 350mA 10W DIM
10W | 350mA | 14-28V | 1-10V
phase-cut dim | 220-240VAC | 50-60Hz
10-100%
L/W/H 102x51x30
IP20



	EUR	CODE
	30,50	90223401

DRIVER 350mA 13W DIM
13W | 350mA | 26-38V | phase-cut dim
220-240VAC | 50-60Hz | 10-100%
L/W/H 138x44x30
IP20



	EUR	CODE
	42,50	90223404

DRIVER 350mA 14.7W DIM
14.7W | 350mA | 26-42V | phase-cut dim
220-240VAC | 50-60Hz
10-100%
L/W/H 125x41x23
IP20



	EUR	CODE
	37,50	90223504

DRIVER 350mA 14W DALI
14W | preset at 350mA | 10-40V
DALI-2 | push dim | 220-240VAC
precabled 150mm wire and quick connector to luminaire | 50-60Hz
1-100%
L/W/H 166x29x21
IP20 68 85 | 78 73 | 88 65



	EUR	CODE
	64,50	90243502

DRIVER 350mA 14W DALI
14W | preset at 350mA | 10-40V
DALI-2 | push dim | 220-240VAC
precabled 150mm wire and quick connector to luminaire | wire through
50-60Hz | 1-100%
L/W/H 185x30x21
IP20



	EUR	CODE
1 pc.	72,50	90243502W
20 pcs.	1160,00	90243502WM

DRIVER 350mA 4.2W IP66
4.2W | 350mA | 3-12V
90-264VAC | 50-60Hz
L/W/H 38x29x23
IP66



	EUR	CODE
	35,00	90213101

DRIVER 350mA 17W IP68
17W | 350mA | 5-49V
220-240VAC | 50-60Hz
L/W/H 122x54x26
IP68



	EUR	CODE
	69,00	90213602

DRIVER 350mA 4.5W DIM IP44
4.5W | 350mA | 8-13V | phase-cut dim
220-240VAC | 50-60Hz | 5-100%
L/W/H 38x30x20
IP44



	EUR	CODE
	33,00	90223101

DRIVER 350/500/700mA 17.5-20W
350/500/700mA output selection
17.5W | 350mA | 25-50V
20W | 500mA | 20-40V
20W | 700mA | 14-28.5V
220-240VAC | 50-60Hz
L/W/H 102x51x30
IP20



	EUR	CODE
	39,00	90218601

DRIVER 350/500/700mA 17-32W DIM
350/500/700mA | dipswitch selection
17W | 350mA | 2-47V
24W | 500mA | 2-47V
32W | 700mA | 2-46V
phase-cut dim | not for ambient dim
220-240VAC | 50-60Hz | push dim
L/W/H 166x46x34
IP20



	EUR	CODE
	62,00	90228801

DRIVER 500mA 6W
6W | 500mA | 3-12V
90-264VAC | 50-60Hz
L/W/H 68x35x21
IP20



	EUR	CODE
	33,00	90214201

DRIVER 500mA 10W
10W | 500mA | 13-20V
220-240VAC | precabled with quick connector to luminaire | 50-60Hz
L/W/H 60x39x20
IP20



	EUR	CODE
	25,50	90214406

DRIVER 500mA 10W
10W | 500mA | 13-20V
220-240VAC | precabled with quick connector to luminaire | 3 pole wire through box | 50-60Hz
L/W/H 60x39x20
IP20



	EUR	CODE
1 pc.	33,50	90214406W
20 pcs.	536,00	90214406WM

DRIVER 500mA 6.5W DIM
6.5W | preset at 500mA
7-13V | phase-cut dim
220-240VAC | 50-60Hz | 10-100%
L/W/H 122x41x23
IP20



	EUR	CODE
	25,50	90224301

DRIVER 500mA 10W DIM
10W | 500mA | 10-20V | phase-cut dim
220-240VAC | precabled with quick connector to luminaire | wire through
50-60Hz
L/W/H 96x45x26
IP20



	EUR	CODE
	37,50	90224404W

DRIVER 500mA 10W DIM
10W | 500mA | 12-21V | phase-cut dim
220-240VAC | precabled with quick connector to luminaire | 50-60Hz
L/W/H 115x41x25
IP20



	EUR	CODE
	37,50	90224403

DRIVER 500mA 10W DIM
10W | 500mA | 12-21V | phase-cut dim
220-240VAC | precabled with quick connector to luminaire | 3 pole wire through box | 50-60Hz
L/W/H 115x41x25
IP20



	EUR	CODE
1 pc.	45,50	90224403W
20 pcs.	728,00	90224403WM

DRIVER 500mA 19W DIM
19W | preset at 500mA
26-38V | phase-cut dim
220-240VAC | 50-60Hz | 10-100%
L/W/H 138x44x30
IP20



	EUR	CODE
	45,50	90224602

DRIVER 500mA 10W 1-10V DIM
10W | 500mA | 10-20V | 1-10V dim
220-240VAC | 50-60Hz | 10-100%
L/W/H 102x51x30
IP20



	EUR	CODE
	35,50	90234401

DRIVER 500mA 15W DALI
15W | 500mA |10-31V | DALI-2
push dim | 220-240VAC | precabled with 150mm wire and quick connector to luminaire | wire through
50-60Hz 10-100%
L/W/H 166x29x21
IP20



	EUR	CODE
	64,50	90244501

DRIVER 500mA 15W DALI
15W | 500mA |10-31V | DALI-2
push dim | 220-240VAC | precabled with 150mm wire and quick connector to luminaire | wire through
50-60Hz 10-100%
L/W/H 185x30x21
IP20



	EUR	CODE
1 pc.	72,50	90244501W
20 pcs.	1160,00	90244501WM

DRIVER 500mA 24W DALI
24W | preset at 500mA | 6-49V
DALI-2 | push dim | 220-240VAC
precabled with quick connector to luminaire | 50-60Hz | 1-100%
L/W/H 143x43x30
IP20



	EUR	CODE
	67,00	90244701

DRIVER 500mA 7W IP67
7W | 500mA | 5-14.5V
100-240VAC | 47-63Hz
L/W/H 57x41x24
IP67



	EUR	CODE
	46,50	90214301

DRIVER 500mA 24W IP68
24W | 500mA | 5-49V
220-240VAC | 50-60Hz
L/W/H 122x54x26
IP68



	EUR	CODE
	74,00	90214702

DRIVER 700mA 6W
6W | 700mA | 3-8.4V
230-240VAC | 50-60Hz
L/W/H 68x35x21
IP20



EUR	CODE
34,50	90215203

DRIVER 700mA 10W DIM
10W | preset at 700mA
8-14V | phase-cut dim
220-240VAC | 50-60Hz | 10-100%
L/W/H 122x41x23
IP20



EUR	CODE
37,50	90225402

DRIVER 700mA 14W DIM
14W | preset at 700mA
12-20V | phase-cut dim
220-240VAC | 50-60Hz | 10-100%
L/W/H 122x41x23
IP20



EUR	CODE
39,00	90225502

DRIVER 700mA 20W DIM
20W | preset at 700mA
15-28V | phase-cut dim
220-240VAC | 50-60Hz | 10-100%
L/W/H 138x44x30
IP20



EUR	CODE
45,50	90225604

DRIVER 700mA 25W DIM
25W | 700mA | 17-35V | phase-cut dim
220-240VAC | 50-60Hz | 5-100%
L/W/H 145x51x30
IP20



EUR	CODE
47,50	90225701

DRIVER 700mA 30W DIM
30W | preset at 700mA
26-42V | phase-cut dim
220-240VAC | 50-60Hz | 10-100%
L/W/H 138x44x30
IP20



EUR	CODE
47,50	90225702

DRIVER 700mA 28W DALI
28W | preset at 700mA | 6-40V
DALI-2 | push dim | 220-240VAC
precabled with quick connector to luminaire | 50-60Hz | 1-100%
L/W/H 97x43x30
IP20



EUR	CODE
67,00	90245704

DRIVER 700mA 7W IP67
7W | 700mA | 3-10.5V
90-295VAC | 47-63Hz
L/W/H 57x41x24
IP67 0.07kg



EUR	CODE
36,50	90215301

DRIVER 24V/15W
15W | 24V
220-240VAC | 50-60Hz
L/W/H 107x33x22
IP20



EUR	CODE
39,00	90212501

DRIVER 24V/25W
2.4-25W | 24V | phase-cut dim | trailing edge only | 220-240VAC | 50-60Hz
L/W/H 128x52x30
IP20



EUR	CODE
46,00	90222701

DRIVER 24V/35W
35W | 24V | PWM dim
220-240VAC | 50-60Hz
L/W/H 142x43x30
IP20



EUR	CODE
42,00	90212801

DRIVER 24V/50W
12-50W | 24V | phase-cut dim | trailing edge only | 220-240VAC | 50-60Hz
L/W/H 166x52x32
IP20



EUR	CODE
68,00	90222901

DRIVER 24V/100W
100W | 24V | PWM dim
220-240VAC | 50-60Hz
L/W/H 295x43x30
IP20



EUR	CODE
73,80	90212902

DRIVER 24V/100W DALI
100W | 24V | DALI
220-240VAC | 50-60Hz
L/W/H 295x43x30
IP20



EUR	CODE
155,00	90242901

DRIVER 24V/35W IP67
35W | 24V
100-277VAC | 50-60Hz
L/W/H 199x42x43
IP67



EUR	CODE
49,00	90212802

DRIVER 24V/100W IP67
100W | 24V
100-277VAC | 50-60Hz
L/W/H 178x68x39
IP67



EUR	CODE
144,60	90212903

back

DRIVER-CONFIGURATOR
weverducre.com/driver-configurator

DRIVER | CONTROL GEAR

Accessories

WIRE THROUGH CONNECTOR BOX

3 pole
L/W/H 105x58x30
IP20 min.66



EUR	CODE
15,00	90059145

WIRE THROUGH CONNECTOR BOX

3 pole + DALI
L/W/H 105x58x30
IP20 min.66



EUR	CODE
17,50	90059146

WIRE THROUGH CONNECTOR BOX

3 pole IP68 | quick IP connection box with Gel included
L/W/H 90x43x20
IP68 min.48

EUR	CODE
36,00	90059149

PAR16 FLAT HEAD

PAR16 | GU10
220-240VAC | 50-60Hz
IP20



EUR	CODE
8,00	90059125

CONNECTION BOX 3P PAR16

incl. strain relief | 3 pole push connector | incl. PAR16 socket
incl. through-wiring
L/W/H 75x35x25



EUR	CODE
12,00	90059126

DALI TO PHASE-CUT DIMMING MODULE

for converting a DALI signal to phase-cut dim | for max. 20 devices
LED | 10-300W | 230V
L/W/H 120x30x22
IP20

EUR	CODE
224,00	90270901

DIMMER DIN RAIL

max. 200W LED | 230V
phase-cut dim
L/W/H 17x55x90
IP30



EUR	CODE
158,00	90019018

DIMMER FOR SWITCH

max. 200W LED | 230V
phase-cut dim
L/W/H 48x18x46
IP30



EUR	CODE
124,00	90019017

back

LED MODULE HO

12W | 350mA | 35Vf
1800-3000K | CRI >90 | 1050lm
compatibility on request
IP20 CE M-26°



	EUR	CODE
	76,00	905251W9
	76,00	905251B9

LED MODULE HO 2700K

12W | 350mA | 35Vf
2700K | CRI >90 | 1340lm
compatibility on request
IP20 CE M-26°



	EUR	CODE
	76,00	905251W3
	76,00	905251B3

LED MODULE HO 3000K

12W | 350mA | 35Vf
3000K | CRI >90 | 1410lm
compatibility on request
IP20 CE M-26°



	EUR	CODE
	76,00	905251W5
	76,00	905251B5

LED MODULE HO 4000K

12W | 350mA | 35Vf
4000K | CRI >90 | 1420lm
compatibility on request
IP20 CE M-26°



	EUR	CODE
	76,00	905251W7
	76,00	905251B7

LED MODULE CABLE

extension cable between LED module and driver



	EUR	CODE
1m	5,50	90019200
2m	6,50	90019201
3m	7,50	90019202

PAR11 LED 2700K

4.3W | GU10 | phase-cut dim | with lens
220-240VAC | 50-60Hz | aluminium
2700K | CRI >90 | 240lm
IP20 CE W-50°



	EUR	CODE
	14,50	901128W3
	14,50	901128B3

PAR11 LED 3000K

4.3W | GU10 | phase-cut dim | with lens
220-240VAC | 50-60Hz | aluminium
3000K | CRI >90 | 255lm
IP20 CE W-50°



	EUR	CODE
	14,50	901128W5
	14,50	901128B5

PAR16 LED 2700K

6.1W | GU10 | phase-cut dim | with lens
220-240VAC | 50-60Hz | aluminium
2700K | CRI >90 | 445lm
IP20 CE M-35°



	EUR	CODE
	16,50	901228W3
	16,50	901228B3

PAR16 LED 3000K

6.1W | GU10 | phase-cut dim | with lens
220-240VAC | 50-60Hz | aluminium
3000K | CRI >90 | 465lm
IP20 CE M-35°



	EUR	CODE
	16,50	901228W5
	16,50	901228B5

PAR16 LED HE 2700K

5W | GU10 | 106 lm/W | phase-cut dim
220-240VAC | 50-60Hz
2700K | CRI >90 | 530lm
IP20 CE M-35°



	EUR	CODE
	19,50	907228W3
	19,50	907228B3

PAR16 LED HE 3000K

5W | GU10 | 107 lm/W | phase-cut dim
220-240VAC | 50-60Hz
2700K | CRI >90 | 535lm
IP20 CE M-35°



	EUR	CODE
	19,50	907228W5
	19,50	907228B5

PAR16 LED 2700K

3.7W | GU10
220-240VAC | 50-60Hz
2700K | CRI >80 | 350lm
IP20 CE M-36°



	EUR	CODE
	13,00	905227S2

PAR16 LED 3000K

3.7W | GU10
220-240VAC | 50-60Hz
3000K | CRI >80 | 350lm
IP20 CE M-36°



	EUR	CODE
	13,00	905227S4

METAL SPRING CLIP

alternative front lamp fixation spring
for ø 50 lamp rings
LED | PAR16 | max. 12W
DEEP ADJUST | **DEEP** 2.0
PLANO | **STRANGE** ceiling
SOLID



	EUR	CODE
	2,00	90019700

SPRING CLIP

lamp fixation | push-in system
for ø 50 lamp rings
LED | PAR16 | max. 12W
DEEP ADJUST | **DEEP** 2.0
PLANO | **STRANGE** ceiling
SOLID

	EUR	CODE
	2,00	900198W0
	2,00	900198S0
	2,00	900198G0
	2,00	900198M0
	2,00	900198Q0
	2,00	900198B0

back

QT14 LED 3000K
3W | G9
220-240VAC | 50-60Hz
3000K | CRI >80 | 300lm
IP20 CE



	EUR	CODE
clear	14,50	9019G703

QT14 LED 2700K
3.5W | G9
220-240VAC | 50-60Hz
2700K | CRI >90 | 340lm
IP20 CE



	EUR	CODE
opal	18,00	9010G803

QT14 LED 3000K
3.5W | G9 | phase-cut dim
220-240VAC | 50-60Hz
3000K | CRI >90 | 350lm
IP20 CE



	EUR	CODE
opal	18,00	9010G805

C35 LED 2700K
5.5W | E14 | phase-cut dim | 20-100%
220-240VAC | 50-60Hz
2700K | CRI >90 | 450lm
IP20 CE



	EUR	CODE
opal	10,50	9003C103

ST64 LED 2200K DIM
5.9W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2200K | CRI >95 | 435lm
IP20 CE



	EUR	CODE
gold tinted	35,00	9003E110

T25-85 LED 2200K
5W | E14 | phase-cut dim
220-240VAC | 50-60Hz
2200K | CRI >90 | 460lm
IP20 CE



	EUR	CODE
gold tinted	29,00	9003C108

T25-85 LED 2500K
5W | E14 | phase-cut dim
220-240VAC | 50-60Hz
2500K | CRI >90 | 480lm
IP20 0.02kg CE



	EUR	CODE
gold tinted	29,00	9003C107

T25-85 LED 2700K
5W | E14 | phase-cut dim
220-240VAC | 50-60Hz
2700K | CRI >90 | 500lm
IP20 CE



	EUR	CODE
gold tinted	29,00	9003C106

T30-225 LED 2200K
5.3W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2200K | CRI >90 | 380lm
IP20 CE



	EUR	CODE
gold tinted	39,00	9003E129

T30-225 LED 2700K
5.3W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2700K | CRI >90 | 425lm
IP20 CE



	EUR	CODE
gold tinted	39,00	9003E136

T30-300 LED 2200K
7.2W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2200K | CRI >90 | 585lm
IP20 CE



	EUR	CODE
gold tinted	43,00	9003E130

T30-300 LED 2700K
7.4W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2700K | CRI >90 | 610lm
IP20 CE



	EUR	CODE
gold tinted	43,00	9003E135

back

A60 LED 2700K DIM
5.6W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2700K | CRI >90 | 480lm
IP20 CE



	EUR	CODE
clear	31,00	9003E138

A60 LED 2700K
9W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2700K | CRI >90 | 800lm
IP20 CE



	EUR	CODE
opal	14,50	9003E152

A65 LED 2700K
14.6W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2700K | CRI >90 | 1375lm
IP20 CE



	EUR	CODE
opal	22,00	9003E153

A60 LED 2200K
3.8W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2200K | CRI >95 | 245lm
IP20 CE



	EUR	CODE
gold tinted	31,00	9003E109

A60 LED 2700K
5.5W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2700K | CRI >90 | 405lm
IP20 CE



	EUR	CODE
gold mirror	32,00	9003E139
silver mirror	32,00	9003E140

G95 LED 2700K
4.5W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2700K | CRI >90 | 375lm
IP20 CE



	EUR	CODE
clear	33,00	9003E160

G95 LED 2700K
11.2W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2700K | CRI >90 | 1100lm
IP20 CE



	EUR	CODE
opal	29,00	9003E154

G95 LED 2700K
10W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2700K | CRI >90 | 1060lm
ceramic soft look
IP20 CE



	EUR	CODE
opal	33,00	9003E163

G95 LED 2200K
5.4W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2200K | CRI >95 | 380lm
IP20 CE



	EUR	CODE
gold tinted	33,00	9003E111

G95 LED 2200K
5.1W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2200K | CRI >95 | 370lm
IP20 CE



	EUR	CODE
gold mirror	35,00	9003E156

G95 LED 2700K
5W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2700K | CRI >90 | 395/410lm
IP20 CE



	EUR	CODE
gold mirror	35,00	9003E142
silver mirror	35,00	9003E157

G125 LED 2200K
6.2W | E27 | phase-cut dim
220-240VAC | 50-60Hz
2200K | CRI >95 | 450lm
IP20 CE



	EUR	CODE
gold tinted	34,00	9003E112

back

REPLACEMENT PLUG
for Switzerland | Liechtenstein



	EUR	CODE
	22,00	90019211

REPLACEMENT PLUG
for UK | Ireland | Malta | Arabic peninsila



	EUR	CODE
	22,00	90019212

HONEYCOMB LOUVER
BLIEK PETIT | CENO | LECA PIRRO | QITO



	EUR	CODE
	14,50	915230B0

LIKO 1.0 HONEYCOMB LOUVER



	EUR	CODE
	14,50	915231B0

LIKO 2.0 HONEYCOMB LOUVER



	EUR	CODE
	16,00	915232B0

LIKO 3.0 HONEYCOMB LOUVER



	EUR	CODE
	17,50	915233B0

ODREY
inner cover for 1.6



	EUR	CODE
	29,00	911420W0
	29,00	911420G0
	29,00	911420B0

MATCH TRIMLESS DRILLING TOOL
for easy plaster finish



	EUR	CODE
	39,00	90019300

FINLIN COVER PLATE ADAPTER
for concrete housings



	EUR	CODE
	12,50	900194B0

FINLIN
wall/base spacer for overlapping luminaires



	EUR	CODE
	31,00	900195B0

FINLIN ROUND
wall/base spacer for overlapping luminaires



	EUR	CODE
	31,00	900196B0

BOX | RAY
flaps for adjustable beam angle white | for BOX/RAY QT14 only



	EUR	CODE
	39,00	900401W0

X-BEAM
snoot



	EUR	CODE
	35,00	90019023

X-BEAM
snoot round



	EUR	CODE
	35,00	90019031

back

DEEP ADJUST PETIT TRIMLESS | BLIEK PETIT TRIMLESS | QITO TRIMLESS
aluminium plasterkit
78-80 80 12.5, 15, 20, 25



EUR	CODE
22,00	90017210

DEEP ADJUST TRIMLESS
aluminium plasterkit
105-110 12.5, 15, 20, 25



EUR	CODE
26,00	90017209

STRANGE PETIT TRIMLESS 1.0
aluminium plasterkit
64x64 7-32



EUR	CODE
37,00	90017202

STRANGE PETIT TRIMLESS 2.0
aluminium plasterkit
64x117 7-32



EUR	CODE
39,00	90017205

STRANGE PETIT TRIMLESS 3.0
aluminium plasterkit
64x169 7-32



EUR	CODE
43,00	90017208

STRANGE TRIMLESS 1.0 SNEAK TRIMLESS 1.0
aluminium plasterkit
86x86 7-32



EUR	CODE
41,00	90017120

STRANGE TRIMLESS 2.0 SNEAK TRIMLESS 2.0
aluminium plasterkit
156x86 7-32



EUR	CODE
45,00	90017121

LITO
plasterkit



EUR	CODE
16,50	90017119

PLASTERKITS

Accessories

PLANO 1.0
plasterkit



EUR	CODE
19,00	90017104

PLANO 2.0
plasterkit



EUR	CODE
26,50	90017105

STRIPE 0.4 | 0.7
recessed housing incl. plasterkit
75x75 ⎍65



EUR	CODE
24,00	90012037

STRIPE 2.2
recessed housing incl. plasterkit
251x76 ⎍65



EUR	CODE
43,00	90012038

ORIS 0.7 | RETO 2.0
recessed housing incl. plasterkit
191x58 ⎍75



EUR	CODE
45,00	90012039

ORIS 0.8 | RETO 0.8
recessed housing incl. plasterkit
70x70 ⎍80



EUR	CODE
46,00	90012047

ORIS 1.3 | RETO 1.3
recessed housing incl. plasterkit
122x122 ⎍75



EUR	CODE
52,00	90012041

ORIS 2.0
recessed housing incl. plasterkit
123x191 ⎍75



EUR	CODE
58,00	90012043

RECESSED HOUSING

Accessories

LITO
always use in combination with plasterkit
122x90 ⎍45



EUR	CODE
26,50	90012027

ORIS 0.7 | RETO 2.0
concrete housing
192x58 ⎍60



EUR	CODE
38,00	90012044

ORIS 0.8 | RETO 0.8
concrete housing
70x70 ⎍65



EUR	CODE
32,00	90012046

ORIS 1.3 | RETO 1.3
concrete housing
122x122 ⎍60



EUR	CODE
39,00	90012040

ORIS 2.0
concrete housing
123x191 ⎍60



EUR	CODE
42,00	90012042

MAP 0.6 | CHART 0.6 BLINK | TRIMLESS
ground housing
137 ⎍110



EUR	CODE
25,00	90012201

MAP 0.9 | CHART 0.9
ground housing
137 ⎍130



EUR	CODE
34,00	90012202

MAP 1.2 | CHART 1.2 MAP ASYM 1.2 | CHART ASYM 1.2
ground housing
190 ⎍158



EUR	CODE
47,00	90012203

MAP 1.6 | CHART 1.6 MAP ASYM 1.6 | CHART ASYM 1.6
ground housing
220 ⎍184



EUR	CODE
61,00	90012204

back

FLYRA SINGLE/MULTI BASE

max. 25W | const. volt. | 24V
phase-cut dim | W/H ø62x102
polycarbonate



		EUR	CODE
		55,00	914224M0
		55,00	914224B0

FLYRA MULTI BASE

max. 50W | const. volt. | 24V
phase-cut dim | W/H ø200x38
polycarbonate



		EUR	CODE
		75,00	914225M0
		75,00	914225B0

FLYRA CABLE CONNECTOR

cable from one luminaire to another
incl. plugs



		EUR	CODE
	0.3m	14,50	915210B0
	0.6m	19,00	915211B0
	0.9m	23,00	915212B0
	1.2m	27,00	915213B0

FLYRA FIX CONNECTOR

electrical | mechanical | straight
central suspension



		EUR	CODE
		24,00	915221B0

ILANE BLACK DIFFUSER

only for 1.0



	EUR	CODE
2m	14,00	911902B1
3m	21,00	911903B1

ILANE BLACK DIFFUSER

only for 3.0



	EUR	CODE
2m	17,00	911912B1
3m	23,00	911913B1

ILANE MINI CONNECTOR

strip to strip - continuous



	EUR	CODE
IP20	2,60	90014272

ILANE MINI CONNECTOR

strip to wire



	EUR	CODE
IP20	1,80	90014268

ILANE MINI CONNECTOR

strip to strip



	EUR	CODE
IP20	3,30	90014269

STREX DRIVER 48V/100W

100W | 48V
220-240VAC | 50-60Hz
L/W/H 350x30x18
IP20



	EUR	CODE
	89,00	90218901

STREX DRIVER 48V/150W

150W | 48V
220-240VAC | 50-60Hz
L/W/H 350x30x18
IP20



	EUR	CODE
	108,00	90218902

STREX DRIVER 48V/250W

250W | 48V
220-240VAC | 50-60Hz
L/W/H 400x40x22
IP20



	EUR	CODE
	135,00	90218903

STREX DALI SELV DEVICE

for 48V system | max. 300W | 48VDC
L/W/H 212x37x26



	EUR	CODE
	158,00	90019193

RECESSED

track | custom cuts | 48V | 15A | DALI



		EUR	CODE
	< 1m	129,00	904111W0CC
	< 1m	129,00	904111B0CC
	< 2m	249,00	904112W0CC
	< 2m	249,00	904112B0CC
	< 3m	363,00	904113W0CC
	< 3m	363,00	904113B0CC

CC = for lengths specifications please add four digits in mm

SURFACE

track | custom cuts | 48V | 15A | DALI



		EUR	CODE
	< 1m	103,00	904211W0CC
	< 1m	103,00	904211B0CC
	< 2m	188,00	904212W0CC
	< 2m	222,00	904212L0CC
	< 2m	222,00	904212M0CC
	< 2m	222,00	904212Q0CC
	< 2m	188,00	904212B0CC
	< 3m	272,00	904213W0CC
	< 3m	323,00	904213L0CC
	< 3m	323,00	904213M0CC
	< 3m	323,00	904213Q0CC
	< 3m	272,00	904213B0CC

CC = for lengths specifications please add four digits in mm

SUSPENDED

track | custom cuts | 48V | 15A | DALI



		EUR	CODE
	< 1m	103,00	904211W0CC
	< 1m	103,00	904211B0CC
	< 2m	188,00	904212W0CC
	< 2m	222,00	904212L0CC
	< 2m	222,00	904212M0CC
	< 2m	222,00	904212Q0CC
	< 2m	188,00	904212B0CC
	< 3m	272,00	904213W0CC
	< 3m	323,00	904213L0CC
	< 3m	323,00	904213M0CC
	< 3m	323,00	904213Q0CC
	< 3m	272,00	904213B0CC

CC = for lengths specifications please add four digits in mm

SUSP. INDIRECT LIGHT

track | custom cuts | 48V | 15A | DALI
3000K | CRI >90 | 14W/m | 950lm/m
with indirect light



		EUR	CODE
	< 2m	595,00	904512W5CC
	< 2m	595,00	904512B5CC
	< 3m	695,00	904513W5CC
	< 3m	695,00	904513B5CC

CC = for lengths specifications please add four digits in mm

back

TRACK ADAPTER 1.0 HV

no space for driver | cable diameter max. 10mm | for suspended luminaires without steel wire
incl. strain relief
max. weight 10kg



	EUR	CODE
	15,00	90014044
■	15,00	90014043

TRACK ADAPTER 2.0 HV

no space for driver | cable diameter max. 5mm | for suspended luminaires without steel wire
incl. strain relief
max. weight 3kg



	EUR	CODE
	16,00	90014277
■	16,00	90014278

ADJUSTABLE CORNER



	EUR	CODE
	38,00	90014042
■	38,00	90014041

COVERPLATE I/L/T/X

only use with recessed tracks



	EUR	CODE
	8,00	90014126
■	8,00	90014127

COVERPLATE END FEEDS

only use with recessed tracks



	EUR	CODE
	9,50	90014124
■	9,50	90014125

X-FEED



	EUR	CODE
	49,00	90014049
■	49,00	90014050

T-FEED 1.0

top view



	EUR	CODE
	44,00	90014010
■	44,00	90014011

T-FEED 2.0

top view



	EUR	CODE
	44,00	90014012
■	44,00	90014013

T-FEED 3.0

top view



	EUR	CODE
	44,00	90014014
■	44,00	90014015

T-FEED 4.0

top view



	EUR	CODE
	44,00	90014016
■	44,00	90014017

CUTTING TOOL

for cutting the inner copper cables of 3-phase track and 48V track
CE TÜV



	EUR	CODE
	112,00	90014165

TRACK ADAPTER HV

no space for driver | cable diameter max. 6.6mm | for suspended luminaires without steel wire
incl. strain relief
max. weight 5kg



	EUR	CODE
	16,00	90014279
■	16,00	90014280

TRACK ADAPTER LV

DALI-2 | 350mA | incl. driver



	EUR	CODE
	90,00	914174W0
■	90,00	914174B0

OPLIA TRACK ADAPTER LV

DALI-2 | 250mA | incl. driver



	EUR	CODE
	90,00	914172W0
■	90,00	914172B0

POWER OUTLET

10A | 220-250V | 50-60Hz
Schuko adapter
PC UL94V0 + copper 50N
L/W/H 85x54x103
IP20 CE



	EUR	CODE
	38,00	90014254
■	38,00	90014253

HOOK

max. weight 5kg



	EUR	CODE
	9,00	90014284
■	9,00	90014285

FLEXIBLE CONNECTOR



	EUR	CODE
	74,00	90014288
■	74,00	90014289

X-FEED



	EUR	CODE
	95,00	90014248
■	95,00	90014249

T-FEED 1.0

top view



	EUR	CODE
	76,00	90014228
■	76,00	90014229

T-FEED 2.0

top view



	EUR	CODE
	76,00	90014230
■	76,00	90014231

T-FEED 3.0

top view



	EUR	CODE
	76,00	90014232
■	76,00	90014233

T-FEED 4.0

top view



	EUR	CODE
	76,00	90014234
■	76,00	90014235

back

SUSPENSION OPTIONS

Accessories

STRAIN RELIEF
for suspended luminaire power cable
fixation in base



	EUR	CODE
	2,80	90052064

CABLE WALL/CEILING BRACKET
for cable 4.25-5.5mm diameter



	EUR	CODE
	11,50	90019197
	11,50	90019198

SINGLE BASE LV
DALI-2 | 350mA | incl. driver



	EUR	CODE
	110,00	914117W0
	110,00	914117B0

OPLIA SINGLE BASE LV
DALI-2 | 250mA | incl. driver



	EUR	CODE
	110,00	914116W0
	110,00	914116B0

MULTI CHANDELIER LV
3 luminaires | 3x175mA
phase-cut dim | incl. driver
always use with hooks



	EUR	CODE
	260,00	914161WW0
	300,00	914161BL0
	260,00	914161BM0
	260,00	914161BQ0
	260,00	914161BB0

MULTI CHANDELIER LV
6 luminaires | 6x175mA
phase-cut dim | incl. driver
always use with hooks



	EUR	CODE
	295,00	914162WW0
	335,00	914162BL0
	295,00	914162BM0
	295,00	914162BQ0
	295,00	914162BB0

MULTI CHANDELIER LV
9 luminaires | 9x175mA
phase-cut dim | incl. driver
always use with hooks



	EUR	CODE
	330,00	914163WW0
	370,00	914163BL0
	330,00	914163BM0
	330,00	914163BQ0
	330,00	914163BB0

MULTI CHANDELIER HV
1-9 luminaires | always use with hooks



	EUR	CODE
	235,00	914160WW0
	275,00	914160BL0
	235,00	914160BM0
	235,00	914160BQ0
	235,00	914160BB0

HOOK
always use for MULTI CHANDELIER



	EUR	CODE
	19,00	90052083
	19,00	90052084

HOOK
for cable 4.25-5.5mm diameter | for
single and multi suspension | also for
textile cable



	EUR	CODE
	18,00	90052079
	18,00	90052080

HOOK
standard multi suspension hook
for ø5 plugs



	EUR	CODE
	4,50	90052025
	4,50	90052024

HOOK
optional multi suspension hook
for ø6 plugs



	EUR	CODE
	4,80	90052066
	4,80	90052065

WIRO | KUJO SUSPENDED

Accessories

WIRO
cable wall bracket
only for WIRO textile cable



	EUR	CODE
	20,00	90052062

WIRO CABLE PLUG & PLAY
E27 LED 4-25W | connector set for
one shade | black textile cable | incl.
cable plug with dimmer | 2 cable
brackets included



	EUR	CODE
8.5m	168,00	90015165

WIRO DECENTER SET 1.0
A60 max. 60W | E27
220-240VAC | 50-60Hz
suspension set for 1 shade
round ceiling base | black textile cable
1 base + 1 end stop included



	EUR	CODE
2.6m	108,00	90052050
6m	118,00	90052051

WIRO DECENTER SET 2.0
2x A60 max. 60W | E27
220-240VAC | 50-60Hz
suspension set for 2 shades
round ceiling base | black textile cable
1 multibase + 2 end stops included



	EUR	CODE
2.6m	198,00	90052055
6m	228,00	90052056

WIRO DECENTER SET 3.0
3x A60 max. 60W | E27
220-240VAC | 50-60Hz
suspension set for 3 shades
round ceiling base | black textile cable
1 multibase + 3 end stops included



	EUR	CODE
2.6m	286,00	90052060
6m	336,00	90052063

WIRO DECENTER SET 4.0
4x A60 max. 60W | E27
220-240VAC | 50-60Hz
suspension set for 4 shades
round ceiling base | black textile cable
1 multibase + 4 end stops included



	EUR	CODE
2.6m	368,00	90052067
6m	418,00	90052078

KUJO BASE
replacement for 1.0, 2.0 for central
steel wire mounting



	EUR	CODE
	245,00	914215W0
	245,00	914215SG0
	245,00	914215M0
	245,00	914215Q0
	245,00	914215B0

KUJO CONNECTORS
cable from one luminaire to another
incl. plugs | only for 2.1, 3.2, 3.2.1



	EUR	CODE
0.3m	14,50	915210W0
0.3m	14,50	915210SG0
0.3m	14,50	915210B0
0.6m	19,00	915211W0
0.6m	19,00	915211SG0
0.6m	19,00	915211B0

KUJO CONNECTORS
cable from one luminaire to another
incl. plugs | only for 2.1, 3.2, 3.2.1



	EUR	CODE
0.9m	23,00	915212W0
0.9m	23,00	915212SG0
0.9m	23,00	915212B0
1.2m	27,00	915213W0
1.2m	27,00	915213SG0
1.2m	27,00	915213B0

back

KIOSK POLE 400
straight pole | incl. ground spike



	EUR	CODE
	114,00	910101A0
	114,00	910101Q0

KIOSK POLE 600
straight pole | incl. ground spike



	EUR	CODE
	125,00	910102A0
	125,00	910102Q0

KIOSK POLE 800
straight pole | incl. ground spike



	EUR	CODE
	138,00	910103A0
	138,00	910103Q0

SWAM POLE 400
straight pole | incl. ground spike



	EUR	CODE
	103,00	910090Q0
	103,00	910090B0

SWAM POLE 600
straight pole | incl. ground spike



	EUR	CODE
	115,00	910091Q0
	115,00	910091B0

SWAM POLE 800
straight pole | incl. ground spike



	EUR	CODE
	128,00	910092Q0
	128,00	910092B0

SWAM POLE 400
curved pole | incl. ground spike



	EUR	CODE
	142,00	910093Q0
	142,00	910093B0

SWAM POLE 600
curved pole | incl. ground spike



	EUR	CODE
	144,00	910094Q0
	144,00	910094B0

SWAM POLE 800
curved pole | incl. ground spike



	EUR	CODE
	155,00	910095Q0
	155,00	910095B0

KIOSK | SWAM
fixation plate



	EUR	CODE
	22,00	90019019

STIPO POLE 200
with fixation plate | 3.0, 4.0



	EUR	CODE
	34,00	910062A0
	34,00	910062Q0

STIPO POLE 400
with fixation plate | 3.0, 4.0



	EUR	CODE
	38,00	910064A0
	38,00	910064Q0

STIPO POLE 600
with fixation plate | 3.0, 4.0



	EUR	CODE
	41,00	910066A0
	41,00	910066Q0

STIPO
ground spike



	EUR	CODE
	27,00	90013106

X-BEAM
ground spike



	EUR	CODE
	29,00	90013115

back

GATE ROUND 1.0 POLE 250
pole with fixation plate



	EUR	CODE
	58,00	910121A0
	58,00	910121Q0

GATE ROUND 1.0 POLE 450
pole with fixation plate



	EUR	CODE
	69,00	910122A0
	69,00	910122Q0

GATE ROUND 1.0 POLE 650
pole with fixation plate



	EUR	CODE
	88,00	910123A0
	88,00	910123Q0

GATE ROUND 2.0 POLE 250
pole with fixation plate



	EUR	CODE
	58,00	910124A0
	58,00	910124Q0

GATE ROUND 2.0 POLE 450
pole with fixation plate



	EUR	CODE
	69,00	910125A0
	69,00	910125Q0

GATE ROUND 2.0 POLE 650
pole with fixation plate



	EUR	CODE
	88,00	910126A0
	88,00	910126Q0

GATE CARRÉ 1.0 POLE 250
pole with fixation plate



	EUR	CODE
	66,00	910111A0
	66,00	910111Q0

GATE CARRÉ 1.0 POLE 450
pole with fixation plate



	EUR	CODE
	77,00	910112A0
	77,00	910112Q0

GATE CARRÉ 1.0 POLE 650
pole with fixation plate



	EUR	CODE
	96,00	910113A0
	96,00	910113Q0

GATE CARRÉ 2.0 POLE 250
pole with fixation plate



	EUR	CODE
	66,00	910114A0
	66,00	910114Q0

GATE CARRÉ 2.0 POLE 450
pole with fixation plate



	EUR	CODE
	77,00	910115A0
	77,00	910115Q0

GATE CARRÉ 2.0 POLE 650
pole with fixation plate



	EUR	CODE
	96,00	910116A0
	96,00	910116Q0

POLE 170
with fixation plate
PALOS ROUND | PALOS CARRÉ



	EUR	CODE
	98,00	910013A0
	98,00	910013Q0
	98,00	910013B0

POLE 170
with concrete ground fixation
PALOS ROUND | PALOS CARRÉ



	EUR	CODE
	124,00	910073A0
	124,00	910073Q0
	124,00	910073B0

POLE 270
with fixation plate
PALOS ROUND | PALOS CARRÉ



	EUR	CODE
	108,00	910014A0
	108,00	910014Q0
	108,00	910014B0

POLE 270
with concrete ground fixation
PALOS ROUND | PALOS CARRÉ



	EUR	CODE
	136,00	910074A0
	136,00	910074Q0
	136,00	910074B0

POLE 470
with fixation plate
PALOS ROUND | PALOS CARRÉ



	EUR	CODE
	123,00	910016A0
	123,00	910016Q0
	123,00	910016B0

POLE 470
with concrete ground fixation
PALOS ROUND | PALOS CARRÉ



	EUR	CODE
	148,00	910076A0
	148,00	910076Q0
	148,00	910076B0

POLE 670
with fixation plate
PALOS ROUND | PALOS CARRÉ



	EUR	CODE
	136,00	910018A0
	136,00	910018Q0
	136,00	910018B0

POLE 670
with concrete ground fixation
PALOS ROUND | PALOS CARRÉ



	EUR	CODE
	162,00	910078A0
	162,00	910078Q0
	162,00	910078B0

POLE 870
with fixation plate
PALOS ROUND | PALOS CARRÉ



	EUR	CODE
	155,00	910010A0
	155,00	910010Q0
	155,00	910010B0

POLE 870
with concrete ground fixation
PALOS ROUND | PALOS CARRÉ



	EUR	CODE
	188,00	910070A0
	188,00	910070Q0
	188,00	910070B0

back

LINUS POLE 150
with fixation plate



	EUR	CODE
	83,00	910024D0
	83,00	910024A0
	83,00	910024Q0

LINUS POLE 350
with fixation plate



	EUR	CODE
	109,00	910026D0
	109,00	910026A0
	109,00	910026Q0

LINUS POLE 550
with fixation plate



	EUR	CODE
	139,00	910028D0
	139,00	910028A0
	139,00	910028Q0

LINUS
ground spike



	EUR	CODE
	62,00	90013103

LINUS
concrete ground fixation



	EUR	CODE
	62,00	90013302

PLUG & PLAY
DRIVER 24V/30W IP67
30W | 24V
220-240VAC | 50Hz
incl. 2.5m cable with 240V plug
incl. 2.5m cable with 24V male plug
CH and UK variants online
L/W/H 110x48x31
IP67 CE



	EUR	CODE
	99,00	90018014

PLUG & PLAY
DRIVER 24V/75W IP67
75W | 24V
220-240VAC | 50Hz
incl. 2.5m cable with 240V plug
incl. 2.5m cable with 24V male plug
CH and UK variants online
L/W/H 129x49x32
IP67 CE



	EUR	CODE
	119,00	90018015

PLUG & PLAY
EXTENSION CABLE
2x 24V male plug
IP67 H07RN-F CE



	EUR	CODE
0.5m	16,00	90014505
1m	26,00	90014506
2.5m	38,00	90014502
5m	58,00	90014503

PLUG & PLAY
STRAIGHT CONNECTOR
2x 24V female connector
IP67 H07RN-F CE



	EUR	CODE
	9,50	90014504

PLUG & PLAY
T-CONNECTOR
3x 24V female connector
incl. 2 optional caps
IP67 CE



	EUR	CODE
	15,50	90014501

back

icons standards

NO MORE MISUNDERSTANDINGS

ICON	ENGLISH	GERMAN	DUTCH	FRENCH	SPANISH	ITALIAN
	Cutout Round	Ausschnitt rund	Ronde inbouwopening	Découpe ronde	Corte circular	Taglio tondo
	Cutout Square	Ausschnitt eckig	Rechthoekige inbouwopening	Découpe rectangulaire	Corte rectangular	Taglio quadro
	Recessed Depth	Einbautiefe	Inbouwdiepte	Profondeur d'encastrement	Profundidad de empotramiento	Profondità dell'incasso
	Ceiling Thickness	Deckenstärke	Plafonddikte	Épaisseur du plafond	Espesar del techo	Spessore del soffitto
0°-X°|X°	Rotatable vertically | horizontally	Drehbar vertikal | horizontal	Draaibaar verticaal | horizontaal	Orientable verticalement | horizontalement	Orientable en vertical | horizontal	Orientabile in verticale | orizzontale
	Beam Angle	Abstrahlwinkel	Reflectorhoek	Faiseau	Ángulo de apertura	Fascio luminoso
N – M – W	narrow – medium – wide beamangle	engstrahlend - medium-strahlend - breitstrahlend	smal - medium - breed	étroit - moyen - large	estecho - medio - ancho	stretto - medio - largo
	Class 1 Fixture	Leuchte der Schutzklasse 1	Toestel klasse 1	Appareil classe 1	Aparato de clase 1	Lampada classe 1
	Class 2 Fixture	Leuchte der Schutzklasse 2	Toestel klasse 2	Appareil classe 2	Aparato de clase 2	Lampada classe 2
III	Class 3 Fixture	Leuchte der Schutzklasse 3	Toestel klasse 3	Appareil classe 3	Aparato de clase 3	Lampada classe 3
IP 20	IP rating	IP Bewertung	IP-classificatie	Indice de protection	Grado IP	Grado di protezione IP
IP 44	Frontal IP rating	Frontale IP Bewertung	IP-classificatie	Évaluation IP frontale	Grado IP en parte frontal	Grado di protezione IP frontale
IK 06	IK rating	Schlagfestigkeit	IK-classificatie	IK rating	Grado IK	IK rating
UGR ≤ 19	Screen-compatible workplace light	Bildschirmtaugliche Arbeitsplatzleuchte	Werkplekverlichting is compatibel met beeldscherm	Éclairage compatible pour écran d'ordinateur	Iluminación para puestos de trabajo compatible con pantallas	Adatta per ambienti di lavoro | uffici
IC rated	IC rated: may be covered with insulation material	IC Rated: kann mit Isoliermaterial abgedeckt werden	IC classificatie: kan worden bedekt met isolatiemateriaal	Classé IC: peut être recouvert d'un matériau isolant	Clasificación IC: puede cubrirse con material aislante	Protezione IC. Può essere coperto con materiale isolante
L80 | 50K	LED Lifetime: Lumen output is minimum 80% after 50.000 hours	LED-Lebensdauer: Die Lichtausbeute nach 50.000 Stunden beträgt mindestens 80 %	Led-levensduur: de lichtopbrengst na 50.000 branduren is minimaal 80%	Durée de vie des LED : l'efficacité lumineuse au bout de 50 000 heures s'élève à 80 % minimum	Vida útil de los LED: la eficiencia luminosa tras 50.000 horas es de al menos el 80 %	Durata dei LED: l'efficienza luminosa è pari ad almeno l'80% dopo 50.000 ore di funzionamento

ICON	ENGLISH	GERMAN	DUTCH	FRENCH	SPANISH	ITALIAN
CE	CE conform	CE-konform	CE-conform	Conformité CE	Conformidad CE	Conformità CE
	ENEC Certificate	ENEC Zertifikat	ENEC Certificaat	Certificat ENEC	Certificado ENEC	Certificato ENEC
	UL Certificate	UL Zertifikat	UL Certificaat	Certificat UL	Certificado UL	Certificato UL
Kelvin	Colour Temperature	Farbtemperatur	Kleurtemperatuur	Température de couleur	Temperatura de color	Temperatura colore
Blue lines	Part not included	Teil nicht inkludiert	Onderdeel niet inbegrepen	Pièce non comprise	Parte no incluida	Articolo non incluso
	Up/Down	Aufwärts/abwärts strahlen	Licht boven of onder	Éclairage haut ou bas	Emisión superior/ inferior	Luce monoemissione sopra/sotto
	Up and Down	Aufwärts und abwärts strahlend	Licht boven en onder	Éclairage haut et bas	Emisión superior e inferior	Luce biemissione sopra/sotto
A - G	Energy labelling regulation	Verordnung über die Energiekennzeichnung	Energielabel	Règlement sur l'étiquetage énergétique	Reglamento sobre el etiquetado energético	Regolamento sull' etichettatura energetica
	Light source replaceable by end user	Lichtquelle durch Endverbraucher austauschbar	Lichtbron vervangbaar door eindgebruiker	Source lumineuse remplaçable par l'utilisateur final	Fuente luminosa sustituible por el usuario	Sorgente luminosa sostituibile dall'utente finale
	Light source not replaceable	Lichtquelle nicht austauschbar	Lichtbron niet vervangbaar	Source lumineuse non remplaçable	Fuente luminosa no sustituible	Sorgente luminosa non sostituibile
	Control gear replaceable by end user	Betriebsgerät durch Endverbraucher austauschbar	Driver vervangbaar door eindgebruiker	Dispositif de commande remplaçable par l'utilisateur final	Mecanismo de control sustituible por el usuario	Dispositivo di controllo sostituibile dall'utente finale
	Control gear not replaceable	Betriebsgerät nicht austauschbar	Driver niet vervangbaar	Dispositif de commande non remplaçable	Mecanismo de control no sustituible	Dispositivo di controllo non sostituibile
	Light source replaceable by authorized professional	Lichtquelle durch autorisierte Fachleute austauschbar	Lichtbron vervangbaar door een erkend vakman	Source lumineuse remplaçable par un professionnel agréé	Fuente luminosa sustituible por un técnico autorizado	Sorgente luminosa sostituibile da tecnici specializzati
	Control gear replaceable by authorized professional	Betriebsgerät durch autorisierte Fachleute austauschbar	Driver vervangbaar door een erkend vakman	Dispositif de commande remplaçable par un professionnel agréé	Mecanismo de controls ustituible por un técnico autorizado	Dispositivo di controllo sostituibile da tecnici specializzati

contact

HEAD OFFICE + SHOWROOM

WEVER & DUCRÉ BV
Spinnerijstraat 99/21
8500 Kortrijk, Belgium
Phone +32 56 492 800
office@weverducre.com
weverducre.com

SHOWROOMS

AUSTRIA
Dokter-Hermann-Thurner-Straße 3 / Top 17
4060 Leonding
Phone +43 316 3170 8570
office.at@weverducre.com

Gleisdorfer Gasse 15
8010 Graz
Phone +43 316 317 085 91
office.at@weverducre.com

Marxergasse 1B
1030 Vienna
Phone +43 1 526 47 84
office.at@weverducre.com

BELGIUM
Gare Maritime
Picardstraat 7
bus 304
1000 Brussels
Phone +32 56 492 800
office@weverducre.com

FINLAND
Sörnäistenkatu 1
00580 Helsinki
Phone +358 50 348 4366
office.fi@weverducre.com

FRANCE
36, Rue Juliette Récamier
69006 Lyon
Phone +33 4 72811199
office.fr@weverducre.com

10, Rue Pecquay
75004 Paris
Phone +33 1 402 981 01
office.fr@weverducre.com

GERMANY
Europa-Allee 18
60327 Frankfurt am Main
Phone +49 69 21029590
office.de@weverducre.com

Helmholtzstraße 2
10587 Berlin
Phone +49 30 39743290
office.de@weverducre.com

Schanzenstraße 36, Geb. 234B
51063 Cologne
Phone +49 221 130649 60
office.de@weverducre.com

Ruhrstraße 11A / Im Phoenixhof
22761 Hamburg
Phone +49 40 85179283 0
office.de@weverducre.com

Maybachstraße 10b
70469 Stuttgart
Phone +49 711 806075 90
office.de@weverducre.com

HONG KONG
RM. 1413, Block A, Sea View Estate
2 Watson Road North Point, Hong Kong
Phone +852 211 069 24
office.hk@weverducre.com
office.cn@weverducre.com

ITALY
Via Monte Popera 4/2
30027 San Donà di Piave - Venezia
Phone +39 0421 177 83 88
office.it@weverducre.com

NETHERLANDS
Design Post Amsterdam
Cruquiusweg 111L, 1019 AG Amsterdam
Phone +31 20 229 6001
info.nl@weverducre.com

POLAND
ul. Komitetu Obrony Robotników 70,
02-146 Warsaw
Phone +48 730 330 358
office.pl@weverducre.com

SPAIN
Plaça Duc de Medinaceli 5
08002 Barcelona
Phone +34 93 5112 189
office.es@weverducre.com

SWEDEN
Norrtullsgatan 12N
11327 Stockholm
Phone +46 10 440 71 10
office.se@weverducre.com

SWITZERLAND
Sonnmatthof 3
6023 Rothenburg
Phone +41 41 361 60 60
office.ch@weverducre.com

UK
477b-478 Batemans Row
London, EC2A 3HH
Phone +44 203 174 01 77
info.uk@weverducre.com

REPRESENTATIVE OFFICES

INDIA
1524, Astralis, Supernova, Sector-94
201301, Noida, Uttar Pradesh
Phone +918377006926
office.in@weverducre.com

NORWAY
Drammensveien 130, Inng. B12
0277 Oslo
Phone +47 24 07 61 11
office.no@weverducre.com

UAE
Office No. 704, HDS Business Center
Cluster M, Jumeirah Lakes Towers, DMCC
PO Box 336603 Dubai
United Arab Emirates
Phone +971 4 436 23 47
office.me@weverducre.com

©WEVER & DUCRÉ® BV

1ST EDITION, MARCH 2026

All prices are non-binding recommended prices excluding VAT, lamps (bulbs) are not included. The prices and terms of payment stated in our order confirmation shall apply. To all prices and all extra expenses, we add the legally applicable value added taxes. Should our costs increase by the time of delivery, the prices can be recalculated on a pro rata basis. The prices stated shall apply net ex works. Information on availability as well as delivery terms and dates are provided as a point of reference only and are not binding. Prices are valid till the publication of a new price list. Please note: The printed prices reflect the pricing at the time of catalogue publication. For the most up-to-date pricing, please refer to our website. We expressively reserve the right to make changes in price, measurements and design. The details provided in this catalogue were correct at the time of publication. They do not constitute any kind of obligation on our part and are for information only. We shall not be held liable for any discrepancies between the illustrations or descriptions given and the actual product neither for any misprints and/or typing errors. We reserve the right to make alterations or modifications to our products at any time. All mentioned RAL codes are indicative and approximative. We shall not be held liable for any discrepancies which may occur. All mentioned wattage, lumen, beam angles, lifetime and SDCM values refer to white luminaires (in terms of finishing, covers or housings) in 3000K. Further values on request. The general terms and conditions of Wever & Ducré BV shall apply to all purchases and orders. The applicable version of the general terms and conditions can be viewed at weverducre.com/en/downloads.

What's that? A whole new product range, and already several project references? See it this way: Inspiration is key to success in design, so what we care for most is inspiring you and showing you the potential of what we at Wever & Ducré do. Thus, we took the liberty of editing some (original) images to give you an impression of how our luminaires improve living, office, outdoor, and other spaces. These pictures are marked with (V)

COVER	Frederik Vercruysse
GRAPHIC DESIGN	Carola Friedrich, Carina Erlach
PRINT PRODUCTION	Carola Friedrich, René Zavadilik
ILLUSTRATION	Carina Erlach, Lukas Hochenwarter
TEXT	Tanja Petschnig
LITHOGRAPHY	Volker Waldhauser
PROJECT MANAGEMENT	Carola Friedrich, Melanie Löffler, Victoria Prath
PRINTING	Drukarnia Perfekt S.A., Warsaw, Poland
VISUALIZATIONS	Animotions - Visuals for brands, Nanopixel bv, Outlier Creative, P1 Studio
PHOTOGRAPHY	Adrian Beck (546), Aikon-Producties-bvba (236), Aleksandr Dal Cero (250), Álvaro Valdecantos (724), Amaury Laparra (204, 252), Andrea Badrutt Fotografie (302), Andrei Valeriu Radulescu (242), Anker & Co (36, 234), Annelien Geenen (510), Annelies Degroote (216, 222, 696), Arnold Ory (98), Axis71 (14, 16), Barbara Corsico (554), Bart Gosselin Photography (118, 166, 192, 298, 340, 662), Beeldcollectief l Lucas Despriet (21), Benoit Ravier-Bollard (282), Bert Demasure (420), Bob Reijnders (342), Camille Huguenot (74), Caroline Dethier (812), Catherine Roider (394), Charlotte Kap Interieurfotografie (230), Chiela van Meerwijk (126, 324, 570), Chris Snook (80), Christian Brandstätter (784), Christoph Hütter Photography (30), Christoph Platzer (654), Christoph Steinbauer (368, 578, 748, 754, 816), Corinna Unterkofler (828, 862), Cornelia Kindsvater (442, 443), Daniel Stauch (328), Dieter Vyvey (272), Elia Kuhn Photographe (120), Elien Jansen (224), Elodie Dugué Photographe (598), Elodie Winter Photography (600), Elsa Young (580), Emanuel Waldmann (136), Empower Spaces (656), Erich Sinzinger, 2019 (858), Erik Đuriš (626, 627), Evgenij Avramenko (610), Fabrizio Carraro (418, 419, 658, 659), Federico Covre – Architectural Photographer (407), Flare Department (78, 130), Florian Zenk (36, 446, 447), French Village (584), Gerald Van Rafelghem (842), Gerard Colomé (92, 194, 195, 416, 814, 834, 844), Gianni Declercq Photography (588), Giovanni Nardi (278, 280), Gonzalo Botet (264), Gregor Titze (636), Hanne Joosen Fotografie (164, 244), Hannes Otte (25, 36, 260, 514, 808), Ilaria Sgambaro from Interni 21.11 (392), In-Between Architects Limited (688), Ingo Rasp Photography (574), Jacek Rokowski (674), Jakob Kotzmuth (794, 795), Jan Kan (714), Jean Pellaprat de VISIBLE (524), Joachim De Rous (102), Joachim Grothus (180, 228), Joachim Grubelnik (828, 862), Johan Méallier (594), Julien Pépy (46), Jurrit van der Waal – The Art of Living magazine (606), Karsten Knocke (734), Kim Donggyu (444), Kris Dekeijser (17, 25, 35, 49, 60, 82, 84, 90, 106, 152, 156, 160, 208, 212, 238, 240, 246, 248, 262, 276, 288, 300, 304, 320, 332, 334, 348, 349, 364, 366, 376, 408, 464, 480, 482, 484, 498, 522, 532, 536, 550, 558, 559, 604, 624, 628, 638 632, 634, 702, 718, 730, 742, 756, 758, 764, 768, 780, 786, 800, 802, 810, 826, 838, 848, 850, 860, 861, 864, 872, 880), Kris Dimitriadis/Kurt Dekeyzer studio PSG 2021 (618), Kristof Claeys (172), Kurt Kuball (762, 796), Lennart Wiedermuth (25, 538), Lenzer (380), Local Minded (378), Lukas Jahn (782), Lukas Vazan (18), Lumine Fotografie (518), M. Leimgruber (29), Margriet Hoekstra (254, 820), Marta D'Avenia Photography (608), Marta Vidal (96, 410, 576), Martin Grobe (642), Max Feldhoff (542), Maxi Conesa (202), Melvin wong weije (806), Mgr. art. Matej Hakár (560), Michaël Radi (596, 597), Miikka Leskinen (572, 682), Miloš Martinović (154), Miriam Raneburger (766), Namsun Lee (218), Niels Nygaard (460), Nikolaus Pfusterschmid (752), nomadic..den (494), Norbert Tukaj (740, 840), nunofoto (804), Open Architectes (876), Oracle – Clément Gerard (676), Paloma Pacheco Turnes (664, 665), Patricia Goijens (496), Paul Ott (516, 564, 565), Peter Baas Photography (108, 256), Peter Margis (388), Petri Immonen (220), Philip Kottlorz Fotografie (292, 296, 372, 640), Pilar Shoots (66, 182, 490), PO Photo (146), Pol Viladoms (646), Pro Urban AG (466), Quy Bui - Wuyhoang Studio (478, 653, 890, 891), Radoje Burzan photography (76), renaatnijs (36), Rupert Asanger (540), Salva López (138), Sandra Mulder (14, 19), Sebastian Reiser (468, 469, 684, 886, 888), Sergio Camplone (544), Søren Kristensen (162), Steenoven (186), Stefano Maniero (692), Stella Kager (9, 13, 26, 30, 35, 38, 644), Stéphanie Mathias (51, 354, 355), Stevie Campbell (672), Stijn Poelstra (614), Stijn Vereeken (132), Studio Blenda (424, 425), Studio Erick Saillet (128), Studio Fo.cus (62), Studio Gataric Fotografie (704), Studio05 (652), Sue Baer (488), Supereal (206), Tijs Vervecken (142), Tom Bremer (322, 346, 612), Tom Lierman photography (352), Trien Byttebier (150, 548), Type Type Hype (37), Uliana Grishina (666), Unique Renovations (650), Victor Chito (86, 832), Victor Sajara Photography (856), Vlad Cioplea (556), Yves Garneau (112), Zvonimir Mihaljek (798)

FSC
www.fsc.org
MIX
Paper from responsible sources
FSC® C016890

WITH GROUPED PRODUCT FAMILIES

index by name

1-PHASE TRACKS 361
3-PHASE TRACKS 385
BENTO 621
BLAS CEILING SURFACE 767
BLAS WALL SURFACE 827
BLIEK 67
BLIEK PETIT CEILING RECESSED 63
BLIEK PETIT CEILING SURFACE 179
BLINK 839

BOX

BOX CEILING SURFACE 235
BOX CEILING SURFACE EXTERIOR 765
BOX ON STREX 335
BOX WALL SURFACE 607
BOX WALL SURFACE EXTERIOR 815
BOX MINI CEILING SURFACE 231
BOX MINI WALL SURFACE 605

CARD 843

CENO

CENO CEILING RECESSED 131
CENO CEILING SURFACE 181
CENO ON STREX 321
CENO WALL SURFACE 585

CENTRAL 617
CENTRAL EXTERIOR 809
CG01 719
CG SQUARE 647
CHART 851
CHART ASYM 853
CITY IP44 173
CLASCO 791

CLEA

CLEA CEILING SURFACE 287
CLEA CEILING SUSPENDED 557
CLEA WALL SURFACE 631

CONE 463
COZY CONE CEILING SUSPENDED 503
COZY CONE ON STREX 345
DARF CEILING SUSPENDED 445
DARF WALL SURFACE 643

DEEP

DEEP 107
DEEP EXTERIOR 745
DEEP IP65 | IP44 161
DEEP ADJUST 119
DEEP ADJUST IQ 115
DEEP ADJUST PETIT 113
DEEP ADJUST PETIT IQ 111
DEEP ADJUST PETIT TRIMLESS 113
DEEP ADJUST TRIMLESS 117
DEEP BIJOU 99
DEEP BIJOU EXTERIOR 741
DEEP BIJOU IP65 157
DEEP IQ 105
DEEP PETIT 103
DEEP PETIT EXTERIOR 743
DEEP PETIT IP65 159
DEEP PETIT IQ 101
DEEP POINT 97
DEEP POINT IP44 155
DEEPER 109
DEEPER IP44 163

DINOR 563

DOCUS

DOCUS CEILING SURFACE 241
DOCUS ON STREX 337
DOCUS MINI CEILING SURFACE 239
DOCUS MINI WALL SURFACE 609

DOMINO 693
DOMY ON STREX 327
DOT 649

DRO

DRO CEILING SURFACE 279
DRO CEILING SUSPENDED 465
DRO FLOOR SURFACE 731
DRO ON 1-PHASE TRACK 373
DRO TABLE 717
DRO TABLE | FLOOR SURFACE 715
DRO WALL SURFACE 623

ELLO SYSTEM 405

FIL

FIL CEILING SUSPENDED 441
FIL SPIN CEILING SURFACE 267
FIL SPIN WALL SURFACE 681

FINELLE CEILING SUSPENDED 423
FLYRA CEILING SUSPENDED 427
FLYRA SYSTEM 401

FINLIN

FINLIN CEILING SURFACE 263
FINLIN CEILING SUSPENDED 433
FINLIN FLOOR SURFACE 727
FINLIN WALL SURFACE 673
FINLIN ROUND 679

GATE CARRÉ FLOOR SURFACE 871
GATE ROUND FLOOR SURFACE 869
GEO FLOOR SURFACE 885
GIGANT 461
HAJO IP44 697

HEXO

HEXO CEILING SURFACE 245
HEXO CEILING SUSPENDED 533
HEXO ON 1-PHASE TRACK 377
HEXO ON 3-PHASE TRACK 393
HEXO ON STREX 339
HEXO MINI CEILING SURFACE 243
HEXO MINI CEILING SUSPENDED HV 531
HEXO MINI CEILING SUSPENDED LV 505
HEXO MINI ON 1-PHASE TRACK 375
HEXO MINI ON 3-PHASE TRACK 391
HEXO MINI WALL SURFACE 611

ILANE 409
INTRA 749

J.J.W.

J.J.W. CEILING SURFACE 289
J.J.W. CEILING SUSPENDED 479
J.J.W. WALL SURFACE 633

KIOSK FLOOR SURFACE EXTERIOR 857
KIOSK WALL SURFACE 793
KUJO CEILING SUSPENDED 453
LARRA 671

LECA

LECA CEILING RECESSED 135
LECA CEILING SURFACE 189
LECA ON STREX 325
LECA SNOOZE 569

LEENS 619
LIKO ON 3-PHASE TRACK 387
LINOO CEILING RECESSED 71
LINOO CEILING SURFACE 211
LINUS 881
LITO 575
MAP 845
MAP ASYM 849

MATCH

MATCH CEILING RECESSED 137
MATCH CEILING SURFACE 193
MATCH CEILING SUSPENDED 509
MATCH ON STREX 329
MATCH SUSPENDED ON STREX 347
MATCH FLOOR SURFACE 729
MATCH TABLE 723
MATCH WALL SURFACE 589
MATCH LUSTA 415
MATCH SNEAK 143
MATCH SNOOZE WALL RECESSED 571
MATCH SNOOZE WALL SURFACE 685
MATCH STICK 145
MATCH POINT 61
MATCH POINT IP44 153

MICK

MICK CEILING SURFACE 199
MICK ON STREX 333
MICK WALL SURFACE 691
MICK SNOOZE 687

MILES 669
MILES CARRÉ 667
MILES ROUND 663
MIRBA IP44 705

MIRBI

MIRBI IP44 CEILING RECESSED 171
MIRBI IP44 CEILING SURFACE 297
MIRBI LONG IP44 707

MIRRO

MIRRO CEILING SURFACE 283
MIRRO CEILING SUSPENDED 467
MIRRO FLOOR SURFACE 733
MIRRO TABLE 721
MIRRO WALL SURFACE 625

HV HIGH VOLTAGE | **LV** LOW VOLTAGE

More product families on next page

WITH GROUPED PRODUCT FAMILIES

index by *name*

MIRRO SOFT CEILING SURFACE 285
MIRRO SOFT CEILING SUSPENDED 471
MIRRO SOFT WALL SURFACE 629

NET 421

ODREY

ODREY CEILING SUSPENDED HV 539
ODREY CEILING SUSPENDED LV 517
ODREY ON 1-PHASE TRACK 379
ODREY ON STREX 353
ODREY WALL SURFACE 599

OPLIA CEILING SUSPENDED 521
OPLIA ON STREX 357
OPLIA CHANDELIER 457
ORIS 581
ORIS EXTERIOR 785
PALOS WALL SURFACE EXTERIOR 819
PALOS CARRÉ FLOOR SURFACE EXTERIOR 877
PALOS ROUND FLOOR SURFACE EXTERIOR 873
PAVIO IP65 711
PAVIO EXTERIOR 831

PERLEZ

PERLEZ IP44 CEILING RECESSED 169
PERLEZ IP44 CEILING SURFACE 295
PERLEZ IP44 WALL SURFACE 701
PERLEZ CLIP IP44 703
PERLEZ GRID 275
PERLEZ SPIN 271

PIRRO

PIRRO CEILING RECESSED 77
PIRRO CEILING SURFACE 215
PIRRO ON 1-PHASE TRACK 371
PIRRO ON BASE 223
PIRRO OPAL 221
PIRRO PETIT CEILING RECESSED 75
PIRRO PETIT CEILING SURFACE 213

PILLO CEILING SURFACE 201
PILLO ON 1-PHASE TRACK 363
PLANO CEILING RECESSED 85
PLANO IP44 CEILING RECESSED 151
PLANO PETIT CEILING RECESSED 83
PLANO PETIT CEILING SURFACE 227
POLA 889
QUBBY CEILING SUSPENDED 459
QUBBY SYSTEM 397
QITO CEILING RECESSED 57
QITO CEILING SURFACE 177

RAY

RAY CEILING SURFACE 251
RAY CEILING SURFACE EXTERIOR 759
RAY CEILING SUSPENDED 537
RAY ON 1-PHASE TRACK 377
RAY ON 3-PHASE TRACK 393
RAY ON STREX 341
RAY WALL SURFACE 615
RAY WALL SURFACE EXTERIOR 805
RAY MINI CEILING SURFACE 247
RAY MINI CEILING SUSPENDED HV 535
RAY MINI CEILING SUSPENDED LV 507
RAY MINI ON 1-PHASE TRACK 375
RAY MINI ON 3-PHASE TRACK 391
RAY MINI WALL SURFACE 613

REED 887

RETO

RETO WALL RECESSED 573
RETO WALL RECESSED EXTERIOR 781
RETO WALL SURFACE EXTERIOR 835
RETO ROUND 833

RIBELLE FLOOR SURFACE 867
RIBELLE IP65 WALL SURFACE 709
RIBELLE WALL SURFACE EXTERIOR 825
RINI SNEAK IP44 167
ROB IP44 301
ROB EXTERIOR 769
ROBY IP44 303
RONY ADJUST 129
RONY ADJUST PETIT 127
RONY PETIT 125
RONY POINT 123

ROOMOR

ROOMOR CEILING SUSPENDED 495
ROOMOR FLOOR SURFACE 735
ROOMOR TABLE 725
ROOMOR WALL SURFACE 639
ROOMOR OFFICE CEILING SURFACE 293
ROOMOR OFFICE CABLE SUSPENDED 499
ROOMOR OFFICE ON 3-PHASE TRACK 395

ROSS IP54 307
ROSS EXTERIOR 771
RUVI CEILING RECESSED 147
RUVI ON 1-PHASE TRACK 383

SARA

SARA ON BASE 203
SARA ON 1-PHASE TRACK 365
SARA SNOOZE 689

SCAVA 695
SHEDDA 449
SHEDDA FRACTAL 451
SHIEK 561
SIRRO 229
SNEAK 93
SNEAK TRIMLESS 91
SOLID 257
SOLID BIJOU 253
SOLID PETIT 255
SOLLI CEILING SUSPENDED 523
SOLLI ON STREX 359
SOLLI COCOON 525
SPIRRA SOFT 475
SQUBE ON BASE 205
SQUBE ON 1-PHASE TRACK 369
SQUBE ON 3-PHASE TRACK 389
STIPO 863
STUDO 437
STRANGE TRIMLESS 89
STRANGE PETIT TRIMLESS 87
STREX DOT MODULE 343
STREX OPAL MODULE 343
STREX SYSTEM | 48V 313
STRIPE 579
STRIPE SLIM 577
SWAM FLOOR SURFACE 859
SWAM WALL SURFACE 821

TAIO

TAIO CEILING RECESSED EXTERIOR 747
TAIO CEILING SURFACE EXTERIOR 757
TAIO IP65 CEILING RECESSED 165
TAIO IP65 CEILING SURFACE 299
TAIO WALL SURFACE EXTERIOR 803

TAPE 817
TAPIS 651
TAPIS SOFT 657
TOWNA IP44 305

TRADORA

TRADORA CEILING SURFACE 775
TRADORA CEILING SUSPENDED 777
TRADORA WALL SURFACE 823

TRACE

TRACE CEILING SURFACE 261
TRACE CEILING SUSPENDED HV 547
TRACE CEILING SUSPENDED LV 511
TRACE ON STREX 351
TRACE WALL SURFACE 593
TRACE CHANDELIER 417
TRACE GRID 273
TRACE MINI ON STREX 331
TRACE MINI WALL SURFACE 591
TRACE SLIM 595
TRACE SPIN 269

TRAIN CEILING SURFACE 761
TRAIN WALL SURFACE 807
TRAM CEILING SURFACE 753
TRAM WALL SURFACE 797
TUBE CEILING SURFACE 755
TUBE WALL SURFACE 799
TUBE CARRÉ CEILING SURFACE 763
TUBE CARRÉ WALL SURFACE 811
VENN CEILING SURFACE 277
VENN WALL SURFACE 683
WAVE SOFT 477
WETRO 549
WIRO CEILING SURFACE 291
WIRO CEILING SUSPENDED 489
WIRO CONE 489
WIRO DIAMOND 493
X-BEAM FLOOR PROJECTOR 865
X-BEAM WALL SURFACE 829

HV HIGH VOLTAGE | **LV** LOW VOLTAGE

COLOURS AND MATERIALS

For specific information on colours and finishes please refer to weverducre.com/materials

Depending on the product and application, the materialization may differ: For more informations on materials, finishes, structures, RAL and NCS colour codes, please check our product page on the website. RAL and NCS colour codes are always approximate and can be checked by the customer based on samples.

Outdoor

METAL

- W White
- D Grey
- A Anthracite Grey
- Q Bronze
- G Gold
- B Black
- K Black and Gold

- CL Classic Alu
- CQ Classic Bronze
- AB Antique Brass

- I Inox | 304 Stainless steel electro polished

RECYCLED PET FELT

- WF White
- MF Marble Grey
- LF Limestone
- OF Oxide Red
- IF Indigo Blue
- AF Anthracite
- F Grey

ALUMINIUM COMPOSITE MATERIAL

- GB Black and Light Gold
- NB Black and Black Chrome
- LB Black and Glossy Aluminium

MARBLE

- MB Black
- MW White

Indoor

GLASS HANDBLOWN

- TS Smoked Striped
- TW Taupe White
- DW Dark Taupe White
- TD Smoked Diamond
- YD Yellow Diamond
- GD Green Diamond
- BD Blue Diamond
- FD Frosted Diamond | Opal
- P Copper Plated
- B Smoked
- W White | Opal

HAJO GLASS

- C Clear
- W Sandblasted
- A Amber
- B Smoked

METAL

- E White and Black
- J White and Gold
- H Champagne and Black
- K Black and Gold
- CH Black and Champagne
- Z Black and Copper
- GW Cement Grey and White
- RR Coral Red and White

OTHERS

- W White | LLDPE

3D PRINTED MATERIAL (IQ)

- RP Recycled PET
- W White ASA
- B Black ASA
- SG Silk grey ASA

METAL

- LS Live Simple
- SG Silk Grey
- FJ Feel Jade
- CC Come Closer
- ME Mother Earth

- YE Yellow CG01
- RE Red CG01
- AU Aubergine CG01
- BE Blue CG01
- B Black CG01

PLASTER

- GW Give Warmth
- ST Stay Together
- FJ Feel Jade
- RA Raw material for custom paint

METAL

- W White
- L Aluminium
- G Gold
- M Champagne
- Q Bronze
- P Copper
- V Corton steel look
- GM Gun metal
- B Black

- A Anodised Aluminium
- T Tumbled Aluminium

LINE BRUSHED FINISH FOR METAL COLOURS

- Line brushed

